

INSPECTION SHEET

Static mechanical check **Activity:** 401600 **Equipment type: Vertisorter Conveyor:** SVD 1.49. **Building Zone:** Area: 1 2100 General Pass Fail n.a. 1 all loose materials/debris/dust removed, conveyor beds are clean 2 identification label with conveyor id is applied on conveyor 3 Conveyor/component is installed on position and angle as per drawing 4 Conveyors/component are with right spacing supported, braced, lined, leveled and fixed to wall, floors, platforms or roof structure. ⁵ Product envelope in relation to surrounding space. (No HVAC piping & ducts etc inside the envelope) 6 No obstructions in maintenance and/or operator area (if applicable) 2110 Workmenship Pass Fail n.a. 1 Paint damage touched up 2120 General conveyor Pass Fail n.a. 1 Conveyor transitions horizontal and vertical aligned. Waterfall applied if required. 2 Bolts and fixings tight (random check carried out) 3 Side, change over guards and guide corners and their braces are installed, without gaps in \square transport direction. If overlap is applied, check that poverlap is in transport direction Return and track rollers installed and aligned 2130 Drive Pass Fail n.a. 1 Check Motor Power: < kW> according specification

2 Brake present <> according specification



_	3	Oil plugs open and positioned on top			
214	0	Belt Check Belt type: <>	Pass	Fail	n.a.
=	2	Check Belt width: < mm>			
-	4	Belts correctly welded & tensioned			
-	5	Tension space left after tensioning			
215	0	Fences Door / sliding gate properly closing and switches adjusted	Pass	Fail	n.a.
	0	Safety Safety precautions (finger protections) installed (if applicable). Without protection: The gap must be smaller then 5 mm or larger then 50mm	Pass	Fail	n.a.
	2	Covers installed on: Drive, tension unit, PTO (Power Take off) / ETU (End Take Up)			
	5	Safety guarding, gates and gate locks are installed and functional			
-	6	Safety hinge pin present complete with chain and split pin			
_	7	Safety warning signs are installed. Sitemanager/Supervisor to advise locations			
-	8	Safety under guarding applied according specification and type of industry. Typicals: BHS RAW and WPP: Between 700-2500mm and operator zones until 2500mm. BHS Tubtrax: Between 1500-2500mm at maintenance zone and operator zone until 2500mm			



Other Comments				
	Customer	Vanderlande	SubContractor	
Signature				
Name				
Date				



INSPECTION SHEET

Static mechanical check **Activity:** 401600 **Equipment type: Vertisorter Conveyor:** SVD 1.51. **Building Zone:** Area: 1 2100 General Pass Fail n.a. 1 all loose materials/debris/dust removed, conveyor beds are clean 2 identification label with conveyor id is applied on conveyor 3 Conveyor/component is installed on position and angle as per drawing 4 Conveyors/component are with right spacing supported, braced, lined, leveled and fixed to wall, floors, platforms or roof structure. ⁵ Product envelope in relation to surrounding space. (No HVAC piping & ducts etc inside the envelope) 6 No obstructions in maintenance and/or operator area (if applicable) 2110 Workmenship Pass Fail n.a. 1 Paint damage touched up 2120 General conveyor Pass Fail n.a. 1 Conveyor transitions horizontal and vertical aligned. Waterfall applied if required. 2 Bolts and fixings tight (random check carried out) 3 Side, change over guards and guide corners and their braces are installed, without gaps in \square transport direction. If overlap is applied, check that poverlap is in transport direction Return and track rollers installed and aligned 2130 Drive Pass Fail n.a. 1 Check Motor Power: < kW> according specification

2 Brake present <> according specification



_	3	Oil plugs open and positioned on top			
2140 1		Belt Check Belt type: <>	Pass	Fail	n.a.
_	2	Check Belt width: < mm>			
_	4	Belts correctly welded & tensioned			
_	5	Tension space left after tensioning			
215	0	Fences Door / sliding gate properly closing and switches adjusted	Pass	Fail	n.a.
2190 1		Safety Safety precautions (finger protections) installed (if applicable). Without protection: The gap must be smaller then 5 mm or larger then 50mm	Pass	Fail	n.a.
- !	2	Covers installed on: Drive, tension unit, PTO (Power Take off) / ETU (End Take Up)			
	5	Safety guarding, gates and gate locks are installed and functional			
	6	Safety hinge pin present complete with chain and split pin			
	7	Safety warning signs are installed. Sitemanager/Supervisor to advise locations			
-	8	Safety under guarding applied according specification and type of industry. Typicals: BHS RAW and WPP: Between 700-2500mm and operator zones until 2500mm. BHS Tubtrax: Between 1500-2500mm at maintenance zone and operator zone until 2500mm			



Other Comments				
	Customer	Vanderlande	SubContractor	
Signature		,		
Name				
Date				