Data contract of the HY Analyst

FundamentalQuantmental

23 October 2026

What this is. The checklist of every kind of data that the HY Analyst reads. Use it when you connect a new data source on another machine.

One connector. The repo holds the method. The data plugs in through one class that implements the protocols in `hy/data/source.py`.

One rule. Every input reaches the analyst through `DataView(source, decision_time)`. The view returns only what was public at the decision time.

1 Rules for every kind

1. Every input reaches the analyst through one `DataView` (`hy/data/view.py`).
2. Every record carries `as_of` and `available_at`.
   - `as_of` is the date or period that the value describes.
   - `available_at` is the first moment the market could read the value.
   - `available_at` is never before `as_of`. The record class rejects such a record.
3. The view filters by `available_at`. It also checks what the source returns. A record public after the decision time raises `LookAheadError`.
4. A source that cannot supply an item raises `DataUnavailable(kind, key, reason)` (`hy/data/pit.py`). The analyst turns most of these into an open question in the memo. Section 3 states what each gap does.
5. Units:
   - Rates, yields, spreads and shares are decimals. 0.065 means 6.5%. 0.0350 means 350 bp.
   - Amounts are in USD millions.
   - Tenors, terms and maturities are in years.
   - Times are naive UTC `datetime` values. A filing's time is its EDGAR acceptance time.
6. Bond observations and the panels are pandas frames, because of their size. Each frame has an `available_at` column. All other kinds are frozen dataclasses in `hy/data/records.py`.

2 The kinds at a glance

No.	Kind	Source method	View method	Required
3.1	Issuer identity	`issuers`	`issuer`	yes
3.2	Quarterly financials	`financials`	`financials`	yes
3.3	Filing facts	`facts`	`facts`	yes
3.4	Filing list	`filings`	`filings`	no
3.5	Balance sheet and schedules	`balance_sheet`	`balance_sheet`	yes
3.6	Filing text	`filing_text`	`filing_text`	no
3.7	First-reported cash flows	`reported_cash_flow`	`reported_cash_flow`	no
3.8	Equity market value	`market_value`	`market_value`	no
3.9	Bond terms	`bonds`	`bonds`	yes
3.10	Bond observations	`observations`	`observations`	yes
3.11	Treasury curve	`curve`, `curves`	`curve`, `curve_history`	yes
3.12	HY index level	`hy_index`	`hy_index`	yes
3.13	Macro forecasts	`forecasts`, `forecast_status`	same	no
3.14	Peer panels	`panel`	`panel`	no
3.15	Classifications, analyst inputs	`classifications`, `analyst_inputs`	same	no

"Required" means that the run cannot form a view of the issuer without it. Section 3 gives the exact effect of each gap.

3 The kinds

3.1 Issuer identity (`Issuer`)

Fields	`ticker`, `gvkey` (the key of the financials, or None), `cik` (the key of the filings, or None), `name`.
Time stamps	None. Identity is static reference data.
Used by	Every step. The process calls `view.issuer(ticker)` first.
When missing	`DataUnavailable`. Step 1 fails, the run prints the reason, and the issuer drops out of the run.

3.2 Quarterly financials (`IssuerFinancials`)

Fields	Key: the issuer's `gvkey`. One record per quarter and per version. USD millions, flows for the quarter, balances at the quarter end. • Income: `revenue`, `cogs`, `ebitda_reported`, `ebitda_adj_company`, `ebitda_covenant`, `depreciation`, `rent_expense`. • Nonrecurring items: tuple of `NonRecurringItem(name, amount, recurs, cash)`. • Cash flows: `operating_cash_flow`, `capex_total`, `capex_maintenance`, `cash_interest`, `cash_taxes`. • Working capital: `inventory`, `receivables`, `payables`. • Liquidity: `cash`, `revolver_commitment`, `revolver_drawn`, `borrowing_base` (infinity when none), `letters_of_credit`. • Debt: `debt_current`, `debt_long_term`, `maturity_schedule` (five yearly amounts), `pension_underfunded`, `guarantees_weak`. `source` is provenance text.
Time stamps	`as_of` is the quarter end. `available_at` is the first moment that version of the quarter was public. A restatement is a new version. The view returns every quarter in its latest version public at the decision time.
Used by	Framework F3 normalisation (step 3: LTM table, earnings-quality tests, margin trend, FCF). F4 liquidity and the scenario start point (methodology 5.1). F5 coverage. G3 monitoring (step 12).
When missing	Step 3 runs with no quarters, so the LTM figures are empty and the memo lists open questions. The scenario start point needs at least one quarter. With none, the run stops with an error. This is a known gap.

3.3 Filing facts (`IssuerFacts`)

Fields: `issuer_ticker` and `values`, a dict of `name: (value, source text)`. The source text travels to the memo. Time stamps: `as_of` and `available_at` are the 10-Q acceptance time. Used by: step 1 inputs, F2 framing, methodology 4.7 clocks, F5, the scenario engine. When missing: `DataUnavailable` stops step 1 and the issuer drops out of the run. A missing single value is None with a source text that says why, and the memo shows it as an open question. The names that the analyst reads:

Name	Unit	Meaning
`ticker`, `name`, `cik`, `gvkey`	text	identity
`q`, `k`	text	accession of the latest 10-Q and 10-K (`k` may be None)
`q_acceptance`, `k_acceptance`	time	their acceptance times
`balance_sheet_date`	date	the 10-Q balance-sheet date
`ltm_ebitda`, `ltm_revenue`	USD m	last-twelve-months totals
`run_rate_revenue`	USD m a year	latest quarter x 4
`interest_rate`	decimal	cash interest / debt
`annual_lease_cost`	USD m a year	operating lease cost
`lease_wavg_term`	years	check only
`uncommenced_window`, `uncommenced_term`	years	signed leases not yet started
`debt_tail_years`	years	length of the "thereafter" debt bucket
`rpo_total`	USD m	remaining performance obligation
`rpo_windows`	(start, length, share)	timing of the RPO, years and decimal
`rpo_tail_years`	years	length of the RPO remainder
`purchase`	(USD m, years)	purchase commitments without a ladder
`archetype`	A1 to A7	framework F2 archetype, from the analyst
`rating`, `recourse`, `scenario_extra_lease`	text or None	analyst judgement
`available_at`	time	the latest release among the inputs

3.4 Filing list (`Filing`)

Fields	`issuer_ticker`, `form` (for example "10-Q"), `accession`.
Time stamps	`as_of` and `available_at` are the acceptance time.
Used by	Framework F11 events (step 12 estimates the next results date from the filing cadence). The walk-forward audit.
When missing	An empty list. Step 12 then has no results-date event.

3.5 Balance sheet and schedules (`BalanceSheet`, `Ladder`)

Fields	One record per filing (the 10-Q and the 10-K of the facts). USD millions, NaN when the filing does not state it. • `debt`, `debt_source`: total financial debt and the tag or rule that gave it. • `operating_lease_liability`, `finance_lease_liability`, `cash`. • `revolver_capacity`: unused or maximum credit-line capacity. None when the filing states none. • `ladders`: `operating_lease`, `finance_lease`, `debt`, `purchase`, each a `Ladder` or None. `Ladder.amounts` are bucket amounts (the last is "thereafter"). `first_length` is the first bucket's length in years. The other buckets are one year. `total` and `reconciles` check the sum. • `lease_not_commenced`: (total USD m, shortest term years, longest term years). • `customer_shares`: named customer to share of revenue, decimal.
Time stamps	`as_of` is the balance-sheet date. `available_at` is the acceptance time.
Used by	Methodology 4.7 clocks (obligation ladders). F5 leverage (debt, leases, cash). The F4 funding gap and the scenario engine (debt lines, revolver).
When missing	`DataUnavailable` for the 10-Q stops step 1 for the issuer. A missing ladder is None. Then the debt ladder comes from the balance-sheet total spread over ten years, and the memo states that assumption.

3.6 Filing text (`FilingText`)

Fields	`issuer_ticker`, `accession`, `text` (plain text of the primary document).
Time stamps	`as_of` and `available_at` are the acceptance time.
Used by	F2 "what it sells" (the first two sentences of Item 1). F5 covenant levels (step 5).
When missing	The business line is empty, and the memo says "no filing text". The covenant table stays open.

3.7 First-reported cash flows (`ReportedCashFlow`)

Fields	USD millions for the quarter: `operating_cash_flow`, `capex`, `interest_paid`, `taxes_paid`, and the `accession` that stated them.
Time stamps	`as_of` is the quarter end. `available_at` is the acceptance time of the first filing that reported the quarter.
Used by	Step 3 only. It fills a quarter whose cash flows the financials leave blank (methodology 3.2).
When missing	The quarter stays blank, and the LTM uses the rule in `hy.state.ltm_total`.

3.8 Equity market value (`MarketValue`)

Fields	`issuer_ticker`, `value` (price x shares, USD millions), `source`.
Time stamps	`as_of` is the quarter end of the price. `available_at` is the report date.
Used by	F7.7 valuation (step 8: market TEV, debt / market TEV). Kricheff and S&P ratios (step 5). Estimate E9.
When missing	The market value is NaN with the reason. Those ratios are then NaN.

3.9 Bond terms (`Bond`)

Fields	`cusip`, `issuer_ticker`, `coupon` (decimal), `maturity` (date), `seniority`, `fixed`, `convertible`, `grade` ("H" for high yield). The domain, not the source, keeps the fixed, non-convertible, senior unsecured or secured bonds.
Time stamps	None. Terms are static between issue and redemption.
Used by	Step 1 bond curve. The F5 capital structure table. F4 refinancing (coupons of bonds due inside 27 months).
When missing	An empty list. Step 1 is partial with an open question. Steps 4 to 15 do not run for the issuer, because it has no spread.

3.10 Bond observations (frame, `BOND_OBS_COLUMNS`)

Fields	In this order: `cusip`, `date` (trade day), `price` (per 100 face, volume-weighted), `yield` (decimal, volume-weighted), `n_trades`, `par_volume` (USD), `available_at`.
Time stamps	`date` is the trade day. `available_at` is when the day's trades became public (TRACE: the next day). The view asks for the 180 days before the decision and keeps rows public by then.
Used by	Step 1 latest snapshot (10 days), G-spreads and the issuer curve, the 5-year spread, the pair gap history (methodology 7.5), the recent-issue point of F4.
When missing	An empty frame works like 3.9. A source error stops step 1 for the issuer.

3.11 Treasury par curve (`Curve`)

Fields	`tenors` (years) and `yields` (decimal par yields), one value per tenor. NaN marks a tenor with no quote. Two reads: `curve(on)` gives the latest curve public at `on`. `curves(start, end)` gives every daily curve in the range, which the view returns as a frame (`curve_history`).
Time stamps	`as_of` is the curve date. `available_at` is when it was published (US Treasury: the next day).
Used by	G-spreads, cash and Treasury returns (step 15), and the pair gap history (step 9b).
When missing	The run needs the current curve and stops without it. An empty history leaves the pair gap persistence as NaN.

3.12 HY index level (`IndexLevel`)

Fields	`spread`: the market's high yield spread level, decimal. `distress`: the share of high yield bonds wider than 1,000 bp, decimal. `name` says how the level was made. The one index rule is `hy.state.hy_index_level` and the one distress rule is `hy.state.distress_ratio`. The TRACE adapter applies both to its benchmark bonds. Another source may supply an index OAS directly, for example ICE BofA H0A0.
Time stamps	`as_of` is the market date. `available_at` is when it was public.
Used by	The F6 phase vote (now, 3 months ago, and once a year for 5 years). The fair spread fallback (methodology 7.2). DTS hedges (steps 9 and 15). Estimate E0. The macro paths.
When missing	A missing past snapshot is NaN in the phase table, and the vote uses the others. The current level is required.

3.13 Macro forecasts (`ForecastRow`) and their status

Fields	`source`, `variable`, `horizon_q` (quarters ahead, 0 to 8), `vintage`, `available_at`, `point`, `q10`, `q50`, `q90`, `method`. Variables: `gdp_growth`, `cpi`, `unemployment`, `policy_rate`, `y2`, `y10`, `sloos_tightening`, `hy_spread`, `distress_ratio`, all decimals. `forecast_status` returns one row per forecast source: `source`, `status`, `last_vintage`, `last_available_at`, `rows`, `rows_after_decision_time`. The run writes it to `_run.json` as its audit trail.
Time stamps	`vintage` is the forecast date. `available_at` is its release.
Used by	Methodology 5.4 macro paths (`hy.macro.build_paths`). The F6 phase vote (SLOOS). The scenario engine.
When missing	A source with no rows is "stubbed". The path builder then uses its fallback order and logs a stated assumption.

3.14 Peer panels (frames)

Every panel has an `available_at` column. The view drops rows that were not public at the decision time.

Panel	Columns and units	Used by
`bond_panel`	`date` (month end), `cusip`, `gvkey`, `years`, `g_spread` (decimal), `available_at`. The backtest also reads `price`, `yield`, `coupon`, `maturity`, `mod_dur`, `tsy_yield`, `bid_ask_pts`, `n_trades`, `par_volume`	step 9 peers, ESP and E13 (7.2, 7.4), and the backtests
`leverage`	`date`, `gvkey`, `leverage` (x), `ltm_ebitda`, `debt` (USD m), `available_at`	peer cells and the implied rating class
`gics`	`gvkey`, `gsector` (two digits), `indfrom`, `indthru`, `available_at`	the peer sector
`ratings`	`gvkey`, `datadate`, `splticrm` (S&P letter), `available_at`	the actual rating class
`annual_ebitda`	`gvkey`, `datadate`, `fyear`, `oibdp`, `debt` (USD m), `available_at`	SPiDER, E15
`equity_monthly`	`gvkey`, `datadate` (month end), `ret` (monthly total return, decimal), `available_at`	OneScore, E16

When missing: without `bond_panel`, `leverage`, `gics` or `ratings`, step 9 has no peer cell. The fair spread then falls back to the HY index, and the memo says so. Without `annual_ebitda`, SPiDER

(E15) is NaN. Without `equity_monthly`, OneScore (E16) is NaN, and ESP carries its weight.

3.15 Classifications and analyst inputs

`Classification` gives the GICS sector and rating class per issuer, valid from `as_of`. `AnalystInput` is the analyst's YAML per issuer. These are part of the protocols, but the process does not read them through the view today. The facts adapter applies the analyst YAML, and the peer step reads the `gics` and `ratings` panels.

3.16 Realised outcomes (not a new kind)

The walk-forward scores each prediction against what happened next. `hy.data.outcomes.RealisedOutcomes(source, decision_time)` reads bond observations, curves and the HY index public after the decision. It uses the same source methods as above. It refuses a time before the decision, and no step that forms a prediction imports it. A test checks this.

4 How to plug in a new source

1. Write one class, for example `MySource`, that implements every protocol in `hy/data/source.py`: `IssuerSource`, `FilingSource`, `BondSource`, `MarketSource`, `EquitySource`, `ReferenceSource`, `ForecastSource`, `AnalystSource` and `PanelSource`.
   - Return the record types of `hy/data/records.py` with the units of section 1.
   - Stamp every record with `as_of` and `available_at`. Never stamp a value earlier than its real release.
   - Raise `DataUnavailable` for an item that you do not have. Do not return a zero for a missing amount.
   - Keep vendor field names inside your class. `FakeSource` in `hy/data/sources.py` is a short model to copy.
2. Pass it to the view: `DataView(MySource(...), decision_time)`.
3. Run the process: `process.run(tickers, end, pairs, view=DataView(MySource(...), decision))`. A run at `end` decides at `end` plus one day.
4. Check the connector:
   - Run `tests/test_pipeline_fake_source.py`. It shows the shape of every kind and runs the whole analyst on made-up data with the network blocked.
   - Run the suite: `python3 -m pytest -q`.
   - Take a golden snapshot on the new machine (`scripts/golden_check.py snapshot`), then run `check` after each change. The numbers will differ from this machine's numbers because the data differs. They must not move between your own runs.
5. Set `HY_DATA_ROOT` for the derived files that stay as files: the backtest summaries (`summary_full.json`, `results_h*.parquet`, `peer_signals_*.parquet`) and the run outputs. Without them, step 14b uses the v0 slope of spec S14b.

5 What stays outside the contract

- `scripts/backtest_alpha.py` and `scripts/backtest_clocks.py` build the warehouse panels from TRACE, Compustat and SEC data. They are panel builders for this warehouse. Another machine supplies the panels through `panel()` instead.
- The pilot subsets (`panel_pilot`, `leverage_pilot`) are warehouse files that `hy.data.history.backtest_panel` reads by tag.

- `scripts/rv_pair.py` keeps a WRDS query for the benchmark band of its figure. The report is display only.
- `scripts/walkforward.py` reads 8-K item codes from the EDGAR cache for its event marks. They are display only.