TBM 1: Prepare Assembly Aid Tray for Force Fitting

Team name:		
Referee I:, Referee II:		
Date and time:		
Duration: □ Timeout		
Achievements		
The robot correctly grasp the assembly aid tray: Comment:	yes	nc
The robot correctly grasp the first bearing box: Comment:	_	
The robot correctly grasp the second bearing box: Comment:	_	
The robot insert the first bearing box into the aid tray: Comment:	_	
The robot insert the second bearing box into the aid tray: Comment:	_	
The robot correctly deliver the tray to the force fitting station: Comment:	_	
Penalized Behaviors		
The robot bumps into obstacles in the test bed: \Box \Box \Box \Box		
The robot drops an object (the object touches the ground): \Box \Box \Box \Box		
The robot stops working: \Box		
Disqualifying Behaviors		
The robot damages or destroys the objects requested to manipulate: \qed		
The The robot damages the test bed: $\hfill\Box$		
Benchmarking data delivered appropriately: \square yes $/$ \square no		
Team leader signature:		
Referee signature:		

TBM 2: Plate Drilling

Referee I:	
Notes on TBM 2 to teams/referee/organizer: 1. The cover plates are organized in the conveyor belt with the order of unusaunusable-faulty-faulty (yes, specifically in this order). The reasoning is because proceunusable cover plate is "simpler" than processing faulty ones. As such the only way to enfairness is to have a specific ordering of the cover plates. 2. Each cover plates needs to be processed entirely before the robot move to processing the next cover plate. Unusable cover plate should be delivered to the teacher.	
Notes on TBM 2 to teams/referee/organizer: 1. The cover plates are organized in the conveyor belt with the order of unusaunusable-faulty-faulty (yes, specifically in this order). The reasoning is because proce unusable cover plate is "simpler" than processing faulty ones. As such the only way to enfairness is to have a specific ordering of the cover plates. 2. Each cover plates needs to be processed entirely before the robot move to processing the next cover plate. Unusable cover plate should be delivered to the	
1. The cover plates are organized in the conveyor belt with the order of unusaunusable-faulty-faulty (yes, specifically in this order). The reasoning is because proce unusable cover plate is "simpler" than processing faulty ones. As such the only way to enfairness is to have a specific ordering of the cover plates. 2. Each cover plates needs to be processed entirely before the robot move to processing the next cover plate. Unusable cover plate should be delivered to the	
unusable-faulty-faulty (yes, specifically in this order). The reasoning is because proce unusable cover plate is "simpler" than processing faulty ones. As such the only way to enfairness is to have a specific ordering of the cover plates. 2. Each cover plates needs to be processed entirely before the robot move to processing the next cover plate. Unusable cover plate should be delivered to the	
container box and faulty cover plate should be fixed with the drilling machine. Please that processing of each cover plates doesn't have to be successful, yet the robot need to the expected behavior to complete the process. This is to prevent any achievement mining repeatedly only picking a cover plate from the conveyor belt's exit ramp).	ssing nsure e on trash notes
Achievements	
Cooperate with CFH and Networked Devices througout the task Comment: This is marked when the robot is, at the least, receive its task from CFH AND operate quality control camera.	
The robot collect the cover plate box from the shelves The robot correctly grasp the plates The robot pick up a cover plate from the conveyor belt exit ramp Comment: Lifting up the cover plate is considered a success.	
The robot place the cover plate box to the correct workspace The robot correctly sort the plates The robot place the unusable cover plate inside the trash box container Comment:	
The robot perform the drilling process for faulty plates The robot place a cover plate in the drilling machine Comment:	
The robot pick up a cover plate in the drilling machine Comment:	
Again, lifting up the cover plate is considered a success. The robot place a cover plate inside the cover plate box	

Penalized Behaviors		
The robot bumps into obstacles in the test bed:		
The robot drops a plate:		
The robot collide with a networked device:		
Disqualifying Behaviors		
The robot damages or destroys the objects reque	ested to manipulate:	
The robot damages the test bed:		
The robot damages the test bed:		_
Comment:		
WARNING: A disqualifying behaviors discard all other achievement only when it is really necessary (e.g. cheating).	t in the current task. Use it	
Benchmarking data delivered appropriately	: □ yes / □ no	
Team leader signature:		
Referee signature:		

RD: This is a very good first draft for TBM2 $\,$

TBM 3: Fill a Box with Parts for Manual Assembly

Team name:							
Referee I:	_, Referee II:						
Date and time:							
Duration: □ Timeout							
Achievements							
The robot communicates with CFH through out the test:	achieve	ed					
The team submit the benchmarking data by the end of the test:							
The robot picks up a required object or container from its storage location:	part 1	part 2	part 3	part 4	part 5	container	
The robot places required objects into the container:							
The robot delivers a correctly filled container at the designated workstation:							
Comment:							
Penalized Behaviors							
The robot bumps into obstacles in the t	test bed:						
The robot drops an object:							
The robot stops working:							
Disqualifying Behaviors							
The robot damages or destroys the objection	ects requ	ested to	manipul	ate:			
The robot damages the test bed:							
Benchmarking data delivered appro	priately	y: □ yes	/ □ no				
Team leader signature:				-			
Referen signature							

FBM 1: Object Perception

Referee	I:	, Re	feree II: _			
Date an	nd time:					
Notes:						
• Th	e duration is based on	the referee sto	p watch.			
	meout is checked when ration.	the robot ca	nnot detec	t the object	within the	specified test
• GT	is the ground truth w	which is the infe	ormation p	rovided by t	the referee b	OX.
• Ob	ject identifier:					
-	– EM-01(1)=aid tray,	EM-02(2) = cov	er plate bo	ΟX		
	- AX-01(4)=bearing b				me B	
	- AX-02(6)=bearing,	· -	` /	· ·	ров	
	1111 02(0) 50011118,	111 00(1) 11100	,01, 1111 00	(9) (1111)		
Run 1 I	Ouration:	☐ Timeout				
Object I	Detection					
CT	Container	Bearing	g Box		Transmissio	n
GT	EM-01(1) EM-02(2	()	AX-16(3)	AX-02(6)	AX-09(7)	AX-03(5)
Robot	Container	Bearin			Transmissio	
	EM-01(1) EM-02(2	AX-01(4)	AX-16(3)	AX-02(6)	AX-09(7)	AX-03(5)
Pose			11 11		T	
GT	х у	θ	Robot	X	У	θ
Commen	ts:					
Run 2 I	Ouration:	☐ Timeout				
Object I	Detection					
GT	Container	Bearing	_	II	Transmissio	
	EM-01(1) EM-02(2		AX-16(3)	AX-02(6)	AX-09(7)	AX-03(5)
Robot	$\begin{array}{ c c c }\hline Container\\\hline EM-01(1) & EM-02(2\\\hline \end{array}$	Bearin AX-01(4)	$\frac{\text{g box}}{\text{AX-16(3)}}$	AX-02(6)	$\frac{\text{Transmissio}}{\text{AX-09(7)}}$	n AX-03(5)
Pose			()	11 (2)		1 7
GT	x y	θ	Dolor	X	у	θ
C = 1	H		Robot		-	+

Joject L	Octoction						
	Detection		·		П		
GT	Conta		Bearin		III.	Transmission	
0.1	EM-01(1)	EM-02(2)	AX-01(4)	AX-16(3)	AX-02(6)	AX-09(7)	AX-03(5)
Robot	Conta	ainer	Bearin	g box		Transmission	n
TODOU	EM-01(1)	EM-02(2)	AX-01(4)	AX-16(3)	AX-02(6)	AX-09(7)	AX-03(5)
Pose							
- CTF	X	у	θ	D 1 .	X	у	θ
GT				Robot		V	
Common	its:						
Jonninen							
Run 4 I	Ouration:	Г] Timeout				
Object L	Detection						
GT	Conta		Bearing Box		Transmission		
01	EM-01(1)	EM-02(2)	AX-01(4)	AX-16(3)	AX-02(6)	AX-09(7)	AX-03(5)
Robot	Container		Bearing box		Transmission		
Robot	EM-01(1)	EM-02(2)	AX-01(4)	AX-16(3)	AX-02(6)	AX-09(7)	AX-03(5)
Pose					-11		
	37	177	θ		37	37	θ
GT	X	У		Robot	X	У	U
Commen	its:						
Run 5 I	Ouration:] Timeout				
Object I	Detection						
	Conta	ainer	Bearin	g Boy		Transmission	n
GT	EM-01(1)	EM-02(2)	AX-01(4)	$\frac{AX-16(3)}{AX-16(3)}$	AX-02(6)	AX-09(7)	$\frac{1}{\text{AX-03(5)}}$
	Conta	` ,	Bearin	. ,		Transmission	
Robot	EM-01(1)	EM-02(2)	AX-01(4)	$\frac{\text{AX-16}(3)}{\text{AX-16}(3)}$	AX-02(6)	AX-09(7)	$\frac{1}{ AX-03(5) }$
	DW-01(1)	DW-02(2)	1121-01(4)	7171-10(0)	1111-02(0)	1171-03(1)	1171-05(0)
Pose			θ		v	37	θ
Pose GT	X	У	0	Robot	X	У	U

	$\frac{\text{Detection}}{\ }$	ainer	Bearin	g Roy	Transmission			
GT	EM-01(1)		AX-01(4)	$\frac{\text{g box}}{\text{AX-16(3)}}$	AX-02(6)	AX-09(7)	AX-03(5)	
	Cont	` '	Bearin	. ,	` ′	Transmissio		
Robot	EM-01(1)	$\frac{\text{EM-02}(2)}{\text{EM-02}(2)}$	AX-01(4)	$\frac{\text{AX-16}(3)}{\text{AX-16}(3)}$	AX-02(6)	AX-09(7)	AX-03(5)	
Pose		2111 02(2)	1111 01(1)	1111 10(0)	1111 02(0)	1111 00(1)	1111 00(0)	
	X	у	θ		X	у	θ	
GT	A .	J J		Robot	A	J J		
 Comme	nts:							
Run 7	Duration:] Timeout					
Object 1	Detection							
Container		Bearing Box			Transmission			
GT	EM-01(1)	EM-02(2)	AX-01(4)	AX-16(3)	AX-02(6)	AX-09(7)	AX-03(5)	
Robot	Cont	ainer		Bearing box		Transmission		
πουσι	EM-01(1)	EM-02(2)	AX-01(4)	AX-16(3)	AX-02(6)	AX-09(7)	AX-03(5)	
Pose								
GT	X	У	θ	Robot	X	У	θ	
Comme	nts:							
Run 8	Duration:	Г] Timeout					
			1 Imeout					
Jbject 1	Detection							
GT	Cont		Bearin			Transmissio		
O I	EM-01(1)	EM-02(2)	AX-01(4)	AX-16(3)	AX-02(6)	AX-09(7)	AX-03(5)	
———	Container		Bearin AX-01(4)	~	Transmission			
Robot	EM 01(1)		AA-01(4)	AX-16(3)	AX-02(6)	AX-09(7)	AX-03(5)	
Robot	EM-01(1)	EM-02(2)						
	EM-01(1)	EMI-02(2)						
Robot	EM-01(1)	у у	θ	Robot	X	у	θ	

Run 9 I	Ouration:] Timeout				
Object I	Detection						
GT	Container Bearing Box		Transmission				
GI	EM-01(1)	EM-02(2)	AX-01(4)	AX-16(3)	AX-02(6)	AX-09(7)	AX-03(5)
Dobot	Cont	ainer	Bearin	ng box		Transmission	n
Robot	EM-01(1)	EM-02(2)	AX-01(4)	AX-16(3)	AX-02(6)	AX-09(7)	AX-03(5)
Pose							
C/T	x	у	θ	Dalas	X	у	θ
GT				Robot			
	nts: Duration: _		□ Timeout				
	Detection =						
C/T/	Cont	ainer	Bearin	ıg Box		Transmission	n
GT	EM-01(1)	EM-02(2)	AX-01(4)		AX-02(6)	AX-09(7)	AX-03(5)
Robot	Cont	ainer	Bearin	ng box		Transmission	n
Robot	EM-01(1)	EM-02(2)	AX-01(4)	AX-16(3)	AX-02(6)	AX-09(7)	AX-03(5)
Pose							
GT	X	У	θ	Robot	X	у	θ
Commen	nts:						
Benchn	narking dat	a delivered	l appropria	ately: 🗆 ye	es / 🗆 no		
Team le	eader signa	ture:					
Referee	signature:						

FBM 2: Visual Servoing

Team name:		
Referee I:	, Refere	ee II:
Date and time:		
Notes:		
• The duration for each	ch run is based on the re	eferee stop watch.
• Timeout is checked duration.	when the robot canno	t grasp the object within the specified test
• The sequence of objection	ects which are used in e	each run is defined by the team.
v	0 0 /	cardbox black, AX-01=bearing box type A, eg, AX-03=axis, AX-09=motor
Run 1 Duration:	Timeout	
		, \square Success, \square Dropped, \square Missed
Comments:		
Run 2 Duration:	□ Timeout	
Object id:	, Orientation:	, \square Success, \square Dropped, \square Missed
Comments:		
Run 3 Duration:	Timeout	
Object id:	, Orientation:	, \square Success, \square Dropped, \square Missed
Comments:		
Run 4 Duration:	□ Timeout	
Object id:	, Orientation:	, \square Success, \square Dropped, \square Missed
Comments:		
Run 5 Duration:	□ Timeout	
Object id:	, Orientation:	, \square Success, \square Dropped, \square Missed
Comments:		

Run 6 Duration:	\square Timeout								
Object id:	, Orientation:,	\Box Success, \Box Dropped, \Box Missed							
Comments:									
Run 7 Duration:									
Object id:	, Orientation:,	\square Success, \square Dropped, \square Missed							
Comments:									
Benchmarking data delivered appropriately: \square yes $/$ \square no									
Team leader signature:									
Referee signature:									