DBMS TASK 7

Loading Example Records into the Database

Purpose

Populate each table with example records so that the database can be tested using realistic customer, product, order, order-line, and payment scenarios.

A. Customer Records

```
USE OnlineShoppingDB;

INSERT INTO Customers (CustomerName, Email, Phone, Address) VALUES
('Arun Prabu', 'arun@example.com', '9876500001', 'Bengaluru'),
('Rahul Kumar', 'rahul@example.com', '9876500002', 'Chennai'),
('Priya Sharma', 'priya@example.com', '9876500003', 'Hyderabad'),
('Sneha Reddy', 'sneha@example.com', '9876500004', 'Mysuru'),
('Karthik Raj', 'karthik@example.com', '9876500005', 'Coimbatore');
```

B. Product Catalogue

```
INSERT INTO Products (ProductName, Category, Price, Stock) VALUES
('Laptop', 'Electronics', 55000.00, 12),
('Headphones', 'Accessories', 1500.00, 30),
('Smartphone', 'Electronics', 25000.00, 18),
('Keyboard', 'Accessories', 800.00, 25),
('Office Chair', 'Furniture', 4500.00, 10);
```

C. Order Headers

```
INSERT INTO Orders (CustomerID, OrderDate, Status) VALUES
(1, '2026-10-01', 'Delivered'),
(2, '2026-10-02', 'Processing'),
(3, '2026-10-03', 'Delivered'),
(1, '2026-10-04', 'Shipped'),
(4, '2026-10-05', 'Pending'),
(5, '2026-10-06', 'Delivered');
```

D. Items Included in Each Order

```
INSERT INTO OrderDetails (OrderID, ProductID, Quantity, UnitPrice) VALUES
(1, 1, 1, 55000.00),
(1, 2, 2, 1500.00),
(2, 3, 1, 25000.00),
(2, 4, 2, 800.00),
(3, 2, 1, 1500.00),
(4, 5, 1, 4500.00),
(5, 3, 1, 25000.00),
(6, 4, 1, 800.00);
```

E. Payment Entries

```
INSERT INTO Payments (OrderID, PaymentMethod, Amount, PaymentStatus) VALUES
(1, 'Credit Card', 58000.00, 'Paid'),
(2, 'UPI', 26600.00, 'Paid'),
(3, 'Debit Card', 1500.00, 'Paid'),
(4, 'UPI', 4500.00, 'Paid'),
(5, 'Cash on Delivery', 25000.00, 'Pending'),
(6, 'Credit Card', 800.00, 'Paid');
```

F. Review the Inserted Data

```
SELECT * FROM Customers;
SELECT * FROM Products;
SELECT * FROM Orders;
SELECT * FROM OrderDetails;
SELECT * FROM Payments;
```

The inserts assume a clean database in which generated IDs begin at 1. If records already exist, check the generated IDs and adjust the dependent inserts before executing them.

Include screenshots of the actual Result Grid for each table.

Closing Remarks

The example records provide a consistent test dataset across all five tables. They can now be used to check filtering, aggregate calculations, joins, and subqueries.