

Inhaltsverzeichnis

1. Einführung und Ziele	3
1.1. Aufgabenstellung	3
1.2. Qualitätsziele	5
1.3. Stakeholder	6
2. Randbedingungen	7
2.1. Technische Randbedingungen	7
2.2. Organisatorische Randbedingungen	8
2.3. Konventionen	9
3. Kontextabgrenzung	10
3.1. Fachlicher Kontext	10
3.2. Technischer Kontext	12
4. Lösungsstrategie	13
5. Bausteinsicht	14
5.1. Whitebox Gesamtsystem	14
5.2. Ebene 2	16
5.3. Ebene 3	16
6. Laufzeitsicht	22
7. Verteilungssicht	23
7.1. Infrastruktur Ebene 1	23
7.2. Infrastruktur Ebene 2	23
8. Querschnittliche Konzepte	24
8.1. <Konzept 1>	24
8.2. <Konzept 2>	24
8.3. <Konzept n>	24
9. Entwurfsentscheidungen	25
10. Qualitätsanforderungen	26
10.1. Qualitätsbaum	26
10.2. Qualitätsszenarien	26

11. Risiken und technische Schulden	27
12. Glossar	28
13. Anhang.	29
13.1. Apollo	29
13.2. Arc42	29
13.3. docToolChain	29

Über arc42

arc42, das Template zur Dokumentation von Software- und Systemarchitekturen.

Erstellt von Dr. Gernot Starke, Dr. Peter Hruschka und Mitwirkenden.

Template Revision: 7.0 DE (asciidoc-based), January 2017

© We acknowledge that this document uses material from the arc42 architecture template, <http://www.arc42.de>. Created by Dr. Peter Hruschka & Dr. Gernot Starke.



Diese Version des Templates enthält Hilfen und Erläuterungen. Sie dient der Einarbeitung in arc42 sowie dem Verständnis der Konzepte. Für die Dokumentation eigener System verwenden Sie besser die *plain* Version.

1. Einführung und Ziele

Dieser Abschnitt führt in die Aufgabenstellung ein und skizziert die Ziele, die Apollo Auto verfolgt.

1.1. Aufgabenstellung

1.1.1. Was ist Apollo Auto?

Apollo ist eine hochleistungsfähige, flexible Architektur, die die Entwicklung, das Testen und den Einsatz von autonomen Fahrzeugen beschleunigt. Apollo Auto bietet unter anderem Lösungen für Valet Parking, V2X-Kommunikation und intelligente Lichtsignalanlagen.

1.1.2. Wesentliche Features:

- Valet Parking
 - Software- und Hardware-Integrationslösung. Multifusionslösung bestand aus Fahrzeug, Cloud, HD-Karte und Parkplätzen
 - Bietet hochwertige Dienstleistungen, wie automatische Parkplatzerkennung und autonomes Parken, für Kunden.
- V2X-Kommunikation
 - Interaktionslösung für intelligente Fahrzeuginfrastruktur
 - Apollo V2X umfasst ein intelligentes Transportsystem für Fahrzeug Straßendatenerfassung und intelligente Verarbeitungsanalyse, Verkehrssicherheit und -effizienz
 - Wahrnehmung aller Verkehrsteilnehmer im Sichtfeld und die bereitgestellten straßenseitigen Sensorinformationen können für die Entscheidungsfindung beim autonomen Fahren auf hohem Niveau verwendet werden
 - Wahrnehmung von Verkehrsteilnehmern ausserhalb des Sichtfeldes

- Bietet einen vollständigen, kontinuierlichen, multimodalen Datendienst mit niedriger Latenz für L4-Autopilot-Fahrzeuge, die in mehreren Szenarien getestet wurden
- Durch die permanente dynamische Erfassung von Verkehrsinformationen und die Cloud-Integration, wird eine weltweite optimale kollaborative Steuerungsfunktionen für Verkehrsteilnehmer und Verkehrsmanagement erreicht
 - Smart Traffic Signals
- Holographisches Wahrnehmen und Verstehen, basierend auf dem holografischen Wahrnehmungs- und Erkennungssystem
- Status von Fußgängern und Fahrzeugen auf jeder Fahrspur genau erkennen und die Leistung des aktuellen Verkehrsflusses wie Volumen, Warteschlangenlänge, Verspätungen usw.
- Vollständige raum-zeitliche Ableitung und Entscheidungsfindung
- Echtzeitsteuerung der gesamten Szene
- Reduzierung der durchschnittlichen Wartezeit um 20-30% während der Rush Hour
 - Robotaxi
- Die Robotaxis, die aus Chinas erstem werkseitig installierten L4-Passagier-Fahrzeug sind zur Zeit auf öffentlichen Straßen im Testbetrieb
- Sie werden in Kooperation von Baido und FAW an einer gemeinsamen Produktionsline hergestellt
 - Minibus
- Die Minibusse ermöglichen ebenfalls autonomes Fahren der Stufe 4
- Funktionen sind unter Anderem Hinderniserkennung und -vermeidung, zu einem Zielort Fahren und Kreuzungen überqueren

1.2. Qualitätsziele

Die folgende Tabelle beschreibt die zentralen Qualitätsziele von DokChess, wobei die Reihenfolge eine grobe Orientierung bezüglich der Wichtigkeit vorgibt.

Qualitätsziel	Motivation und Erläuterung
<i>Zugängliches Beispiel (Analysierbarkeit)</i>	Apollo Auto ist eine offene Plattform, daher ist es wichtig, dass sich neue Entwickler möglichst schnell in die Architektur, Entwurf und Implementierung einarbeiten können
<i>Echzeitsteuerung von einzelnen Fahrzeugen und Verkehrströmen</i>	Apollo Auto übernimmt zuverlässig und sicher die autonome Steuerung von Fashrzeugen auf Level 4
<i>Echtzeit Umfelderkennung</i>	Für die Steuerung von Fahrzeugen wird ein Modell des Umfelds benötigt. Aus den Sensoprdaten wird ein digitales Abbild des Fahrweges, von beweglichen und unbeweglichen Hindernissen und von Signalen geschaffen
<i>Prediction</i>	Um die Fahrsicherheit weiter zu erhöhen, wird auf die Sensor- und Zustandsdaten von anderen Verkehrsteilnehmern in Echtzeit zugegriffen

1.3. Stakeholder

Die folgende Tabelle stellt die Stakeholder von Apollo Auto und ihre jeweilige Intention dar.

Rolle	Interesse, Bezug
<i>Softwarearchitekten</i>	Wollen ein Gefühl bekommen, wie Architekturdokumentation für ein konkretes System aussehen kann. Möchten sich Dinge (z.B. Form, Notation) für Ihre tägliche Arbeit abgucken. Gewinnen Sicherheit für Ihre eigenen Projekte.
<i>Entwickler</i>	Nehmen Architekturaufgaben im Team wahr. Brauchen ein generelles Verständnis für die Architektur.
<i>OEM & Lieferanten</i>	Entwickeln neue Produkte auf Grundlage von Apollo Auto. Wollen Anregungen für eigene Produkte finden.
<i>Gesetzgeber & Genehmigungsbehörden</i>	Entwickeln einen gesetzlichen Rahmen zur Zulassung von fahrerlosen Fahrzeugen im öffentlichen Straßenverkehr. Etablieren Prüfvorschriften und Tests für Genehmigungsverfahren.
<i>Universitäten</i>	Entwickeln eigene Forschungsprojekte auf Grundlage von Apollo Auto. Wollen Anregungen für weitere Forschungsprojekte und studentische Arbeiten finden.
<i>Studenten</i>	Interessieren sich aufgrund ihres Studiums für die verschiedenen Aspekte einer Architekturdokumentation. Setzen eigene Projekte (z.B. Masterarbeit) zum Thema autonomes Fahren mit Apollo Auto um. Schreiben eine Architekturdokumentation zu Apollo Auto.

2. Randbedingungen

Beim Einsatz von Apollo sind verschiedene Randbedingungen zu beachten. Dieser Abschnitt stellt sie dar und erklärt auch – wo nötig – deren Motivation.

2.1. Technische Randbedingungen

- Für den Einsatz von Apollo Auto wird eine anspruchsvolle Hardwareausstattung benötigt. Eine Umsetzung mit einem marktüblichen Standard-Notebook allein ist nicht möglich.
- Es wird ein Fahrzeug benötigt, dass mit By-Wire-Systemen ausgestattet ist, zum Beispiel Brake-by-Wire, Steering-by-Wire, Throttle-by-Wire oder Shift-by-Wire (Apollo wird derzeit auf Lincoln MKZ getestet).
- Ein Rechner mit einem 4-Kern-Prozessor und mindestens 8 GB Speicher (16 GB für Apollo 3.5 und höher)
- Ubuntu 18.04
- Zusätzlich wird eine umfangreiche Sensorik benötigt die Bild- und Abstandsinformationen aus dem Umfeld aufnehmen
- Arbeitskenntnisse über Docker

2.2. Organisatorische Randbedingungen

Randbedingung	Erläuterungen, Hintergrund
<i>github</i>	<i>Quellcode ist über github verfügbar.</i>
<i>Bereitstellung von Daten</i>	<i>Alle Daten müssen in einem Format hochgeladen werden, das den Apollo-Datenspezifikationen entspricht.</i>
<i>Speicherung von Daten</i>	<i>Daten, die in China gesammelt wurden, dürfen nur auf Servern in China gespeichert werden. Daten, die in anderen Ländern und Regionen erhoben werden, unterliegen den Beschränkungen der Datenspeicherung, die durch die Gesetze der jeweiligen Länder festgelegt sind.</i>
<i>Bereitstellung von Daten</i>	<i>Als Initiator dieser Plattform stellt Baidu die Ausgangsdaten für diese Plattform bereit. Die Daten stehen allen Partnern dieser Plattform offen. Das Prinzip der fairen Daten stellt sicher, dass Partner mit größeren eigenen Beiträgen mehr Daten und Dienste von dieser Plattform erhalten.</i>
<i>Datenschutz</i>	<i>Jeder Partner kann seine eigenen Daten anzeigen und die Datenschutzeigenschaften der Daten als privat oder öffentlich festlegen. Die von Partnern hochgeladenen Daten gelten standardmäßig als privat.</i>
<i>Entscheidungsführung</i>	<i>Grundsätzlich handelt es sich bei Apollo Auto um eine offene Plattform. Allerdings wurde Baidu um die architektonische Integrität, die Systemzuverlässigkeit und die schnelle Entwicklung von Apollo zu gewährleisten, bei Bedarf wichtige Entscheidungen treffen, während die aktive Beteiligung der breiteren Gemeinschaft erhalten bleibt.</i>

2.3. Konventionen

Konvention	Erläuterungen, Hintergrund
<i>Dokumentation</i>	<i>Terminologie und Gliederung nach dem deutschen arc42-Template in der Version 6.0</i>
<i>Kodierrichtlinien für C++</i>	<i>C++ Coding Conventions von Sun/Oracle, geprüft mit Hilfe von CheckStyle</i>
<i>Kodierrichtlinien für Python</i>	<i>Python Coding Conventions von Sun/Oracle, geprüft mit Hilfe von CheckStyle</i>
<i>Spezifische Datenformate und Frameworks für autonomes Fahren</i>	<i>Verwendung etablierter Standards für autonomes Fahren. zum Beispiel sind alle Softwaremodule als ROS(Robot Operating System)-Knoten zu behandeln.</i>

3. Kontextabgrenzung

Dieser Abschnitt beschreibt das Umfeld von Apollo Auto. Für welche Benutzer ist es da, und mit welchen Fremdsystemen interagiert es?

3.1. Fachlicher Kontext




Abbildung 1. Fachlicher Kontext von Apollo Auto

3.1.1. Open Vehicle Certification Platform

Certified Apollo Compatible Drive-by-wire Vehicle Open Vehicle Interface Standard ===== Hardware Development Platform Computing Unit GPS/IMU

You could integrate 2 types of Navigation Hardware with Apollo. Refer to their individual Installation guides for more information.

- Novatel
 - NovAtel Propak6 with NovAtel IMU-IGM-A1
 - SPAN-IGM-A1 *Navtech NV-GI120

Camera

You could integrate 3 types of Camera's with Apollo.

- Leopard Imaging Inc's Camera - LI-USB30-AZ023WDRB
- Truly Camera
- Wissen Camera

Refer to their individual Installation guides for more information. If you currently use the ASU, you could integrate any of the camera's below, if not, only the Leopard Camera would work with Apollo.

LiDAR

You could integrate 3 types of LiDAR's with Apollo. Refer to their individual Installation guides for more information.

- Velodyne - Apollo 3.0 provides support to 2 types of Velodyne LiDARs:
 - HDL64E-S3
 - VLP Series
 - VLS-128
- Hesai
- Innovusion

Radar

You could integrate 3 types of Radar's with Apollo. Refer to their individual Installation guides for more information.

- Continental ARS408-21 Radar
- Racobit B01HC Radar

Ultrasonic Radar HMI Device Black Box

ASU Apollo Sensor Unit (ASU) is designed to work with Industrial PC (IPC) to implement sensor fusion, vehicle control and network access in Apollo's autonomous driving platform.

The ASU system provides sensor interfaces to collect data from various sensors, including cameras, Lidars, Radars, and Ultrasonic Sensors. The system also utilizes pulse per second (PPS) and GPRMC signals from GNSS receiver to implement data collection synchronization for the camera and LiDAR sensors.

The communication between the ASU and the IPC is through PCI Express Interface. ASU collects sensor data and passes to IPC via PCI Express Interface, and the IPC uses the ASU to send out Vehicle Control commands in the Controller Area Network (CAN) protocol.

In addition, Lidar connectivity via Ethernet, WWAN gateway via 4G LTE module, and WiFi access point via WiFi module will be enabled in the future

releases.

AXU

Apollo Extension Unit (AXU) is designed to boost computation capability and expand storage capacity by enabling developers to plug-in additional accelerators including GPU, FPGA modules, and etc.

V2X OBU

3.1.2. Open Software Platform

Map Engine Localization Perception Prediction Planning Control HMI V2X
Adaptor Apollo Cyber RT RTOS

3.1.3. Cloud Service Platform

HD Map Simulation Production Components Security OTA DuerOS V2X Fuel
Data Service

3.2. Technischer Kontext




Abbildung 2. Technischer Kontext von Apollo Auto

4. Lösungsstrategie

Dieser Abschnitt enthält einen stark verdichteten Architekturüberblick. Eine Gegenüberstellung der wichtigsten Ziele und Lösungsansätze.

Begründung

<Erläuternder Text>

Enthaltene Bausteine

<Beschreibung der enthaltenen Bausteine (Blackboxen)>

Wichtige Schnittstellen

<Beschreibung wichtiger Schnittstellen>

5.1.1. <Name Blackbox 1>

<Zweck/Verantwortung>

<Schnittstelle(n)>

<(Optional) Qualitäts-/Leistungsmerkmale>

<(Optional) Ablageort/Datei(en)>

<(Optional) Erfüllte Anforderungen>

<(optional) Offene Punkte/Probleme/Risiken>

5.1.2. <Name Blackbox 2>

<Blackbox-Template>

5.1.3. <Name Blackbox n>

<Blackbox-Template>

5.1.4. <Name Schnittstelle 1>

...

5.1.5. <Name Schnittstelle m>

5.2. Ebene 2

5.2.1. Whitebox <Baustein 1>

<Whitebox-Template>

5.2.2. Whitebox <Baustein 2>

<Whitebox-Template>

...

5.2.3. Whitebox <Baustein m>

<Whitebox-Template>

5.3. Ebene 3

5.3.1. Whitebox <_Baustein x.1_>

<Whitebox-Template>

5.3.2. Whitebox <_Baustein x.2_>

<Whitebox-Template>

5.3.3. Whitebox <_Baustein y.1_>

<Whitebox-Template>

Hardware Development Platform

STUFF

ASU · Apollo Sensor Unit (ASU) is designed to work with Industrial PC (IPC) to implement sensor fusion, vehicle control and network access in Apollo's autonomous driving platform. · The ASU system provides sensor interfaces to

collect data from various sensors, including cameras, Radars, and Ultrasonic Sensors. The system also utilizes pulse per second (PPS) and GPRMC signals from GNSS receiver to enable synchronization for the camera and LiDAR sensors. · The communication between the ASU and the IPC is through PCI Express Interface. ASU collects sensor data and passes to IPC via PCI Express Interface, and the IPC uses the ASU to send out Vehicle Control commands in the Controller Area Network (CAN) protocol.

AXU Apollo Extension Unit (AXU) is designed to boost computation capability and expand storage capacity by enabling developers to plug-in additional accelerators including GPU, FPGA modules, and etc.

ACU Apollo Computing Unit Introduction · Integrated Autosar software · ASIL-D functional safety level with special hardware safety island design · 100% Auto-grade components · IATF16949 design with PPAP supply chain and production management

Features: · Power supply 8~16V · Max Power Consumption 28W · Static Power Consumption <0.1mA · Computing Power Up to 1.5TOPS · SOC/MCU Xilinx ZU5/ Aurix TC297 · Operating temperature -40~85 · OS Linux/QNX & AUTOSAR · Size · 200 x 170 x 36mm Working temperatures 85C or · 200 x 120 x 36mm Working temperatures 70C · Cooling: Natural Cooling · Interface · 5 GMSL Video Input - support 1.3 megapixel and 2 megapixel · 1 GMSL Video Output · 4 CAN support CAN-FD · 12 Ultrasonic Radar Interface · 1 100BASE-T1 · 3 Analog Switch

CAN-PCIE/402-B4

Nuvo-6108GC Vendor Neousys Apollo Platform Supported Introduction Nuvo-6018GC is world's first industrial-grade GPU computer supporting high-end graphics cards. It's designed to fuel emerging GPU-accelerated applications, such as artificial intelligence, VR, autonomous driving and CUDA computing, by accommodating NVIDIA® GPU with up to 250W TDP. [Link](#)

ProPak6™ Vendor NovAtel Apollo Platform Supported Introduction ProPak6™ is an enclosure product manufactured by NovAtel. From standalone metre-level to RTK centimetre-level positioning, the ProPak6 is flexible to meet your

positioning needs. Reliability is safeguarded as a result of the extremely rugged and water resistant IP67 housing combined with its wide operating temperature range. NovAtel has also assured faster time to market by reducing integration time with standardized software and hardware connections. The ProPak6 offers optional GPRS/HSPA cellular modem and/or heading options to provide a solution for many applications. Link PwrPak 7D

Vendor—NovAtelApollo Platform Supported Introduction—The PwrPak7D is a robust, high precision receiver ideal for ground vehicle, marine or aircraft based systems. Its multi-frequency dual antenna input allows the PwrPak7D to utilize NovAtel CORRECT® with RTK and ALIGN® functionality. The PwrPak7D has a powerful OEM7® Global Navigation Satellite System (GNSS) inside and offers built-in Wi-Fi, on board NTRIP client and server support and 16 GB of internal storage. Link NV-GI120 Vendor—NavTech Inc.Apollo Hardware Development Platform Supported Introduction—NV-GI120 is a position and orientation system for automatic drive of NAV Technology. With the high-precision GNSS board card and high-precision MEMS gyro, it has the real-time attitude and position resolving ability while transmitting the original data of the sensor and board card for post-processing high-precision resolution.

Newton-M1 Vendor—Starneto Introduction—Newton series MEMS inertial/satellite integrated navigation products not only have compact structure , rich interface resources, but also highly cost-effective. Moreover, they can realize high frequency and precision position, speed detection and attitude determination for various vehicles. Link

MARS Vendor—ON SemiconductorApollo Hardware Development Platform supported Introduction—The Modular Automotive Reference System (MARS) is a complete imaging solution for camera system developers and software developers working on automotive imaging applications. MARS gives engineers and software developers the fundamental building blocks needed to create next generation imaging systems, while reducing the design effort and resources required to develop a working solution. Link Vendor—Wissen TechnologiesApollo Hardware Development Platform Supported Introduction—
· 30mm x 30mm coax camera module · 1080p FHD YUV422 data · HDR function(High Dynamic Range) higher than 100dB · support external trigger function Link LI-USB30-AR023ZWDR Vendor—Leopard Imaging Inc.Apollo

Platform Supported Introduction · Key Features · USB 3.0 Super Speed support · Support register access function · ON Semiconductor AR023Z 1080p HD Sensor · Support CS lens · Pixel Size: 3.0um x 3.0um · Provide customization services · YUV output without compression · USB +5VDC powered device · UVC compliance · Built in AP0202 ISP · Support External Trigger, Software Trigger · Compact Size: 30mm x 30mm

ARS408-21 Vendor Continental Apollo Platform Supported Introduction The ARS408 realized a broad field of view by two independent scans in conjunction with the high range functions like Adaptive Cruise Control, Forward Collision Warning and Emergency Brake Assist can be easily implemented. Its capability to detect stationary objects without the help of a camera system emphasizes its performance. The ARS408 is a best in class radar, especially for the stationary target detection and separation. Link B01HC Vendor Racobit Apollo Hardware Development Platform Supported Introduction The 77GHz millimeter-wave automotive anti-collision radar developed by RACO (Beijing Racobit Electronic Information Technology Co., Ltd) utilizing MIMO virtual aperture technology achieves higher precision, finer angle resolution and smaller volume, which is compatible with long-and-mid-range detection function. It enables real-time detection of the vehicle's driving environment as well as other vehicle targets in various working environments, which is the core sensor of the driverless technology and ADAS system.

VLS-128 Vendor Velodyne Apollo Platform Supported Introduction · 360° Horizontal FOV · +15° to -25° Vertical FOV · Up to 300m Range · Minimum Angular Resolution: 0.11° · Up to 4 Return Modes · Up to ~9.6 Million Points per Second · Environmental Protection: IP67 · Connectors: RJ45 / M12 · High Volume, Automotive Grade Contract Pricing Link Scala 2 Vendor Valeo Apollo Hardware Development Platform supported Introduction Valeo provides its laser scanner to Apollo. The Valeo SCALA® is the first 3D laser scanner compliant with the fierce requirements for automotive mass production. SCALA® offers an unique combination of wide field of view, large detection range and high precision, capable of detecting both stationary and moving objects during day and night. Link M16-LSR Vendor LeddarTech Apollo Hardware Development Platform supported Introduction The Leddar M16

Sensor Modules are advanced, solid-state LiDAR solutions that combine wide-beam flash illumination with 16 independent detection segments to simultaneously deliver rapid, continuous and precise detection and ranging for multiple objects along with excellent lateral discrimination. Based on the patented Leddar Technology, LeddarTech's off-the-shelf solid-state LiDAR modules for mobility applications are ready for integration into specific projects for R&D, proof-of-concept, field validation, and platform seeding. [Link](#) [LEDDARVU \(VU8\) Vendor](#) [LeddarTechApollo Hardware Development Platform supported Introduction](#) [Leddar Vu8](#) is an affordable, versatile solid-state LiDAR sensor module that delivers exceptional detection and ranging performance in a small, robust package. LeddarVu modules provide the ability to detect and track multiple objects simultaneously over eight distinct segments with superior lateral discrimination capabilities. Based on the patented Leddar Technology, LeddarTech's off-the-shelf solid-state LiDAR modules for mobility applications are ready for integration into specific projects for R&D, proof-of-concept, field validation, and platform seeding. [Link](#) [HDL-64E S3 Vendor](#) [VelodyneApollo Platform Supported Introduction](#) [The HDL-64E LiDAR sensor](#) is designed for obstacle detection and navigation of autonomous ground vehicles and marine vessels. Its durability, 360° field of view and very high data rate makes this sensor ideal for the most demanding perception applications as well as 3D mobile data collection and mapping applications. The HDL-64E's innovative laser array enables navigation and mapping systems to observe more of their environment than any other LiDAR sensor. [Link](#) [ULTRA Puck VLP-32C Vendor](#) [VelodyneApollo Hardware Development Platform supported Introduction](#) [Velodyne LiDAR's ULTRA Puck™ VLP-32C](#) is the newest long-range LiDAR sensor in its product portfolio that combines best-in-class performance with a small form factor. A high-resolution LiDAR sensor that is cost-effective when compared to similar performance sensors but developed with automotive applications in mind to ensure reliability while delivering the performance demanded by the market. The VLP-32C retains the innovative breakthroughs in 3D LiDAR such as 360° surround view along with real-time 3D data that includes distance and calibrated reflectivity measurements along with rotational angles. [Link](#) [PUCK VLP-16, PUCK Hi-Res, PUCK LITE Vendor](#) [VelodyneApollo Hardware](#)

Development Platform Supported Introduction □ Velodyne's new PUCK™ (VLP-16) sensor is the smallest, newest, and most advanced product in Velodyne's 3D LiDAR product range. Vastly more cost-effective than similarly priced sensors, and developed with mass production in mind, it retains the key features of Velodyne's breakthroughs in LiDAR: Real-time, 360°, 3D distance and calibrated reflectivity measurements. Link Pandora Vendor □ Hesai Apollo Platform Supported Introduction □ Pandora is an all-in-one sensor kit for environmental sensing for self-driving cars. It integrates cameras, LiDAR and data processing ability (from Baidu Apollo) into the same module, with advanced synchronization and calibration solutions. Link Vendor □ Innovusion Apollo Hardware Development Platform Supported Introduction □ · Resolution: provides near picture quality with over 300 lines of resolution and several hundred pixels in both the vertical and horizontal dimensions. · Range: detects both light and dark objects at distances up to 150 meters away which allows cars to react and make decisions at freeway speeds and during complex driving situations. · Sensor fusion: fuses LiDAR raw data with camera video in the hardware layer which dramatically reduces latency, increases computing efficiency and creates a superior sensor experience. · Accessibility: enables a compact design which allows for easy and flexible integration without impairing vehicle aerodynamics. Innovusion's products leverage components available from mature supply chain partners, enabling fast time-to-market, affordable pricing and mass production. C16 Series Vendor □ LeiShen Intelligent System Apollo Hardware Development Platform Supported Introduction □ LeiShen's developing 3D Multi-channel LiDARs including 2/4/8/16/32-channel have excellent cost performance ratio and wide range of applications. Link Rs-LiDAR-16 Vendor □ Robosense Apollo Hardware Development Platform Supported Introduction □ The compact housing of RS-LiDAR-16 mounted with 16 laser/detector pairs rapidly spins and sends out high-frequency laser beams to continuously scan the Surrounding environment. Advanced digital signal processing and ranging algorithms calculate point cloud data and reflectivity of objects to enable machine to 'see' the world and providing reliable data for localization, navigation and obstacle avoidance.

6. Laufzeitsicht

Diese Sicht visualisiert im Gegensatz zur statischen Bausteinsicht dynamische Aspekte. Wie spielen die Teile zusammen?

7. Verteilungssicht

7.1. Infrastruktur Ebene 1

<Übersichtsdiagramm>

Begründung

<Erläuternder Text>

Qualitäts- und/oder Leistungsmerkmale

<Erläuternder Text>

Zuordnung von Bausteinen zu Infrastruktur

<Beschreibung der Zuordnung>

7.2. Infrastruktur Ebene 2

7.2.1. *<Infrastrukturelement 1>*

<Diagramm + Erläuterungen>

7.2.2. *<Infrastrukturelement 2>*

<Diagramm + Erläuterungen>

...

7.2.3. *<Infrastrukturelement n>*


<Diagramm + Erläuterungen>

8. Querschnittliche Konzepte

Dieser Abschnitt beschreibt allgemeine Strukturen und Aspekte, die systemweit gelten. Darüber hinaus stellt er verschiedene technische Lösungskonzepte vor.

8.1. <Konzept 1>

<Erklärung>



8.2. <Konzept 2>

<Erklärung>

...

8.3. <Konzept n>

<Erklärung>


9. Entwurfsentscheidungen

10. Qualitätsanforderungen

Dieser Abschnitt beinhaltet konkrete Qualitätsszenarien, welche die zentralen Qualitätsziele, aber auch andere geforderte Qualitätseigenschaften besser fassen. Sie ermöglichen es, Entscheidungsoptionen zu bewerten.

10.1. Qualitätsbaum

Das folgende Bild gibt einen Überblick über die relevanten Qualitätsmerkmale und den ihnen jeweils zugeordneten Szenarien.



10.2. Qualitätsszenarien

11. Risiken und technische Schulden

Die folgenden Risiken wurden zu Beginn des Vorhabens identifiziert. Sie beeinflussten die Planung der ersten drei Iterationen maßgeblich. Seit Abschluss der dritten Iteration werden sie beherrscht. Dieser Architekturüberblick zeigt die Risiken inklusive der damaligen Eventualfallplanung weiterhin, wegen ihres großen Einflusses auf die Lösung.

12. Glossar

Das folgende Glossar erklärt Begriffe aus dem Bereich Autonomes Fahren.

Begriff	Definition
<i>By-Wire</i>	<i>Bezeichnung für (zumindest partielles) Fahren oder Steuern von Fahrzeugen ohne mechanische Kraftübertragung der Bedienelemente zu den entsprechenden Stellelementen wie etwa Drosselklappen. Das By-Wire-Konzept umfasst dabei zumindest zwei oder mehr der „X-by-Wire“- Systeme wie etwa Brake-by-Wire (Bremssteuerung) und Steer-by-Wire (Lenkung)..</i>
<i>LIDAR</i>	<i>ist eine dem Radar verwandte Methode zur optischen Abstands- und Geschwindigkeitsmessung sowie zur Fernmessung. Statt der Radiowellen wie beim Radar werden Laserstrahlen verwendet.</i>
<i>RADAR</i>	<i>ist die Bezeichnung für verschiedene Erkennungs- und Ortungsverfahren und -geräte auf der Basis elektromagnetischer Wellen im Radiofrequenzbereich (Funkwellen).</i>

13. Anhang

13.1. Apollo

13.2. Arc42

- die Dokumentation muss bereits zu Beginn der Arbeiten an der Architektur/am Quellcode erfolgen um stets den aktuellen Stand abbilden zu können.
- die Dokumentation soll mit dem Projekt wachsen!
- die nachträgliche Dokumentation ist eine Sysiphusarbeit
 - Beispiel:
 - Diagramme in der Laufzeitsicht sind effizienter zu gestalten während ein Modul im Entstehen ist. Änderungen können mit jeder Entwicklungsstufe eingepflegt werden.
 - Ein fertiges Modul in ein Diagramm zu überführen erfordert viel Zeit, da alle beteiligten Module und deren Funktionsweise erst identifiziert werden müssen.

13.3. docToolChain

- plantUML ist zwar bei sehr einfachen Diagrammen eine Erleichterung, kommt aber an beispielsweise draw.io oder tikz (in Latex) nicht heran wenn es um komplexe und detaillierte Diagramme geht
 - teilweise werden bei der inline-Erstellung bei plantUML Diagrammeinstellungen nicht übernommen
- Schriftgrößen sind nicht einstellbar, was an manchen Stellen - z.B Tabellen nötig gewesen wäre
- Ansonsten ist docToolChain eine interessante Alternative, besonders in Bezug auf den CI-Task in github.
 - damit nicht bei jedem Commit die Dokumentation neu erstellt wird,

bietet github die Möglichkeit über Commitnachrichten, z.B "[no ci]" oder "[skip ci]" den CI-Task auszusetzen. Hier wäre es sinnvoller über Commitnachrichten explizit die Generierung zu starten.