

Table of Contents

1	Introduction to Emacs Lisp Byte Code and LAP	1
1.1	Why is Emacs Lisp Byte Code Important and How is Emacs as a Program Different?	1
1.2	Emacs Lisp Byte Code and LAP	2
	Example showing use of <code>byte-compile-lapcode</code>	2
1.3	Emacs Lisp Virtual Machine	3
2	Emacs Lisp Byte-Code Environment	4
2.1	Byte-Code Objects	5
2.1.1	The Byte-Code Function Type and Literal	5
2.1.1.1	Function Parameter (lambda) List	6
2.1.1.2	Byte-code Unibyte String	7
2.1.1.3	Constants Vector	7
2.1.1.4	Maximum Stack Usage	8
2.1.1.5	Docstring	8
2.1.1.6	“Interactive” Specification	8
2.2	Byte-Code Compiler	10
2.3	Byte-Code Interpreter	11
2.4	Byte-Code Instructions	12
2.5	Byte-Code Files	13
3	Emacs Lisp Byte-Code Instructions	15
3.1	Instruction-Description Format	15
3.1.1	Instruction Jargon	15
3.1.2	Instruction Description Fields	16
3.2	Argument-Packing Instructions	18
	<code>stack-ref</code> (1–7)	18
	<code>varref</code> (8–15)	19
	<code>varset</code> (16–23)	20
	<code>varbind</code> (24–31)	21
	<code>call</code> (32–39)	22
	<code>unbind</code> (40–47)	23
3.3	Constants-Vector Retrieval Instructions	24
	<code>constant</code> (192–255)	24
	<code>constant2</code> (129)	25
3.4	Exception-Handling Instructions	26
	<code>pophandler</code> (48)	26
	<code>pushconditioncase</code> (49)	27
	<code>pushcatch</code> (50)	28
3.5	Control-Flow Instructions	29
	<code>goto</code> (130)	29

goto-if-nil (131).....	30
goto-if-not-nil (132).....	31
goto-if-nil-else-pop (133).....	32
goto-if-not-nil-else-pop (134).....	33
return (135).....	34
switch (135).....	35
3.6 Function-Call Instructions.....	36
3.6.1 Lisp Function Instructions.....	36
symbolp (57).....	36
consp (58).....	37
stringp (59).....	38
listp (60).....	39
eq (61).....	40
memq (62).....	41
not (63).....	42
symbol-value (74).....	43
symbol-function (75).....	44
set (76).....	45
fset (77).....	46
get (78).....	47
equal (154).....	48
member (157).....	49
assq (158).....	50
numberp (167).....	51
integerp (168).....	52
3.6.2 List Function Instructions.....	53
nth (56).....	53
car (64).....	54
cdr (65).....	55
cons (66).....	56
list1 (67).....	57
list2 (68).....	58
list3 (69).....	59
list4 (70).....	60
listN (175).....	61
length (71).....	62
aref (72).....	63
aset (73).....	64
nthcdr (155).....	65
elt (156).....	66
nreverse (159).....	67
setcar (160).....	68
setcdr (161).....	69
car-safe (162).....	70
cdr-safe (163).....	71
nconc (164).....	72
3.6.3 Arithmetic Function Instructions.....	73
sub1 (83).....	73

add1 (84)	74
eqlsign (85)	75
gtr (86)	76
lss (87)	77
leq (88)	78
geq (89)	79
diff (90)	80
negate (91)	81
plus (92)	82
mult (95)	83
max (93)	84
min (94)	85
quo (165)	86
rem (166)	87
3.6.4 String Function Instructions	88
substring (79)	88
concat2 (80)	89
concat3 (81)	90
concat4 (82)	91
concatN (174)	92
upcase (150)	93
downcase (151)	94
stringeqlsign (152)	95
stringlss (153)	96
3.6.5 Emacs Buffer Instructions	97
current-buffer (112)	97
set-buffer (113)	98
save-current-buffer-1 (114)	99
buffer-substring (123)	100
3.6.6 Emacs Position Instructions	101
point (96)	101
goto-char (98)	102
point-max (100)	103
point-min (101)	104
forward-char (117)	105
forward-word (118)	106
forward-line (121)	107
skip-chars-forward (119)	108
skip-chars-backward (120)	109
narrow-to-region (125)	110
widen (126)	111
3.6.7 Emacs Text Instructions	112
insert (99)	112
insertN (99)	113
char-after (102)	114
following-char (103)	115
preceding-char (104)	116
current-column (105)	117

eolp (108)	118
eobp (109)	119
bolp (110)	120
bobp (111)	121
delete-region (124)	122
end-of-line (127)	123
3.6.8 Emacs Misc Function Instructions	124
char-syntax (122)	124
save-excursion (138)	125
set-marker (147)	126
match-beginning (148)	127
match-end (149)	128
3.7 Stack-Manipulation Instructions	129
discard (136)	129
discardN (180)	130
dup (137)	131
stack-set (178)	132
stack-set2 (179)	133
3.8 Obsolete or Unused Instructions	134
save-current-buffer (97)	134
mark (97)	134
scan-buffer (107)	134
read-char (114)	134
set-mark (115)	134
interactive-p (116)	134
save-window-excursion (139)	134
condition-case (143)	135
temp-output-buffer-setup (144)	135
temp-output-buffer-show (145)	136
unbind-all (146)	136
3.8.12 Relative Goto Instructions	137
Rgoto (170)	137
Rgotoifnil (171)	137
Rgotoifnonnil (172)	137
Rgotoifnilesepop (173)	137
Rgotoifnonnilesepop (174)	137

4 Instruction Changes Between Emacs Releases .. 138

4.1 After 16 and Starting in 18.31	138
Version 18 Release History	138
4.2 After 18.59 and Starting 19.34	139
Version 19 Release History	140
4.3 After 19.34 and Starting in 20.1	141
Version 20 Release History	141
4.4 After 20.1 and Starting in 21.1	142
Version 21 Release History	142
4.5 After 21.4 and Starting in 22.1	142
Version 22 Release History	142

4.6	After 22.3 and Starting in 23.1	142
	Version 23 Release History.....	143
4.7	After 23.4 and Starting in 24.1	143
	Version 24 Release History.....	143
4.8	After 24.5 and Starting in 25.1	144
	Version 25 Release History.....	144
4.9	After 25.3 and Starting in 26.1	144
4.10	After 26.1 and Starting in 27.1	144
5	Opcode Table	145
5.1	Opcodes (0000-0077)	145
5.2	Opcodes (0100-0177)	147
5.3	Opcodes (0200-0277)	149
5.4	Opcodes (0300-3277) Constants.....	151
6	References	153
	Instruction Index	154
	Byte-Code Function Index	156

1 Introduction to Emacs Lisp Byte Code and LAP

1.1 Why is Emacs Lisp Byte Code Important and How is Emacs as a Program Different?

If you were to look at two comparable complex programs circa 2018, Firefox 53.0.3 and Emacs 25.3, you would see that relative sizes of Firefox tarball is 5 times bigger than for Emacs. But how are these made up, or what languages are they comprised of?

For Firefox whose core is written in C++ we have:

```
$ cloc --match-f='\.(js|c|cpp|html|py|css)$' firefox-53.0.3
  89156 text files.
  86240 unique files.
   1512 files ignored.
```

```
cloc v 1.60  T=244.20 s (353.2 files/s, 56012.8 lines/s)
```

Language	files	comment	code
C++	7267	418019	3057110
Javascript	25855	532629	2859451
HTML	45311	120520	2209067
C	3482	400594	1664666

And for Emacs whose core is written in C we have:

```
$ cloc emacs-25.3.tar.xz
  3346 text files.
  3251 unique files.
   1130 files ignored.
```

```
cloc 1.60  T=13.85 s (160.1 files/s, 154670.7 lines/s)
```

Language	files	comment	code
Lisp	1616	200820	1270511
C	255	66169	256314
C/C++ Header	176	11505	34891

If you look at the relative ratio of C++ versus Javascript code in Firefox, and the ratio of C versus Lisp code in Emacs, you'll see that there is much more of Emacs written in Lisp than say of Firefox written in Javascript. (And if you look at the C code for Emacs, a lot of it looks like Lisp written using C syntax). My take is that Emacs a lot more orthogonal in its basic concepts and construction. Just as Leibniz was amazed that such diversity could come out of such simple rules of mathematics and physics, so it is remarkable that something as complex as Emacs can come out of the relatively simple language Lisp.

1.2 Emacs Lisp Byte Code and LAP

However pervasively used, Emacs Lisp is in making up the Emacs ecosystem, Emacs Lisp is not and never has been a speedy language compared to say, C, C++, Go, Rust, or Java. And that's where LAP and bytecode come in.

As stated in a comment in `byte-opt.el` added circa 1996:

No matter how hard you try, you can't make a racehorse out of a pig.

You can, however, make a faster pig.

—Eric Naggum

Emacs Lisp bytecode is the custom lower-level language used by Emacs' bytecode interpreter. As with all bytecode, bytecode instructions are compact. For display purposes, there is a `disassemble` command that unpacks the fields of the instruction. With this and the constants vector, bytecode can be printed in an assembly-language-like format.

I'll often use Emacs Lisp bytecode instruction refer to an assembly representation of an Emacs Lisp bytecode instruction.

LAP stands for Lisp Assembly Program. It is an internal representation of the bytecode instructions in a more symbolic form. It is used behind the scenes to that make bytecode more amenable to optimization, since the instructions are in a structure which is easier to operate on.

If you want to write the instruction sequence in this symbolic form rather than give a byte-encoded form, you can do that using the function `byte-compile-lapcode`.

Example showing use of `byte-compile-lapcode`

```
(defalias 'get-foo
  (make-byte code
    #x000                ;; lexical parameter counts
    (byte-compile-lapcode
      '((byte-varref . 0)
        (byte-return)))  ;; instruction sequence
    [foo]                ;; constants vector
    1))                  ;; max stack usage
```

Silly Loop Example (https://www.gnu.org/software/emacs/manual/html_node/elisp/Speed-of-Byte_002dCode.html) in the Emacs Lisp Manual gives a program to time running in some code Bytecode interpreter versus running the code in the Lisp interpreter. When I ran this program, bytecode ran 2.5 times faster¹. The Emacs Lisp manual gets a speed improvement of about 3 times.

¹ Code was compiled to use dynamic binding for variable access, same as was probably used in the Emacs Lisp manual. We should note that, byte-compiling with lexical binding for variable access gives code that runs a bit faster than when dynamic binding is used.

1.3 Emacs Lisp Virtual Machine

The Emacs Lisp bytecode interpreter, like many bytecode interpreters such as Smalltalk, C Python, Forth, or PostScript, has an evaluation stack and a code stack. Emacs Lisp Bytecode instructions come in the order used in Reverse Polish Notation: operands appear prior to the operator. This is how many other bytecode interpreters work. It is the opposite of the way Lisp works. Thus, to add the values of two variables we might write `(+ a b)`. However in bytecode it is the other way around: the operator or function comes last. So the corresponding bytecode is:

```
0      varref    a
1      varref    b
2      plus
```

As in most language-specific virtual machines, but in contrast to a typical a number of general-purpose virtual machines, the things that are on the evaluation stack are the same objects as found in the system that they model. Here, these objects can include Emacs buffers, or font faces, Lisp objects like hashes or vectors, or simply (30-bit) Lisp integers. Compare this with say LLVM IR, or JVM instructions where the underlying objects on the stack are registers which can act as pointers and the internal memory layout of objects is exposed.

Control flow in Lisp bytecode is similar to a conventional assembly language: there are unconditional and conditional jumps. More complex control structures are simply built out of this.

Although it may be obvious, one last thing I'd like to point out is that the Emacs Lisp bytecode instruction set is custom to Emacs. In addition to primitives that you'd expect for Lisp like `"car"` and `"cdr"`, there are primitive bytecodes for more complex Emacs editor-specific concepts like `"save-excursion"`¹.

The interpreter is largely backwards compatible, but not forwards compatible². So old versions of Emacs can't run new byte code. Each instruction is between 1 and 3 bytes. The first byte is the opcode and the second and third bytes are either a single operand, a single immediate value. Some operands are packed into the opcode byte.

¹ The fact that the semantic level difference between Emacs Lisp and its bytecode is not great makes writing a decompiler for it more feasible than if the bytecode language were of a general nature such as say LLVM IR.

² well, eventually old Emacs Lisp bytecode instructions *do* die

2 Emacs Lisp Byte-Code Environment

In this chapter we will discuss the ways Emacs creates, modifies and uses bytecode in order to run code. We describe a little of the two kinds of interpreters Emacs has, what goes into a bytecode file, and the interoperability of bytecode between versions.

2.1 Byte-Code Objects

Emacs Lisp bytecode isn't a low-level sequence of octets (bytes) that requires a lot of additional special-purpose machinery to run. There is however custom C code interpreter to handle each of the instruction primitives, and that is basically it. And even here, many of the instructions are simply a bytecode form of some existing Emacs primitive function like "car" or "point".

Emacs Lisp bytecode is a built-in Emacs Lisp type (same as a say a Lisp "cons" node, or a Lisp symbol). You can check if a value is bytecode using the `byte-compile-function-p` predicate function. Functions `aref` and `mapcar` can be used extract the components of bytecode once it is built, the bytecode object is made up of other normal Emacs Lisp objects described next. Byte code is created using the `make-byte-code` function.

One important component of the bytecode object is the "constants vector." It contains important Lisp Objects that are required to make sense of the bytecode-instruction operands: functions that share the same bytecode-instruction byte string, but differ in their constants vectors, can do very different things.

2.1.1 The Byte-Code Function Type and Literal

This section is largely lifted from Chris Wellons' Emacs byte code Internals. See references at the end of this doc.

An Emacs Lisp object of a byte code type is analogous to an Emacs Lisp vector. As with a vector, elements are accessed in constant time.

The print syntax of this type is similar to vector syntax, except `#[...]` is displayed to display a bytecode literal instead of `([...])` as is used in a vector.

In contrast to vector object, there are no functions to index or extract parts of a code object once it is build, and a byte-code object can be evaluated as a function. Valid byte-code objects have 4 to 6 elements and each element has a particular structure elaborated on below.

There are two ways to create a byte-code object: using a byte-code object literal or with `make-byte-code`. Like vector literals, byte-code functions don't need to be quoted.

Examples of calling `make-byte-code`:

```
(make-byte-code 0 "" [] 0)
;; => #[0 "" [] 0]
```

```
#[1 2 3 4]
;; => #[1 2 3 4]
```

```
(#[0 "" [] 0])
;; error: Invalid byte opcode
```

The elements of a bytecode function literal are:

1. Function Parameter (lambda) List
2. Byte-code Unibyte String
3. Constants Vector
4. Maximum Stack Usage

5. Docstring
6. “Interactive” Specification

2.1.1.1 Function Parameter (lambda) List

The first element of a bytecode-function literal is the parameter list for the `lambda`. The object takes on two different forms depending on whether the function is lexically or dynamically scoped. If the function is dynamically scoped, the argument list is exactly what appears in Lisp code.

Example showing how a parameter list is transformed:

```
(setq lexical-binding nil) ; force lexical binding
(byte-compile
 (lambda (a b &optional c) 5))
;; => #[(a b &optional c) "\300\207" [5] 1]
```

Above we show raw bytecode data. in Emacs after versions after 25 efforts have been made to hide the data.

There’s really no shorter way to represent the parameter list because preserving the argument names is critical. Remember that, in dynamic scope, while the function body is being evaluated these variables are globally bound (eww!) to the function’s arguments.

On the other hand, when the function is lexically scoped, the parameter list is packed into an Emacs Lisp integer, indicating the counts of the different kinds of parameters: required, `&optional`, and `&rest`. No variable names are needed.

The following shows how parameter counts and flags are encoded:



The least significant 7 bits indicate the number of required arguments. Notice that this limits compiled, lexically-scoped functions to 127 required arguments. The 8th bit is the number of `&rest` arguments (up to 1). The remaining bits indicate the total number of optional and required arguments (not counting `&rest`). It’s really easy to parse these in your head when viewed as hexadecimal because each portion almost always fits inside its own “digit.”

Example showing how lexical parameters are encoded:

```
(byte-compile-make-args-desc '())
;; => #x000 (0 args, 0 rest, 0 required)

(byte-compile-make-args-desc '(a b))
;; => #x202 (2 args, 0 rest, 2 required)

(byte-compile-make-args-desc '(a b &optional c))
;; => #x302 (3 args, 0 rest, 2 required)
```

```
(byte-compile-make-args-desc '(a b &optional c &rest d))
;; => #x382 (3 args, 1 rest, 2 required)
```

The names of the arguments don't matter in lexical scope: they're purely positional. This tighter argument specification is one of the reasons lexical scope is sometimes faster: the byte-code interpreter doesn't need to parse the entire lambda list and assign all of the variables on each function invocation; furthermore, variable access is via a compact index located usually in the operand value rather than an index into the constants vector followed by a lookup of the variable.

2.1.1.2 Byte-code Unibyte String

The second element of a bytecode-function literal is a unibyte string — it strictly holds octets and is not to be interpreted as any sort of Unicode encoding. These strings should be created with `unibyte-string` because `string` may return a multibyte string. To disambiguate the string type to the lisp reader when higher values are present (> 127), the strings are printed in an escaped octal notation, keeping the string literal inside the ASCII character set.

Example of a unibyte string:

```
(unibyte-string 100 200 250)
;; => "d\310\372"
```

It's unusual to see a byte-code string that doesn't end with 135 (`#o207`, return). Perhaps this should have been implicit? I'll talk more about the byte code below.

2.1.1.3 Constants Vector

The third object in a bytecode-function literal is a constants vector. It's a normal Emacs Lisp vector and can be created with `(vector ...)` or a vector literal.

In addition to the normal kinds of things one thinks of as constants — numbers, strings, and compositions of these — the constants vector importantly contains symbol constants of those dynamic variables and function names which are referred to by the instructions of the byte-code unibyte string.

The amount of space used by an Emacs byte-code instruction, and the number of ways an operand in an instruction can refer to an Lisp object is rather limited. Most operands are only a few bits in length, some fill an entire byte, and occasionally an operand can be two bytes in length. Given this, you can't have an arbitrary string or structured Lisp object listed directly inside an operand. Instead, operands reference either the constants vector or they index into the evaluation stack itself.

Example showing a constants vector:

```
ELISP> (byte-compile
        (lambda (a b)
          (my-func '("hi" "there") a nil 5)))
#[(a b)
  "\301\302\303\304\207"
 [a my-func
  ("hi" "there")
  nil 5]
```

5]

The above assumes that dynamic binding is in effect.

The constants vector in the above example contains 5 elements:

- **a** — the symbol **a** which refers to a variable
- **myfunc** the symbol **myfunc** which likely refers to an external function
- **("hi" "there")** a list constant containing two strings
- **nil** the nil constant
- **5** the integer constant 5

The properties of symbol **a** and symbol **myfunc** are consulted at run time, so as such there is no knowledge in the bytecode representing the fact that **a** is a dynamically-bound parameter while **my-func** is probably an external function.

If the lambda were a lexically-scoped, the constants vector would not have the variable symbol **a** listed, but instead there would be a stack entry.

Note that although the symbol **b** is a parameter of the lambda, it doesn't appear in the constants vector, since it is not used in the body of the function.

2.1.1.4 Maximum Stack Usage

The fourth object in a bytecode-function literal is an integer which gives the maximum stack space used by this byte-code. This value can be derived from the byte code itself, but it's pre-computed so that the byte-code interpreter can quickly check for stack overflow. Under-reporting this value is probably another way to crash Emacs.

In our example above, maximum-stack value is five since function **myfunc** is called with four parameters which are pushed onto the stack, and there is an additional stack entry pushed the **myfunc** symbol itself. All of this needs to be in place on the stack just before a **call** instruction runs to perform the **myfunc** call.

2.1.1.5 Docstring

The fifth object in a bytecode-function literal is simple and completely optional. Depending on how the function was created the docstring is either the docstring, or a cons cell indicating a compiled `'elc'` and a position for lazy access. Only one position, the start, is needed because the lisp reader is used to load it and it knows how to recognize the end.

2.1.1.6 “Interactive” Specification

When there is a sixth field in the bytecode-function the function is a command, i.e an “interactive” function. Otherwise the function is not a command. That parameter holds the exactly contents of the argument to **interactive** in the uncompiled function definition. Note that **(interactive)** causes the sixth field to be nil, which is distinct from there not being a sixth field.

Examples showing the interactive specification:

```
ELISP> (byte-compile
        (lambda (n)
          (interactive "nNumber: ") n))
;; => #[(n) "\010\207" [n] 1 nil "nNumber: "]
```

```
ELISP> (byte-compile
        (lambda (n)
          (interactive (list (read))) n))
;; => #[(n) "\010\207" [n] 1 nil (list (read))]
```

The interactive expression usually interpreted, which is fine because, by definition, this code is going to be waiting on user input. However, it slows down keyboard macro playback.

2.2 Byte-Code Compiler

The Byte-Code compiler is an ahead-of-time compiler that accepts Emacs Lisp input and produces bytecode that can be run by Emacs. The compiler itself is written in Emacs Lisp¹, and is a comparatively compact program contained in the files `bytecomp.el` and `byte-opt.el`.

Internally, the compiler first produces an intermediate Lisp structure in LAP code, then performs various optimizations on that, and finally translates the LAP code into bytecode. LAP code is used during compilation, but not kept in memory or used when running bytecode.

It is possible to go back to LAP code from bytecode; this is done in order to inline functions and when bytecode disassembly is requested.

¹ usually, the compiler itself is compiled into bytecode, which avoids overflow problems

2.3 Byte-Code Interpreter

When a function is called and the function is represented as bytecode, control passes to the bytecode interpreter. The interpreter is written in C and is written more for speed than readability.

The bytecode interpreter operates on a single function at a time; for a function call, the bytecode interpreter calls other parts of Emacs, which might call the bytecode interpreter again, recursively. Thus, in contrast to languages like FORTH, there is no code stack per se, just the C stack.

The bytecode interpreter implements a stack machine utilizing a fixed-size evaluation stack, which is usually allocated as a block on the C stack. Instructions can access either this stack or a constants vector, which is produced at compile time and made part of the bytecode object.

The evaluation stack, as well as the constants vector, contains Lisp values, usually 64-bit words containing an integer (Emacs integers are limited to 62 bits on 64-bit machines), symbol index, or a tagged pointer to one of various Emacs structures such as markers, buffers, floating-point numbers, vectors, or cons cells.

Values on the evaluation stack are created at run time; values in the constants vector are created when the byte-compiled file is read and converted into bytecode objects. The underlying bit representation of values in the constants vector can vary between Emacs instances: they are constants in the sense that they do not vary within a single Emacs instance.

Bytecode objects contain a number safely estimating the maximum stack size the evaluation stack can grow to.

2.4 Byte-Code Instructions

The bytecode interpreter, once it has set up the evaluation stack and constants vector, executes the instructions that make up the bytecode byte string: each instruction is between one and three bytes in length, containing an opcode in the first byte and sometimes an eight- or 16-bit integer in the following bytes. Those integers are usually unsigned, and 16-bit integers are stored in little-endian byte order, regardless of whether that is the natural byte order for the machine Emacs runs on.

Some opcodes, allocated in blocks, encode an integer as part of the opcode byte.

Bytecode instructions operate on the evaluation stack: for example, **plus**, the addition function, removes two values from the top of the stack and pushes a single value, the sum of the first two values, back on the stack.

Since the arguments for a function call need to be on the stack before the function can operate on them, bytecode instructions use Reverse Polish Notation: first the arguments are pushed on the stack, then the function or operation is called. For example, the Lisp expression `(+ a b)` turns into this bytecode:

PC	Byte	Instruction
0	8	varref a
1	9	varref b
2	92	plus

First **a** and **b** are dereferenced and their values pushed onto the evaluation stack; then **plus** is executed, leaving only a single value, the sum of **a** and **b**, on the stack.

2.5 Byte-Code Files

When Emacs is build from source code, there is C code for some primitive or built-in functions. These include Lisp functions like `car`, or primitive Emacs functions like `point`. Other equally important functions are implemented in Emacs Lisp. These are byte compiled and then loaded into Emacs. On many systems there is the ability to dump Emacs in some kind of image format after these basic functions have been loaded. But even if that doesn't happen, a file called `loaddefs.el` is created that contains many of the important basic primitive functions as bytecode.

When you invoke Emacs then, it has a number of functions already loaded and these are either coded in C or have been byte compiled and loaded. Before running a function, Emacs queries the type of code that is associated with the function symbol and calls either its lambda S-expression interpreter or its bytecode interpreter.

When you run `load`, which reads and evaluates Lisp code from a file, at the top-level it doesn't matter whether the file contains bytecode or Emacs Lisp source code. Either way the only thing done is to open the file, and read the contents of the file using the normal Lisp reader. The difference between the two kinds of files is more about convention than it is strictly about the contents of the file.

The difference between a Emacs Lisp bytecode file and a Emacs Lisp source file, then is two things. First the bytecode file will have a comment header in it that starts `;ELC^W^@^@^@` while the source code probably doesn't. (However there's nothing to stop you from adding in that line if you feel like it). In addition to this comment header, a bytecode file will have other meta-comments such as which version of Emacs was used to compile the file and whether optimization was used. In earlier versions, there was information about the program that was used to compile the program was given, like its version number. And the source code path used to be in there as well. (I think these things should still be in there but that's a different story). See Chapter 4 [Instruction Changes Between Emacs Releases], page 138, where we give examples of the headers to show how that has changed.

The second thing that is typically different between source code files and bytecode files is the prevalence of the `byte-code` calls used in the file and with the inclusion of those comes a lack of any `defun`, `defmacro`, or `lambda` calls. But again I suppose there's nothing stopping you from using doing likewise in your source code.

In fact, you can take a file with the `.elc` extension, rename it to have an `.el` extension instead and `load` that. And that will run exactly the same if it had been loaded as a byte code file¹.

Similarly, just as you can concatenate any number of independent Emacs Lisp source code files into one file², you can do the same with Emacs Lisp bytecode files.

Of course, there will probably certain programs that are fooled when the extension is changed. In particular, the `byte-recompile-directory` function it will think that the bytecode file doesn't exist because it has the wrong extension. So even though Emacs is permissive about such matters, it is best to stick with the normal Emacs conventions.

¹ If you go the other direction and rename a Lisp file as a bytecode file, Emacs will notice the discrepancy because at the top of the file is a header that Emacs checks. But if you add a reasonable-looking header you can go that direction as well.

² and this is sometimes done as a poor-man's way to create a package

The final thing that should be mentioned when talking about bytecode files is interoperability between Emacs versions.

Even though a bytecode header has a meta comment indicating the version of Emacs that was used to compile it, that information is not used in determining whether the bytecode file can be run or not.

This has the benefit of being able to run bytecode compiled in different Emacs version than the version you are currently running. Since Emacs bytecode instructions do not change that often, this largely works. The scary part though is that opcode meanings have changed over the 30 years, and the interpreter is and has been sometimes lacking in checks. (In the past the interpreter has aborted when running an invalid bytecode). So Emacs doesn't even know that you are running bytecode from a different interpreter. There is no check that you aren't going off a cliff running older or newer bytecode.

However, Emacs developer(s) maintain that in practice problems haven't occurred with such frequency that it has been reported happened enough to be a problem. Also, they try to keep backward compatibility between versions. In other words, bytecode that was generated in an older version of Emacs but is no longer generated will often still be interpreted in the new version of Emacs. While this is a nice intention, the facts seem to suggest that this isn't always the case. (Nor could it be in reality for a program that is 30 years old or so).

See Chapter 4 [Instruction Changes Between Emacs Releases], page 138, then for when this is likely to work and in what cases it won't. And although running newer bytecode in an older version of Emacs isn't explicitly considered, again, since bytecode doesn't change that often, in reality this too can sometimes work out.

Note that this is in sharp contrast other bytecode interpreters like Python where the magic used in compiling has to be the same as the value of running interpreter or Python will refuse to run.

Personally, I think it would be nice to have a Emacs Lisp bytecode checker, perhaps a **safer-load** function that does look at the bytecode and its meta-comments gleans when there is something that is known to cause problems. Any volunteers?

3 Emacs Lisp Byte-Code Instructions

3.1 Instruction-Description Format

In this chapter we'll document instructions over the course of the entire history of Emacs. Or at least we aim to.

For the opcode names, we will prefer canonicalized names from the Emacs C source `bytecode.c` (under directory `src/`) when those differ from the names in `bytecomp.el` (under directory `lisp/emacs-lisp`). Most of the time they are the same under the transformation described below.

We use names from `bytecode.c` because that is a larger set of instruction names. Specifically, obsolete instructions names (both those that can be interpreted even though they are no longer generated, and some that are no longer interpreted) are defined in that file, whereas that is not the case in `bytecomp.el`.

Names in `bytecode.c` must follow C conventions and must be adjusted to harmonize with other C names used. But this aspect isn't of use here, so we canonicalize those aspects away.

For example, in `bytecode.c` there is an opcode whose name is `Bbuffer_substring`. We will drop the initial `B` and replace all underscores (`_`) with dashes (`-`). Therefore we use `buffer-substring`.

The corresponding name for that opcode in `bytecomp.el` is `byte-buffer-substring`. For the most part, if you drop the initial `byte-` prefix in the `bytecomp.el` name you will often get the canonic name from `bytecode.c`.

However this isn't always true. The instruction that the Emacs Lisp `save-current-buffer` function generates nowadays has opcode value 114. In the C code, this value is listed as `B_save_current_buffer_1`; `bytecomp.el` uses the name `byte-save-current-buffer`. We report the instruction name for opcode 114 as `save-current-buffer-1`.

To shorten and regularize instruction descriptions, each instruction is described a standard format. We will also require a small amount of jargon. This jargon are explained below.

3.1.1 Instruction Jargon

- **TOS** The value of top of the evaluation stack. Many instructions either read or push onto this.
- **S** This is an array of evaluation stack items. `S[0]` is the top of the stack, or **TOS**.
- **top** A pointer to the the top of the evaluation stack. In C this would be `&TOS`. When we want the stack to increase in size, we add to `top`. For example, to makes space to store a new single new value, we can use `top++` and then assign to **TOS**.

Note that in changing `top`, the value accessed by **TOS** or **S** values all change.

- ϕ This is used in describing stack effects for branching instructions where the stack effect is different on one branch versus the other. This is a function of two arguments. The first argument gives the stack effect on the non-nil branch and the second argument gives the stack effect for the nil branch. So $\phi(0, -1)$ which is seen in `goto-if-not-nil-else-pop` means that if the jump is taken, the stack effect is 0, otherwise the effect removes or pops an evaluation-stack entry.

- instruction-name subscripting (`[]`) In many instructions such as `constant`, `varref`, you will find an index after the instruction name. What’s going on is that instruction name is one of a number of opcodes in a class encodes an index into the instruction. We generally call this an “Argument-encoding” instruction. In the display of the opcode in assembly listings and in the opcode table chapter where we list each opcode, we will include that particular instruction variant in subscripts.

For example consider `constant[0]` versus `constant[1]`. The former has opcode 192 while the latter has opcode 193. In terms of semantics, the former is the first or zeroth-index entry in a function’s constant vector while the latter is the second or 1-index entry.

3.1.2 Instruction Description Fields

The description of fields use for describing each instruction is as follows

Implements:

A description of what the instruction does.

Generated via:

These give some Emacs Lisp constructs that may generate the instruction. Of course there may be many constructs and there may be limiting situations within that construct. We’ll only give one or a few of the constructs, and we’ll try to indicate a limiting condition where possible.

Operand: When an instruction has an operand, this describes the type of the operand. Note that the size of the operand (or in some cases the operand value) will determine the instruction size.

Instruction size:

The number of bytes in the instruction. This is 1 to 3 bytes.

Stack effect:

This describes how many stack entries are read and popped and how many entries stack entries are pushed. Although this is logically a tuple, we’ll list this a tuple like $(-3, 2)$ as a single scalar $-3 + 2$. In this example, we read/remove three stack entries and add two. The reason we give this as $-3 + 2$ rather than the tuple format is so that the overall effect (removing a stack entry) can be seen by evaluating the expression.

Added in: This is optional. When it is given this gives which version of Emacs the opcode was added. It may also give when the opcode became obsolete or was no longer implemented.

Example: Some Emacs Lisp code to show how the instruction is used. For example the for the `goto` instruction we give:

```
(defun goto-eg(n)
  (while (n) 1300))
```

generates:

PC	Byte	Instruction
0	192	<code>constant[0] n</code>
1	32	<code>call[0]</code>

```

2 133 goto-if-nil-else-pop [8]
      8
      0
5 130 goto [0]
      0
      0
8 135 return

```

Constants Vector: [n]

From the above we see that the `goto` instruction at program counter (PC) 5, has decimal opcode 130. The instruction is three bytes long: a one-byte opcode followed by a two-byte operand.

The instruction name at PC 0 with opcode 192, `constant[0]`, looks like it is indexing, but it is a just name, where the brackets and number are part of the name. We use this kind of name because it is suggestive of how it works: it indexes the first element into the constants vector and pushes that value onto the evaluation stack. `constant[1]` with opcode 193 pushes the second element of the constants vector onto the stack. We could have also used instruction names like `constant0` and `constant1` for opcodes 192 and 193 instead.

Unless otherwise stated, all code examples were compiled in Emacs 25 with optimization turned off.

3.2 Argument-Packing Instructions

These instructions from opcode 1 to 47 encode an operand value from 0 to 7 encoded into the first byte. If the encoded value is 6, the actual operand value is the byte following the opcode. If the encoded value is 7, the actual operand value is the two-byte number following the opcode, in Little-Endian byte order.

stack-ref (1–7)

Reference a value from the evaluation stack.

Implements:

top++; TOS <- S[i+1] where i is the value of the instruction operand.

Generated via:

let, let* and lambda arguments.

Operand: A stack index

Instruction size:

1 byte for stack-ref[0] .. stack-ref[4]; 2 bytes for stack-ref[5], 8-bit operand; 3 bytes for stack-ref[6], 16-bit operand.

Stack effect:

-0 + 1.

Added in: Emacs 24.1. See Section 4.7 [Emacs 24], page 143.

Example: When lexical binding and optimization are in effect,

```
(defun stack-ref-eg()
  (let ((a 5) (_b 6) (c 7))
    (+ a c)))}
```

generates:

PC	Byte	Instruction
0	192	constant[0] 5 ;; top++; TOS <- 5
1	193	constant[1] 6 ;; top++; TOS <- 6
2	194	constant[2] 7 ;; top++; TOS <- 7
3	2	stack-ref[2] ;; top++; TOS <- S[3] (5)
4	1	stack-ref[1] ;; top++; TOS <- S[2] (7)
5	92	plus
6	135	return

Constants Vector: [5 6 7]

Warning Running an instruction with opcode 0 (logically this would be called stack-ref[0]), will cause an immediate abort of Emacs in versions after version 20 and before version 25! The abort of the opcode was in place before this instruction was added.

Zero is typically an invalid in bytecode and in machine code, since zero values are commonly found data, e.g. the end of C strings, or data that has been initialized to value but represents data that hasn't been written to yet. By having it be an invalid instruction, it is more likely to catch situations where random sections of memory are run such as by setting the PC incorrectly.

varref (8–15)

varref (8–15)

Pushes the value of the symbol in the constants vector onto the evaluation stack.

Implements:

```
top++; TOS <- (eval constants_vector[i]) where i is the value of instruction operand
```

Generated via:

dynamic variable access

Operand: A constants vector index. The constants vector item should be a variable symbol.

Instruction size:

1 byte for `varref[0] .. varref[4]`; 2 bytes for `varref[5]`, 8-bit operand; 3 bytes for `varref[6]`, 16-bit operand.

Stack effect:

$-0 + 1$.

Example: When dynamic binding is in effect,

```
(defun varref-eg(n)
  n)
```

generates:

PC	Byte	Instruction
0	8	varref[0] n
1	135	return

Constants Vector: [n]

varset (16–23)

varset (16–23)

Sets a variable listed in the constants vector to the TOS value of the stack.

Implements:

```
constants_vector[i] <- TOS; top-- where i is the value of the instruction  
operand.
```

Operand: A constants vector index. The constants vector item should be a variable symbol.

Instruction size:

1 byte for `varset[0] .. varset[4]`; 2 bytes for `varset[5]`, 8-bit operand; 3 bytes for `varset[6]`, 16-bit operand.

Stack effect:

$-0 + 1$.

Example: When dynamic binding is in effect,

```
defun varset-eg(n)  
  (setq n 5))
```

generates:

PC	Byte	Instruction
0	193	constant[1] 5
1	137	dup
2	16	varset[0] n ;; sets variable n
3	135	return

Constants Vector: [n 5]

varbind (24–31)

varbind (24–31)

Binds a variable to a symbol in the constants vector, and adds the symbol to a special-bindings stack.

Implements:

`(set_internal(constants_vector[i])` where `i` is the value of the instruction operand.

Instruction size:

1 byte for `varbind[0] .. varbind[4]`; 2 bytes for `varbind[5]`, 8-bit operand;
3 bytes for `varbind[6]`, 16-bit operand.

Stack effect:

$-0 + 1$.

Example: When dynamic binding is in effect,

```
defun varbind-eg()
  (let ((c 1))
    (1+ c)))
```

generates:

PC	Byte	Instruction
0	193	constant[1] 1
1	137	dup
2	24	varbind[0] c ;; creates variable c
3	84	add1
4	41	unbind[1] ;; removes variable c
5	135	return

Constants Vector: [c 1]

call (32–39)

call (32–39)

Calls a function. The instruction argument specifies the number of arguments to pass to the function from the stack, excluding the function itself.

Implements:

`(set_internal(constants_vector[i])` where `i` is the value of the instruction operand.

Instruction size:

1 byte for `call[0] .. call[4]`; 2 bytes for `call[5]`, 8-bit operand; 3 bytes for `call[6]`, 16-bit operand.

Stack effect:

$-0 + 1$.

Example:

```
(defun call-eg()
  (exchange-point-and-mark)
  (next-line 2))
```

generates:

PC	Byte	Instruction
0	192	constant[0] exchange-point-and-mark
1	32	call[0]
2	136	discard
3	193	constant[1] next-line
4	194	constant[2] 2
5	33	call[1]
6	135	return

Constants Vector: [exchange-point-and-mark next-line 2]

unbind (40–47)

unbind (40–47)

Remove the binding of a variable to symbol and from the special stack. This is done when the variable is no longer needed.

Implements:

undo's a `let`, `unwind-protects`, and `save-excursions`

Generated via:

`let` in dynamic binding. Balancing the end of `save-excursion`.

Instruction size:

1 byte for `unbind[0]` .. `unbind[4]`; 2 bytes for `unbind[5]`, 8-bit operand; 3 bytes for `unbind[6]`, 16-bit operand.

Stack effect:

−0 + 0.

Example: When dynamic binding is in effect,

```
defun varbind-eg()
  (let ((c 1))
    (1+ c)))
```

generates:

PC	Byte	Instruction
0	193	constant[1] 1
1	137	dup
2	24	varbind[0] c ;; creates variable c
3	84	add1
4	41	unbind[1] ;; removes variable c
5	135	return

Constants Vector: [c 1]

3.3 Constants-Vector Retrieval Instructions

The instructions from opcode 192 to 255 push a value from the Constants Vector. See Section 2.1.1.3 [Constants Vector], page 7. Opcode 192 pushes the first entry, opcode 193, the second and so on. If there are more than 64 constants, opcode `constant2` (opcode 129) is used instead.

`constant (192–255)`

Pushes a value from the constants vector on the evaluation stack. There are special instructions to push any one of the first 64 entries in the constants stack.

Implements:

```
top++; TOS <- constants_vector[i] where i is the value of the instruction
operand.
```

Instruction size:

1 byte

Stack effect:

$-0 + 1$.

Example:

```
defun n3(n)
  (+ n 10 11 12))
generates:
PC  Byte  Instruction
0   193   constant[1] +
1    8    varref[0] n
2   194   constant[2] 10
3   195   constant[3] 11
4   196   constant[4] 12
5    36   call[4]
6   135   return
```

Constants Vector: [n + 10 11 12]

constant2 (129)

constant2 (129)

Pushes a value from the constants vector on the evaluation stack. Although there are special instructions to push any one of the first 64 entries in the constants stack, this instruction is needed to push a value beyond one the first 64 entries.

Implements:

```
top++; TOS <- constants_vector[i] where i is the value of the instruction
operand.
```

Operand: a 16-bit index into the constants vector.

Instruction size:

3 bytes

Stack effect:

-0 + 1.

Example:

```
(defun n64(n)
  (+ n 0 1 2 3 .. 64))
```

generates:

PC	Byte	Instruction
0	193	constant[1] +
1	8	varref[0] n
2	194	constant[2] 0
3	195	constant[3] 1
4	196	constant[4] 2
[...]		
63	255	constant[63] 61
64	129	constant2 [64] 62
		64
		0
67	129	constant2 [65] 63
		65
		0
70	129	constant2 [66] 64
		66
		0
73	38	call [66]
		66
75	135	return

Constants Vector: [n + 0 1 2 .. 61 62 63 64]

3.4 Exception-Handling Instructions

pophandler (48)

Implements:

Removes last condition pushed by `pushconditioncase`

Generated via:

`condition-case`

Instruction size:

1 byte

Stack effect:

$-0 + 0$.

Added in: Emacs 24.4. See Section 4.7 [Emacs 24], page 143.

Example:

```
(defun pushconditioncase-eg()
  (condition-case nil
    5
    (one-error 6)
    (another-error 7)))
```

generates:

PC	Byte	Instruction
0	192	constant[0] (another-error)
1	49	pushconditioncase [16]
		16
		0
4	193	constant[1] (one-error)
5	49	pushconditioncase [12]
		12
		0
8	194	constant[2] 5
9	48	pophandler
10	48	pophandler
11	135	return
12	48	pophandler
13	136	discard
14	195	constant[3] 6
15	135	return
16	136	discard
17	196	constant[4] 7
18	135	return

Constants Vector: [(another-error) (one-error) 5 6 7]

pushconditioncase (49)

pushconditioncase (49)

Implements:

Pops the TOS which is some sort of condition to test on and registers that. If any of the instructions errors with that condition, a jump to the operand occurs.

Operand: 16-bit PC address

Instruction size:

3 bytes

Stack effect:

-1 + 0.

Added in: Emacs 24.4. See Section 4.7 [Emacs 24], page 143.

Example:

```
(defun pushconditioncase-eg()
  (condition-case nil
    5
    (one-error 6)
    (another-error 7)))
```

generates:

PC	Byte	Instruction
0	192	constant[0] (another-error)
1	49	pushconditioncase [16]
		16
		0
4	193	constant[1] (one-error)
5	49	pushconditioncase [12]
		12
		0
8	194	constant[2] 5
9	48	pophandler
10	48	pophandler
11	135	return
12	48	pophandler
13	136	discard
14	195	constant[3] 6
15	135	return
16	136	discard
17	196	constant[4] 7
18	135	return

Constants Vector: [(another-error) (one-error) 5 6 7]

pushcatch (50)

pushcatch (50)

?

3.5 Control-Flow Instructions

goto (130)

Implements:

Jump to label given in the 16-bit operand

Generated via:

while and various control-flow constructs

Operand: 16-bit PC address

Instruction size:

3 bytes

Stack effect:

-0 + 0

Example: (defun goto-eg(n) (while (n) 1300)) generates:

PC	Byte	Instruction
0	192	constant[0] n
1	32	call[0]
2	133	goto-if-nil-else-pop [8]
		8
		0
5	130	goto [0]
		0
		0
8	135	return

Constants Vector: [n]

goto-if-nil (131)

goto-if-nil (131)

Implements:

Jump to label given in the 16-bit operand if TOS is nil. In contrast to `goto-if-nil-else-pop`, the test expression, TOS, is always popped.

Generated via:

if with “else” clause and various control-flow constructs

Operand: 16-bit PC address

Instruction size:

3 bytes

Stack effect:

−1 + 0

Example: (defun goto-if-nil-eg(n) (if (n) 1310 1311)) generates:

PC	Byte	Instruction
0	192	constant[0] n
1	32	call[0]
2	131	goto-if-nil [9]
		9
		0
5	193	constant[1] 1310
6	130	goto [10]
		10
		0
9	194	constant[2] 1311
10	135	return

Constants Vector: [n 1310 1311]

goto-if-not-nil (132)

goto-if-not-nil (132)

Implements:

Jump to label given in the 16-bit operand if TOS is not nil. In contrast to `goto-if-not-nil-else-pop`, the test expression, TOS, is always popped.

Generated via:

or inside an `if` with optimization and various control-flow constructs

Operand: 16-bit PC address

Instruction size:

3 bytes

Stack effect:

$-1 + 0$

Example: With bytecode optimization, `(defun goto-if-not-nil-eg(n) (if (or (n) (n)) 1320))` generates:

PC	Byte	Instruction
0	192	constant[0] n
1	32	call[0]
2	132	goto-if-not-nil [10] 10 0
5	192	constant[0] n
6	32	call[0]
7	133	goto-if-nil-else-pop [11] 11 0
10	193	constant[1] 1320
11	135	return

Constants Vector: [n 1320]

Note the change in opcode when bytecode optimization is not performed.

goto-if-nil-else-pop (133)

goto-if-nil-else-pop (133)

Implements:

Jump to label given in the 16-bit operand if TOS is nil; otherwise pop the TOS, the tested condition. This allows the test expression, nil, to be used again on the branch as the TOS.

Generated via:

cond, if and various control-flow constructs

Operand: 16-bit PC address

Instruction size:

3 bytes

Stack effect:

$\phi(0, -1) + 0$

Example: (defun goto-if-nil-else-pop-eg(n) (cond ((n) 1330))) generates:

PC	Byte	Instruction
0	192	constant[0] n
1	32	call[0]
2	133	goto-if-nil-else-pop [6]
		6
		0
5	193	constant[1] 1330
6	135	return

Constants Vector: [n 1330]

goto-if-not-nil-else-pop (134)

goto-if-not-nil-else-pop (134)

Implements:

Jump to label given in the 16-bit operand if TOS is not nil; otherwise pop TOS, the tested condition. This allows the tested expression on TOS to be used again when the jump is taken.

Generated via:

cond, if and various control-flow constructs

Operand: 16-bit PC address

Instruction size:

3 bytes

Stack effect:

$\phi(0, -1) + 0$

Example:

```
(defun goto-if-not-nil-else-pop-eg(n)
  (if (or (n) (n))
      1340))
```

generates:

PC	Byte	Instruction
0	192	constant[0] n
1	32	call[0]
2	134	goto-if-not-nil-else-pop [7]
		7
		0
5	192	constant[0] n
6	32	call[0]
7	133	goto-if-nil-else-pop [11]
		11
		0
10	193	constant[1] 1340
11	135	return

Constants Vector: [n 1340]

Note the change in opcode when bytecode optimization is performed.

return (135)

return (135)

Implements:

Return from function. This is the last instruction in a function's bytecode sequence. The top value on the evaluation stack is the return value.

Generated via:

lambda

Instruction size:

1 byte

Stack effect:

-1 + 0

Example: (defun return-eg(n) 1350) generates:

PC	Byte	Instruction
0	192	constant[0] 1350
1	135	return

Constants Vector: [1350]

switch (135)

switch (135)

Jumps to entry in a jumptable

Implements:

Jumps to entry in a jumptable

Generated via:

??

Instruction size:

1 byte

Stack effect:

$-2 + 0$

Added in: Emacs 26.1

Example: ?

3.6 Function-Call Instructions

These instructions use up one byte, and are followed by the next instruction directly. They are equivalent to calling an Emacs Lisp function with a fixed number of arguments: the arguments are popped from the stack, and a single return value is pushed back onto the stack.

3.6.1 Lisp Function Instructions

These instructions correspond to general functions which are not specific to Emacs; common cases are usually inlined for speed by the bytecode interpreter.

symbolp (57)

Call `symbolp`.

Implements:

`TOS <- (symbolp TOS).`

Generated via:

`symbolp.`

Instruction size:

1 byte

Stack effect:

$-1 + 1$.

Example: When lexical binding is in effect, `(defun symbolp-eg(n) (symbolp n))` generates:

PC	Byte	Instruction
0	137	<code>dup</code>
1	57	<code>symbolp</code>
2	135	<code>return</code>

consp (58)

consp (58)

Call consp.

Implements:

TOS <- (consp TOS).

Generated via:

consp.

Instruction size:

1 byte

Stack effect:

-1 + 1.

Example: When lexical binding is in effect, (defun consp-eg(n) (consp n)) generates:

PC	Byte	Instruction
0	137	dup
1	58	consp
2	135	return

stringp (59)

stringp (59)

Call stringp.

Implements:

TOS <- (stringp TOS).

Generated via:

unary stringp.

Instruction size:

1 byte

Stack effect:

-1 + 1.

Example: When lexical binding is in effect, (defun stringp-eg(n) (stringp n)) generates:

PC	Byte	Instruction
0	137	dup
1	59	stringp
2	135	return

listp (60)

listp (60)

Call listp.

Implements:

TOS <- (listp TOS).

Generated via:

unary listp.

Instruction size:

1 byte

Stack effect:

-1 + 1.

Example: When lexical binding is in effect, (defun listp-eg(n) (listp n)) generates:

PC	Byte	Instruction
0	137	dup
1	60	listp
2	135	return

eq (61)

eq (61)

Call eq.

Implements:

`S[1] <- (eq S[1] TOS); top--.`

Generated via:

binary eq.

Instruction size:

1 byte

Stack effect:

$-2 + 1$.

Example: When lexical binding is in effect, `(defun eq-eg(a b) (eq a b))` generates:

PC	Byte	Instruction
0	1	stack-ref[1]
1	1	stack-ref[1]
2	61	eq
3	135	return

memq (62)

memq (62)

Call memq.

Implements:

```
S[1] <- (memq S[1] TOS); top--.
```

Generated via:

binary memq.

Instruction size:

1 byte

Stack effect:

$-2 + 1$.

Example: When lexical binding is in effect, (defun memq-eg(a b) (memq a b)) generates:

PC	Byte	Instruction
0	1	stack-ref[1]
1	1	stack-ref[1]
2	62	memq
3	135	return

not (63)

not (63)

Call not.

Implements:

TOS <- (not TOS).

Generated via:

unary not.

Instruction size:

1 byte

Stack effect:

-1 + 1.

Example: When lexical binding is in effect, (defun not-eg(a) (not a)) generates:

PC	Byte	Instruction
0	137	dup
1	63	not
2	135	return

symbol-value (74)

symbol-value (74)

Call symbol-value.

Implements:

```
TOS <- (symbol-value TOS).
```

Generated via:

```
symbol-value.
```

Instruction size:

```
1 byte
```

Stack effect:

```
-1 + 1.
```

Example: When lexical binding is in effect, (defun symbol-value-eg(a) (symbol-value a)) generates:

PC	Byte	Instruction
0	137	dup
1	74	symbol-value
2	135	return

symbol-function (75)

symbol-function (75)

Call symbol-function.

Implements:

```
TOS <- (symbol-function TOS).
```

Generated via:

```
symbol-function.
```

Instruction size:

1 byte

Stack effect:

-1 + 1.

Example: When lexical binding is in effect, (defun symbol-function-eg(a) (symbol-function a)) generates:

PC	Byte	Instruction
0	137	dup
1	75	symbol-function
2	135	return

set (76)

set (76)

Call set.

Implements:

```
S[1] <- (set S[1] TOS); top--.
```

Generated via:

```
set.
```

Instruction size:

1 byte

Stack effect:

$-2 + 1$.

Example: When lexical binding is in effect, `(defun set-eg(a b) (set a b))` generates:

PC	Byte	Instruction
0	1	stack-ref[1]
1	1	stack-ref[1]
2	76	set
3	135	return

fset (77)

fset (77)

Call fset.

Implements:

`S[1] <- (fset S[1] TOS); top--.`

Generated via:

`binary fset.`

Instruction size:

1 byte

Stack effect:

$-2 + 1$.

Example: When lexical binding is in effect, `(defun fset-eg(a b) (fset a b))` generates:

PC	Byte	Instruction
0	1	stack-ref[1]
1	1	stack-ref[1]
2	77	fset
3	135	return

get (78)

get (78)

Call get.

Implements:

`S[1] <- (get S[1] TOS); top--.`

Generated via:

binary get.

Instruction size:

1 byte

Stack effect:

$-2 + 1$.

Example: When lexical binding is in effect, `(defun get-eg(a b) (get a b))` generates:

PC	Byte	Instruction
0	1	stack-ref[1]
1	1	stack-ref[1]
2	78	get
3	135	return

equal (154)

equal (154)

Call equal.

Implements:

```
S[1] <- (equal S[1] TOS); top--.
```

Generated via:

binary equal.

Instruction size:

1 byte

Stack effect:

-2 + 1.

Added in: Emacs 19.34. See Section 4.2 [Emacs 19], page 139.

Example: When lexical binding is in effect, (defun equal-eg(a b) (equal a b)) generates:

PC	Byte	Instruction
0	1	stack-ref[1]
1	1	stack-ref[1]
2	154	equal
3	135	return

member (157)

member (157)

Call member.

Implements:

```
S[1] <- (member S[1] TOS); top--.
```

Generated via:

```
member.
```

Instruction size:

```
1 byte
```

Stack effect:

```
-2 + 1.
```

Example: When lexical binding is in effect, (defun member-eg(a b) (member a b)) generates:

PC	Byte	Instruction
0	1	stack-ref[1]
1	1	stack-ref[1]
2	157	member
3	135	return

assq (158)

assq (158)

Call assq.

Implements:

```
S[1] <- (assq S[1] TOS); top--.
```

Generated via:

```
binary assq.
```

Instruction size:

```
1 byte
```

Stack effect:

```
-2 + 1.
```

Example: When lexical binding is in effect, (defun assq-eg(a b) (assq a b)) generates:

PC	Byte	Instruction
0	1	stack-ref[1]
1	1	stack-ref[1]
2	158	assq
3	135	return

numberp (167)

numberp (167)

Call numberp.

Implements:

TOS <- (numberp TOS).

Generated via:

numberp.

Instruction size:

1 byte

Stack effect:

-1 + 1.

Added in: Emacs 19.34. See Section 4.2 [Emacs 19], page 139.

Example: When lexical binding is in effect, (defun numberp-eg(a) (numberp a)) generates:

PC	Byte	Instruction
0	137	dup
1	167	numberp
2	135	return

integerp (168)

integerp (168)

Call integerp.

Implements:

TOS <- (integerp TOS).

Generated via:

integerp.

Instruction size:

1 byte

Stack effect:

-1 + 1.

Added in: Emacs 19.34. See Section 4.2 [Emacs 19], page 139.

Example: When lexical binding is in effect, (defun integerp-eg(a) (integerp a)) generates:

PC	Byte	Instruction
0	137	dup
1	168	integerp
2	135	return

3.6.2 List Function Instructions

These instructions correspond to general functions which are not specific to Emacs; common cases are usually inlined for speed by the bytecode interpreter.

nth (56)

Call **nth** with two stack arguments.

Implements:

```
S[1] <- (nth S[1] TOS); top--.
```

Generated via:

```
nth.
```

Instruction size:

```
1 byte
```

Stack effect:

```
-2 + 1.
```

Example: When lexical binding is in effect, `(defun nth-eg(1) (nth 560 1))` generates:

PC	Byte	Instruction
0	192	constant[0] 560
1	1	stack-ref[1]
2	56	nth
3	135	return

Constants Vector: [560]

car (64)

car (64)

Call `car` with one stack argument.

Implements:

```
TOS <- (car TOS).
```

Generated via:

```
car.
```

Instruction size:

1 byte

Stack effect:

$-1 + 1$.

Example: When lexical binding is in effect, `(defun car-eg(1) (car 1))` generates:

PC	Byte	Instruction
0	137	dup
1	64	car
2	135	return

cdr (65)

cdr (65)

Call `cdr` with one stack argument.

Implements:

`TOS <- (cdr TOS).`

Generated via:

`cdr.`

Instruction size:

1 byte

Stack effect:

$-1 + 1$.

Example: When lexical binding is in effect, `(defun cdr-eg(1) (cdr 1))` generates:

PC	Byte	Instruction
0	137	dup
1	65	cdr
2	135	return

cons (66)

cons (66)

Call cons with two stack arguments.

Implements:

```
S[1] <- (cons S[1] TOS); top--.
```

Generated via:

```
cons.
```

Instruction size:

```
1 byte
```

Stack effect:

```
-2 + 1.
```

Example: (defun cons-eg() (cons 'a 'b)) generates:

PC	Byte	Instruction
0	192	constant[0] a
1	193	constant[1] b
2	66	cons
3	135	return

Constants Vector: [a b]

list1 (67)

list1 (67)

Call list with TOS.

Implements:

```
TOS <- (list TOS).
```

Generated via:

```
list.
```

Instruction size:

```
1 byte
```

Stack effect:

```
-1 + 1.
```

Example: (defun list1-eg() (list 'a)) generates:

PC	Byte	Instruction
0	192	constant[0] a
1	67	list1
2	135	return

Constants Vector: [a]

Call list with TOS.

list2 (68)

list2 (68)

Call `list` with two stack items.

Implements:

```
S[1] <- (list S[1] TOS); top--.
```

Generated via:

```
list.
```

Instruction size:

1 byte

Stack effect:

$-2 + 1$.

Example: `(defun list2-eg() (list 'a 'b))` generates:

PC	Byte	Instruction
0	192	constant[0] a
1	193	constant[1] b
2	68	list2
3	135	return

Constants Vector: [a b]

list3 (69)

list3 (69)

Call `list` with three stack items.

Implements:

```
S[2] <- (list S[2] S[1] TOS); top -= 2.
```

Generated via:

```
list
```

Instruction size:

```
1 byte
```

Stack effect:

```
-3 + 1.
```

Example: `(defun list3-eg() (list 'a 'b 'c))` generates:

PC	Byte	Instruction
0	192	constant[0] a
1	193	constant[1] b
2	194	constant[2] c
3	69	list3
4	135	return

Constants Vector: [a b c]

list4 (70)

list4 (70)

Call `list` with four stack items.

Implements:

```
S[3] <- (list S[3] S[2] S[1] TOS); top -= 2.
```

Generated via:

```
list.
```

Instruction size:

1 byte

Stack effect:

$-4 + 1$.

Example: `(defun list4-eg() (list 'a 'b 'c 'd))` generates:

PC	Byte	Instruction
0	192	constant[0] a
1	193	constant[1] b
2	194	constant[2] c
3	195	constant[3] d
4	70	list4
5	135	return

Constants Vector: [a b c d]

listN (175)

listN (175)

Call `list` on up to 255 items. Note that there are special instructions for the case where there are 1 to 4 items in the list.

Implements:

`S[n-1] <- (list S[n-1] S[n-2] ... TOS); top -= (n-1)` where `n` is the value of the operand.

Generated via:

`list.`

Operand: 8-bit number of items in list

Instruction size:

2 bytes

Stack effect:

$-n + 1$ where n is the value of the instruction operand.

Added in: Emacs 19.34. See Section 4.2 [Emacs 19], page 139.

Example: `(defun listN-eg() (list 'a 'b 'c 'd 'e))` generates:

PC	Byte	Instruction
0	192	constant[0] a
1	193	constant[1] b
2	194	constant[2] c
3	195	constant[3] d
4	196	constant[4] e
5	175	listN [5]
		5
7	135	return

Constants Vector: [a b c d e]

length (71)

length (71)

Call `length` with one stack argument.

Implements:

```
TOS <- (length TOS).
```

Generated via:

```
length.
```

Instruction size:

```
1 byte
```

Stack effect:

```
-1 + 1.
```

Example: `(defun length-eg() (length '(a b)))` generates:

PC	Byte	Instruction
0	192	constant[0] (a b)
1	71	length
2	135	return

Constants Vector: [(a b)]

aref (72)

aref (72)

Call `aref` with two stack arguments.

Implements:

```
S[1] <- (aref S[1] TOS); top--.
```

Generated via:

```
aref.
```

Instruction size:

1 byte

Stack effect:

$-2 + 1$.

Example: `(defun aref-eg() (aref '[720 721 722] 0))` generates:

PC	Byte	Instruction
0	192	constant[0] [720 721 722]
1	193	constant[1] 0
2	72	aref
3	135	return

Constants Vector: `[[720 721 722] 0]`

aset (73)

aset (73)

Call aset with three stack arguments.

Implements:

```
S[2] <- (aset S[2] S[1] TOS); top-=2.
```

Generated via:

```
aset.
```

Instruction size:

```
1 byte
```

Stack effect:

```
-2 + 1.
```

Example: (defun aset-eg() (aset array-var 0 730)) generates:

PC	Byte	Instruction
0	8	varref[0] array-var
1	193	constant[1] 0
2	194	constant[2] 730
3	73	aset
4	135	return

Constants Vector: [array-var 0 730]

nthcdr (155)

nthcdr (155)

Call **nthcdr** with two stack arguments.

Implements:

```
S[1] <- (nthcdr S[1] TOS); top --.
```

Generated via:

```
nthcdr.
```

Instruction size:

```
1 byte
```

Stack effect:

```
-2 + 1.
```

Added in: Emacs 19.34. See Section 4.2 [Emacs 19], page 139.

Example: (defun nthcdr-eg() (nthcdr '(1550 1551 1552) 2)) generates:

PC	Byte	Instruction
0	192	constant[0] (1550 1551 1552)
1	193	constant[1] 2
2	155	nthcdr
3	135	return

Constants Vector: [(1550 1551 1552) 2]

elt (156)

elt (156)

Call `elt` with two stack arguments.

Implements:

```
S[1] <- (elt S[1] TOS); top --.
```

Generated via:

```
elt.
```

Instruction size:

```
1 byte
```

Stack effect:

```
-2 + 1.
```

Added in: Emacs 19.34. See Section 4.2 [Emacs 19], page 139.

Example: `(defun elt-eg() (elt '(1560 1561 1562) 2))` generates:

PC	Byte	Instruction
0	192	constant[0] (1560 1561 1562)
1	193	constant[1] 2
2	156	elt
3	135	return

Constants Vector: [(1560 1561 1562) 2]

nreverse (159)

nreverse (159)

Call `nreverse` with one stack argument.

Implements:

```
TOS <- (elt TOS).
```

Generated via:

```
nreverse.
```

Instruction size:

1 byte

Stack effect:

-1 + 1.

Added in: Emacs 19.34. See Section 4.2 [Emacs 19], page 139.

Example: `(defun nreverse-eg() (nreverse '(1590 1591)))` generates:

PC	Byte	Instruction
0	192	constant[0] (1590 1591)
1	159	nreverse
2	135	return

Constants Vector: [(1590 1591)]

setcar (160)

setcar (160)

Call `setcar` with two stack arguments.

Implements:

```
S[1] <- (setcar S[1] TOS); top--.
```

Generated via:

```
setcar.
```

Instruction size:

1 byte

Stack effect:

$-2 + 1$.

Added in: Emacs 19.34. See Section 4.2 [Emacs 19], page 139.

Example: With lexical binding in effect, `(defun setcar-eg(1) (setcar 1 1600)))` generates:

PC	Byte	Instruction
0	137	dup
1	192	constant[0] 1600
2	160	setcar
3	135	return

Constants Vector: [1600]

setcdr (161)

setcdr (161)

Call `setcdr` with two stack arguments.

Implements:

```
S[1] <- (setcdr S[1] TOS); top--.
```

Generated via:

```
setcdr.
```

Instruction size:

```
1 byte
```

Stack effect:

```
-2 + 1.
```

Added in: Emacs 19.34. See Section 4.2 [Emacs 19], page 139.

Example: With lexical binding in effect, `(defun setcdr-eg(1) (setcdr 1 1610)))` generates:

PC	Byte	Instruction
0	137	dup
1	192	constant[0] 1610
2	161	setcdr
3	135	return

Constants Vector: [1610]

car-safe (162)

car-safe (162)

Call `car-safe` with one argument.

Implements:

```
TOS <- (car-safe TOS).
```

Generated via:

```
car-safe.
```

Instruction size:

1 byte

Stack effect:

$-1 + 1$.

Added in: Emacs 19.34. See Section 4.2 [Emacs 19], page 139.

Example: With lexical binding in effect, `(defun car-safe-eg(1) (car-safe 1))` generates:

PC	Byte	Instruction
0	137	dup
1	162	car-safe
2	135	return

cdr-safe (163)

cdr-safe (163)

Call `cdr-safe` with one stack argument.

Implements:

```
TOS <- (cdr-safe TOS).
```

Generated via:

```
cdr-safe.
```

Instruction size:

```
1 byte
```

Stack effect:

```
-1 + 1.
```

Added in: Emacs 19.34. See Section 4.2 [Emacs 19], page 139.

Example: With lexical binding in effect, `(defun cdr-safe-eg(1) (cdr-safe 1))` generates:

PC	Byte	Instruction
0	137	dup
1	163	cdr-safe
2	135	return

nconc (164)

nconc (164)

Call `nconc` with two stack arguments.

Implements:

```
S[1] <- (nconc S[1] TOS); top--.
```

Generated via:

```
nconc.
```

Instruction size:

```
1 byte
```

Stack effect:

```
-2 + 1.
```

Added in: Emacs 19.34. See Section 4.2 [Emacs 19], page 139.

Example: With lexical binding in effect, `(defun nconc-eg(a b) (nconc a b))` generates:

PC	Byte	Instruction
0	1	stack-ref[1]
1	1	stack-ref[1]
2	164	nconc
3	135	return

3.6.3 Arithmetic Function Instructions

These instructions correspond to general functions which are not specific to Emacs; common cases are usually inlined for speed by the bytecode interpreter.

sub1 (83)

Call 1-.

Implements:

TOS <- (1- TOS).

Generated via:

1-.

Instruction size:

1 byte

Stack effect:

-1 + 1.

Example: When lexical binding is in effect, (defun sub1-eg(n) (1- n)) generates:

PC	Byte	Instruction
0	137	dup
1	83	sub1
2	135	return

add1 (84)

add1 (84)

Call 1+.

Implements:

TOS <- (1+ TOS).

Generated via:

unary -.

Instruction size:

1 byte

Stack effect:

-1 + 1.

Example: When lexical binding is in effect, (defun add1-eg(n) (1+ n)) generates:

PC	Byte	Instruction
0	137	dup
1	84	add1
2	135	return

eqlsign (85)

eqlsign (85)

Call =.

Implements:

`S[1] <- (= S[1] TOS); top--.`

Generated via:

binary =.

Instruction size:

1 byte

Stack effect:

$-2 + 1$.

Example: When dynamic binding is in effect, `(defun eqlsign-eg(a b) (= a b))` generates:

PC	Byte	Instruction
0	8	varref[0] a
1	9	varref[1] b
2	85	eqlsign
3	135	return

Constants Vector: [a b]

gtr (86)

gtr (86)

Call >.

Implements:

`S[1] <- (> S[1] TOS); top--.`

Generated via:

`>.`

Instruction size:

1 byte

Stack effect:

$-2 + 1$.

Example: When lexical binding is in effect, `(defun gtr-eg(a b) (> a b))` generates:

PC	Byte	Instruction
0	1	stack-ref[1]
1	1	stack-ref[1]
2	86	gtr
3	135	return

lss (87)

lss (87)

Call <.

Implements:

`S[1] <- (< S[1] TOS); top--.`

Generated via:

`<.`

Instruction size:

1 byte

Stack effect:

$-2 + 1$.

Example: When dynamic binding is in effect, `(defun lss-eg(a b) (< a b))` generates:

PC	Byte	Instruction
0	8	varref[0] a
1	9	varref[1] b
2	87	lss
3	135	return

Constants Vector: [a b]

leq (88)

leq (88)

Call <=.

Implements:

`S[1] <- (<= S[1] TOS); top--.`

Instruction size:

1 byte

Generated via:

<=.

Instruction size:

1 byte

Stack effect:

$-2 + 1$.

Example: When dynamic binding is in effect, `(defun leq-eg(a b) (<= a b))` generates:

PC	Byte	Instruction
0	8	varref[0] a
1	9	varref[1] b
2	88	leq
3	135	return

Constants Vector: [a b]

geq (89)

geq (89)

Call >=.

Implements:

```
S[1] <- (>= S[1] TOS); top--.
```

Instruction size:

1 byte

Generated via:

>=.

Instruction size:

1 byte

Stack effect:

-2 + 1.

Example: When lexical binding is in effect, (defun geq-eg(a b) (>= a b)) generates:

PC	Byte	Instruction
0	1	stack-ref[1]
1	1	stack-ref[1]
2	89	geq
3	135	return

diff (90)

diff (90)

Call binary `-`.

Implements:

```
S[1] <- (- S[1] TOS); top--.
```

Generated via:

binary `-`.

Instruction size:

1 byte

Instruction size:

1 byte

Stack effect:

$-2 + 1$.

Example: When lexical binding is in effect, `(defun diff-eg(a b) (- a b))` generates:

PC	Byte	Instruction
0	1	stack-ref[1]
1	1	stack-ref[1]
2	90	diff
3	135	return

negate (91)

negate (91)

Call unary -.

Implements:

TOS <- (- TOS).

Generated via:

unary -.

Instruction size:

1 byte

Instruction size:

1 byte

Stack effect:

-1 + 1.

Example: When lexical binding is in effect, (defun negate-eg(a) (- a)) generates:

PC	Byte	Instruction
0	8	varref[0] a
1	91	negate
2	135	return

Constants Vector: [a]

plus (92)

plus (92)

Call unary +.

Implements:

```
S[1] <- (+ S[1] TOS); top--.
```

Generated via:

+

Instruction size:

1 byte

Stack effect:

-2 + 1.

Example: When dynamic binding is in effect, (defun plus-eg(n) (+ n n)) generates:

PC	Byte	Instruction
0	8	varref[0] n
1	137	dup
2	92	plus
3	135	return

Constants Vector: [n]

mult (95)

mult (95)

Call *.

Implements:

S[1] <- (* S[1] TOS); top--.

Generated via:

*.

Instruction size:

1 byte

Stack effect:

-2 + 1.

Added in: Emacs 19.34. See Section 4.2 [Emacs 19], page 139.

Example: When dynamic binding is in effect, (defun mult-eg(n) (* n n)) generates:

PC	Byte	Instruction
0	8	varref[0] n
1	137	dup
2	95	mult
3	135	return

Constants Vector: [n]

max (93)

max (93)

Call max.

Implements:

`S[1] <- (max S[1] TOS); top--.`

Generated via:

`max.`

Instruction size:

1 byte

Stack effect:

$-2 + 1$.

Example: When dynamic binding is in effect, `(defun max-eg(a b) (max a b))` generates:

PC	Byte	Instruction
0	8	varref[0] a
1	9	varref[1] b
2	93	max
3	135	return

Constants Vector: [a b]

min (94)

min (94)

Call min.

Implements:

TOS <- (min(S[1] TOS).

Generated via:

binary min.

Instruction size:

1 byte

Stack effect:

-2 + 1.

Example: When dynamic binding is in effect, (defun min-eg(a b) (min a b)) generates:

PC	Byte	Instruction
0	8	varref[0] a
1	9	varref[1] b
2	94	min
3	135	return

Constants Vector: [a b]

quo (165)

quo (165)

Call /.

Implements:

`S[1] <- (/ S[1] TOS); top--.`

Generated via:

`/.`

Instruction size:

1 byte

Stack effect:

$-2 + 1$.

Example: When dynamic binding is in effect, `(defun min-quo(a b) (/ a b))` generates:

PC	Byte	Instruction
0	8	varref[0] a
1	9	varref[1] b
2	165	quo
3	135	return

Constants Vector: [a b]

rem (166)

rem (166)

Call %.

implements:

`S[1] <- (% S[1] TOS); top--.`

generated via:

`%`

Instruction size:

1 byte

Stack effect:

$-2 + 1$

Added in: Emacs 19.34. See Section 4.2 [Emacs 19], page 139.

Example: When lexical binding is in effect, `(defun rem-eg(a b) (% a b))` generates:

PC	Byte	Instruction
0	1	stack-ref[1]
1	1	stack-ref[1]
2	166	rem
3	135	return

3.6.4 String Function Instructions

These instructions correspond to general functions which are not specific to Emacs; the bytecode interpreter calls the corresponding C function for them.

substring (79)

Call `substring` with three stack arguments.

Implements:

```
S[2] <- (substring S[2] S[1] TOS); top-=2.
```

Generated via:

```
substring.
```

Instruction size:

1 byte

Stack effect:

$-2 + 1$.

Example: `(defun substring-eg() (substring "abc" 0 2))` generates:

PC	Byte	Instruction
0	192	constant[0] "abc"
1	193	constant[1] 0
2	194	constant[2] 2
3	79	substring
4	135	return

Constants Vector: ["abc" 0 2]

concat2 (80)

concat2 (80)

Call `concat` with two stack arguments.

Implements:

```
S[1] <- (concat S[1] TOS); top--.
```

Generated via:

```
concat.
```

Instruction size:

```
1 byte
```

Stack effect:

```
-2 + 1.
```

Added in: Emacs 19.34. See Section 4.2 [Emacs 19], page 139.

Example: `(defun concat2-eg() (concat "a" "b"))` generates:

PC	Byte	Instruction
0	192	constant[0] "a"
1	193	constant[1] "b"
2	80	concat2
3	135	return

Constants Vector: ["a" "b"]

concat3 (81)

concat3 (81)

Call concat with three stack arguments.

Implements:

```
S[2] <- (concat S[2] S[1] TOS); top-=2.
```

Generated via:

```
concat.
```

Instruction size:

1 byte

Stack effect:

-2 + 1.

Example: (defun concat3-eg() (concat "a" "b" "c")) generates:

PC	Byte	Instruction
0	192	constant[0] "a"
1	193	constant[1] "b"
2	194	constant[2] "c"
3	81	concat3
4	135	return

Constants Vector: ["a" "b" "c"]

concat4 (82)

concat4 (82)

Call `concat` with four stack arguments.

Implements:

```
S[3] <- (concat S[3] S[2] S[1] TOS); top -= 2.
```

Generated via:

```
concat.
```

Instruction size:

1 byte

Stack effect:

$-4 + 1$.

Example: `(defun concat4-eg() (concat "a" "b" "c" "d"))` generates:

PC	Byte	Instruction
0	192	constant[0] "a"
1	193	constant[1] "b"
2	194	constant[2] "c"
3	195	constant[3] "d"
4	82	concat4
5	135	return

Constants Vector: ["a" "b" "c" "d"]

concatN (174)

concatN (174)

Call `concat` on up to 255 stack arguments. Note there are special instructions for the case where there are 2 to 4 items to concatenate.

Implements:

```
S[n-1] <- (concat S[n-1] S[n-2] ... TOS); top -= (n-1).
```

Generated via:

```
concat.
```

Operand: 8-bit number of items in `concat`

Instruction size:

2 bytes

Stack effect:

$-n + 1$ where n is the value of the instruction operand.

Added in: Emacs 19.34. See Section 4.2 [Emacs 19], page 139.

Example: `(defun concatN-eg() (concat "a" "b" "c" "d" "e"))` generates:

PC	Byte	Instruction
0	192	constant[0] "a"
1	193	constant[1] "b"
2	194	constant[2] "c"
3	195	constant[3] "d"
4	196	constant[4] "e"
5	176	concatN [5]
		5
7	135	return

Constants Vector: ["a" "b" "c" "d" "e"]

upcase (150)

upcase (150)

Call `upcase` with one stack argument.

Implements:

```
TOS <- (upcase TOS).
```

Generated via:

```
upcase.
```

Instruction size:

```
1 byte
```

Stack effect:

```
-1 + 1.
```

Added in: Emacs 19.34. See Section 4.2 [Emacs 19], page 139.

Example: `(defun upcase-eg() (upcase "abc"))` generates:

PC	Byte	Instruction
0	192	constant[0] "abc"
1	150	upcase
2	135	return

Constants Vector: ["abc"]

downcase (151)

downcase (151)

Call `downcase` with one argument.

Implements:

```
TOS <- (downcase TOS).
```

Generated via:

```
downcase.
```

Instruction size:

```
1 byte
```

Stack effect:

```
-1 + 1.
```

Added in: Emacs 19.34. See Section 4.2 [Emacs 19], page 139.

Example: `(defun downcase-eg(1) (downcase "ABC"))` generates:

PC	Byte	Instruction
0	192	constant[0] "ABC"
1	151	downcase
2	135	return

Constants Vector: ["ABC"]

stringeqsign (152)

stringeqsign (152)

Call `string=` with two stack arguments, comparing two strings for equality.

Implements:

```
S[1] <- (string= S[1] TOS); top--.
```

Generated via:

```
string=.
```

Instruction size:

```
1 byte
```

Stack effect:

```
-2 + 1.
```

Added in: Emacs 19.34. See Section 4.2 [Emacs 19], page 139.

Example: With lexical binding in effect,
(defun stringeqsign-eg(a)
 (string= a "b"))

generates:

PC	Byte	Instruction
0	137	dup
1	192	constant[0] "b"
2	152	string=
3	135	return

Constants Vector: ["b"]

stringlss (153)

stringlss (153)

Call `string<` with two stack arguments, comparing two strings.

Implements:

```
S[1] <- (string< S[1] TOS); top--.
```

Generated via:

```
string<.
```

Instruction size:

```
1 byte
```

Stack effect:

```
-2 + 1.
```

Added in: Emacs 19.34. See Section 4.2 [Emacs 19], page 139.

Example: With lexical binding in effect,

```
(defun stringlss-eg(a)
  (string< a "b"))
```

generates:

PC	Byte	Instruction
0	137	dup
1	192	constant[0] "b"
2	153	string<
3	135	return

Constants Vector: ["b"]

3.6.5 Emacs Buffer Instructions

current-buffer (112)

Call current-buffer.

Implements:

```
TOS <- (current-buffer)
```

Generated via:

```
current-buffer
```

Instruction size:

1 byte

Stack effect:

$-0 + 1$.

Example: (defun current-buffer-eg() (current-buffer)) generates:

PC	Byte	Instruction
0	112	current-buffer
1	135	return

set-buffer (113)

set-buffer (113)

Call set-buffer with TOS.

Implements:

```
TOS <- (set-buffer TOS)
```

Generated via:

```
set-buffer
```

Instruction size:

1 byte

Stack effect:

-1 + 1.

Example: (defun set-buffer-eg() (set-buffer "*scratch")) generates:

PC	Byte	Instruction
0	192	constant[0] "*scratch"
1	113	set-buffer
2	135	return

Constants Vector: ["*scratch"]

save-current-buffer-1 (114)

save-current-buffer-1 (114)

Call `save-current-buffer`.

Replaces older `save-current-buffer`. See [save-current-buffer], page 134.

Implements:

```
TOS <- (save-current-buffer)
```

Generated via:

```
save-current-buffer
```

Instruction size:

1 byte

Stack effect:

-1 + 1.

Added in: Emacs 22. See Section 4.5 [Emacs 22], page 142.

Example:

```
(defun save-current-buffer-1-eg()
  (save-current-buffer (prog 5)))}
```

generates:

PC	Byte	Instruction
0	114	save-current-buffer
1	192	constant[0] prog
2	193	constant[1] 5
3	33	call[1]
4	41	unbind[1]
5	135	return

Constants Vector: [prog 5]

buffer-substring (123)

buffer-substring (123)

Call `buffer-substring` with two stack arguments.

Implements:

```
S[1] <- (buffer-substring S[1] TOS); top--.
```

Generated via:

```
buffer-substring.
```

Instruction size:

1 byte

Stack effect:

$-2 + 1$. Emacs 19.34. See Section 4.2 [Emacs 19], page 139.

Example: `(defun buffer-substring-eg() (buffer-substring 1230 1231))` generates:

PC	Byte	Instruction
0	192	constant[0] 1230
1	193	constant[1] 1231
2	123	buffer-substring
3	135	return

Constants Vector: [1230 1231]

3.6.6 Emacs Position Instructions

These instructions correspond to Emacs-specific position functions that are found in the "Positions" chapter of the Emacs Lisp Reference Manual. They are not inlined by the bytecode interpreter, but simply call the corresponding C function.

point (96)

Call point.

Implements:

```
TOS <- (point)
```

Generated via:

```
point
```

Instruction size:

```
1 byte
```

Stack effect:

```
-0 + 1.
```

Added in: Emacs 18.31, renamed from `dot`. See Section 4.1 [Emacs 18], page 138.

Example: `(defun point-eg() (point))` generates:

PC	Byte	Instruction
0	96	point
1	135	return

goto-char (98)

goto-char (98)

Call goto-char with one stack argument.

Implements:

```
TOS <- (goto-char TOS)
```

Generated via:

```
goto-char
```

Instruction size:

1 byte

Stack effect:

-1 + 1.

Example: With lexical binding in effect, (defun goto-char-eg(n) (goto-char n)) generates:

PC	Byte	Instruction
0	137	dup
1	98	goto-char
2	135	return

point-max (100)

point-max (100)

Call point-max.

Implements:

```
TOS <- (point-max)
```

Generated via:

```
point-max
```

Instruction size:

1 byte

Stack effect:

-0 + 1.

Added in: Emacs 18.31, renamed from `dot-max`. See Section 4.1 [Emacs 18], page 138.

Example: (defun point-max-eg() (point-max)) generates:

PC	Byte	Instruction
0	100	point-max
1	135	return

point-min (101)

point-min (101)

Call point-min.

Implements:

```
TOS <- (point-min)
```

Generated via:

```
point-min
```

Instruction size:

1 byte

Stack effect:

$-0 + 1$.

Added in: Emacs 18.31, renamed from `dot-min`. See Section 4.1 [Emacs 18], page 138.

Example: (defun point-min-eg() (point-min)) generates:

PC	Byte	Instruction
0	101	point-min
1	135	return

forward-char (117)

forward-char (117)

Call forward-char with one stack argument.

Implements:

```
TOS <- (forward-char TOS)
```

Generated via:

```
forward-char
```

Instruction size:

```
1 byte
```

Stack effect:

```
-1 + 1.
```

Added in: Emacs 19.34. See Section 4.2 [Emacs 19], page 139.

Example: (defun forward-char-eg() (forward-char 1)) generates:

PC	Byte	Instruction
0	192	constant[0] 1
1	117	forward-char
2	135	return

Constants Vector: [1]

forward-word (118)

forward-word (118)

Call forward-word with one stack argument.

Implements:

```
TOS <- (forward-word TOS)
```

Generated via:

```
forward-word
```

Instruction size:

1 byte

Stack effect:

-1 + 1.

Added in: Emacs 19.34. See Section 4.2 [Emacs 19], page 139.

Example: (defun forward-word-eg() (forward-word 1)) generates:

PC	Byte	Instruction
0	192	constant[0] 1
1	118	forward-word
2	135	return

Constants Vector: [1]

forward-line (121)

`forward-line (121)`

Call `forward-line` with one stack argument.

Implements:

```
TOS <- (forward-line TOS)
```

Generated via:

```
forward-line
```

Instruction size:

```
1 byte
```

Stack effect:

```
-1 + 1.
```

Added in: Emacs 19.34. See Section 4.2 [Emacs 19], page 139.

Example: `(defun forward-line-eg() (forward-line 1))` generates:

PC	Byte	Instruction
0	192	constant[0] 1
1	121	forward-line
2	135	return

Constants Vector: [1]

skip-chars-forward (119)

skip-chars-forward (119)

Call skip-chars-forward with two stack arguments.

Implements:

```
S[1] <- (skip-chars-forward S[1] TOS); top--.
```

Generated via:

```
skip-chars-forward.
```

Instruction size:

1 byte

Stack effect:

-2 + 1.

Added in: Emacs 19.34. See Section 4.2 [Emacs 19], page 139.

Example: (defun skip-chars-forward-eg() (skip-chars-forward "aeiou" 3))
generates:

PC	Byte	Instruction
0	192	constant[0] "aeiou"
1	193	constant[1] 3
2	119	skip-chars-forward
3	135	return

Constants Vector: ["aeiou" 3]

skip-chars-backward (120)

skip-chars-backward (120)

Call skip-chars-backward with two stack arguments.

Implements:

```
S[1] <- (skip-chars-backward S[1] TOS); top--.
```

Generated via:

```
skip-chars-backward.
```

Instruction size:

```
1 byte
```

Stack effect:

```
-2 + 1.
```

Added in: Emacs 19.34. See Section 4.2 [Emacs 19], page 139.

Example: (defun skip-chars-backward-eg() (skip-chars-backward "aeiou" 3))
generates:

PC	Byte	Instruction
0	192	constant[0] "aeiou"
1	193	constant[1] 3
2	120	skip-chars-backward
3	135	return

Constants Vector: ["aeiou" 3]

narrow-to-region (125)

narrow-to-region (125)

Call narrow-to-region with two stack arguments.

Implements:

```
S[1] <- (narrow-to-region S[1] TOS); top--.
```

Generated via:

```
narrow-to-region.
```

Instruction size:

```
1 byte
```

Stack effect:

```
-2 + 1.
```

Added in: Emacs 19.34. See Section 4.2 [Emacs 19], page 139.

Example: (defun narrow-to-region-eg() (narrow-to-region 1250 1251)) generates:

PC	Byte	Instruction
0	192	constant[0] 1250
1	193	constant[1] 1251
2	125	narrow-to-region
3	135	return

Constants Vector: [1250 1251]

widen (126)

widen (126)

Call widen.

Implements:

TOS <- (widen)

Generated via:

widen

Instruction size:

1 byte

Stack effect:

-0 + 1.

Added in: Emacs 19.34. See Section 4.2 [Emacs 19], page 139.

Example: (defun widen-eg() (widen)) generates:

PC	Byte	Instruction
0	126	widen
1	135	return

3.6.7 Emacs Text Instructions

These instructions correspond to Emacs-specific text manipulation functions found in the "Text" chapter of the Emacs Lisp Reference Manual. They are not inlined by the bytecode interpreter, but simply call the corresponding C function.

insert (99)

Call `insert` with one stack argument.

Implements:

```
TOS <- (insert TOS)
```

Generated via:

```
insert
```

Instruction size:

```
1 byte
```

Stack effect:

```
-1 + 1.
```

Example: With lexical binding in effect, `(defun insert-eg(n) (insert n))` generates:

PC	Byte	Instruction
0	137	dup
1	99	insert
2	135	return

insertN (99)

insertN (99)

Call `insert` on up to 255 stack arguments. Note there is a special instruction when there is only one stack argument.

Implements:

```
S[n-1] <- (insert S[n-1] S[n-2] ... TOS); top -= (n-1).
```

Generated via:

```
insert
```

Operand: 8-bit number of items in concat

Instruction size:

```
2 bytes
```

Stack effect:

$-n + 1$ where n is the value of the instruction operand.

Added in: Emacs 19.34. See Section 4.2 [Emacs 19], page 139.

Example: With lexical binding in effect, `(defun insertN-eg(a b c) (insert a b c))` generates:

PC	Byte	Instruction
0	2	stack-ref[2]
1	2	stack-ref[2]
2	2	stack-ref[2]
3	177	insertN [3]
		3
5	135	return

char-after (102)

char-after (102)

Call char-after with one stack argument.

Implements:

```
TOS <- (char-after TOS)
```

Generated via:

```
char-after
```

Instruction size:

```
1 byte
```

Stack effect:

```
-1 + 1.
```

Example: (defun char-after-eg() (char-after)) generates:

PC	Byte	Instruction
0	192	constant[0] nil
1	102	char-after
2	135	return

```
Constants Vector: [nil]
```

following-char (103)

following-char (103)

Call following-char.

Implements:

```
TOS <- (following-char TOS)
```

Generated via:

```
following-char
```

Instruction size:

1 byte

Stack effect:

-1 + 1.

Example: (defun following-char-eg() (following-char)) generates:

PC	Byte	Instruction
0	103	following-char
1	135	return

preceding-char (104)

preceding-char (104)

Call preceding-char.

Implements:

```
TOS <- (preceding-char TOS)
```

Generated via:

```
preceding-char
```

Instruction size:

1 byte

Stack effect:

-1 + 1.

Example: (defun preceding-char-eg() (preceding-char)) generates:

PC	Byte	Instruction
0	104	preceding-char
1	135	return

current-column (105)

current-column (105)

Call current-column.

Implements:

TOS <- (current-column)

Generated via:

current-column

Instruction size:

1 byte

Stack effect:

-0 + 1.

Example: (defun current-column-eg() (current-column)) generates:

PC	Byte	Instruction
0	105	current-column
1	135	return

eolp (108)

eolp (108)

Call eolp.

Implements:

```
TOS <- (eolp)
```

Generated via:

```
eolp
```

Instruction size:

1 byte

Stack effect:

$-0 + 1$.

Example: (defun eolp-eg() (eolp)) generates:

PC	Byte	Instruction
0	108	eolp
1	135	return

eobp (109)

eobp (109)

Call eobp.

Implements:

TOS <- (eobp)

Generated via:

eobp

Instruction size:

1 byte

Stack effect:

-0 + 1.

Example: (defun eobp-eg() (eobp)) generates:

PC	Byte	Instruction
0	109	eobp
1	135	return

bolp (110)

bolp (110)

Call bolp.

Implements:

TOS <- (bolp)

Generated via:

bolp

Instruction size:

1 byte

Stack effect:

-0 + 1.

Example: (defun bolp-eg() (bolp)) generates:

PC	Byte	Instruction
0	110	bolp
1	135	return

bobp (111)

bobp (111)

Call bobp.

Implements:

TOS <- (bobp)

Generated via:

bobp

Instruction size:

1 byte

Stack effect:

-0 + 1.

Example: (defun bobp-eg() (bobp)) generates:

PC	Byte	Instruction
0	111	bobp
1	135	return

delete-region (124)

delete-region (124)

Call delete-region with two stack arguments.

Call delete-region with two stack arguments.

Implements:

```
S[1] <- (delete-region S[1] TOS); top--.
```

Generated via:

```
delete-region.
```

Instruction size:

1 byte

Stack effect:

$-2 + 1$.

Added in: Emacs 19.34. See Section 4.2 [Emacs 19], page 139.

Example: (defun delete-region-eg() (delete-region 1240 1241)) generates:

PC	Byte	Instruction
0	192	constant[0] 1240
1	193	constant[1] 1241
2	124	delete-region
3	135	return

Constants Vector: [1240 1241]

end-of-line (127)

end-of-line (127)

Call end-of-line with one stack argument.

Implements:

(end-of-line TOS; top--

Generated via:

delete-region.

Instruction size:

1 byte

Stack effect:

-1 + 0-.

Added in: Emacs 19.34. See Section 4.2 [Emacs 19], page 139.

Example: (defun end-of-line-eg() (end-of-line)) generates:

PC	Byte	Instruction
0	192	constant[0] nil
1	127	end-of-line
2	135	return

Constants Vector: [nil]

3.6.8 Emacs Misc Function Instructions

These instructions correspond to miscellaneous Emacs-specific functions. They are not inlined by the bytecode interpreter, but simply call the corresponding C function.

char-syntax (122)

Call `char-syntax` with one stack argument.

Implements:

```
TOS <- (char-syntax TOS)
```

Generated via:

```
char-syntax
```

Instruction size:

1 byte

Stack effect:

$-1 + 1$.

Added in: Emacs 19.34. See Section 4.2 [Emacs 19], page 139.

Example: `(defun char-syntax-eg() (char-syntax ?a))` generates:

PC	Byte	Instruction
0	192	constant[0] 97
1	122	char-syntax
2	135	return

Constants Vector: [97]

save-excursion (138)

save-excursion (138)

Make a binding recording buffer, point, and mark.

This instruction manipulates the special-bindings stack by creating a new binding when executed. It needs to be balanced with `unbind` instructions.

Implements:

`(save-excursion).`

Generated via:

`save-excursion`

Instruction size:

1 byte

Stack effect:

$-0 + 0$.

Example: When lexical binding is in effect, `(defun save-excursion-eg() (save-excursion 1380))` generates:

PC	Byte	Instruction
0	138	<code>save-excursion</code>
1	192	<code>constant[0] 1380</code>
2	41	<code>unbind[1]</code>
3	135	<code>return</code>

Constants Vector: [1380]

set-marker (147)

set-marker (147)

Call `set-marker` with three stack arguments.

Implements:

```
S[2] <- (set-marker S[2] S[1] TOS); top -= 2.
```

Generated via:

```
set-marker
```

Instruction size:

```
1 byte
```

Stack effect:

```
-3 + 1.
```

Added in: Emacs 19.34. See Section 4.2 [Emacs 19], page 139.

Example: When lexical binding is in effect, `(defun set-marker-eg(marker position)
(set-marker marker position))` generates:

PC	Byte	Instruction
0	1	stack-ref[1]
1	1	stack-ref[1]
2	192	constant[0] nil
3	147	set-marker
4	135	return

Constants Vector: [nil]

match-beginning (148)

match-beginning (148)

Call match-beginning with one stack argument.

Implements:

```
TOS <- (match-beginning TOS)
```

Generated via:

```
match-beginning
```

Instruction size:

```
1 byte
```

Stack effect:

```
-1 + 1.
```

Added in: Emacs 19.34. See Section 4.2 [Emacs 19], page 139.

Example: (defun match-beginning-eg() (match-beginning 1)) generates:

PC	Byte	Instruction
0	192	constant[0] 1
1	148	match-beginning
2	135	return

Constants Vector: [1]

match-end (149)

match-end (149)

Call `match-end` with one stack argument.

Implements:

```
TOS <- (match-end TOS)
```

Generated via:

```
match-end
```

Instruction size:

```
1 byte
```

Stack effect:

```
-1 + 1.
```

Added in: Emacs 19.34. See Section 4.2 [Emacs 19], page 139.

Example: `(defun match-end-eg() (match-end 1))` generates:

PC	Byte	Instruction
0	192	constant[0] 1
1	148	match-end
2	135	return

Constants Vector: [1]

3.7 Stack-Manipulation Instructions

discard (136)

Discard one value from the stack.

Implements:

top--

Instruction size:

1 byte

Generated via:

Function calls that do not use the returned value; the end of **let** forms in lexical binding to remove locally-bound variables.

Stack effect:

-1 + 0.

Example: (defun discard-eg() (exchange-point-and-mark) (point)) generates:

PC	Byte	Instruction
0	192	constant[0] exchange-point-and-mark
1	32	call[0]
2	136	discard
3	96	point
4	135	return

Constants Vector: [exchange-point-and-mark]

discardN (180)

discardN (180)

Discards up to 127 arguments from the stack. Note there is a special instruction when there is only one argument.

Implements:

```
if (n & 8) S[n] <- TOS; top -= n & 7;  where n where n is the value of the
operand.
```

operand: 7-bit number of items to discard. The top 8th bit when set indicates to keep the old TOS value after discarding.

Instruction size:

2 bytes

Generated via:

Function calls that do not use the returned value; the end of `let` forms in lexical binding with optimization to remove locally-bound variables.

Stack effect:

$-n + 0$

Added in: Emacs 24.1. See Section 4.7 [Emacs 24], page 143.

Example: When lexical binding is in effect and optimization are in effect,

```
(1+ (let ((a 1) (_b) (_c)) a)))
```

generates:

PC	Byte	Instruction
0	192	constant[0] 1
1	193	constant[1] nil
2	137	dup
3	2	stack-ref[2]
4	182	discardN [131]
		131
6	84	add1
7	135	return

Constants Vector: [1 nil]

dup (137)

dup (137)

Make a copy of the top-of-stack value and push that onto the top of the evaluation stack.

Implements:

```
top++; TOS <- S[1]
```

Generated via:

`setq` in dynamic bindings to set a value and then use it. In lexical binding, to use the first argument parameter.

Instruction size:

1 byte

Stack effect:

$-0 + 1$.

Example: When lexical binding is in effect,

generates:

PC	Byte	Instruction
0	137	dup ;; duplicates top of stack, argument n
1	135	return

stack-set (178)

stack-set (178)

Sets a value on the evaluation stack to TOS.

Implements:

`S[i] <- TOS; top--` where `i` is the value of the instruction operand.

Note that `stack-set[0]` has the same effect as `discard`, but does a little more work to do this. `stack-set[1]` has the same effect as `discardN 1` with the top bit of `discardN` set to preserve TOS.

Generated via:

`let`, `let*` and `lambda` arguments.

Operand: A 8-bit integer stack index

Instruction size:

2 bytes

Stack effect:

$-1 + 0$.

Added in: Emacs 24.1. See Section 4.7 [Emacs 24], page 143.

Example: When lexical binding is in effect and optimization

```
defun stack-set-eg()
  (let ((a 5) a)))
```

generates:

PC	Byte	Instruction
0	192	constant[0] 5
1	193	constant[1] nil
2	193	constant[1] nil
3	178	stack-set [2]
		2
5	136	discard
6	135	return

Constants Vector: [5 nil]

stack-set2 (179)

stack-set2 (179)

Implements:

`S[i] <- TOS; top--` where `i` is the value of the instruction operand.

Note that `stack-set2[0]` has the same effect as `discard`, but does a little more work to do this. `stack-set2[1]` has the same effect as `discardN 1` with the top bit of `discardN` set to preserve `TOS`.

Generated via:

`let`, `let*` and `lambda` arguments.

Operand: A 16-bit integer stack index

Instruction size:

3 bytes

Stack effect:

$-1 + 0$.

Added in: Emacs 24.1. See Section 4.7 [Emacs 24], page 143.

Example: ??

3.8 Obsolete or Unused Instructions

These instructions are not generated. In some cases, they were generated in a older version of Emacs. In some cases the instructions were planned on being used but never were. In some cases, the instructions are still handled if they appear (such as from older bytecode), but in other cases they are no longer accepted by the interpreter

save-current-buffer (97)

Replaced by `save-current-buffer-1`. See [save-current-buffer-1], page 99.

mark (97)

Used in V 17; obsolete in Emacs 18.31. See Section 4.1 [Emacs 18], page 138.

scan-buffer (107)

Obsolete in Emacs 18.31. See Section 4.1 [Emacs 18], page 138.

read-char (114)

set-mark (115)

Obsolete in Emacs 18.31. See Section 4.1 [Emacs 18], page 138.

interactive-p (116)

save-window-excursion (139)

Call `save-window-excursion`.

Implements:

`(save-window-excursion BLOCK)`

Generated via:

`save-window-excursion`

Instruction size:

1 byte

Stack effect:

$-1 + 0$.

Obsolete since:

Emacs 24.1. See Section 4.7 [Emacs 24], page 143. Now generates a sequence of bytecode that includes calls to `current-window-configuration` and `set-window-configuration`

Example:

```
(defun save-window-excursion()
  (save-window-excursion 1390))
```

generates:

PC	Byte	Instruction
0	192	constant[0] (1390)

```
1 139 save-window-excursion
2 135 return
```

Constants Vector: [(1390)]

condition-case (143)

Replaced by `pushconditioncase`. See [pushconditioncase], page 27,

Implements:

?

Generated via:

?

Instruction size:

1 byte

Stack effect:

$-2 + 1$.

Obsolete since:

Emacs 24.4. See Section 4.7 [Emacs 24], page 143.

Example: (defun condition-case-eg() (??)) generates:

temp-output-buffer-setup (144)

Implements:

Setup for `with-output-to-temp-buffer`.

Generated via:

`with-output-to-temp-buffer`

Instruction size:

1 byte

Stack effect:

$-1 + 0$.

Obsolete since:

Emacs 24.1. See Section 4.7 [Emacs 24], page 143.

Example: (defun wottb-eg () (with-output-to-temp-buffer "wottb" 5)) generates:

PC	Byte	Instruction
0	192	constant[0] "wottb"
1	144	temp-output-buffer-setup
2	193	constant[1] 5
3	145	temp-output-buffer-show
4	135	return

Constants Vector: ["wottb" 5]

temp-output-buffer-show (145)

Implements:

Finishing code of with-output-to-temp-buffer.

Generated via:

with-output-to-temp-buffer

Instruction size:

1 byte

Stack effect:

$-0 + 0$.

Obsolete in:

Emacs 24.1. See Section 4.7 [Emacs 24], page 143.

Example: (defun wottb-eg () (with-output-to-temp-buffer "wottb" 5)) generates:

PC	Byte	Instruction
0	192	constant[0] "wottb"
1	144	temp-output-buffer-setup
2	193	constant[1] 5
3	145	temp-output-buffer-show
4	135	return

Constants Vector: ["wottb" 5]

unbind-all (146)

Introduced in Emacs 19.34 for tail-recursion elimination by jwz, but never used. See Section 4.2 [Emacs 19], page 139.

3.8.12 Relative Goto Instructions

In Emacs 19.34, Hallvard Furuseth introduced relative goto instructions. However, have never been generated in bytecode.

Rgoto (170)

Relative jump version of see [goto], page 29.

Introduced but unused in Emacs 19.34. See Section 4.2 [Emacs 19], page 139.

Rgotoifnil (171)

Relative jump version of see [goto-if-nil], page 30.

Introduced but unused in Emacs 19.34. See Section 4.2 [Emacs 19], page 139.

Rgotoifnonnil (172)

Relative-jump version of see [goto-if-not-nil], page 31.

Introduced but unused in Emacs 19.34. See Section 4.2 [Emacs 19], page 139.

Rgotoifnilelsep (173)

Relative-jump version of see [goto-if-nil-else-pop], page 32.

Introduced but unused in Emacs 19.34. See Section 4.2 [Emacs 19], page 139.

Rgotoifnonnilelsep (174)

Relative-jump version of see [goto-if-not-nil-else-pop], page 33.

Introduced but unused in Emacs 19.34. See Section 4.2 [Emacs 19], page 139.

4 Instruction Changes Between Emacs Releases

4.1 After 16 and Starting in 18.31

The following instructions were renamed:

- `dot` becomes `mark` (97). See [mark], page 134.
- `dot-min` becomes `point-min` (100). See [point-min], page 104.
- `dot-max` becomes `point-max` (101). See [point-max], page 103.

The following instructions became obsolete:

- `mark` (97). See [mark], page 134.
- `scan-buffer` (107). See [scan-buffer], page 134.
- `set-mark` (115). See [set-mark], page 134.

Version 18 Release History

- Emacs 18.31 was released Nov 23, 1986
- Emacs 18.32 was released Dec 6, 1986
- Emacs 18.33 was released Dec 12, 1986
- Emacs 18.35 was released Jan 5, 1987
- Emacs 18.36 was released Jan 21, 1987
- Emacs 18.37 was released Feb 11, 1987
- Emacs 18.38 was released Mar 3, 1987
- Emacs 18.39 was released May 14, 1987
- Emacs 18.40 was released Mar 18, 1987
- Emacs 18.41 was released Mar 22, 1987
- Emacs 18.44 was released Apr 15, 1987
- Emacs 18.46 was released Jun 8, 1987
- Emacs 18.47 was released Jun 15, 1987
- Emacs 18.48 was released Aug 30, 1987
- Emacs 18.49 was released Sep 17, 1987
- Emacs 18.50 was released Feb 13, 1988
- Emacs 18.51 was released May 6, 1988
- Emacs 18.52 was released Aug 31, 1988
- Emacs 18.59 was released Oct 30, 1988

4.2 After 18.59 and Starting 19.34

jwz and Hallvard made major changes and additions to the bytecode interpreter.

The following instructions were added:

- `mult` (97). See [mult], page 83.
- `forward-char` (117). See [forward-char], page 105.
- `forward-word` (118). See [forward-word], page 106.
- `skip-chars-forward` (119). See [skip-chars-forward], page 108.
- `skip-chars-backward` (120). See [skip-chars-backward], page 109.
- `forward-line` (121). See [forward-line], page 107.
- `char-syntax` (122). See [char-syntax], page 124.
- `buffer-substring` (123). See [buffer-substring], page 100.
- `delete-region` (124). See [delete-region], page 122.
- `narrow-to-region` (125). See [narrow-to-region], page 110.
- `widen` (126). See [widen], page 111.
- `end-of-line` (127). See [end-of-line], page 123.
- `unbind-all` (146). See [unbind-all], page 136.
- `set-marker` (147). See [set-marker], page 126.
- `match-beginning` (148). See [match-beginning], page 127.
- `match-end` (149). See [match-end], page 128.
- `upcase` (150). See [upcase], page 93.
- `downcase` (151). See [downcase], page 94.
- `stringeqqlsign` (152). See [stringeqqlsign], page 95.
- `stringlss` (153). See [stringlss], page 96.
- `equal` (154). See [equal], page 48.
- `nthcdr` (155). See [nthcdr], page 65.
- `elt` (156). See [elt], page 66.
- `member` (157). See [member], page 49.
- `assq` (158). See [assq], page 50.
- `nreverse` (159). See [nreverse], page 67.
- `setcar` (160). See [setcar], page 68.
- `setcdr` (161). See [setcdr], page 69.
- `car-safe` (162). See [car-safe], page 70.
- `cdr-safe` (163). See [cdr-safe], page 71.
- `nconc` (164). See [nconc], page 72.
- `quo` (165). See [quo], page 86.
- `rem` (166). See [rem], page 87.
- `numberp` (167). See [numberp], page 51.
- `integerp` (162). See [integerp], page 52.

- `Rgoto` (170). See [Rgoto], page 137.
- `Rgotoifnil` (171). See [Rgotoifnil], page 137.
- `Rgotoifnonnil` (172). See [Rgotoifnonnil], page 137.
- `Rgotoifnilesepop` (173). See [Rgotoifnilesepop], page 137.
- `Rgotoifnonnilesepop` (174). See [Rgotoifnonnilesepop], page 137.
- `listN` (175). See [listN], page 61.
- `concatN` (176). See [concatN], page 92.
- `insertN` (177). See [insertN], page 113.

Instruction `unbind-all` was added to support tail-recursion removal. However this was never subsequently implemented; so this instruction was never generated.

Starting in this version, unless C preprocessor variable `BYTE_CODE_SAFE` (off by default) is defined, the obsolete instructions listed in 18.59 are not implemented.

The following obsolete instructions throw an error when `BYTE_CODE_SAFE` is defined:

- `mark` (97)
- `scan-buffer` (107)
- `set-mark` (115)

Bytecode meta-comments look like this:

```
;;; compiled by rms@psilocin.gnu.ai.mit.edu on Mon Jun 10 17:37:37 1996
;;; from file /home/fsf/rms/e19/lisp/bytecomp.el
;;; emacs version 19.31.2.
;;; bytecomp version FSF 2.10
;;; optimization is on.
;;; this file uses opcodes which do not exist in Emacs 18.
```

Version 19 Release History

- Emacs 19.7 was released May 22 1993
- Emacs 19.8 was released May 25 1993
- Emacs 19.9 was released May 27 1993
- Emacs 19.10 was released May 30 1993
- Emacs 19.11 was released Jun 1, 1993
- Emacs 19.12 was released Jun 1, 1993
- Emacs 19.13 was released Jun 8, 1993
- Emacs 19.14 was released Jun 17, 1993
- Emacs 19.15 was released Jun 19, 1993
- Emacs 19.16 was released Jul 6, 1993
- Emacs 19.17 was released Jul 7, 1993
- Emacs 19.18 was released Aug 8, 1993
- Emacs 19.19 was released Aug 14, 1993
- Emacs 19.20 was released Nov 11, 1993
- Emacs 19.21 was released Nov 16, 1993

- Emacs 19.22 was released Nov 27, 1993
- Emacs 19.23 was released May 17, 1994
- Emacs 19.24 was released May 23, 1994
- Emacs 19.25 was released May 30, 1994
- Emacs 19.26 was released Sep 7, 1994
- Emacs 19.27 was released Sep 11, 1994
- Emacs 19.29 was released Jun 19, 1995
- Emacs 19.30 was released Nov 24, 1995
- Emacs 19.31 was released May 25, 1996
- Emacs 19.31 was released May 25, 1996
- Emacs 19.32 was released Aug 7, 1996
- Emacs 19.33 was released Sept 11, 1996

The Emacs Lisp tarball for 19.2 is Aug, 1992. (The tarball date for 19.2 is much later; and even after the date on the 20.1 tarball.)

4.3 After 19.34 and Starting in 20.1

`save-current-buffer` (97). See `[save-current-buffer]`, page 134, and `save-current-buffer-1` (114) do the same thing, but the former is deprecated. The latter opcode replaces `read-char` which was not generated since v19.

I am not sure why the change; changing this opcode number however put it next to other buffer-related opcodes.

Bytecode meta-comments look like this:

```
;;; Compiled by rms@psilocin.gnu.ai.mit.edu on Sun Aug 31 13:07:37 1997
;;; from file /home/fsf/rms/e19/lisp/emacs-lisp/bytecomp.el
;;; in Emacs version 20.0.97.1
;;; with bytecomp version 2.33
;;; with all optimizations.
;;; This file uses opcodes which do not exist in Emacs 18.
```

Version 20 Release History

- Emacs 20.1 was released Sep 15, 1997
- Emacs 20.2 was released Sep 19, 1997
- Emacs 20.3 was released Aug 19, 1998
- Emacs 20.4 was released Jul 14, 1999

4.4 After 20.1 and Starting in 21.1

There were no instruction changes. However there were major changes in the bytecode interpreter.

An instruction with opcode 0 causes an abort.

Bytecode meta-comments look like this:

```
;;; Compiled by pot@pot.cnuce.cnr.it on Tue Mar 18 15:36:26 2003
;;; from file /home/pot/gnu/emacs-pretest.new/lisp/emacs-lisp/bytecomp.el
;;; in Emacs version 21.3
;;; with bytecomp version 2.85.4.1
;;; with all optimizations.
```

Version 21 Release History

- Emacs 21.1 was released Oct 20, 2001
- Emacs 21.2 was released Mar 16, 2002
- Emacs 21.3 was released Mar 18, 2003
- Emacs 21.4 was released Feb 6, 2005

4.5 After 21.4 and Starting in 22.1

There were no instruction changes.

The bytecode meta-comment no longer includes the bytecomp version used.

Bytecode meta-comments look like this:

```
;;; Compiled by cyd@localhost on Sat Jun 2 00:54:30 2007
;;; from file /home/cyd/emacs/lisp/emacs-lisp/bytecomp.el
;;; in Emacs version 22.1
;;; with all optimizations.
```

```
;;; This file uses dynamic docstrings, first added in Emacs 19.29.
```

Version 22 Release History

- Emacs 22.1 was released Jun 02, 2007
- The Emacs 22.2 tarball is dated Mar 26 2008
- The Emacs 22.3 tarball is dated Sep 05 2008

4.6 After 22.3 and Starting in 23.1

There were no instruction changes.

Bytecode meta-comments look like this:

```
;;; Compiled by cyd@furry on Wed Jul 29 11:15:02 2009
;;; from file /home/cyd/emacs/lisp/emacs-lisp/bytecomp.el
;;; in Emacs version 23.1
;;; with all optimizations.
```

```
;;; This file uses dynamic docstrings, first added in Emacs 19.29.
```

Version 23 Release History

- Emacs 23.1 was released Jul 29, 2009
- Emacs 23.2 was released May 7, 2010
- Emacs 23.3 was released Mar 7, 2011
- The Emacs 23.4 tarball is dated Jan 28, 2012

4.7 After 23.4 and Starting in 24.1

An error is thrown for unknown bytecodes rather than aborting.

The following instructions were added:

- `stack-set` (178). See [stack-set], page 132.
- `stack-set2`, (179). See [stack-set2], page 133.
- `discardN`, (180). See [discardN], page 130.

Unless C preprocessor variable `BYTE_CODE_SAFE` (off by default) is defined, obsolete instructions below and from earlier versions are not implemented.

- `temp-output-buffer-setup` (144). See [temp-output-buffer-setup], page 135.
- `temp-output-buffer-show` (145). See [temp-output-buffer-show], page 136.
- `save-window-excursion` (139). See [save-window-excursion], page 134.

Instruction `unbind-all`, which never was generated, was marked obsolete in this version.

The bytecode meta-comment no longer who user/hostname compiled and at what time. A message indicating whether utf-8 non-ASCII characters is used is included.

The following instructions were added in 24.4:

- `pophandler` (48). See [pophandler], page 26.
- `pushconditioncase` (49). See [pushconditioncase], page 27.
- `pushcatch` (50). See [pushcatch], page 28.

Bytecode meta-comments look like this:

```
;;; from file /misc/emacs/bzr/emacs24-merge/lisp/emacs-lisp/bytecomp.el
;;; in Emacs version 24.3
;;; with all optimizations.
```

```
;;; This file uses dynamic docstrings, first added in Emacs 19.29.
```

```
;;; This file does not contain utf-8 non-ASCII characters,
;;; and so can be loaded in Emacs versions earlier than 23.
```

Version 24 Release History

- The Emacs 24.1 tarball is dated Jun 10, 2012
- The Emacs 24.2 tarball is dated Aug 27, 2012
- Emacs 24.3 was released Mar 11, 2013
- Emacs 24.4 was released Oct 20, 2014
- Emacs 24.5 was released Apr 10, 2015

4.8 After 24.5 and Starting in 25.1

Instruction 0 becomes an error rather than aborting emacs.

A number of changes were made to `bytecode.c`.

The bytecode meta-comment no longer includes the source-code path.

Bytecode meta-comments look like this:

```
;;; Compiled
;;; in Emacs version 25.2
;;; with all optimizations.

;;; This file uses dynamic docstrings, first added in Emacs 19.29.

;;; This file does not contain utf-8 non-ASCII characters,
;;; and so can be loaded in Emacs versions earlier than 23.
```

Version 25 Release History

- Emacs 25.1 was released Sep 16, 2016
- The Emacs 25.2 tarball is dated Apr 21, 2017
- Emacs 25.3 was released Sep 11, 2017

4.9 After 25.3 and Starting in 26.1

The following instruction was added:

- `switch` (267)

4.10 After 26.1 and Starting in 27.1

No changes yet.

5 Opcode Table

In the table below, a * before the instruction name indicates an obsolete instruction, or instruction that is no longer generated by the bytecode compiler. On the other hand, ! indicates not just an obsolete instruction, but one that no longer is interpreted. See Section 3.1 [Instruction-Description Format], page 15, for abbreviations used here, a description of how to interpret an opcode when it contains an index, and for a description of how to interpret the stack-effect field.

5.1 Opcodes (0000-0077)

Oct	Dec	Instruction	Size	Description	Stack
00	0			An error. Before 25.1 it is an immediate program abort! Logically <code>stack-ref[0]</code> but <code>dup</code> should be used instead.	
01	1	<code>stack-ref[1]</code>	1	See [stack-ref], page 18.	+1
02	2	<code>stack-ref[2]</code>	1	See [stack-ref], page 18.	+1
03	3	<code>stack-ref[3]</code>	1	See [stack-ref], page 18.	+1
04	4	<code>stack-ref[4]</code>	1	See [stack-ref], page 18.	+1
05	5	<code>stack-ref[5]</code>	1	See [stack-ref], page 18.	+1
06	6	<code>stack-ref[6]</code>	2	See [stack-ref], page 18.	+1
07	7	<code>stack-ref[7]</code>	3	See [stack-ref], page 18.	+1
010	8	<code>varref[0]</code>	1	See [varref], page 19.	+1
011	9	<code>varref[1]</code>	1	See [varref], page 19.	+1
012	10	<code>varref[2]</code>	1	See [varref], page 19.	+1
013	11	<code>varref[3]</code>	1	See [varref], page 19.	+1
014	12	<code>varref[4]</code>	1	See [varref], page 19.	+1
015	13	<code>varref[5]</code>	1	See [varref], page 19.	+1
016	14	<code>varref[6]</code>	2	See [varref], page 19.	+1
017	15	<code>varref[7]</code>	3	See [varref], page 19.	+1
020	16	<code>varset[0]</code>	1	See [varset], page 20.	-1
021	17	<code>varset[1]</code>	1	See [varset], page 20.	-1
022	18	<code>varset[2]</code>	1	See [varset], page 20.	-1
023	19	<code>varset[3]</code>	1	See [varset], page 20.	-1
024	20	<code>varset[4]</code>	1	See [varset], page 20.	-1
025	21	<code>varset[5]</code>	1	See [varset], page 20.	-1
026	22	<code>varset[6]</code>	2	See [varset], page 20.	-1
027	23	<code>varset[7]</code>	3	See [varset], page 20.	-1
030	24	<code>varbind[0]</code>	1	See [varbind], page 21.	-1
031	25	<code>varbind[1]</code>	1	See [varbind], page 21.	-1

032	26	varbind[2]	1	See [varbind], page 21.	-1
033	27	varbind[3]	1	See [varbind], page 21.	-1
034	28	varbind[4]	1	See [varbind], page 21.	-1
035	29	varbind[5]	1	See [varbind], page 21.	-1
036	30	varbind[6]	2	See [varbind], page 21.	-1
037	31	varbind[7]	3	See [varbind], page 21.	-1
040	32	call0	1	See [call], page 22.	-1 + 1
041	33	call1	1	See [call], page 22.	-2 + 1
042	34	call2	1	See [call], page 22.	-3 + 1
043	35	call3	1	See [call], page 22.	-4 + 1
044	36	call4	1	See [call], page 22.	-5 + 1
045	37	call5	1	See [call], page 22.	-6 + 1
046	38	call6	2	See [call], page 22.	-n - 1 + 1
047	39	call7	3	See [call], page 22.	-n - 1 + 1
050	40	unbind0	1	See [unbind], page 23.	-0
051	41	unbind1	1	See [unbind], page 23.	-0
052	42	unbind2	1	See [unbind], page 23.	-0
053	43	unbind3	1	See [unbind], page 23.	-0
054	44	unbind4	1	See [unbind], page 23.	-0
055	45	unbind5	1	See [unbind], page 23.	-0
056	46	unbind6	2	See [unbind], page 23.	-0
057	47	unbind7	3	See [unbind], page 23.	-0
060	48	pophandler	1		-0
061	49	conditioncase	3		-1 + $\phi(0, +1)$
062	50	pushconditioncase	1		-0
063	51			Unused	
064	52			Unused	
065	53			Unused	
066	54			Unused	
067	55			Unused	
070	56	nth	1	See [nth], page 53.	-2 + 1
071	57	symbolp	1	See [symbolp], page 36.	-1 + 1
072	58	consp	1	See [consp], page 37.	-1 + 1
073	59	stringp	1	See [stringp], page 38.	-1 + 1
074	60	listp	1	See [listp], page 39.	-1 + 1
075	61	eq	1	See [eq], page 40.	-2 + 1
076	62	memq	1	See [memq], page 41.	-2 + 1
077	63	not	1	See [not], page 42.	-1 + 1

5.2 Opcodes (0100-0177)

Oct	Dec	Instruction	Size	Description	Stack
0100	64	car	1	See [car], page 54.	-1 + 1
0101	65	cdr	1	See [cdr], page 55.	-1 + 1
0102	66	cons	1	See [cons], page 56.	-2 + 1
0103	67	list1	1	See [list1], page 57.	-1 + 1
0104	68	list2	1	See [list2], page 58.	-2 + 1
0105	69	list3	1	See [list3], page 59.	-3 + 1
0106	70	list4	1	See [list4], page 60.	-4 + 1
0107	71	length	1	See [length], page 62.	-1 + 1
0110	72	aref	1	See [aref], page 63.	-2 + 1
0111	73	aset	1	See [aset], page 64.	-3 + 1
0112	74	symbol-value	1	See [symbol-value], page 43.	-1 + 1
0113	75	symbol-function	1	See [symbol-function], page 44.	-1 + 1
0114	76	set	1	See [set], page 45.	-2 + 1
0115	77	fset	1	See [fset], page 46.	-2 + 1
0116	78	get	1	See [get], page 47.	-2 + 1
0117	79	substring	1	See [substring], page 88.	-3 + 1
0120	80	concat2	1	See [concat2], page 89.	-2 + 1
0121	81	concat3	1	See [concat3], page 90.	-3 + 1
0122	82	concat4	1	See [concat4], page 91.	-4 + 1
0123	83	sub1	1	See [sub1], page 73.	-1 + 1
0124	84	add1	1	See [add1], page 74.	-1 + 1
0125	85	eqlsign	1	See [eqlsign], page 75.	-2 + 1
0126	86	gtr	1	See [gtr], page 76.	-2 + 1
0127	87	lss	1	See [lss], page 77.	-2 + 1
0130	88	leq	1	See [leq], page 78.	-2 + 1
0131	89	geq	1	See [geq], page 79.	-2 + 1
0132	90	diff	1	See [diff], page 80.	-2 + 1
0133	91	negate	1	See [negate], page 81.	-1 + 1
0134	92	plus	1	See [plus], page 82.	-2 + 1
0135	93	max	1	See [max], page 84.	-2 + 1
0136	94	min	1	See [min], page 85.	-2 + 1
0135	95	mult	1	See [mult], page 83.	-2 + 1
0140	96	point	1	See [point], page 101.	
0141	*97	*mark	1	See [mark], page 134,	-0 + 1
0142	98	goto-char	1	See [goto-char], page 102.	-1 + 1
0143	99	insert	1	See [insert], page 112.	-1 + 1
0145	100	point-max	1	See [point-max], page 103.	-0 + 1
0146	101	point-min	1	See [point-min], page 104.	-0 + 1
0144	102	char-after	1	See [char-after], page 114.	-1 + 1
0147	103	following-char	1	See [following-char], page 115.	-0 + 1

0150	104	preceding-char	1	See [preceding-char], page 116.	-0 + 1
0151	105	current-column	1	See [current-column], page 117.	-0 + 1
0153	*107	*scan-buffer		See [scan-buffer], page 134.	
0154	108	eolp	1	See [eolp], page 118.	-0 + 1
0155	109	eobp	1	See [eobp], page 119.	-0 + 1
0156	110	bolp	1	See [bolp], page 120.	-0 + 1
0157	111	bobp	1	See [bobp], page 121.	-0 + 1
0160	112	current-buffer	1	See [current-buffer], page 97.	-0 + 1
0161	113	set-buffer	1	See [set-buffer], page 98.	-1 + 1
0162	114	save-current- buffer-1	1	See [save-current-buffer-1], page 99.	-0
0162	*114	*read-char	1	See [read-char], page 134.	+1
0163	*115	*set-mark	1	See [set-mark], page 134.	-0
0164	*116	*interactive-p	1	See [interactive-p], page 134.	+1
0165	117	forward-char	1	See [forward-char], page 105.	-1 + 1
0166	118	forward-word	1	See [forward-word], page 106.	-1 + 1
0167	119	skip-chars-forward	1	See [skip-chars-forward], page 108.	-2 + 1
0170	120	skip-chars-backward	1	See [skip-chars-backward], page 109.	-2 + 1
0171	121	forward-line	1	See [forward-line], page 107.	-1 + 1
0172	122	char-syntax	1	See [char-syntax], page 124.	-1 + 1
0173	123	buffer-substring	1	See [buffer-substring], page 100.	-2 + 1
0174	124	delete-region	1	See [delete-region], page 122.	-2 + 1
0175	125	narrow-to-region	1	See [narrow-to-region], page 110.	-2 + 1
0176	126	widen	1	See [widen], page 111.	-0 + 1
0177	127	end-of-line	1	See [end-of-line], page 123.	-1 + 1

5.3 Opcodes (0200-0277)

Oct	Dec	Instruction	Size	Description	Stack
0201	129	constant2	1	See [constant2], page 25.	+1
0202	130	goto	1	See [goto], page 29.	-1 + 0
0203	131	goto-if-nil	1	See [goto-if-nil], page 30.	-1 + 0
0204	132	goto-if-not-nil	1	See [goto-if-not-nil], page 31.	-1 + 0
0205	133	goto-if-nil-else-pop	1	See [goto-if-nil-else-pop], page 32.	$\phi(-1, 0) + 0$
0206	134	goto-if-not-nil-else-pop	1	See [goto-if-not-nil-else-pop], page 33.	$\phi(-1, 0) + 0$
0207	135	return	1	See [return], page 34.	-1 + 0
0210	136	discard	1	See [discard], page 129.	-1 + 0
0211	137	dup	1	See [dup], page 131.	-0 + 1
0212	138	save-excursion	1	See [save-excursion], page 125.	-0 + 0
0213	*139	*save-window-excursion	1	See [save-window-excursion], page 134.	-1 + 0
0214	140			Unused	
0215	141			Unused	
0216	142			Unused	
0217	*143	*condition-case	1	See [condition-case], page 135.	-1 + 1
0220	144	temp-output-buffer-setup		See [temp-output-buffer-setup], page 135.	-1 + 0
0221	145	temp-output-buffer-show		See [temp-output-buffer-show], page 136.	-0 + 0
0222	146			Unused	
0223	147			Unused	
0256	174			Unused	
0257	175	listN	2	See [listN], page 61.	-n + 1
0260	176	concatN	2	See [concatN], page 92.	-n + 1
0261	177	insertN	2	See [insertN], page 113.	-n + 1
0262	178	stack-set	1	See [stack-set], page 132.	-1
0263	179	stack-set2	1	See [stack-set2], page 133.	-1
0222	*146	*unbind-all	1	See [unbind-all], page 136.	-0
0223	147	set-marker	1	See [set-marker], page 126.	-3 + 1
0224	148	match-beginning	1	See [match-beginning], page 127.	-1 + 1
0225	149	match-end	1	See [match-end], page 128.	-1 + 1
0226	150	upcase	1	See [upcase], page 93.	-1 + 1
0227	151	downcase	1	See [downcase], page 94.	-1 + 1

0230	152	stringeqsign	1	See [stringeqsign], page 95.	$-2 + 1$
0231	153	stringlss	1	See [stringlss], page 96.	$-2 + 1$
0232	154	equal	1	See [equal], page 48.	$-2 + 1$
0233	155	nthcdr	1	See [nthcdr], page 65.	$-2 + 1$
0234	156	elt	1	See [elt], page 66.	$-2 + 1$
0235	157	member	1	See [member], page 49.	$-2 + 1$
0236	158	assq	1	See [assq], page 50.	$-2 + 1$
0237	159	nreverse	1	See [nreverse], page 67.	$-1 + 1$
0240	160	setcar	1	See [setcar], page 68.	$-2 + 1$
0241	161	setcdr	1	See [setcdr], page 69.	$-2 + 1$
0242	162	car-safe	1	See [car-safe], page 70.	$-1 + 1$
0243	163	cdr-safe	1	See [cdr-safe], page 71.	$-1 + 1$
0244	164	nconc	1	See [nconc], page 72.	$-2 + 1$
0245	165	quo	1	See [quo], page 86.	$-2 + 1$
0246	166	rem	1	See [rem], page 87.	$-2 + 1$
0247	167	numberp	1	See [numberp], page 51.	$-1 + 1$
0250	168	integerp	1	See [integerp], page 52.	$-1 + 1$
0251	169			Unused	
0252	*170	*Rgoto	1	See [Rgoto], page 137.	$-1 + 0$
0253	*171	*Rgotoifnil	1	See [Rgotoifnil], page 137.	
0254	*172	*Rgotoifnonnil	1	See [Rgotoifnonnil], page 137.	$-1 + 0$
0255	*173	*Rgotoifnilesepop	1	See [Rgotoifnilesepop], page 137.	$\phi(-1, 0) + 0$
0256	*174	*Rgotoifnonnilesepop	1	See [Rgotoifnonnilesepop], page 137,	$\phi(-1, 0) + 0$
0257	175	listN	2	See [listN], page 61.	$-n + 1$
0260	176	concatN	2	See [concatN], page 92.	
0261	177	insertN	1	See [insertN], page 113.	$-n + 1$
0262	178	stack-set	1	See [stack-set], page 132.	$-0 + 0$
0263	179	stack-set2	2	See [stack-set2], page 133.	$-0 + 0$
0264	180			Unused	
0265	181			Unused	
0266	182	discardN	1	See [discardN], page 130.	$-n + 0$
0267	183	switch	1	See [switch], page 35.	$-2 + 0$
0270	184			Unused	
0271	185			Unused	
0272	186			Unused	
0273	187			Unused	
0274	188			Unused	
0275	189			Unused	
0276	190			Unused	
0277	191			Unused	

5.4 Opcodes (0300-3277) Constants

Oct	Dec	Instruction	Size	Description	Stack
0300	192	constant[0]	1	See [constant], page 24.	+1
0301	193	constant[1]	1	See [constant], page 24.	+1
0302	194	constant[2]	1	See [constant], page 24.	+1
0303	195	constant[3]	1	See [constant], page 24.	+1
0304	196	constant[4]	1	See [constant], page 24.	+1
0305	197	constant[5]	1	See [constant], page 24.	+1
0306	198	constant[6]	1	See [constant], page 24.	+1
0307	199	constant[7]	1	See [constant], page 24.	+1
0310	200	constant[8]	1	See [constant], page 24.	+1
0311	201	constant[9]	1	See [constant], page 24.	+1
0312	202	constant[10]	1	See [constant], page 24.	+1
0313	203	constant[11]	1	See [constant], page 24.	+1
0314	204	constant[12]	1	See [constant], page 24.	+1
0315	205	constant[13]	1	See [constant], page 24.	+1
0316	206	constant[14]	1	See [constant], page 24.	+1
0317	207	constant[15]	1	See [constant], page 24.	+1
0320	208	constant[16]	1	See [constant], page 24.	+1
0321	209	constant[17]	1	See [constant], page 24.	+1
0322	210	constant[18]	1	See [constant], page 24.	+1
0323	211	constant[19]	1	See [constant], page 24.	+1
0324	212	constant[20]	1	See [constant], page 24.	+1
0325	213	constant[21]	1	See [constant], page 24.	+1
0326	214	constant[22]	1	See [constant], page 24.	+1
0327	215	constant[23]	1	See [constant], page 24.	+1
0330	216	constant[24]	1	See [constant], page 24.	+1
0331	217	constant[25]	1	See [constant], page 24.	+1
0332	218	constant[26]	1	See [constant], page 24.	+1
0333	219	constant[27]	1	See [constant], page 24.	+1
0334	220	constant[28]	1	See [constant], page 24.	+1
0335	221	constant[29]	1	See [constant], page 24.	+1
0336	222	constant[30]	1	See [constant], page 24.	+1
0337	223	constant[31]	1	See [constant], page 24.	+1
0340	224	constant[32]	1	See [constant], page 24.	+1
0341	225	constant[33]	1	See [constant], page 24.	+1
0342	226	constant[34]	1	See [constant], page 24.	+1
0343	227	constant[35]	1	See [constant], page 24.	+1
0344	228	constant[36]	1	See [constant], page 24.	+1
0345	229	constant[37]	1	See [constant], page 24.	+1
0346	230	constant[38]	1	See [constant], page 24.	+1
0347	231	constant[39]	1	See [constant], page 24.	+1
0350	232	constant[40]	1	See [constant], page 24.	+1
0351	233	constant[41]	1	See [constant], page 24.	+1

0352	234	constant[42]	1	See [constant], page 24.	+1
0353	235	constant[43]	1	See [constant], page 24.	+1
0354	236	constant[44]	1	See [constant], page 24.	+1
0355	237	constant[45]	1	See [constant], page 24.	+1
0356	238	constant[46]	1	See [constant], page 24.	+1
0357	239	constant[47]	1	See [constant], page 24.	+1
0360	240	constant[48]	1	See [constant], page 24.	+1
0361	241	constant[49]	1	See [constant], page 24.	+1
0362	242	constant[50]	1	See [constant], page 24.	+1
0363	243	constant[51]	1	See [constant], page 24.	+1
0364	244	constant[52]	1	See [constant], page 24.	+1
0365	245	constant[53]	1	See [constant], page 24.	+1
0366	246	constant[54]	1	See [constant], page 24.	+1
0367	247	constant[55]	1	See [constant], page 24.	+1
0370	248	constant[56]	1	See [constant], page 24.	+1
0371	249	constant[57]	1	See [constant], page 24.	+1
0372	250	constant[58]	1	See [constant], page 24.	+1
0373	251	constant[59]	1	See [constant], page 24.	+1
0374	252	constant[60]	1	See [constant], page 24.	+1
0375	253	constant[61]	1	See [constant], page 24.	+1
0376	254	constant[62]	1	See [constant], page 24.	+1
0377	255	constant[63]	1	See [constant], page 24.	+1

6 References

- Execution of byte code produced by bytecomp.el (<http://git.savannah.gnu.org/cgit/emacs.git/tree/src/bytecode.c>)
- bytecomp.el — compilation of Lisp code into byte code (<http://git.savannah.gnu.org/cgit/emacs.git/tree/lisp/emacs-lisp/bytecomp.el>)
- data.c — Primitive operations on Lisp data types (<http://git.savannah.gnu.org/cgit/emacs.git/tree/src/data.c>)
- Emacs Byte-code Internals (<http://nullprogram.com/blog/2014/01/04/>)
- Emacs Wiki ByteCodeEngineering (<https://www.emacswiki.org/emacs/ByteCodeEngineering>)
- Assembler for Emacs' bytecode interpreter (https://groups.google.com/forum/#!topic/gnu.emacs.sources/oMfZT_40xrc easm.el)
- Emacs Lisp Decompiler (<https://github.com/rocky/elisp-decompile>)
- Emacs source code since Emacs 21.4a (<https://ftp.gnu.org/pub/gnu/emacs>)
- Emacs source code since Emacs 21.4a (<https://ftp.gnu.org/pub/gnu/emacs>)
- Emacs source code before Emacs 21.4a (<https://ftp.gnu.org/pub/old-gnu/emacs>)

Instruction Index

A

add1.....	74
aref.....	63
aset.....	64
assq.....	50

B

bobp.....	121
bolp.....	120
buffer-substring.....	100

C

call.....	22
car.....	54
car-safe.....	70
cdr.....	55
cdr-safe.....	71
char-after.....	114
char-syntax.....	124
concat2.....	89
concat3.....	90
concat4.....	91
concatN.....	92
condition-case.....	135
cons.....	56
consp.....	37
constant.....	24
constant2.....	25
current-buffer.....	97
current-column.....	117

D

delete-region.....	122
diff.....	80
discard.....	129
discardN.....	130
downcase.....	94
dup.....	131

E

elt.....	66
end-of-line.....	123
eobp.....	119
eolp.....	118
eq.....	40
eqlsign.....	75
equal.....	48

F

following-char.....	115
forward-char.....	105
forward-line.....	107
forward-word.....	106
fset.....	46

G

geq.....	79
get.....	47
goto.....	29
goto-char.....	102
goto-if-nil.....	30
goto-if-nil-else-pop.....	32
goto-if-not-nil.....	31
goto-if-not-nil-else-pop.....	33
gtr.....	76

I

insert.....	112
insertN.....	113
integerp.....	52
interactive-p.....	134

L

length.....	62
leq.....	78
list1.....	57
list2.....	58
list3.....	59
list4.....	60
listN.....	61
listp.....	39
lss.....	77

M

mark.....	134
match-beginning.....	127
match-end.....	128
max.....	84
member.....	49
memq.....	41
min.....	85
mult.....	83

N

narrow-to-region	110
nconc	72
negate	81
not	42
nreverse	67
nth	53
nthcdr	65
numberp	51

P

plus	82
point	101
point-max	103
point-min	104
pophandler	26
preceding-char	116
pushcatch	28
pushconditioncase	27

Q

quo	86
-----------	----

R

read-char	134
rem	87
return	34
Rgoto	137
Rgotoifnil	137
Rgotoifnilelsep	137
Rgotoifnonnil	137
Rgotoifnonnilelsep	137

S

save-current-buffer	134
save-current-buffer-1	99
save-excursion	125
save-window-excursion	134
scan-buffer	134
set	45
set-buffer	98
set-mark	134
set-marker	126
setcar	68
setcdr	69
skip-chars-backward	109
skip-chars-forward	108
stack-ref	18
stack-set	132
stack-set2	133
stringeqsign	95
stringlss	96
stringp	38
sub1	73
substring	88
switch	35
symbol-function	44
symbol-value	43
symbolp	36

T

temp-output-buffer-setup	135
temp-output-buffer-show	136

U

unbind	23
unbind-all	136
upcase	93

V

varbind	21
varref	19
varset	20

W

widen	111
-------------	-----

Byte-Code Function Index

A

aref 5

B

byte-compile 6

byte-compile-function-p 5

byte-compile-lapcode 2

byte-compile-make-args-desc 6

M

make-byte-code 2, 5

mapcar 5