

# DSC 102: Systems for Scalable Analytics

## Programming Assignment 0

### 1 Introduction

The goal of this programming assignment is to get you comfortable with datasets that do not fit in single-node memory and are too big for tools like Pandas or NumPy. You will be using Dask library to explore secondary storage aware data access on a single machine. In this assignment, you will be learning to setup dask on AWS and computing several descriptive statistics about the data to build intuitions for feature engineering for the final assignment.

### 2 Dataset Description

You are provided with the Amazon Reviews dataset with the *reviews* table as CSV file. The schemas are provided in Table 1. The dataset is available on the s3 bucket: `s3://dsc102-public`.

Column name	Column description	Example
reviewerID	ID of the reviewer	A32DT10X9WS4D0
asin	ID of the product	B003VX9DJM
reviewerName	name of the reviewer	Slade
helpful	helpfulness rating of the review	[0, 0]
reviewText	text of the review	this was a gift for my friend who loves touch lamps.
overall	rating of the product	1
summary	summary of the review	broken piece
unixReviewTime	summary of the review	1397174400
reviewTime	time of the review (raw)	04 11, 2014

Table 1: Schema of Reviews table

### 3 Tasks

You will use the *reviews* table to explore features related to users. Specifically, you will create the users table with the schema given in Table 2.

A code stub with function signature for this task has been provided to you. The input to the function is the reviews CSV file and you will be carrying out a series of transformations to produce the users table as DataFrame. Plug in the DataFrame you obtained as a result in `<YOUR_USERS_DATAFRAME>` and write this to `results_PA0.json` file. We will time the execution of the function PA0.

We have shared with you the “development” dataset and our accuracy results. Our code’s runtime on 1 node is roughly 615s. You can use this to validate your results and debug your code. The final evaluation will happen on separate held-out test sets. The runtime will be different for the held-out test set.

### 4 Deliverables

Submit your source code as `<YOUR-TEAM-ID>.py` on Canvas. Your source code must confirm to the function signatures provided to you. Make sure that your code is writing results to `results_PA0.json`.

Column name	Column description
reviewerID (PRIMARY KEY)	ID of the reviewer
number_productsRated	Total number of products rated by the reviewer
avg_ratings	Average rating given by the reviewer across all the reviewed products
reviewing_since	The year in which the user gave their first review
helpful_votes	Total number of helpful votes received for the users' reviews
total_votes	Total number of votes received for the users' reviews

Table 2: Schema of users table

## 5 Getting Started

1) Once we have set up your groups in canvas, a role will be created in AWS associated with your group. Access your AWS account using single sign-on ID: [https://ets-apps.ucsd.edu/individual/DSC102\\_SP23\\_A00/roster](https://ets-apps.ucsd.edu/individual/DSC102_SP23_A00/roster).

### Roster for DSC102\_SP23\_A00

Student	Name	Team	AWS Acct	Overall Limit	Daily Limit	Total	Past Week	Past Day	Calendar Day	Updated
grader-dsc102-02	Grader account, Dsc102	Grader	035170873046	\$50.00	\$3.00	\$0.16	\$0.16	\$0.13	\$0.00	2023-04-05 01:57:04
ets-course-c7-student001	Unassigned Account		488708370265	\$50.00	\$3.00	\$0.13	\$0.13	\$0.01	\$0.00	2023-04-05 01:57:04
ets-course-c7-student002	Unassigned Account		589087017987	\$50.00	\$3.00	\$0.13	\$0.13	\$0.01	\$0.00	2023-04-05 01:57:04
ets-course-c7-student003	Unassigned Account		372373662974	\$50.00	\$3.00	\$0.13	\$0.13	\$0.01	\$0.00	2023-04-05 01:57:04
ets-course-c7-student004	Unassigned Account		865980814762	\$50.00	\$3.00	\$0.13	\$0.13	\$0.01	\$0.00	2023-04-05 01:57:04
ets-course-c7-student005	Unassigned Account		662540020747	\$50.00	\$3.00	\$0.16	\$0.14	\$0.01	\$0.00	2023-04-05 01:57:04
ets-course-c7-student006	Unassigned Account		871652672975	\$50.00	\$3.00	\$0.19	\$0.15	\$0.01	\$0.00	2023-04-05 01:57:04
ets-course-c7-student007	Unassigned Account		914790398682	\$50.00	\$3.00	\$0.13	\$0.13	\$0.01	\$0.00	2023-04-05 01:57:04
ets-course-c7-student008	Unassigned Account		159603041841	\$50.00	\$3.00	\$0.22	\$0.16	\$0.01	\$0.00	2023-04-05 01:57:04
ets-course-c7-student009	Unassigned Account		668068694130	\$50.00	\$3.00	\$0.18	\$0.15	\$0.01	\$0.00	2023-04-05 01:57:04
ets-course-c7-student010	Unassigned Account		095222248856	\$50.00	\$3.00	\$0.17	\$0.15	\$0.01	\$0.00	2023-04-05 01:57:04
ets-course-c7-student011	Unassigned Account		987273165451	\$50.00	\$3.00	\$0.13	\$0.13	\$0.01	\$0.00	2023-04-05 01:57:04
ets-course-c7-student012	Unassigned Account		526151398948	\$50.00	\$3.00	\$0.13	\$0.13	\$0.01	\$0.00	2023-04-05 01:57:04

Select your group name from the menu and you will find a summary page indicating your overall budget, daily budget, and usage. You will also find a breakdown of costs. Click the 'Click here to access AWS' link at the very bottom of the page to access the AWS console, or alternatively click the 'Generate API KEYS (for CLI/scripting)' to get credentials for the AWS command line interface. More information on the AWS command line interface can be found here: <https://aws.amazon.com/cli/>

## EDUCATIONAL TECHNOLOGY SERVICES

### DSC102\_SP23\_A00\_student (Roster) - AWS Educate

Usage for: grader-dsc102-02

Billing for AWS account 035170873046

Overall Limit	Daily Limit	Total	Past Week	Past Day	Calendar Day	Updated
\$50.00	\$3.00	\$0.16	\$0.16	\$0.13	\$0.00	2023-04-05 01:57:04

	2023-04-03	2023-04-04	Weekly Total
UCSD estimated EC2	0.00	0.00	0.00
BurnRate:USW2-BoxUsage:t2.micro	0.00	0.01	0.01
BurnRate:USW2-BoxUsage:t2.xlarge	0.00	0.09	0.09
BurnRate:USW2-SpotUsage:t2.xlarge	0.00	0.02	0.02
Total	0.00	0.12	0.12

#### Notes:

- Spot instances are a useful way to reduce EC2 costs, but because of AWS limitations, **one-time spot instances will be terminated**, launch persistent spot instances in the [AWS Spot Instance Request documentation](#).
- UCSD-estimated usage reflects unbilled EC2 activity only.
- Other usage information is based on AWS billing records and can be delayed ~12-16 hours.
- Services with minimal charges have been omitted from the above tables, thus Total values may slightly disagree.
- EC2 instances are halted when Daily limit exceeded, but other charges (e.g. VolumeUsage) continue to accrue.
- [Detailed billing data for DSC102\\_SP23\\_A00\\_student/grader-dsc102-02 \(CSV/text format\)](#).
- [Generate API Keys \(for CLI/scripting\)](#)

[Click here to access AWS.](#)

2) We have setup the Dask environment on an AMI with name “dsc102-dask-environment-public.” Go to “AMIs” (under “Images”) in your EC2 dashboard, select public images, and then search by name to find it. Select this AMI and click ‘Launch Instance from AMI’. See Figure 1 and Figure 2 .

aws

Services

Search

[Option+S]

Ore

New EC2 Experience

Tell us what you think

EC2 Dashboard

EC2 Global View

Events

Tags

Limits

▼ Instances

Instances

Instance Types

Launch Templates

Spot Requests

Savings Plans

Reserved Instances

Dedicated Hosts

Scheduled Instances

Capacity Reservations

▼ Images

AMIs

AMI Catalog

▼ Elastic Block Store

Volumes

Snapshots

Resources

EC2 Global view

You are using the following Amazon EC2 resources in the US West (Oregon) Region:

Instances (running)	0	Auto Scaling Groups	0	Dedicated Hosts	0
Elastic IPs	0	Instances	0	Key pairs	1
Load balancers	0	Placement groups	0	Security groups	2
Snapshots	1	Volumes	0		

Easily size, configure, and deploy Microsoft SQL Server Always On availability groups on AWS using the AWS Launch Wizard for SQL Server. [Learn more](#)

Launch instance

To get started, launch an Amazon EC2 instance, which is a virtual server in the cloud.

Launch instance

Migrate a server

Note: Your instances will launch in the US West (Oregon) Region

Scheduled events

US West (Oregon)

Service health

AWS Health Dashboard

Region

US West (Oregon)

Status

This service is operating normally

Zones

Zone name	Zone ID

Figure 1




Figure 2

3) You will be launching one EC2 *Spot* instance that will be used to run dask remotely (in the cloud, not on your personal machine). Note that an AWS spot instance is heavily discounted in price, in exchange for giving AWS permissions to shut down your instance if demand for compute is high. Be mindful about backing up your code and associated artifacts.

a) You should now be on the 'Launch an Instance' page, as indicated in Figure 3. Under 'Name', give your instance a name you will remember. Under 'Number of instances' on the right side of the page, leave the value as 1.

[EC2](#) > [Instances](#) > Launch an instance

## Launch an instance Info

Amazon EC2 allows you to create virtual machines, or instances, that run on the AWS Cloud. Quickly get started by following the simple steps below.

### Name and tags Info

Name

MY\_MEMORABLE\_EC2\_NAME

[Add additional tags](#)

### Application and OS Images (Amazon Machine Image) Info

An AMI is a template that contains the software configuration (operating system, application server, and applications) required to launch your instance. Search or Browse for AMIs if you don't see what you are looking for below

[AMI from catalog](#)
[My AMIs](#)
[Quick Start](#)

Amazon Machine Image (AMI)
dsc102-dask-environment-public
ami-03b7694feb0fc4f8d

[Browse more AMIs](#)

Including AMIs from AWS, Marketplace and the Community

### Summary

Number of instances Info

1

Software Image (AMI)
dsc102-dask-environment-public...[read more](#)
ami-03b7694feb0fc4f8d

Virtual server type (instance type)
t2.micro

Firewall (security group)
New security group

Storage (volumes)
1 volume(s) - 8 GiB

*Free tier:* In your first year includes 750 hours of t2.micro (or t3.micro in the Regions in which t2.micro is unavailable) instance usage on free tier AMIs per month, 30 GiB of EBS storage, 2 million IOs, 1 GB of snapshots, and 100 GB of bandwidth to the internet.

Cancel
Launch instance
[Review commands](#)

Figure 3

b) Leave the ‘Application and OS Images (Amazon Machine Image)’ field as is, as that was pre-populated by your selection to run from the dsc102 AMI. Under ‘instance type’, select “t2.xlarge”. Under the key pair (login) heading, click ‘create new key pair’, give the key pair a name that you will remember, leave ‘key pair type’ RSA checked, and then select the private key file format ‘.pem’ if your personal computer is Mac or Linux, or ‘.ppk’ if you are using Putty on Windows. Once you have performed this step, you will only have to select your existing key pair for future iterations. Download the key to a location you will remember as you will be reusing this each time you want to log in to your machine. Here is a more info for mac users: [https://www.youtube.com/watch?v=8UqtMcX\\_kg0](https://www.youtube.com/watch?v=8UqtMcX_kg0) and for Windows users: <https://www.youtube.com/watch?v=kzLRxVgos2M> Under the ‘network settings’ header, create a new security group and leave the “Allow SSH traffic from ... Anywhere 0.0.0.0/0 checked”.

6

▼ Instance type [Info](#)

t2.xlarge

Family: t2 4 vCPU 16 GiB Memory  
On-Demand Windows pricing: 0.2266 USD per Hour  
On-Demand Linux pricing: 0.1856 USD per Hour  
On-Demand SUSE pricing: 0.2856 USD per Hour  
On-Demand RHEL pricing: 0.2456 USD per Hour

All generations

Compare instance types

▼ Key pair (login) [Info](#)

You can use a key pair to securely connect to your instance. Ensure that you have access to the selected key pair before you launch the instance.

Key pair name - *required*

Select

Create new key pair

▼ Network settings [Info](#)

Edit

Network [Info](#)

vpc-62cee51a

Subnet [Info](#)

No preference (Default subnet in any availability zone)

Auto-assign public IP [Info](#)

Enable

Firewall (security groups) [Info](#)

A security group is a set of firewall rules that control the traffic for your instance. Add rules to allow specific traffic to reach your instance.

Create security group

Select existing security group

We'll create a new security group called `launch-ec2-sg` with the following rules:

▼ Summary

Number of instances [Info](#)

1

Software Image (AMI)

dsc102-dask-environment-public...[read more](#)  
ami-03b7694feb0fc4f8d

Virtual server type (instance type)

t2.xlarge

Firewall (security group)

New security group

Storage (volumes)

1 volume(s) - 8 GiB

Free tier:

In your first year includes 750 hours of t2.micro (or t3.micro in the Regions in which t2.micro is unavailable) instance usage on free tier AMIs per month, 30 GiB of EBS storage, 2 million IOs, 1 GB of snapshots, and 100 GB of bandwidth to the internet.

Cancel

Launch instance

[Review commands](#)

Figure 4

7

☒ **Allow SSH traffic from**  
Helps you connect to your instance

Anywhere  
0.0.0.0/0

☐ **Allow HTTPS traffic from the internet**  
To set up an endpoint, for example when creating a web server

☐ **Allow HTTP traffic from the internet**  
To set up an endpoint, for example when creating a web server

Rules with source of 0.0.0.0/0 allow all IP addresses to access your instance. We recommend setting security group rules to allow access from known IP addresses only.

▼ **Configure storage**
Info

Advanced

1x

40

GiB

gp3

Root volume (Not encrypted)

Free tier eligible customers can get up to 30 GB of EBS General Purpose (SSD) or Magnetic storage

Add new volume

The selected AMI contains more instance store volumes than the instance allows. Only the first 0 instance store volumes from the AMI will be accessible from the instance

0 x File systems

Edit

▼ **Advanced details**
Info

Purchasing option Info

☒ **Request Spot Instances**

Customize

Request Spot Instances at the Spot price, capped at the On-Demand price

▼ **Summary**

Number of instances
Info

1

Software Image (AMI)  
dsc102-dask-environment-public...read more  
ami-03b7694feb0fc4f8d

Virtual server type (instance type)  
t2.xlarge

Firewall (security group)  
New security group

Storage (volumes)  
1 volume(s) - 40 GiB

**Free tier:** In your first year includes 750 hours of t2.micro (or t3.micro in the Regions in which t2.micro is unavailable) instance usage on free tier AMIs per month, 30 GiB of EBS storage, 2 million IOs, 1 GB of snapshots, and 100 GB of bandwidth to the internet.

Cancel

Launch instance

Review commands

Figure 5

c) Under ‘Configure Storage’, select “40GB” of storage on a ‘general purpose SSD (gp3)’. Under ‘Advanced Details’, check the ‘Request Spot Instances’ box and leave all the sub-values as defaults. Under ‘IAM instance profile’ select ‘Dsc102Role\_InstanceProfile’ (it should be your only option). Retain other fields unchanged.



Purchasing option [Info](#)

☒ Request Spot Instances [Customize](#)

Request Spot Instances at the Spot price, capped at the On-Demand price

Domain join directory [Info](#)

Select

Create new directory

IAM instance profile [Info](#)

Dsc102Role\_InstanceProfile  
arn:aws:iam::035170873046:instance-profile/Dsc102Role\_InstanceProfile

Create new IAM profile

Hostname type [Info](#)

IP name

DNS Hostname [Info](#)

☒ Enable IP name IPv4 (A record) DNS requests  
☒ Enable resource-based IPv4 (A record) DNS requests  
☐ Enable resource-based IPv6 (AAAA record) DNS requests

Instance auto-recovery [Info](#)

Select

Shutdown behavior [Info](#)

Stop

Stop - Hibernate behavior [Info](#)

Select

Not applicable for Spot Requests.

Termination protection [Info](#)

Off

Summary

Number of instances [Info](#)

1

Software Image (AMI)  
dsc102-dask-environment-public...[read more](#)  
ami-03b7694feb0fc4f8d

Virtual server type (instance type)  
t2.xlarge

Firewall (security group)  
New security group

Storage (volumes)  
1 volume(s) - 40 GiB

Free tier:

In your first year includes 750 hours of t2.micro (or t3.micro in the Regions in which t2.micro is unavailable) instance usage on free tier AMIs per month, 30 GiB of EBS storage, 2 million IOs, 1 GB of snapshots, and 100 GB of bandwidth to the internet.

Cancel

Launch instance  
[Review commands](#)

d) Finally, after pressing the “Launch Instance” button. Return to the ‘Instances’ page and wait for your instance’s ‘Instance state’ to be set to ‘Running’.

e) Click the instance ID and you should see details on your instance. Copy the public IPv4 address.




Figure 8

4) Next, you will start the jupyter notebook server on the instance.

a) Change permission of the ssh keyfile to make sure your private key file isn't publicly viewable: `chmod 400 <keyfilename>.pem`. Linux and Mac users in particular will need the `chmod`.

b) SSH into one of the nodes using command: `ssh -i 'YOUR-KEY-NAME.pem' ubuntu@<ip-address-of-EC2-instance>`. This command is shown in the Figure 9 below. `<ip-address-of-EC2-instance>` is shown in the red box in Figure 10. Activate the dask environment with command: `source dask_env/bin/activate`. Start jupyter notebook server on one terminal with: `jupyter notebook --port=8888`.




Figure 9

c) Open a new terminal and SSH to jupyter notebook using: `ssh -i 'dask-key.pem' ubuntu@<ip-address-of-EC2-instance> -L 8888:localhost:8888`. '-L' will port forward any connection to port 8888 on the local machine to port 8888 on `<ip-address-of-EC2-instance>`. Run `source dask_env/bin/activate` again to re-activate the dask env in your terminal. Type in `jupyter notebook list` to get the token/password for the jupyter notebook. Open your browser and go to `localhost:8888` and paste the token, or copy the entire path, as port 8888 is mapped to local. You can write your code here using jupyter notebook. To see dashboard on localhost port 8001 use command: `ssh -i 'dask-key.pem' ubuntu@<ip-address-of-EC2-instance> -L 8001:localhost:8787`.

Consider using utilities like `tmux` or `nohup` for managing terminals.

5) The data and files are available from the s3 bucket (`s3://dsc102-public`). This contains the function signatures




Figure 10

(PA0.py), dataset (user\_reviews.csv), schema of expected output (OutputSchema\_PA0.json), and the expected result on the development dataset (results\_PA0.json).

a) First, verify that you have S3 access from your EC2 instance by running:

```
aws s3 ls
```

You should see a listing that includes the s3://dsc102-public bucket.

b) Use the command `aws s3 sync s3://dsc102-public /local-file-path` to download the files from S3 to local disk. Make sure that data is available in the same path where the jupyter notebook client is running.

6) Open the dashboard and click on “Workers” to double check if all workers (all threads of the single machine) are connected and you are now ready to code up.

7) Terminate the EC2 instance once you are done.

**VERY IMPORTANT: Download your progress to your local machine (or backup to a private GitHub repo) at regular intervals and terminate your instance when you decide to pause working. You have only \$50 for both PA0 and PA1 and so DO NOT leave instances running. If you terminate without downloading, you WILL LOSE all your work. Every time you start a new instance, you must download the dataset from S3 to your instance. Also, start only AWS Spot Instances and NOT On-Demand instances.**