

Shor's Algorithm

1. Pick x at random s.t. $1 < x < N$

2. If $GCD(x, N) = d \neq 1$ then d is a factor of N , so we recurse on N/d . Else x and N are coprime, so we try to find the multiplicative order of x modulo N .

The quantum computer is initialized to $|\psi_0\rangle = |0\rangle |0\rangle$. Register one has t qubits ($N^2 \leq 2^t < 2N^2$), and register two has $n = \lceil \log_2 N \rceil$ qubits.

3. Apply the Hadamard operator t times to the first register, yielding

$$|\psi_1\rangle = H^{\otimes t} |\psi_0\rangle = \frac{1}{\sqrt{2^t}} \sum_{j=0}^{2^t-1} |j\rangle |0\rangle . \quad (1)$$

4. Apply the linear operator $V_x(|j\rangle |k\rangle) = |j\rangle |k + x^j\rangle$ to obtain

$$\begin{aligned} |\psi_2\rangle &= V_x |\psi_1\rangle \\ &= \frac{1}{\sqrt{2^t}} \sum_{j=0}^{2^t-1} |j\rangle |x^j\rangle \\ &= \frac{1}{\sqrt{2^t}} \sum_{b=0}^{r-1} \sum_{a=0}^{\frac{2^t}{r}-1} |ar + b\rangle |x^b\rangle . \end{aligned} \quad (2)$$

5. Measure the second register, fixing $b = b_0$, where b_0 is a random number between 0 and $r - 1$, obtaining

$$|\psi_3\rangle = \sqrt{\frac{r}{2^t}} \sum_{a=0}^{\frac{2^t}{r}-1} |ar + b_0\rangle |x^{b_0}\rangle . \quad (3)$$

6. Apply the inverse Fourier transform, $DFT^\dagger(|k\rangle) = \frac{1}{\sqrt{N}} \sum_{j=0}^{N-1} e^{-2\pi i j k / N} |j\rangle$, yielding

$$|\psi_4\rangle = \frac{1}{\sqrt{r}} \left(\sum_{j=0}^{2^t-1} \left[\frac{1}{2^t/r} \sum_{a=0}^{\frac{2^t}{r}-1} e^{\frac{-2\pi i j a}{2^t/r}} \right] e^{-2\pi i j b_0 / 2^t} |j\rangle \right) |x^{b_0}\rangle . \quad (4)$$

7. Measuring the first register, we get the value $k_0 2^t / r$, for some $k_0 \in \{0, 1, \dots, r-1\}$. If we obtain $k_0 = 0$ we run the algorithm again. Else we divide $k_0 2^t / r$ by 2^t , obtaining k_0 / r .

8. To extract r , we represent k_0 / r by a finite continued fraction, and then ... ???