

Specs

Aircraft

Weight (with propellers, without accessories) ^[1]	DJI Mavic 3E: 915 g DJI Mavic 3T/3TA: 920 g
Max Takeoff Weight	DJI Mavic 3E/3T/3TA: 1050 g * With DJI Mavic 3 Enterprise Series Battery (EU C1 Version) and DJI Mavic 3 Enterprise Series Low-Noise Propellers, the max takeoff weight of DJI Mavic 3E/3T/3TA is 899 g. ** Note: A Mavic 3 Enterprise Series drone with a C2 label cannot be considered C1-compliant if used with an EU-C1 version battery.
Dimensions	Folded (without propellers): 221×96.3×90.3 mm (L×W×H) Unfolded (without propellers): 347.5×283×107.7 mm (L×W×H)
Diagonal Distance	380.1 mm
Max Ascent Speed	6 m/s (Normal Mode) 8 m/s (Sport Mode)
Max Descent Speed	6 m/s (Normal Mode) 6 m/s (Sport Mode)
Max Flight Speed (at sea level, no wind)	15 m/s (Normal Mode) Forward: 21 m/s, Side: 20 m/s, Backward: 19 m/s (Sport Mode) ^[2]
Max Wind Speed Resistance	12 m/s ^[3]
Max Take-off Altitude Above Sea Level	6000 m (without payload)
Max Flight Time (no wind)	45 minutes ^[4] (with DJI Mavic 3 Series Intelligent Flight Battery and DJI Mavic 3 Enterprise Series Propellers) 36 minutes (with DJI Mavic 3 Enterprise Series Battery (EU C1 Version) and DJI Mavic 3 Enterprise Series Low Noise Propellers) Note: A Mavic 3 Enterprise Series drone with a C2 label cannot be considered C1-compliant if used with an EU-C1 version battery.
Max Hovering Time (no wind)	38 minutes (with DJI Mavic 3 Series Intelligent Flight Battery and DJI Mavic 3 Enterprise Series Propellers) 30 minutes (with DJI Mavic 3 Enterprise Series Battery (EU C1 Version) and DJI Mavic 3 Enterprise Series Low Noise Propellers) Note: A Mavic 3 Enterprise Series drone with a C2 label cannot be considered C1-compliant if used with an EU-C1 version battery.
Max Flight Distance	32 km (with DJI Mavic 3 Series Intelligent Flight Battery and DJI Mavic 3 Enterprise Series Propellers) 24 km (with DJI Mavic 3 Enterprise Series Battery (EU C1 Version) and DJI Mavic 3 Enterprise Series Low-Noise Propellers) Note: A Mavic 3 Enterprise Series drone with a C2 label cannot be considered C1-compliant if used with an EU-C1 version battery.



Max Pitch Angle	30° (Normal Mode) 35° (Sport Mode)
Max Angular Velocity	200°/s
GNSS	GPS+Galileo+BeiDou+GLONASS (GLONASS is supported only when the RTK module is enabled)
Hovering Accuracy	Vertical: ±0.1 m (with Vision System); ±0.5 m (with GNSS); ±0.1 m (with RTK) Horizontal: ±0.3 m (with Vision System); ±0.5 m (with High-Precision Positioning System); ±0.1 m (with RTK)
Operating Temperature Range	-10° to 40° C (14° to 104° F)
Internal Storage	N/A
Motor Model	2008
Propeller Model	9453F Propellers for Enterprise
Beacon	Built into the aircraft
Class	C2 (EU)

Wide Camera

Sensor	DJI Mavic 3E: 4/3 CMOS, Effective pixels: 20 MP DJI Mavic 3T/3TA: 1/2-inch CMOS, Effective pixels: 48 MP
Lens	DJI Mavic 3E: FOV: 84° Equivalent Focal Length: 24mm Aperture: f/2.8-f/11 Focus: 1 m to ∞ DJI Mavic 3T/3TA: FOV: 84° Equivalent Focal Length: 24mm Aperture: f/2.8 Focus: 1 m to ∞
ISO Range	DJI Mavic 3E: 100-6400 DJI Mavic 3T/3TA: 100-25600
Shutter Speed	DJI Mavic 3E: Electronic Shutter: 8-1/8000 s Mechanical Shutter: 8-1/2000 s DJI Mavic 3T/3TA: Electronic Shutter: 8-1/8000 s
Max Image Size	DJI Mavic 3E: 5280×3956 DJI Mavic 3T/3TA: 8000×6000
Still Photography Modes	DJI Mavic 3E: Single: 20 MP Timed: 20 MP JPEG: 0.7/1/2/3/5/7/10/15/20/30/60 s JPEG+RAW: 3/5/7/10/15/20/30/60 s Smart Low-light Shooting: 20 MP Panorama: 20 MP (raw image)



DJI Mavic 3T/3TA:
Single: 12 MP/48 MP
Timed: 12 MP/48 MP
JPEG: 2/3/5/7/10/15/20/30/60 s*
Panorama: 12 MP (raw image); 100 MP (stitched image)

* Shooting 48MP photo does not support 2s interval
Smart Low-light Shooting: 12 MP

Video Resolution	H.264 4K: 3840×2160@30fps FHD: 1920×1080@30fps
Bitrate	DJI Mavic 3E: 4K: 130 Mbps FHD: 70 Mbps DJI Mavic 3T/3TA: 4K: 85 Mbps FHD: 30 Mbps
Supported File Formats	exFAT
Photo Format	DJI Mavic 3E: JPEG/DNG (RAW) DJI Mavic 3T/3TA: JPEG
Video Format	MP4 (MPEG-4 AVC/H.264)

Tele Camera

Sensor	1/2-inch CMOS, Effective pixels: 12 MP
Lens	FOV: 15° Equivalent Focal Length: 162mm Aperture: f/4.4 Focus: 3 m to ∞
ISO Range	DJI Mavic 3E: 100-6400 DJI Mavic 3T/3TA: 100-25600
Shutter Speed	Electronic Shutter: 8-1/8000 s
Max Image Size	4000×3000
Photo Format	JPEG
Video Format	MP4 (MPEG-4 AVC/H.264)
Still Photography Modes	DJI Mavic 3E: Single: 12 MP Timed: 12 MP JPEG: 0.7/1/2/3/5/7/10/15/20/30/60 s Smart Low-light Shooting: 12 MP DJI Mavic 3T/3TA: Single: 12 MP Timed: 12 MP



JPEG: 2/3/5/7/10/15/20/30/60 s
Smart Low-light Shooting: 12 MP

Video Resolution	H.264 4K: 3840×2160@30fps FHD: 1920×1080@30fps
Bitrate	DJI Mavic 3E: 4K: 130 Mbps FHD: 70 Mbps DJI Mavic 3T/3TA: 4K: 85 Mbps FHD: 30 Mbps
Digital Zoom	8x (56x hybrid zoom)

Thermal Camera ^[5]

Thermal Imager	Uncooled VOx Microbolometer
Pixel Pitch	DJI Mavic 3T: 12 μm DJI Mavic 3TA: 8 μm
Frame Rate	30 Hz
Lens	DJI Mavic 3T: DFOV: 61° Equivalent Focal Length: 40mm Aperture: f/1.0 Focus: 5 m to ∞ DJI Mavic 3TA: DFOV: 41.2° Equivalent Focal Length: 60mm Aperture: f/1.0 Focus: 5 m to ∞
Noise Equivalent Temperature Difference (NETD)	≤50 mK@F1.0
Temperature Measurement Method	Spot Meter, Area Measurement
Temperature Measurement Range	-20° to 150° C (-4° to 302° F, High Gain Mode) 0° to 500° C (32° to 932° F, Low Gain Mode)
Palette	White Hot/Black Hot/Tint/Iron Red/Hot Iron/Arctic/Medical/Fulgurite/Rainbow 1/Rainbow 2
Photo Format	JPEG (8-bit) R-JPEG (16-bit)
Video Resolution	640×512@30fps
Bitrate	6 Mbps
Video Format	MP4 (MPEG-4 AVC/H.264)



Still Photography Modes	DJI Mavic 3T/3TA: Single: 640×512 Timed: 640×512 JPEG: 2/3/5/7/10/15/20/30/60 s
Digital Zoom	28x
Infrared Wavelength	8-14 μm
Infrared Temperature Measurement Accuracy	High Gain: ±2°C or ±2% (using the larger value) Low Gain: ±5°C or ±3% (using the larger value)

Gimbal

Stabilization	3-axis (tilt, roll, pan)
Mechanical Range	DJI Mavic 3E: Tilt: -135° to 100° Roll: -45° to 45° Pan: -27° to 27° DJI Mavic 3T/3TA: Tilt: -135° to 45° Roll: -45° to 45° Pan: -27° to 27°
Controllable Range	Tilt: -90° to 35° Pan: Not controllable
Max Control Speed (tilt)	100°/s
Angular Vibration Range	±0.007°

Sensing

Type	Omnidirectional binocular vision system, supplemented with an infrared sensor at the bottom of the aircraft
Forward	Measurement Range: 0.5-20 m Detection Range: 0.5-200 m Effective Sensing Speed: Flight Speed ≤15 m/s FOV: Horizontal 90°, Vertical 103°
Backward	Measurement Range: 0.5-16 m Effective Sensing Speed: Flight Speed ≤12 m/s FOV: Horizontal 90°, Vertical 103°
Lateral	Measurement Range: 0.5-25 m Effective Sensing Speed: Flight Speed ≤15 m/s FOV: Horizontal 90°, Vertical 85°
Upward	Measurement Range: 0.2-10 m Effective Sensing Speed: Flight Speed ≤6 m/s FOV: Front and Back 100°, Left and Right 90°



Downward	Measurement Range: 0.3-18 m Effective Sensing Speed: Flight Speed ≤6 m/s FOV: Front and Back 130°, Left and Right 160°
Operating Environment	Forward, Backward, Lateral, and Upward: Surface with a clear pattern and adequate lighting (lux >15) Downward: Diffuse reflective surface with diffuse reflectivity>20% (e.g. walls, trees, people) and adequate lighting (lux >15)

Video Transmission

Video Transmission System	DJI O3 Enterprise Transmission
Live View Quality	Remote Controller: 1080p/30fps
Operating Frequency ^[6]	2.400-2.4835 GHz 5.725-5.850 GHz
Max Transmission Distance (unobstructed, free of interference) ^[7]	DJI Mavic 3E/3T/3TA: FCC: 15 km CE: 8 km SRRC: 8 km MIC: 8 km
Max Transmission Distance (Obstructed) ^[8]	Strong Interference (dense buildings, residential areas, etc.): 1.5-3 km (FCC/CE/SRRC/MIC) Medium Interference (suburban areas, city parks, etc.): 3-9 km (FCC), 3-6 km (CE/SRRC/MIC) Low Interference (open spaces, remote areas, etc.): 9-15 km (FCC), 6-8 km (CE/SRRC/MIC)
Max Download Speed ^[9]	15 MB/s (with DJI RC Pro Enterprise)
Latency (depending on environmental conditions and mobile device)	Approx. 200 ms
Antenna	4 Antennas, 2T4R
Transmission Power (EIRP)	2.4 GHz: <33 dBm (FCC), <20 dBm (CE/SRRC/MIC) 5.8 GHz: <33 dBm (FCC), 30 dBm (SRRC), <14 dBm (CE)

DJI RC Pro Enterprise

Video Transmission System	DJI O3 Enterprise Transmission
Max Transmission Distance (unobstructed, free of interference) ^[7]	FCC: 15 km CE/SRRC/MIC: 8 km
Video Transmission Operating Frequency ^[6]	2.400-2.4835 GHz 5.725-5.850 GHz
Antenna	4 Antennas, 2T4R
Video Transmission Transmitter Power (EIRP)	2.4 GHz: <33 dBm (FCC), <20 dBm (CE/SRRC/MIC) 5.8 GHz: <33 dBm (FCC), <14 dBm (CE), 23 dBm (SRRC)

Wi-Fi Protocol	802.11 a/b/g/n/ac/ax Support 2×2 MIMO Wi-Fi
----------------	--



Wi-Fi Operating Frequency ^[6]	2.400-2.4835 GHz 5.150-5.250 GHz 5.725-5.850 GHz
Wi-Fi Transmitter Power (EIRP)	2.4 GHz: <26 dBm (FCC), <20 dBm (CE/SRRC/MIC) 5.1 GHz: <26 dBm (FCC), <23 dBm (CE/SRRC/MIC) 5.8 GHz: <26 dBm (FCC/SRRC), <14 dBm (CE)
Bluetooth Protocol	Bluetooth 5.1
Bluetooth Operating Frequency	2.400-2.4835 GHz
Bluetooth Transmitter Power (EIRP)	< 10 dBm
Screen Resolution	1920×1080
Screen Size	5.5 inches
Screen	60 fps
Brightness	1,000 nits
Touchscreen Control	10-point multi-touch
Battery	Li-ion (5000 mAh @ 7.2 V)
Charging Type	Recommended to be charged with the included DJI USB-C Power Adapter (100W) or USB charger at 12 V or 15 V
Rated Power	12 W
Storage Capacity	Internal Storage (ROM): 64 GB Supports a microSD card for expanded capacity.
Charging Time	Approx. 1 hour 30 minutes (with the included DJI USB-C Power Adapter (100W) only charging the remote controller or a USB charger at 15 V) Approx. 2 hours (with a USB charger at 12 V) Approx. 2 hours 50 minutes (with the included DJI USB-C Power Adapter (100W) charging the aircraft and remote controller simultaneously)
Operating Time	Approx. 3 hours
Video Output Port	Mini-HDMI port
Operating Temperature Range	-10° to 40° C (14° to 104° F)
Storage Temperature	-30° to 60° C (-22° to 140° F) (within one month) -30° to 45° C (-22° to 113° F) (one to three months) -30° to 35° C (-22° to 95° F) (three to six months) -30° to 25° C (-22° to 77° F) (more than six months)
Charging Temperature	5° to 40° C (41° to 104° F)
Supported DJI Aircraft ^[10]	DJI Mavic 3E/3T/3TA
GNSS	GPS+Galileo+GLONASS
Dimensions	Antennas folded and controller sticks unmounted: 183.27×137.41×47.6 mm (L×W×H)



	Antennas unfolded and controller sticks mounted: 183.27×203.35×59.84 mm (L×W×H)
Weight	Approx. 680 g
Model	RM510B

Storage

Supported Memory Cards	Aircraft: U3/Class10/V30 or above is required. A list of recommended microSD cards can be found below.
Recommended microSD Cards	Remote Controller: SanDisk Extreme PRO 64GB V30 A2 microSDXC SanDisk High Endurance 64GB V30 microSDXC SanDisk Extreme 128GB V30 A2 microSDXC SanDisk Extreme 256GB V30 A2 microSDXC SanDisk Extreme 512GB V30 A2 microSDXC Lexar 667x 64GB V30 A2 microSDXC Lexar High-Endurance 64GB V30 microSDXC Lexar High-Endurance 128GB V30 microSDXC Lexar 667x 256GB V30 A2 microSDXC Lexar 512GB V30 A2 microSDXC Samsung EVO Plus 64GB V30 microSDXC Samsung EVO Plus 128GB V30 microSDXC Samsung EVO Plus 256GB V30 microSDXC Samsung EVO Plus 512GB V30 microSDXC Kingston Canvas Go! Plus 128GB V30 A2 microSDXC Kingston Canvas React Plus 128GB V90 A1 microSDXC Aircraft: SanDisk Extreme 32GB V30 A1 microSDHC SanDisk Extreme PRO 32GB V30 A1 microSDHC SanDisk Extreme 512GB V30 A2 microSDXC Lexar 1066x 64GB V30 A2 microSDXC Kingston Canvas Go! Plus 64GB V30 A2 microSDXC Kingston Canvas React Plus 64GB V90 A1 microSDXC Kingston Canvas Go! Plus 128GB V30 A2 microSDXC Kingston Canvas React Plus 128GB V90 A1 microSDXC Kingston Canvas React Plus 256GB V90 A2 microSDXC Samsung PRO Plus 256GB V30 A2 microSDXC

Battery

Capacity	DJI Mavic 3 Series Intelligent Flight Battery: 5000 mAh DJI Mavic 3 Enterprise Series Battery (EU C1 Version): 4230 mAh
Standard Voltage	15.4 V
Max Charging Voltage	17.6 V
Type	LiPo 4S
Chemical System	LiCoO2
Energy	DJI Mavic 3 Series Intelligent Flight Battery: 77 Wh DJI Mavic 3 Enterprise Series Battery (EU C1 Version): 65.15 Wh



Weight	DJI Mavic 3 Series Intelligent Flight Battery: 335.5 g DJI Mavic 3 Enterprise Series Battery (EU C1 Version): 285 g
--------	--

Charging Temperature	5° to 40° C (41° to 104° F)
----------------------	-----------------------------

Charger

Input	100-240 V (AC Power), 50-60 Hz, 2.5 A
Output Power	100 W
Output	Max. 100 W (total) When both ports are used, the maximum output power of each interface is 82 W, and the charger will dynamically allocate the output power of the two ports according to the load power.

Charging Hub

Input	USB-C: 5-20 V, 5.0 A
Output	Battery Port: 12-17.6 V, 8.0 A
Rated Power	100 W
Charging Type	Three batteries charged in sequence
Charging Temperature Range	5° to 40° C (41° to 104° F)

RTK Module

Dimensions	50.2×40.2×66.2 mm (L×W×H)
Weight	24±2 g
Interface	USB-C
Power	Approx. 1.2 W
RTK Positioning Accuracy	RTK Fix: Horizontal: 1 cm + 1 ppm; Vertical: 1.5 cm + 1 ppm

Speaker

Dimensions	114.1×82.0×54.7 mm (L×W×H)
Weight	85±2 g
Interface	USB-C
Rated Power	3 W
Max Volume ^[11]	110 dB @ 1 m
Effective Broadcast Distance ^[11]	100 m @ 70 dB



