



DJI AGRAS T40

Accessories Specs Video FAQ Downloads

Specs

Aircraft Parameters

Total weight	38 kg (without battery) 50 kg (with battery)
Max Takeoff Weight ^[1]	Max takeoff weight for spraying: 90 kg (at sea level) Maximum takeoff weight for spreading: 101 kg (at sea level)
Max Diagonal Wheelbase	2184 mm
Dimensions	2800 mm × 3150 mm × 780 mm (arms & propellers unfolded) 1590 mm × 1930 mm × 780 mm (arms unfolded, propellers folded) 1125 mm × 750 mm × 850 mm (arms folded)
Hovering Accuracy Range (with strong GNSS signal)	RTK positioning enabled: ±10 cm horizontal, ±10 cm vertical RTK positioning disabled: ±60 cm horizontal and ±30 cm vertical (radar enabled: ±10 cm)
RTK/GNSS Operating Frequency	RTK: GPS L1/L2, GLONASS F1/F2, BeiDou B1/B2, Galileo E1/E5 GNSS: GPS L1, GLONASS F1, Galileo E1, BeiDou B1
Hovering Time ^[2]	Hovering without payload: 18 min (@30000 mAh & takeoff weight 50 kg) Hovering and spraying with full payload: 7 min (@30000 mAh & takeoff weight 90 kg) Hovering and speading with full payload: 6 min (@30000 mAh & takeoff weight 101 kg)
Max flight radius can be set	2000 m
Max Wind Resistance	6 m/s

Propulsion System - Motor

Stator Size	100×33 mm
Motor KV Value	48 RPM/V
Motor Power	4000 W/rotor

Propulsion System - Propeller

Diameter	54 inch
Rotor Quantity	8

Dual Atomized Spraying System - Operation Box

Operation Box Capacity	Full load 40 L
Operating Payload	Full load 40 kg ^[1]

Dual Atomized Spraying System - Sprinkler

Sprinkler Model	LX8060SZ
Sprinkler Quantity	2
Droplet Size	50-500 μm
Max Effective Spray Width ^[3]	11 m (relative operating altitude 2.5 m, flight speed 7 m/s)

Dual Atomized Spraying System - Water Pump

Pump Model	Magnetic Drive Impeller Pump
Max Flow Rate	6 L/min*2

DJI AGRAS T40 Spreading System

Applicable Materials	Solid dry particles with a diameter of 0.5 to 5 mm ^[9]
Spread Tank Volume	70 L
Spread Tank Internal Load	50 kg ^[1]
Spread Width of Spreading System ^[4]	7 m
Recommended Operating Temperature	0°C to 40°C (32°F to 104°F)

Active Phased Array Omnidirectional Radar

Model Number	RD2484R
Terrain Follow	Max incline: 30°
Obstacle Avoidance ^[5]	Sensible distance (horizontal): 1.5-50 m FOV: 360° horizontal, ±45° vertical Operating conditions: Flying higher than 1.5 m over the obstacle at a speed not exceeding 7 m/s Safe distance: 2.5 m (distance between the propeller tip and obstacle when the aircraft is hovering after braking) Sensing direction: horizontal omnidirectional avoidance; Sensible distance (above): 1.5-30 m FOV: 45° Operating conditions: Available during takeoff, landing, and ascending when an obstacle is more than 1.5 m above the aircraft Safe distance: 2.5 m (distance between the top of the aircraft and the obstacle when the aircraft is hovering after braking)

	braking) Sensing direction: Upward
--	---------------------------------------

Active Phased Array Backward and Downward Radar

Model Number	RD2484B
Altitude Detection ^[5]	Within the altitude detection range: 1-45 m Fixed altitude range: 1.5-30 m
Rear Obstacle Avoidance ^[5]	Sensible distance (rear): 1.5-30 m FOV: ±60° horizontal, ±25° vertical Operating conditions: Available during takeoff, landing, and ascending when an obstacle is more than 1.5 m b aircraft and the flight speed does not exceed 7 m/s Safe distance: 2.5 m (distance between the propeller tip and obstacle when the aircraft is hovering after brakir Sensing direction: backward

Binocular Vision System

Measurable Range	0.4-25 m
Effective Sensing Speed	≤7 m/s
FOV	Horizontal: 90°; Vertical: 106°
Work Environment Requirements	Normal lighting with clearly textured surfaces

Intelligent Remote Controller

O3 Pro Operating Frequency ^[6]	2.4000 to 2.4835 GHz 5.725 to 5.850 GHz
O3 Pro Signal Effective Distance	SRRC: 5 km MIC/KCC/CE: 4 km FCC: 7 km (aircraft altitude at 2.5 m in an unobstructed environment with no interference)
Wi-Fi Protocol	WIFI 6
Wi-Fi Operating Frequency ^[6]	2.4000 to 2.4835 GHz 5.150 to 5.250 GHz 5.725 to 5.850 GHz
Bluetooth Protocol	Bluetooth 5.1
Bluetooth Operating Frequency	2.4000-2.4835 GHz
Location	GPS + Galileo + BeiDou
Display Screens	7.02-inch touch LCD with 1920*1200 resolution and 1200cd/m brightness ²
Supported Aircraft	AGRAS T40, AGRAS T20P
Operating temperature	-20°C to 50°C (-4°F to 122°F)

Storage Temperature Range	-30°C to 45°C (within one month) -30°C to 35°C (between one month and three months) -30°C to 30°C (between three months and one year)
Charging Temperature	5° to 40°C (41° to 104°F)
Internal Battery Life	3.3 hours
External Battery Life	2.7 hours
Charging Type	Use a USB-C charger with a maximum rated power and voltage of 65 W and 20 V. The DJI Portable Charger is recommended.
Charging Time	Two hours for both internal and internal plus external batteries (to use the official charging method when the off)

DJI AGRAS T40 Intelligent Flight Battery

Model	BAX601-30000mAh-52.22V
Weight	Approx. 12 kg
Capacity	30000 mAh
Voltage	52.22 V

D12000iE Multifunctional Inverter Generator

Output Channel	1.DC charging output 42-59.92V/9000W 2.Power supply for air-cooled heat sink 12 V/6 A 3.AC output 230V/1500W or 120V/750W [7].
Battery Charging Time	To fully charge one battery (T40 battery) takes 9-12 mins
Fuel Tank Capacity	30 L
Starting Method	Starting the Generator via the One-Button Start Switch
Max Power of Engine	12000 W
Fuel Type	Unleaded gasoline with RON ≥91 (AKI ≥87) and alcohol content less than 10% (*Brazil: unleaded gasoline with RON ≥ 91 and alcohol content of 27%)
Reference Fuel Consumption [8]	500 ml/kWh
Engine Oil Model	SJ 10W-40

Definition

	[1] Data was measured at sea level. The payload weight is greatly affected by the ambient temperature and alt The payload weight needs to be reduced by 10 kg for every 1,000m increase in altitude. The DJI Agras app will recommend the payload weight according to the current status and surroundings of the aircraft. When adding materials, the maximum weight should not exceed the recommended value, otherwise flight safety may be compromised. [2] Hovering time measured at sea level with a wind speed lower than 3 m/s and ambient temperature of 25°C
--	--

- the battery power fell from 100% to 0%. The data is for reference only. The actual environment may differ from testing environment. The figure listed is for reference only.

[3] The spray width of the spraying system depends on the operating scenario.

[4] The spread width of the spreading system depends on the operating scenario.

[5] The effective sensing range varies depending on the material, position, shape, and other properties of the

[6] In some countries, the 5.1 and 5.8GHz frequencies are prohibited, or the 5.1GHz frequency is only allowed indoor use. Please refer to local laws and regulations.

[7] The actual power and voltage may vary according to local regulations

[8] Measured using RON 92 gasoline at near sea level with an ambient temperature of 25°C, while charging at

[9] Avoid spreading sharp, hard particles

The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI Trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.



Others

Guaranteed software updates until	2026/12/31
-----------------------------------	------------

Only in the DJI Store App

Try Virtual Flight online for free, and enjoy convenient one-stop device services.

Download App

Product Categories

Consumer

Professional

Enterprise

Components

Service Plans

DJI Care Refresh

DJI Care Pro

DJI Care Enterprise

DJI Maintenance Program

Where to Buy

DJI Online Store

Flagship Stores

DJI-Operated Stores

Retail Stores

Enterprise Retailers

Agricultural Drone Dealer

Delivery Drone Dealer

Pro Retailers

DJI Store App

Cooperation

Become a Dealer

Apply For Authorized Store

Fly Safe

Fly Safe

DJI Flying Tips

Support

Product Support

Service Request and Inquiry

Help Center

After-Sales Service Policies

Download Center

Security and Privacy

Explore

Media Center

Buying Guides

DJI Trust Center

DJI Blog

Trending Now

Phone Gimbals

Action Cameras

Wireless Microphones

Portable Power Stations

Vlog Cameras

Community

SkyPixel

DJI Forum

Developer

Subscribe

Get the latest news from

Your email address

DJI Logo

Who We Are

Contact Us

Careers

Dealer Portal

RoboMaster

DJI Privacy Policy

Use of Cookies

Terms of Use

Business Information

Accessibility

Do Not Sell Or Share My Personal Information

Cookie Preferences

Copyright © 2026 DJI All Rights Reserved.

Feedback on web experience