



Hough Transform Generalizations

- It locates straight lines (SHT) - standard, simple HT
- It locates straight line intervals
- It locates circles
- It locates algebraic curves
- It locates arbitrary specific shapes in an image
 - **But you pay progressively for complexity of shapes by time and memory usage**




Harris corner detector


- C.Harris, M.Stephens. “A Combined Corner and Edge Detector”. 1988




Harris Detector: Basic Idea



“flat” region:
no change in
all directions




“edge”:
no change along
the edge direction




“corner”:
significant
change in all
directions

Harris Detector: Mathematics

Change of intensity for the shift $[u, v]$:




Window function $w(x, y) =$




1 in window, 0 outside

or



Gaussian

Harris Detector: Mathematics



Harris Detector: Mathematics



For small shifts $[u, v]$ we have a *bilinear* approximation:




where M is a 2×2 matrix computed from image derivatives:




Harris Detector: Mathematics

Classification of
image points using
eigenvalues of M :



Harris Detector: Mathematics

Measure of corner response:




(k – empirical constant, $k = 0.04-0.06$)

Harris Detector: Mathematics



- R depends only on eigenvalues of M
- R is large for a **corner**
- R is negative with large magnitude for an **edge**
- $|R|$ is small for a **flat** region



Harris Detector

- The Algorithm:
 - Find points with large corner response function R ($R > \text{threshold}$)
 - Take the points of local maxima of R


Harris Detector: Workflow



- Smooth image first !
 - Detection involves 1st and 2nd derivatives
 - Smoothing reduces effect of noise on the gradient maps

Harris Detector: Workflow

Compute corner response R



Harris Detector: Workflow

Find points with large corner response: $R > \text{threshold}$



Harris Detector: Workflow

Take only the points of local maxima of R



Harris Detector: Workflow



Harris Detector: Summary

- Average intensity change in direction $[u, v]$ can be expressed as a bilinear form:




- Describe a point in terms of eigenvalues of M :
measure of corner response



- A good (corner) point should have a *large intensity change in all directions*, i.e. R should be large positive

Harris Detector: Some Properties

- Rotation invariance



Ellipse rotates but its shape (i.e. eigenvalues) remains the same



Corner response R is invariant to image rotation

Harris Detector: Some Properties

- Partial invariance to *affine intensity* change

✓ Only derivatives are used \Rightarrow invariance to intensity shift $I \rightarrow I + b$

✓ Intensity scale: $I \rightarrow a I$




Application: Finding corresponding points



Harris Detector: Some Properties

- But: non-invariant to *image scale*!



All points will be
classified as *edges*



Corner !

Digital Image Processing (CSE/ECE 478)

Lecture-18: Image Segmentation (contd.)

Ravi Kiran

Sudipta Banerjee

Center for Visual Information Technology (CVIT), IIIT Hyderabad



Many slides borrowed from Vineet Gandhi @CVIT!

Image Segmentation



Partitioning an image into a collection of connected sets of pixels.

1. into **regions**, which usually cover the image



2. into **linear structures**, such as

- line segments
- curve segments



3. into **2D shapes**, such as

- circles
- ellipses
- ribbons (long, symmetric regions)





Image Segmentation


Partitioning an image into a collection of connected sets of pixels.

1. into **regions**, which usually cover the image





2. into linear structures, such as

- line segments
- curve segments



3. into 2D shapes, such as


- circles
- ellipses
- ribbons (long, symmetric regions)



Region Segmentation: Segmentation Criteria

A segmentation is a partition of an image I into a set of regions S satisfying:

1. $\cup S_i = S$ Partition covers the whole image.
2. $S_i \cap S_j = \phi, i \neq j$ No regions intersect.
3. $\forall S_i, P(S_i) = \text{true}$ Homogeneity predicate
4. $P(S_i \cup S_j) = \text{false},$
 $i \neq j, S_i \text{ adjacent } S_j$ Union of adjacent regions
does not satisfy homogeneity.



Segmentation: Thresholding based approaches

Two class Segmentation: Motivating example

- Separate pixels associated with object of interest from background

Two damning reports linking the Philippine military to a wave of political killings have left President Gloria Arroyo with a major challenge, analysts say — how to discipline the very people who have ensured her political survival.

The reports, one by a special U.N. envoy and the other by an independent commission of inquiry set up by Arroyo herself, have implicated the country's military in hundreds of political assassina-

wrote "We Men in P cracy," a military "weakens leaves in p In the w political ki dled the 6 the killing armed for a vanguard Meanwhile closed ran

Two damning reports linking the Philippine military to a wave of political killings have left President Gloria Arroyo with a major challenge, analysts say — how to discipline the very people who have ensured her political survival.

The reports, one by a special U.N. envoy and the other by an independent commission of inquiry set up by Arroyo herself, have implicated the country's military in hundreds of political assassina-

wrote "We Men in P cracy," s military "weakens leaves in p In the w political ki dled the 6 the killing armed for a vanguard Meanwhile closed ran

Thresholding

- Separate pixels associated with object of interest from background
- Given a image $f(x,y)$, the segmented image $g(x,y)$ is given by:

$$g(x, y) = \begin{cases} 1 & \text{if } f(x, y) > T \\ 0 & \text{if } f(x, y) \leq T \end{cases}$$


If T is constant over the entire image \rightarrow Global Thresholding

If T changes over the image \rightarrow Variable Thresholding

The main question is: **How to find T ?**

Thresholding

- How to find T ?
- One Idea is to explore the intensity histograms (if there is clear separation)




a b

FIGURE 10.35

Intensity histograms that can be partitioned (a) by a single threshold, and (b) by dual thresholds.

a	b	c
d	e	f

FIGURE 10.36 (a) Noiseless 8-bit image. (b) Image with additive Gaussian noise of mean deviation of 10 intensity levels. (c) Image with additive Gaussian noise of mean 0 and standard deviation of 50 intensity levels. (d)–(f) Corresponding histograms.







FIGURE 10.37 (a) Noisy image. (b) Intensity ramp in the range $[0.2, 0.6]$. (c) Product of (a) and (b). (d)–(f) Corresponding histograms.

Choosing a threshold is something of a “black art”:

```
n=imread('nodules1.jpg');  
figure(1); imshow(n);  
n1=im2bw(n,0.35);  
n2=im2bw(n,0.75);  
figure(2), imshow(n1);  
figure(3), imshow(n2);
```



Finding T: Basic Global Thresholding

Iterative approach

1. Select an initial estimate of global threshold T
2. Segment the image using T
 - This will produce two groups of pixels ($G1$ and $G2$)
3. Compute the average (mean) intensity values $m1$ and $m2$ for the pixels in $G1$ and $G2$ respectively
4. Compute a new threshold value $T_{\text{new}} = (m1+m2)/2$
5. If $|T_{\text{new}} - T| < \text{eps}$, stop.
6. Else, set $T = T_{\text{new}}$. Go to Step 2.

Finding T: Basic Global Thresholding

Iterative approach


1. Select an initial estimate of global threshold T
2. Segment the image using T
 - This will produce two groups of pixels ($G1$ and $G2$)
3. Compute the average (mean) intensity values $m1$ and $m2$ for the pixels in $G1$ and $G2$ respectively
4. Compute a new threshold value $T_{\text{new}} = (m1+m2)/2$
5. If $|T_{\text{new}} - T| < \text{eps}$, stop.
6. Else, set $T = T_{\text{new}}$. Go to Step 2.

Matlab function: `opthr`

a b c









FIGURE 10.38 (a) Noisy fingerprint. (b) Histogram. (c) Segmented result using a global threshold was added for clarity). (Original courtesy of the National Institute of Standards and Technology)



Global Thresholding

T is usually located at the valley/ one of the valleys





- No valleys
- BG intensity close to ROI (region-of-interest) intensity



Global Thresholding: Otsu's Method

- Based on histograms
- Automatically finds the optimal threshold maximizing the between class variance
- Proposed in 1975
- Preliminaries:
 - What is the formula for mean and variance of intensities in an image ?
 - What does variance measure ?
 - A probabilistic / normalized-histogram perspective for mean, variance

- Variance = A measure of region homogeneity
- Regions with high homogeneity will have a low variance.

Otsu's algorithm: Find the threshold that minimizes intra-class variance.

1. Consider all possible thresholds T
2. For each threshold t in T
 1. Compute the variance for Class-1 pixels (intensities $< t$)
 2. Compute the variance for Class-2 pixels (intensities $\geq t$)

Intra-class variance \rightarrow

$$\sigma_f^2(t) = \omega_1(t)\sigma_1^2(t) + \omega_2(t)\sigma_2^2(t)$$

191

255

Class-1 probability (fraction of pixels whose intensity $< t$)

- Variance = A measure of region homogeneity
- Regions with high homogeneity will have a low variance.

Otsu's algorithm: Find the threshold that minimizes intra-class variance.

1. Consider all possible thresholds T
2. For each threshold t in T
 1. Compute the variance for Class-1 pixels (intensities $< t$)
 2. Compute the variance for Class-2 pixels (intensities $\geq t$)

Intra-class variance \rightarrow

$$\sigma_f^2(t) = \omega_1(t)\sigma_1^2(t) + \omega_2(t)\sigma_2^2(t)$$

191

255



Otsu's Method

- Compute the normalized histogram of the input image.
- Denote the components of the histogram by p_i , $i = 0, 1, 2, 3, \dots, L - 1$
- Suppose a threshold is selected k , $0 < k < L - 1$
- C_1 is the set of pixels with levels $[0, 1, 2, 3, \dots, k]$
- C_2 is the set of pixels with levels $[k + 1, k + 2, k + 3, \dots, L - 1]$
- Obtain the value of threshold which **maximizes** the between class variance

$$\sigma_B^2(k) = P_1(k) (m_1(k) - m_G)^2 + P_2(k) (m_2(k) - m_G)^2$$

Otsu's Method

$$\sigma_B^2(k) = P_1(k) (m_1(k) - m_G)^2 + P_2(k) (m_2(k) - m_G)^2$$

- $P_1(k)$ is probability of C_1 occurring

$$P_1(k) = \sum_{i=0}^k p_i, k = 0, 1, 2, \dots, k$$

$$P_2(k) = \sum_{i=k+1}^{L-1} p_i = 1 - P_1(k), k = 0, 1, 2, \dots, k$$

- $m_1(k)$ and $m_2(k)$ are means of C_1 and C_2

$$m_1(k) = \frac{\sum_{i=0}^k i p_i}{P_1(k)} \quad m_2(k) = \frac{\sum_{i=k+1}^{L-1} i p_i}{P_2(k)}$$

Otsu's Method

$$\sigma_B^2(k) = P_1(k) (m_1(k) - m_G)^2 + P_2(k) (m_2(k) - m_G)^2$$

$$\sigma_B^2(k^*) = \max_{0 \leq k \leq L-1} \sigma_B^2(k)$$




In simple words, we evaluate all values of k and select the value of k that yielded the maximum $\sigma_B^2(k)$

This idea can be easily extended to compute multiple thresholds!


a	b
c	d






FIGURE 10.39

(a) Original image.
 (b) Histogram (high peaks were clipped to highlight details in the lower values).
 (c) Segmentation result using the basic global algorithm from Section 10.3.2.
 (d) Result obtained using Otsu's method. (Original image courtesy of



Otsu's Method





Otsu's method: Main Limitation

Two damning reports linking the Philippine military to a wave of political killings have left President Gloria Arroyo with a major challenge, analysts say — how to discipline the very people who have ensured her political survival.

The reports, one by a special U.N. envoy and the other by an independent commission of inquiry set up by Arroyo herself, have implicated the country's military in hundreds of political assassina-






wrote "We Men in P cracy," s militaryme "weakens leaves in p In the w political ki dled the b the killing armed for a vanguard Meanwhile closed ran





Two damning reports linking the Philippine military to a wave of political killings have left President Gloria Arroyo with a major challenge, analysts say — how to discipline the very people who have ensured their political survival.


The reports, one by a special U.N. envoy and the other by an independent commission of inquiry set up by Arroyo herself, have implicated the country's military in hundreds of political assassina-

wrote "We Men in P cracy," s militaryme "weakens leaves in p In the w political ki dled the b the killing armed for a vanguard Meanwhile closed ran

Pai et al. PR 2010







ogram. (c) Segmentation of (a) using Otsu's method. (e) Image subimage individually.





FIGURE 10.47
Histograms of the six subimages in Fig. 10.46(e).

Per pixel variable Thresholding

- Compute standard deviation and mean of each pixel (around local neighborhood)
- Let σ_{xy} , m_{xy} denote the standard deviation and mean value contained in neighborhood S_{xy} centred around (x, y)
- Example threshold function:

$$g(x, y) = \begin{cases} 1 & \text{if } f(x, y) > T_{xy} \\ 0 & \text{if } f(x, y) \leq T_{xy} \end{cases}$$

$$T_{xy} = a\sigma_{xy} + bm_{xy} \quad \text{or} \quad T_{xy} = a\sigma_{xy} + bm_G$$

a	b
c	d


FIGURE 10.48

(a) Image from Fig. 10.43.

(b) Image segmented using the dual thresholding approach discussed in Section 10.3.6.

(c) Image of local standard deviations.

(d) Result obtained using local thresholding.



Per pixel: moving average




FIGURE 10.49 (a) Text image corrupted by spot shading. (b) Result of global thresholding using Otsu's method. (c) Result of local thresholding using moving averages.

a b c

FIGURE 10.50 (a) Text image corrupted by sinusoidal shading. (b) Result of global threshold method. (c) Result of local thresholding using moving averages.



Choosing thresholding algorithms

- Based on typical sizes of objects/regions of interest
 - Small → Adaptive/Local
 - Large → Global

Thresholding: Summary

- Many methods

- Survey

Sezgin, M and Sankur, B (2004), "Survey over Image Thresholding Techniques and Quantitative Performance Evaluation", Journal of Electronic Imaging 13(1): 146-165

- Comparison

http://www.fmwconcepts.com/imagemagick/threshold_comparison/index.php