

About

kickoff is a Command-Line tool, which can be used to easily create boilerplate code for new projects and other things based on archetypes stored in GitHub repos.

You can do the following things with kickoff:

1. Install kickoff in global mode.
2. Create the repository on github for the project template, including mustache templates.
3. Place the `.kickoff.yml` file, to define the questionnaire for collecting parameter values for template files.

In order to learn more about how to install and use the tool, read the [Get Started](#) page, then continue with reading the [documentation](#).

Get Started

Installation

Prerequisites:

kickoff needs [Node.js](#) and [NPM](#) installed on the machine, before start installing and using it.

Installation steps

The kickoff tool can be installed as any other node module, but you have to install to the global node_modules folder, so use the -g switch to npm.

To install kickoff, execute the following command:

```
$ npm install -g kickoff
```

To check, whether kickoff is installed successfully, run the following command:

```
$ kickoff -V
```

Usage of the kickoff utility

Check if kickoff is properly installed:

```
$ kickoff -h
```

```
Usage: kickoff [options]
```

```
Options:
```

-h, --help	output usage information
-V, --version	output the version number
-v, --verbose	Verbose mode
-a, --data-file <path>	Path to the yaml format datafile
-f, --folder <path>	Path to the source directory
-s, --src <username/repository>	Git repository
-d, --dest <dst>	Destination folder

Create your first project from a repository

The following command will create a new command line tool project with all the required boilerplate code, unsing the [ncli-archetype](#) repository:

```
$ kickoff -s tombenke/nccli-archetype -d new_app
? The name of the application: new_app
? The full name of the author of the application: Tamás Benke
? The email address of the author: tombenke@gmail.com
? The github account (username) of the author: tombenke
```

Check the results in the newly created new_app directory, and see also how the parameters requested through the console have substituted the mustache parameters in README.md and package.json files.

In order to learn more about how to use the tool, read the [documentation](#) pages.

Documentation

Installation

The prerequisites and installation of the tool is described in the [Get Started](#) page.

Create the template repository

This is a normal repository, which can contain anything, including mustache templates. These files will be copied to the destination folder without modification. During this transfer, each file is processed by the mustache template engine, so you can place parameters into these files, which will be replaced by actual values, that you can define through the command line interface of the tool.

The enquiry for these parameters can be described in the `.kickoff.yml` file, that you can place into the root of the repository.

© 2017 Tamás Benke. All rights reserved. MIT License. [View License](#)

See [ncli-archetype](#) repository on GitHub, that is a Project archetype for Command Line tools using Node.js.

The .kickoff.yml file

You can describe the questionnaire for template parameters within the .kickoff.yml file.

This is a sample configuration file for the kickoff utility:

```
description: |
  This is a project archetype for node.js based, cli applications.
  New projects can be generated from this archetype by the
  [kickoff](https://github.com/tombenke/kickoff) utility.

welcome: >

  You are generating a JavaScript project, which is
  using node.js, and running as a command-line application.

postscript: >

  Next steps:

  - Install the npm modules required by the newly generated application:

    cd <dest-folder>
    npm install

questions:
-
  type: input
  name: appname
  message: The name of the application
  default: anonymous
-
  type: input
  name: author_full_name
  message: The full name of the author of the application
  default: Anonymous
-
  type: input
  name: author_email
  message: The email address of the author
  default: anonymous@some-domain.com
-
  type: input
  name: author_github_account
  message: The github account (username) of the author
  default: anonymous
```

You can add as many parameters as you need, using the same names you put into the mustache templates.

Load the context data from YAML file instead of querying

Let's suppose, you create a new_app executing the following command:

```
$ kickoff -s tombenke/ncli-archetype -d new_app
? The name of the application: new_app
? The full name of the author of the application: Tamás Benke
? The email address of the author: tombenke@gmail.com
? The github account (username) of the author: tombenke
```

You can achieve the same result, if you create a YAML file (for example: desc.yml), with the following content:

```
appname: new_app
author_full_name: Tamás Benke
author_email: tombenke@gmail.com
author_github_account: tombenke
```

With the -a, --data-file argument, you can load the context data in the YAML format file instead of using the interactive inquiry via the console, so execute the next command:

```
$ kickoff -a ncli.yml -s tombenke/ncli-archetype -d new_app
```

The result will be something similar to this:

You are generating a JavaScript project, which is using node.js, and running as a command-line application.

Loading data from ncli.yml instead of querying...

Next steps:

```
- Install the npm modules required by the newly generated application:

  cd <dest-folder>
  npm install
```

This method can be used, if the volume of the context data is big, and/or it has a complex structure (nested arrays and objects, etc.).

Get Help

Find answers and ask questions on the following StackOverflow tag <http://stackoverflow.com/questions/tagged/kickoff> or email me anytime at tombenke@gmail.com if you need any assistance or have feedback.

you run into problems or have feedback.