

EVIDENCIAS

1.- Verificar el estado del Cluster

```
kubectl --kubeconfig ~/.kube/config cluster-info
Kubernetes control plane is running at https://127.0.0.1:6443
CoreDNS is running at https://127.0.0.1:6443/api/v1/namespaces/kube-system/services/kube-dns:dns/proxy

To further debug and diagnose cluster problems, use 'kubectl cluster-info dump'.
```

2.- Listado de Nodos del Clúster

```
kubectl --kubeconfig ~/.kube/config get nodes
```

NAME	STATUS	ROLES	AGE	VERSION
docker-desktop	Ready	control-plane	21d	v1.34.1

3.- Obtener los Pods de la aplicación

```
kubectl --kubeconfig ~/.kube/config get pods -n ns-rodrigo-videla
```

NAME	READY	STATUS	RESTARTS	AGE
app-rodrigo-videla-75bd96cd76-7trhh	1/1	Running	0	6h53m
app-rodrigo-videla-75bd96cd76-txlr9	1/1	Running	0	6h53m

4.- Obtener el Deployment

```
kubectl --kubeconfig ~/.kube/config get deployment -n ns-rodrigo-videla
```

NAME	READY	UP-TO-DATE	AVAILABLE	AGE
app-rodrigo-videla	2/2	2	2	7h22m

5.- Obtener el Servicio

```
kubectl --kubeconfig ~/.kube/config get svc -n ns-rodrigo-videla
```

NAME	TYPE	CLUSTER-IP	EXTERNAL-IP	PORT(S)	AGE
svc-rodrigo-videla	ClusterIP	10.101.209.127	<none>	80/TCP	7h23m

6.- Ver los Logs de la aplicación NestJS

```
kubectl --kubeconfig ~/.kube/config logs deployment/app-rodrigo-videla -n ns-rodrigo-videla
Found 2 pods, using pod/app-rodrigo-videla-75bd96cd76-txlr9
[Nest] 1 - 06/04/2026, 2:26:12 PM LOG [NestFactory] Starting Nest application...
[Nest] 1 - 06/04/2026, 2:26:12 PM LOG [InstanceLoader] AppModule dependencies initialized +5ms
[Nest] 1 - 06/04/2026, 2:26:12 PM LOG [RoutesResolver] AppController {/}: +2ms
[Nest] 1 - 06/04/2026, 2:26:12 PM LOG [RouterExplorer] Mapped {/, GET} route +1ms
[Nest] 1 - 06/04/2026, 2:26:12 PM LOG [RouterExplorer] Mapped {/lab, GET} route +1ms
[Nest] 1 - 06/04/2026, 2:26:12 PM LOG [NestApplication] Nest application successfully started +1ms
```

7.- Inspeccionar las Variables de Entorno dentro del Pod en ejecución

```
kubectl --kubeconfig ~/.kube/config exec deployment/app-rodrigo-videla -n ns-rodrigo-videla -- printenv
PATH=/usr/local/sbin:/usr/local/bin:/usr/sbin:/usr/bin:/sbin:/bin
HOSTNAME=app-rodrigo-videla-75bd96cd76-txlr9
AMBIENTE=produccion-laboratorio
API_KEY=mi-super-clave-secreta
SVC_RODRIGO_VIDELA_PORT_80_TCP=tcp://10.101.209.127:80
SVC_RODRIGO_VIDELA_PORT_80_TCP_PROTO=tcp
KUBERNETES_PORT=tcp://10.96.0.1:443
KUBERNETES_PORT_443_TCP_PROTO=tcp
KUBERNETES_PORT_443_TCP_ADDR=10.96.0.1
SVC_RODRIGO_VIDELA_SERVICE_HOST=10.101.209.127
SVC_RODRIGO_VIDELA_PORT_80_TCP_PORT=80
SVC_RODRIGO_VIDELA_PORT_80_TCP_ADDR=10.101.209.127
KUBERNETES_SERVICE_HOST=10.96.0.1
KUBERNETES_SERVICE_PORT_HTTPS=443
KUBERNETES_PORT_443_TCP=tcp://10.96.0.1:443
SVC_RODRIGO_VIDELA_SERVICE_PORT=80
SVC_RODRIGO_VIDELA_PORT=tcp://10.101.209.127:80
KUBERNETES_SERVICE_PORT=443
KUBERNETES_PORT_443_TCP_PORT=443
NODE_VERSION=22.22.3
YARN_VERSION=1.22.22
PORT=3000
HOME=/root
```

8.- Obtener el ConfigMap

```
kubectl --kubeconfig ~/.kube/config get configmap config-rodrigo-videla -n ns-rodrigo-videla
NAME          DATA  AGE
config-rodrigo-videla  1      7h25m
```

9.- Obtener el Secreto

```
kubectl --kubeconfig ~/.kube/config get secret secret-rodrigo-videla -n ns-rodrigo-videla
NAME          TYPE      DATA  AGE
secret-rodrigo-videla  Opaque    1      7h26m
```

9.- Pruebas de la aplicación

```
kubectl --kubeconfig ~/.kube/config port-forward svc/svc-rodrigo-videla 8085:80 -n ns-rodrigo-videla
Forwarding from 127.0.0.1:8085 -> 3000
Forwarding from [::1]:8085 -> 3000
Handling connection for 8085
```

```
curl http://localhost:8085/lab
{"AMBIENTE":"produccion-laboratorio","API_KEY":"mi-super-clave-secreta"}%
```

10.- Historial de ejecuciones en Jenkins Stage View y confirmación de despliegue exitoso (Build #15)

