

Bywaf Usage Guide

Overview

Bywaf is a Python 3 commandlet framework for authorized web application and network testing workflows. It presents a Metasploit-like interactive shell, loads commandlets from plugins, and connects commandlets through a SQLite-backed event bus.

The core idea is simple: one commandlet discovers something and publishes it as an event; another commandlet consumes that event and publishes the next result. For example, hostscanner can publish live hosts, portscanner can consume those hosts and publish open ports, and HTTP commandlets can consume open ports and probe web services.

Use Bywaf only on systems and networks where you have explicit authorization.

Installation

During development, run Bywaf from the repository root:

```
cd bywaf
python3 -m bywaf --help
python3 -m bywaf repl
```

For an editable local install:

```
python3 -m pip install -e .
bywaf --help
bywaf repl
```

The project metadata defines a console script named bywaf, so packaged installations can expose Bywaf as a normal command instead of requiring `python3 -m bywaf`.

The host and port scanner commandlets use nmap through a Python adapter. A local nmap binary is required for real scans. The adapter prefers nmaplib, then python-nmap, then nmapthor, then libnmap.

Starting Bywaf

Start the interactive shell:

```
bywaf
```

or, from a source checkout:

```
python3 -m bywaf
```

Run one command non-interactively:

```
bywaf run ls
bywaf run cat README.md
bywaf run 'hostscanner 127.0.0.1 | portscanner'
```

Simple run commands do not need quotes. Use quotes when the command contains shell metacharacters such as `|`, `&`, `>`, or spaces that must be preserved inside a single argument.

REPL Basics

The REPL prompt is:

```
bywaf>
```

Commandlets can be run directly:

```
bywaf> ls
bywaf> cat README.md
bywaf> hostscanner 127.0.0.1
```

Built-in commands manage the shell and the event database:

```
help
help <command>
plugins
cmds
vars
history
jobs
runs
topics
show <topic|job=id|run=id|pipeline=id>
load <resource>
save <resource>
exit
```

help <command> shows the same help as <command> --help for commandlets.

Commandlets

A commandlet is an executable unit exposed by a plugin. Each commandlet declares its name, description, arguments, consumed topics, and emitted topics.

Examples:

```
bywaf> help hostscanner
bywaf> hostscanner --help
bywaf> portscanner --help
```

Many scanning commandlets support -s or --silent to suppress console alerts. Without silent mode, commandlets print discovery alerts such as:

```
hostscanner <hostscanner-...>: discovered host 127.0.0.1
portscanner <portscanner-...>: discovered port 127.0.0.1:80/tcp
```

Plugins

A plugin provider groups related commandlets. The plugins command lists loaded providers:

```
bywaf> plugins
discovery
http
network
os
```

The cmds command lists commandlets grouped by provider:

```
bywaf> cmds
discovery
  hostscanner
http
  http_headers
  http_probe
network
```

```
portscanner
os
cat
less
ls
```

Bundled plugins are listed in `bywaf/plugins/plugins.json`. Adding a plugin file is not enough to load it by default; add its dotted path to that config.

Load an additional plugin by name from `.bywaf/plugins`:

```
bywaf> load plugin=myplugin
```

Load a plugin from an explicit filesystem path:

```
bywaf> load plugin=./plugins/myplugin
bywaf> load plugin=~/.bywaf-plugins/myplugin
```

Pipelines

Pipelines connect commandlets with `|`:

```
bywaf> hostscanner 127.0.0.1 | portscanner
```

The runner executes each stage in order. Events emitted by one stage are passed to the next stage as input. Events are also stored in SQLite with a pipeline ID and command run ID.

This model allows downstream commandlets to consume only the output relevant to the current pipeline, rather than every historical event in the database.

Background Execution

Append `&` to background a commandlet or pipeline:

```
bywaf> hostscanner 192.168.0.1-255 &
```

Stage-level backgrounding works inside pipelines:

```
bywaf> hostscanner 192.168.0.1-255 & | portscanner &
```

In that example, `portscanner` listens for `host.found` rows created by the immediately upstream `hostscanner` run in the same pipeline. It does not consume unrelated `host.found` rows from older scans.

List jobs:

```
bywaf> jobs
```

Show one job:

```
bywaf> show job=<id>
```

Database and Event Model

Bywaf stores events in SQLite. The default database is:

```
.bywaf/bywaf.sqlite3
```

SQLite is used in WAL mode. Inserts are committed immediately; there is no separate document-style save step. On shutdown, Bywaf checkpoints the WAL using `PRAGMA wal_checkpoint(TRUNCATE)` so WAL contents are folded back into the main database file.

List known event topics:

```
bywaf> topics
```

Show recent events for a topic:

```
bywaf> show host.found
```

```
bywaf> show port.open
```

List command runs:

```
bywaf> runs
```

Show events by command run or pipeline:

```
bywaf> show run=<command-run-id>
```

```
bywaf> show pipeline=<pipeline-id>
```

Save a database snapshot:

```
bywaf> save db=snapshot.sqlite3
```

Switch to another database:

```
bywaf> load db=snapshot.sqlite3
```

Resource Files

Bywaf keeps default state in:

```
.bywaf/
```

Important files:

```
.bywaf/bywaf.sqlite3
```

```
.bywaf/config.json
```

```
.bywaf/history.bywaf
```

```
.bywaf/plugins/
```

Resource resolution rules are consistent:

```
plugin=<name> -> .bywaf/plugins/<name>
```

```
script=<name> -> ./<name>
```

```
db=<name> -> ./<name>
```

```
config=<name> -> ./<name>
```

```
history=<name> -> ./<name>
```

Explicit paths are used as filesystem paths for every resource type:

```
./name
```

```
../name
```

```
~/name
```

```
/absolute/name
```

Examples:

```
bywaf> load script=scan.bywaf
```

```
bywaf> load script=./scripts/scan.bywaf
```

```
bywaf> save config=session.json
```

```
bywaf> load config=session.json
```

```
bywaf> save history=session-history.bywaf
```

```
bywaf> load history=session-history.bywaf
```

Variables

List variables:

```
bywaf> vars
```

Set a variable:

```
bywaf> vars name=value
```

Common examples:

```
bywaf> vars http_probe.cookie-file=/tmp/cookies.txt  
bywaf> vars history.timestamp-format=%Y-%m-%d %H:%M:%S %Z
```

Save variables:

```
bywaf> save config=config.json
```

Load variables:

```
bywaf> load config=config.json
```

Config files are JSON objects containing session variables.

History

Every non-empty REPL command is appended to:

```
.bywaf/history.bywaf
```

History lines are stored as commands followed by a timestamp comment:

```
hostscanner 127.0.0.1 # 2026-05-12 10:15:30 EDT
```

The history command shows only commands from the current REPL invocation:

```
bywaf> history
```

The persistent history file can be viewed with the OS commandlets:

```
bywaf> cat .bywaf/history.bywaf  
bywaf> less .bywaf/history.bywaf
```

Because timestamps are comments, history lines can be copied into a script file.

Change the timestamp format:

```
bywaf> vars history.timestamp-format=%Y/%m/%d %H:%M:%S %Z
```

Scripts

Scripts are text files with one command expression per line:

```
# scan local host  
hostscanner 127.0.0.1  
portscanner --from-topic host.found
```

Blank lines and lines beginning with # are ignored. Inline comments are also allowed after whitespace:

```
plugins # list loaded plugin providers
```

Run a script:

```
bywaf> load script=scan.bywaf
```

Bundled Commandlets

os

ls lists local files:

```
bywaf> ls
bywaf> ls bywaf/plugins
```

cat prints a local text file:

```
bywaf> cat README.md
```

less opens the system less pager when running interactively:

```
bywaf> less README.md
```

Use / to search inside less, arrow keys or paging keys to scroll, and q to quit.

discovery

hostscanner discovers live hosts with nmap:

```
bywaf> hostscanner 127.0.0.1
bywaf> hostscanner 192.168.0.1-255
bywaf> hostscanner 192.168.1-3.1-255
```

It emits host.found events.

network

portscanner scans hosts for open ports:

```
bywaf> portscanner 127.0.0.1
bywaf> portscanner --ports 22,80,443 127.0.0.1
```

If --ports is omitted, nmap uses its normal default top-port behavior. It emits port.open events.

Use listen mode to consume newly inserted hosts:

```
bywaf> portscanner --listen
```

http

http_headers performs HTTP HEAD requests and emits http.headers events:

```
bywaf> http_headers example.com
bywaf> http_headers --ssl true example.com
```

http_probe probes HTTP endpoints and emits http.endpoint events:

```
bywaf> http_probe https://example.com/
```

For authorized session-aware testing, it can use cookies:

```
bywaf> vars http_probe.cookie-file=/path/to/cookies.txt
```

```
bywaf> http_probe https://example.com/  
bywaf> http_probe --firefox-profile ~/.mozilla/firefox/<profile>
```

Common Workflows

Scan one host for live status:

```
bywaf> hostscanner 127.0.0.1
```

Scan one host for ports:

```
bywaf> portscanner 127.0.0.1
```

Discover hosts and scan their ports:

```
bywaf> hostscanner 192.168.0.1-255 | portscanner
```

Run discovery and port scanning in the background:

```
bywaf> hostscanner 192.168.0.1-255 & | portscanner &
```

Probe HTTP services after port scanning:

```
bywaf> hostscanner 127.0.0.1 | portscanner --ports 80,443 | http_probe
```

Save the current database:

```
bywaf> save db=scan-results.sqlite3
```

Save variables and session history:

```
bywaf> save config=session.json  
bywaf> save history=session.bywaf
```

Troubleshooting

If python is not available, use python3:

```
python3 -m bywaf
```

If scanning fails with an nmap error, verify that nmap is installed and that the selected Python nmap binding is available.

If socket creation is denied, the process may be running inside a sandbox or without the privileges needed by the selected scan type.

If a command is unknown, check loaded commandlets:

```
bywaf> cmds
```

If a plugin does not load, verify its directory structure and that it defines a plugin() factory returning a commandlet.

SQLite WAL files such as .sqlite3-wal and .sqlite3-shm are normal. Bywaf checkpoints the WAL on shutdown.

Developer Notes

The main package layout is:

bywaf/app.py	REPL and built-in commands
bywaf/runner.py	parsing, pipelines, foreground/background execution
bywaf/db.py	SQLite event store

bywaf/plugin.py	commandlet protocol and specs
bywaf/registry.py	plugin discovery and loading
bywaf/completion.py	readline completion
bywaf/plugins/	bundled plugin providers
tests/	unit tests

Run tests:

```
python3 -m unittest discover -s tests
```

Add a commandlet by defining a class with a `CommandSpec` and a `run()` method, then expose it through a `plugin()` factory. Add bundled commandlets to `bywaf/plugins/plugins.json` when they should load by default.

Reference

Useful built-ins:

```
help [command]
plugins
cmds
vars [name=value]
history
jobs
runs
topics
show <topic>
show job=<id>
show run=<id>
show pipeline=<id>
load plugin=<resource>
load script=<resource>
load db=<resource>
load config=<resource>
load history=<resource>
save db=<resource>
save config=<resource>
save history=<resource>
prompt [pattern]
exit
```

Common event topics:

```
host.found
port.open
http.headers
http.endpoint
job.started
job.finished
job.failed
```