

oops, an object oriented practical scribe’s package.*

Erwann Rogard†

Released 2020/04/10

Abstract

`oops` is a package for L^AT_EX (hence “scribe”) for generating macro definitions as the need arises in the document, and to organize them along two dimensions: functions and objects, hence “OO”. This is done using a minimalist interface built upon `xparse`[4]. Specifically, `\Ops<object>` begins a series of instructions alternating between ‘text’ and definitions, that themselves optionally expand using predefined or inline rules. For example,

```
\Ops<Math>[Let~]{Space=\Omega}*[-denote the sample space]{}
```

expands to: “Let Ω denote the sample space”. As a side effect, `\Space<Math>$` encodes “ Ω ”. `Math` being the default for `<object>`, it can be dropped. `DEBUG` Optionally, the definitions can be written to a file, and restored, which can be useful for typesetting documents sharing the same notational conventions. Altogether, “practical”.

Contents

I	Usage	3
1	Convention	3
2	Loading the package	3
3	\Ops	3
3.1	<code><tl₁></code>	3
3.2	<code>[tl₂]</code>	4
3.3	<code>i{code₁}</code>	4
3.4	<code>{kv₁}</code>	4
3.5	<code>+</code>	4
3.6	<code>*</code>	4
3.7	<code>s{tl₃}tl₃tl₄tl₃tl₄tl₅}</code>	4
3.8	<code>o{code₂}</code>	4
3.9	<code>[tl₆]</code>	4
4	\OpsClear	5

*This file describes version v1.4, last revised 2020/04/10.

†firstname dot lastname AusTria gmail dot com

5	\OpsDebug	5
6	\OpsHook	5
7	\OpsOption	5
	7.10 Expans	5
	7.11 Inner	5
	7.12 Name	5
	7.13 Outer	5
	7.14 Separ	5
	7.15 Write	5
8	\OpsRead	5
8	Do's and dont's	5
II	Listing	7
	Listing 1.	7
	Listing 2.	7
	Listing 3.	8
	Listing 4.	8
	Listing 6.	9
	Listing 7.	9
	Listing 8.	9
III	Other	11
1	Acknowledgment	11
2	Also see	11
3	Install	11
4	Issue	11
5	Support	11
6	Testing	11
IV	Implementation	13
1	aux	13

2	log	15
3	make_key	16
4	make_oops	17
5	msg	19
6	option	19
7	prop	20
8	seq	21
9	Front-end	22
10	Misc	24

Part I

Usage

This part describes .

Convention

1. Loosely, those of [3] and [4], for example as to the meaning of $\langle token\ list \rangle$ and -NoValue-.
2. If unspecified, the environment in which a function must be declared is `document`.
3. Where $\langle tl_1 \rangle$ is an optional argument, its default is `Math`.

`\usepackage` `\usepackage{oops}`

Environment Preamble

Requirement `oops.sty` is in the path of the L^AT_EX engine. See [Part III, section 5](#).

`\Ooops` `\Ooops<tl1>`
`[<tl2>]`
`i{<code1>}`
`f{<kv11>}`
`+`
`*`
`s{f{<tl3>}}f{<tl3>}}f{<tl4>}}f{<tl3>}}f{<tl4>}}f{<tl5>}}`
`o{<code2>}`
`[<tl6>]`

Requirement $\langle kv1_1 \rangle$ is specified (all others optional).

$\langle tl_1 \rangle$

Example Math, ModelA, ModelB

Semantics Registers a new object, if applicable

$\langle tl_2 \rangle$

Example Let~

Semantics Expands $\langle tl_2 \rangle$

$\langle code_1 \rangle$

Example $\mathbb{\#1}$

Semantics 1. $\langle val_i \rangle \leftarrow \langle code_1 \rangle$ applied to $\langle val_i \rangle$

$\langle kvl_1 \rangle$

Example Elms={ ω_1 , \dots , ω_n }, Sample= Ω

Semantics 2. $\langle key_i \rangle \langle tl_1 \rangle \leftarrow \langle val_i \rangle$ defined in step **1**.

3. If Write= BooleanTrue , writes the definitions made in step **2** to file $\text{oops}\langle digits \rangle.\text{tex}$, where $\langle digits \rangle = \text{pdfdate}$

+

Other Needed to make the side effect $\backslash\text{Ops}$ ' within a local group persist thereafter

Semantics Appends step **2** and step **3** to $\backslash\text{OpsHook}$

*

Semantics 5. Expands $\langle code_2 \rangle$ applied to the list created in step **1**, using the separator specified by $\langle tl_3 \rangle$, $\langle tl_4 \rangle$, and $\langle tl_5 \rangle$.

$\langle tl_3 \rangle$

Example $\{\sim\text{in}\sim\}$

$\langle tl_4 \rangle$

Example $\{, \sim\}$

$\langle tl_5 \rangle$

Example $\{\sim\&\sim\}$

$\langle code_2 \rangle$

Example $\$\left\{\#1\right\}\right\$$

$\langle tl_6 \rangle$

Semantics $\backslash\text{Ops}\langle tl_1 \rangle[\langle tl_6 \rangle]$

<hr/> <hr/>	<code>\OpsClear<⟨keyval list⟩></code>
	Semantics Clears any data created by <code>\Ops{⟨tl₁⟩}</code> , for all <code>⟨tl₁⟩</code> in <code>⟨keyval list⟩</code>
<hr/> <hr/>	
<hr/> <hr/>	<code>\OpsDebug</code>
	Semantics See Part IV
<hr/> <hr/>	
<hr/> <hr/>	<code>\OpsHook</code>
	Example <code>\AfterEndEnvironment{theorem}{\OpsHook}</code>
<hr/> <hr/>	
<hr/> <hr/>	<code>\OpsOption{⟨kv10⟩}</code>
	Semantics Set default options for <code>\Ops</code>
Expans	
	Default <code>xo</code>
	Semantics Controls expansion in step 2
	Syntax Either of <code>eo</code> , <code>ee</code> , <code>ex</code> , <code>xe</code> , <code>xo</code> , <code>xe</code> , <code>xx</code>
Inner	
	Semantics Default for <code>⟨code₁⟩</code>
	Syntax Use <code>####1</code> as the argument to be replaced
Name	
	Semantics Default for <code>⟨tl₁⟩</code>
Outer	
	Semantics Default for <code>⟨code₂⟩</code>
	Syntax Use <code>####1</code> as the argument to be replaced
Separ	
	Semantics Default for <code>{⟨tl₃⟩} {⟨tl₃⟩}{⟨tl₄⟩} {⟨tl₃⟩}{⟨tl₄⟩}{⟨tl₅⟩}</code>
	Syntax That of ‘separators’ in [3, Section 8 of l3seq]
Write	
	Syntax <code>⟨boolean⟩</code>
<hr/> <hr/>	
<hr/> <hr/>	<code>\OpsRead[⟨path⟩]</code>
	Other The default for <code>⟨path⟩</code> is the last write-file (see <code>⟨kv1⟩</code>)
	Semantics 1. Reads the definitions in <code>⟨path⟩</code> . 2. Writes to <code>oops.log</code> : ‘read from <code>⟨path⟩</code> ’

Do's and don't's

1.

Don't: `\Oups{ A = a, B = b }[Hello, world!]`.

Do: `\Oups{ A = a, B = b }[Hello, world!]{}`, or
`\Oups{ A = a, B = b } Hello, world!`

2.

Don't: `$\langle key_i \rangle <x$`.

Do: `$\langle key_i \rangle \{<\}x$`

3.

Don't: `\Oups[[a, b)]`.

Do: `\Oups{\{[a, b{)}}}`

4.

Don't: `\Oups{ F = \cal F }`.

Do: `\Oups{ F = \cal{F} }` or `\Oups{ F = \mathcal{F} }`

5. Also see [Part III, section 4](#)

Part II

Listing

Warning: To reproduce the listings in a L^AT_EX document, use the same setting as thout of the documentation portion of oops.dtx (such as `\documentclass`, `\usepackage`, and `\newtcblisting`), and remove any `^^A`. Any deviation from the original may require tinkering.¹

Listing 1.

```
% \OpsOption{
% ^^A% spaces betw. inner and outer brackets matter!->
% Separ={\ \char`@\ }{\ \%\ }{\ \char`@\ }}
% \Ops<Test>{ X = x, Y = y }*[\]
% { X = x, Y = y, Z = z }*[\]
% { X = x, Y = y }*s{\ \&\ }{[\]}
% { X = x, Y = y }*s{\ \&\ }{\ ,\ }{[\]}
% { X = x, Y = y, Z = z }*s{\ \&\ }{[\]}
% { X = x, Y = y, Z = z }*s{\ \&\ }{\ ,\ }{[\]}
% { X = x, Y = y, Z = z }*s{\ \&\ }{\ ,\ }{\ \&\ }{\ }
%
```

```
x @ y
x % y @ z
x & y
x & y
x & y & z
x, y & z
x, y & z
```

Listing 2.

```
% \OpsOption{ Separ = {\}\{.\}\{.}\}, Outer = {####1} }
% \OpsOption{ Write = \BooleanTrue }
% \Ops<Test>
% { KeyA = {.\}, KeyB = {!}, KeyC = {\%} }[]
% { KeyD = {d}, KeyE = {\%} }[]i{\#1\}
% { KeyF = {H}, KeyG = {e}, KeyH = {l} }*[]
% { KeyI = {\%}, KeyJ = {\%}, KeyK = {\%} }{.\{l\}.\{o\}}
% { KeyL = {l}, KeyM = {\char`[]}, KeyN = {\char`[]}}{}
% { KeyO = {o}, KeyP = {\%}, KeyQ = {\%} }{\ ,\ }
% { KeyR = {w}, KeyS = {o}, KeyT = {r} }*s{\}\{\}\}\o{\char`[]\#1\}[]
% { KeyU = {\%}, KeyV = {\%}, KeyW = {\%} }[]
% { KeyX = {\%}, KeyY = {\%}, KeyZ = {\KeyB<Test>} }\nobreak
% \KeyL<Test>\KeyD<Test>\KeyZ<Test>\KeyN<Test>\
% \OpsClear
```

¹For instance, in testing v1.1, I realized `\usepackage[T1]{fontenc}` was needed, to work with `\documentclass{article}` in place of `\documentclass[full]{l3doc}`, hence added it to the documentation portion of oops.dtx

```
% \OpsOption{ Write = \BooleanFalse }
%
```

{H}. {e}. {l}. {l}. {o}, [world!]

Listing 3.

```
% \OpsRead
% \KeyF<Test>\KeyA<Test>\nobreak
% \KeyG<Test>\KeyA<Test>\nobreak
% \KeyH<Test>\KeyA<Test>\nobreak
% \KeyH<Test>\KeyA<Test>\nobreak
% {\}\nobreak\KeyO<Test>{\}, {\ }\nobreak
% \KeyM<Test>\KeyR<Test>\nobreak
% \KeyO<Test>\nobreak
% \KeyT<Test>\nobreak
% \KeyL<Test>\nobreak
% \KeyD<Test>\nobreak
% \KeyZ<Test>\nobreak
% \KeyN<Test>\nobreak
% \OpsClear<Test>
%
```

{H}. {e}. {l}. {l}. {o}, [world!]

Listing 4.

```
% \OpsOption{Inner, Separ, Outer}
% \Ops[We call~]{Elems={\omega_1}, {\dots}, {\omega_n}}}*
% [~the elementary events, and ]{Space=\Omega}
% [\begin{equation*}\Space=(\Elems)\end{equation*}~the sample space.]
% {}
% \OpsClear
%
```

We call $\omega_1, \dots, \omega_n$ the elementary events, and

$$\Omega = (\omega_1, \dots, \omega_n)$$

the sample space.

Listing 5.

```
% \OpsOption{ Write = \BooleanTrue }
% \Ops[Let~]
% {Space=\Omega, Field=\mathcal{F}, Meas=\mathcal{P}}
% *s{{,}}o{{\${1}\$}}
% [~denote the probability space, where $\Field\subset 2^{\Space}$.]
```



```
% {}
% \OpsClear
% \OpsOption{ Write = \BooleanFalse }
%
```

Let $\{\Omega, \mathcal{F}, \mathcal{P}\}$ denote the probability space, where $\mathcal{F} \subset 2^\Omega$.

Listing 6.

```
% \OpsRead \tab $\Omega$ $\Field$ $\Meas$
% \OpsClear
%
```

$\Omega \mathcal{F} \mathcal{P}$

Listing 7.

```
% \OpsOption{ Write = \BooleanTrue }
% \newtheorem{theorem}{Theorem}
% \AfterEndEnvironment{theorem}{\OpsHook}
% \Ops i{\mathbb{#1}}
% { N = { N } , R = { R } }+[]
% { Grad = { \operatorname{grad} } }+
% [\begin{theorem}
% [Mittelwertsatz f\"ur $n$ Variable]Es~sei~
% { OffMenge = {D}, Ci = {C^{1}} , Strecke = { [x_0,x] } }+
% [$n \in \mathbb{N}, \sim \text{OffMenge} \subseteq \mathbb{N}^n$ eine offene Menge und
% $f \in C^1(\text{OffMenge}, \mathbb{R})$].
% Dann gibt es auf jeder Strecke $\text{Strecke} \subseteq \text{OffMenge}$ einen
% Punkt $\xi \in \text{Strecke}$,~
% { Steig = { \frac{ f(x)-f(x_0) }{ x-x_0 } }, Punkt = { \xi } }+
% [so dass gilt
% \begin{equation*}
% \text{Steig} = \text{Grad } f(\text{Punkt})^{\top}
% \end{equation*}
% \end{theorem}]
% {}
% \OpsClear
% \OpsOption{ Write = \BooleanFalse }
%
```

Theorem 1 (Mittelwertsatz für n Variable) Es sei $n \in \mathbb{N}$, $D \subseteq \mathbb{R}^n$ eine offene Menge und $f \in C^1(D, \mathbb{R})$. Dann gibt es auf jeder Strecke $[x_0, x] \subset D$ einen Punkt $\xi \in [x_0, x]$, so dass gilt

$$\frac{f(x) - f(x_0)}{x - x_0} = \text{grad} f(\xi)^\top$$

Listing 8.

```
%      \OpsRead \tab $N$ $R$ $OffMenge$ $Ci$ $Strecke$
%
```

$$\mathbb{N} \times \mathbb{R} \times D \times C^1[x_0, x]$$

Part III

Other

1 Acknowledgment

This work has benefited from Q&A's from the L^AT_EX community, see here: <https://tex.stackexchange.com/users/112708/erwann?tab=questions>. Specific references are made in Part IV. Listing 4 and Listing 5 are from [1]. Listing 7 is from tcolbox[5, 17.3].

2 Also see

1. The package cool[2]

3 Install

Compiling `oops.dtx` (under Unix, `$tex oops.dtx`) will generate `oops.sty` and `oops.pdf`

4 Issue

1. **Don't:** `\newtheorem{definition}{Definition};`
and `\Oops[\begin{definition}]{ $\langle key_i \rangle$ = $\langle val_i \rangle$ }`
Symptom: ERROR: Undefined control sequence. (not systematic) for $\langle key_i \rangle$
Do: `\Oops \meta{\pkgkey} = \meta{\pkgval} \begin{definition}]{`
2. **Don't:** `Inner={\####1\}`
Symptom: `\OopsRead` fails
Do: `Inner={\char'####1\char'}`
See: Listing 1

5 Support

This package is available from <https://www.ctan.org/pkg/oops> and <https://github.com/rogard/oops>.

6 Testing

It's not possible to check the expansion of a certain class of macros against predefined values[6]. Instead, one can check that Part II, as generated in section 3 on one's own machine, agrees with `bench.pdf` available at <https://github.com/rogard/oops>,

References

- [1] A.N. Shiryaev *Probability* Springer, 1995
- [2] Nick Setzer *The cool package*, 2005 <https://www.ctan.org/pkg/cool>
- [3] The L^AT_EX3 Project Team *The L^AT_EX3 interfaces* <http://ftp.math.purdue.edu/mirrors/ctan.org/macros/latex/contrib/l3kernel/interface3.pdf>
- [4] The L^AT_EX3 Project Team *The xparse package* <http://ftp.math.purdue.edu/mirrors/ctan.org/macros/latex/contrib/l3packages/xparse.pdf>
- [5] Thomas F. Sturm *The tcolorbox package* <http://www.texdoc.net/texmf-dist/doc/latex/tcolorbox/tcolorbox.pdf>
- [6] <https://tex.stackexchange.com/a/534100/112708>

Part IV

Implementation

```

1 <@@=oops>
2 \NeedsTeXFormat{LaTeX2e}[2019/10/01]
3 \ExplSyntaxOn

```

1 aux

```

\__oops_aux_inner_set:n #1 : <code>

4 \cs_new_protected:Nn \__oops_aux_inner_set:n
5 {
6   \cs_gset:Npn \__oops_aux_inner:n ##1 {#1}
7   \cs_generate_variant:Nn \__oops_aux_inner:n { e }
8 }

(End definition for \__oops_aux_inner_set:n.)

\__oops_aux_key:w #1 : <key>
#2 : <value>

9 \cs_new_protected:Npn \__oops_aux_key:w #1 = #2 \q_stop
10 {
11   \seq_gput_right:Nx \g__oops_aux_key_seq { \tl_trim_spaces:n{#1} }
12 }

(End definition for \__oops_aux_key:w.)

\__oops_aux_key:n #1 : <key = value>

13 \cs_new_protected:Nn \__oops_aux_key:n
14 {
15   \__oops_aux_key:w #1 \q_stop
16 }

(End definition for \__oops_aux_key:n.)

\__oops_aux_key:N #1 : <seq>

17 \cs_new_protected:Nn \__oops_aux_key:N
18 {
19   \seq_gclear_new:N \g__oops_aux_key_seq
20   \seq_map_function:NN #1 \__oops_aux_key:n
21 }

(End definition for \__oops_aux_key:N.)

\__oops_aux_outer_set:n #1 : <inline code>

22 \cs_new_protected:Nn \__oops_aux_outer_set:n
23 {
24   \cs_gset:Npn \__oops_aux_outer:n ##1 {#1}
25 }

(End definition for \__oops_aux_outer_set:n.)

\__oops_aux_prop:w #1 : <key>

```

```

#2 : < value >
26 \prop_new:N \g__oops_aux_prop
27 \cs_new_protected:Nn \__oops_aux_prop:nn
28 {
29   \prop_gput:Nnn \g__oops_aux_prop{#1}{#2}
30 }
31 \cs_generate_variant:Nn \__oops_aux_prop:nn { eo, ee, ex, xo, xe, xx }
32 \tl_new:N \g__oops_option_expans_tl
33 \cs_new_protected:Npn \__oops_aux_prop:w #1 = #2 \q_stop
34 {
35   \exp_args:Nx
36   \use:c{\__oops_aux_prop:\g__oops_option_expans_tl}
37   { \tl_trim_spaces:n{#1} }
38   { \__oops_aux_inner:n{ \tl_trim_spaces:n{#2} } }
39   %^^A { \__oops_aux_inner:e{ \tl_trim_spaces:n{#2} } }% DEBUG
40 }

```

(End definition for __oops_aux_prop:w.)

```

\__oops_aux_prop:n #1 : < key = value >
41 \cs_new_protected:Nn \__oops_aux_prop:n
42 {
43   \__oops_aux_prop:w #1 \q_stop
44 }

```

(End definition for __oops_aux_prop:n.)

```

\__oops_aux_prop:N #1 : < keyval list >
45 \cs_new_protected:Nn \__oops_aux_prop:N
46 {
47   \prop_gclear_new:N \g__oops_aux_prop
48   \seq_if_empty:NTF #1
49   { \c_empty_tl }
50   {
51     \seq_map_function:NN #1 \__oops_aux_prop:n
52   }
53 }

```

(End definition for __oops_aux_prop:N.)

```

\__oops_aux_separ:nn #1 : < int >
#2 : < tokens >
54 \cs_new:Nn \__oops_aux_separ:nn
55 {
56   \int_case:nnTF {#1}
57   {
58     {1}
59     { \prg_replicate:nn{ 3 }{#2} }
60     {2}
61     {
62       { \use_i:nn #2 }
63       { \use_ii:nn #2 }
64       { \use_i:nn #2 }
65     }

```

```

66     {3}{#2}
67   }
68   { \c_empty_tl }
69   {
70     \msg_error:nnnn { __erw }
71     { separ }
72     { \exp_not:N \__oops_aux_separ:nn }
73     {#2}
74   }
75 }
76 \cs_generate_variant:Nn \__oops_aux_separ:nn { e }

```

(End definition for __oops_aux_separ:nn.)

```

\__oops_aux_separ:n #1 : < tokens >
77 \cs_new:Nn \__oops_aux_separ:n
78 {
79   \__oops_aux_separ:en{ \tl_count:n{#1} }{#1}
80 }

```

(End definition for __oops_aux_separ:n.)

```

\__oops_aux_val:Nn #1 : < seq >
#2 : < tl var name >
81 \cs_new_protected:Nn \__oops_aux_val:Nn
82 {
83   \seq_gclear_new:N \g__oops_aux_val_seq
84   \__oops_seq_from_prop:NNn \g__oops_aux_val_seq #1 { \__oops_prop_name:n{#2} }
85 }

```

(End definition for __oops_aux_val:Nn.)

2 log

```

\__oops_log_close:
86 \iow_new:N \g__oops_log_iow
87 \AtEndDocument{\iow_close:N \g__oops_log_iow}
88 \bool_set_false:N \g__oops_log_open_bool
89 \cs_new_protected:Nn \__oops_log_close:
90 {
91   \iow_close:N \g__oops_log_iow
92   \bool_gset_false:N \g__oops_log_open_bool
93 }

```

(End definition for __oops_log_close:.)

```

\__oops_log_open:
94 \cs_new_protected:Nn \__oops_log_open:
95 {
96   \tl_gset:Nx \g__oops_log_to_tl{oops\pdfdate}
97   \iow_open:Nn \g__oops_log_iow {\g__oops_log_to_tl}
98   \bool_gset_true:N \g__oops_log_open_bool
99 }

```

(End definition for _oops_log_open:.)

```
\_oops_log_read:n #1 : <path>
100 \cs_new_protected:Nn \_oops_log_read:n
101 {
102   \file_input:n{#1}
103   \tl_log:n{read~from~#1}
104 }
105 \cs_generate_variant:Nn \_oops_log_read:n { e }
```

(End definition for _oops_log_read:n.)

```
\_oops_log_read:
106 \cs_new_protected:Nn \_oops_log_read:
107 {
108   \_oops_log_read:e{\g__oops_log_to_tl}
109 }
```

(End definition for _oops_log_read:.)

```
\_oops_log_write:n
110 \tl_new:N \g__oops_log_to_tl
111 \cs_new_protected:Nn \_oops_log_write:n
112 {
113   \bool_if:nTF{ \g__oops_log_open_bool }
114   {
115     \iow_now:Nn \g__oops_log_iow {#1}
116     \tl_log:n{ write~to~#1 }
117   }
118   { \msg_error:nnn{ __oops }{ iow }{ \g__oops_log_iow } }
119 }
120 \cs_generate_variant:Nn \_oops_log_write:n { e }
```

(End definition for _oops_log_write:n.)

3 make_key

```
\_oops_make_key:Nn #1 : < token >
#2 : < key >
121 \cs_new_protected:Nn \_oops_make_key:Nn
122 {
123   \exp_args:NNx
124   \ProvideDocumentCommand{#1}
125   { D<>{\g__oops_option_name_tl} }
126   {
127     \_oops_prop_item:nn{##1}{#2}
128   }
129 }
130 \cs_generate_variant:Nn \_oops_make_key:Nn { c }
```

(End definition for _oops_make_key:Nn.)


```

__oops_make_key:n #1 : < key >

131 \cs_new_protected:Nn __oops_make_key:n
132 {
133   __oops_make_key:cn{#1}{#1}
134 }
135 \cs_generate_variant:Nn __oops_make_key:n { e }

(End definition for __oops_make_key:n.)

```

```

__oops_make_key:N #1 : < seq >

136 \cs_new_protected:Nn __oops_make_key:N
137 {
138   \seq_map_function:NN #1 __oops_make_key:e
139 }

(End definition for __oops_make_key:N.)

```

4 make_oops

```

__oops_make_oops_exp:nnn

140 \cs_new_protected:Nn __oops_make_oops_exp:nnn
141 {
142   __oops_aux_val:Nn \g__oops_aux_key_seq {#1}
143   __oops_aux_outer_set:n{#3}
144   __oops_aux_outer:n
145   {
146     \exp_args:NNf
147     __oops_seq_use:Nn
148     \g__oops_aux_val_seq
149     {#2}
150   }
151 }

(End definition for __oops_make_oops_exp:nnn.)

```

```

__oops_make_oops_key:nnn

152 \cs_new_protected:Nn __oops_make_oops_key:nnn
153 {
154   __oops_prop_if_exist:nTF{#1}
155   { \c_empty_tl }
156   { __oops_prop_new:n{#1} }
157   \exp_args:No __oops_aux_inner_set:n{#2}
158   \seq_set_from_clist:Nn \g__oops_aux_keyval_seq {#3}
159   __oops_aux_prop:N \g__oops_aux_keyval_seq
160   __oops_prop_append:Nn \g__oops_aux_prop {#1}
161   __oops_aux_key:N \g__oops_aux_keyval_seq
162   __oops_make_key:N \g__oops_aux_key_seq
163 }

(End definition for __oops_make_oops_key:nnn.)

```

_oops_make_oops_sideeffect:nnn

```

164 \cs_new_protected:Nn \_oops\_make\_oops\_sideeffect:nnn
165 {
166   \_oops\_make\_oops\_key:nnn{#1}{#2}{#3}
167   \bool_if:nTF{ \g\_oops\_log\_open\_bool }
168   {%^^A https://tex.stackexchange.com/questions/536597
169     \_oops\_log\_write:n
170     {
171       \begingroup
172       \def \_oops\_log\_entry { \Ops<#1>i{#2}{#3} } \expandafter
173       \endgroup \_oops\_log\_entry
174     }
175   }\c\_empty\_tl}
176 }

```

(End definition for _oops_make_oops_sideeffect:nnn.)

_oops_make_oops:nnnn #1 : < token list >
 #2 : < seq₁ >
 #3 : < seq₂ >
 #4 : < prop >

```

177 \def\OpsHook{\c\_empty\_tl}
178 \cs_new_protected:Npn \_oops\_make\_oops:nnnn #1 #2 #3 #4
179 {
180   \exp_args:NNx \DeclareDocumentCommand \Ops
181   {%^^A      2      3      4 5 6      7 8      9
182     D<>{#1} +o E{ i }{#{2}} m t+ s E{ s o }{#{3}{#4}} +o
183   }
184   {
185     \IfValueT{##2}{##2}
186     \_oops\_make\_oops\_sideeffect:nnn{##1}{##3}{##4}
187     \IfBooleanT{##6}
188     {
189       \_oops\_make\_oops\_exp:nnn{##1}{##7}{##8}
190     }
191     \bool_if:nTF{##5}
192     {
193       \gappto{\OpsHook}
194       {
195         \_oops\_make\_oops\_sideeffect:nnn{##1}{##3}{##4}
196       }
197     }
198     {\c\_empty\_tl}
199     \IfValueT{##9}
200     {
201       \exp_not:n{ \Ops<##1>[##9] }
202     }
203   }
204 }

```

(End definition for _oops_make_oops:nnnn.)

5 msg

```

205 \msg_new:nnn {__oops}{ generic }{#1}
206 \msg_new:nnn {__oops}{ iow }{#1~is~closed~can't~write}
207 \msg_new:nnn {__oops}{ keyonly }{#1~does~not~take~values;~keyval~is~#2}
208 \msg_new:nnn {__oops}{ keywrong }{#1~does~not~recognize~key~#2}
209 \msg_new:nnn {__oops}{ separ }{#1~expects~1~to~3~items,~#2}
210 \msg_new:nnn {__oops}{ unset }{#1~unset}

```

6 option

```

\__oops_aux_inner:n #1: <code>

211 \cs_new_protected:Nn \__oops_option_inner:n
212 {
213   \tl_gset:Nn \g__oops_option_inner_tl {#1}
214 }
215 \__oops_option_inner:n
216 {
217   \msg_warning:nnn{ __oops }{ unset }{ \exp_not:N \g__oops_option_inner_tl }
218 }

```

(End definition for __oops_aux_inner:n.)

```

\__oops_option_name:n #1: <token list>

219 \cs_new:Nn \__oops_option_name:n
220 {
221   \tl_gset:Nn \g__oops_option_name_tl{#1}
222 }
223 \__oops_option_name:n
224 {
225   \msg_error:nnx{ __oops }
226   { generic }
227   { \exp_not:N\g__oops_option_name_tl~undefined }
228 }

```

(End definition for __oops_option_name:n.)

```

\__oops_option_outer:n #1: < inline code >

229 \cs_new_protected:Nn \__oops_option_outer:n
230 {
231   \tl_gset:Nn \g__oops_option_outer_tl {#1}
232 }
233 \__oops_option_outer:n
234 {
235   \msg_warning:nnn{ __oops }{ unset }{ \exp_not:N \g__oops_option_outer_tl }
236 }

```

(End definition for __oops_option_outer:n.)

```

\__oops_option_separ:n #1: {< token list1 >}{< token list2 >}{< token list3 >}}

237 \cs_new_protected:Nn \__oops_option_separ:n
238 {
239   \cs_gset:Npn \g__oops_option_separ_tl {#1}
240 }

```

```

241 \__oops_option_separ:n
242 {
243   \msg_warning:nnn{ __oops }{ unset }{ \exp_not:N \g__oops_option_separ_tl }
244 }

```

(End definition for __oops_option_separ:n.)

7 prop

```

\__oops_prop_append:NN #1 : < prop1 >
\__oops_prop_append:cN #2 : < prop2 >

245 \cs_new_protected:Npn \__oops_prop_append:NN #1 #2
246 {
247   \cs_set:Nn \__oops_prop_append:nn
248   {
249     \prop_gput:Nnx #1 {##1}{ \prop_item:Nn #2{##1} }
250   }
251   \prop_map_function:NN #2 \__oops_prop_append:nn
252 }
253 \cs_generate_variant:Nn \__oops_prop_append:NN { cN }

```

(End definition for __oops_prop_append:NN.)

```

\__oops_prop_append:Nn #1 : < prop >
#2 : < tl var name >

254 \cs_new_protected:Nn \__oops_prop_append:Nn
255 {
256   \__oops_prop_append:cN{ \__oops_prop_name:n {#2} } #1
257 }

```

(End definition for __oops_prop_append:Nn.)

```

\__oops_prop_clear_new:n #1 : < tl var name >

258 \cs_new_protected:Nn \__oops_prop_clear_new:n
259 {
260   \exp_args:No \prop_clear_new:c{ \__oops_prop_name:n {#1} }
261 }

```

(End definition for __oops_prop_clear_new:n.)

```

\__oops_prop_clear_new_map:n #1 : < keyval list >

262 \cs_new_protected:Nn \__oops_prop_clear_new_map:n
263 {
264   \seq_set_from_clist:Nn \g__oops_aux_key_seq {#1}
265   \seq_map_function:NN \g__oops_aux_key_seq \__oops_prop_clear_new:n
266 }

```

(End definition for __oops_prop_clear_new_map:n.)

```

\__oops_prop_if_exist:nTF #1 : < token list1 >
#2 : < token list2 >

```

```

#3 :  $\langle token list_3 \rangle$ 
267 \cs_new:Nn \__oops_prop_if_exist:nTF
268 {
269   \prop_if_exist:cTF{ \__oops_prop_name:n {#1} }{#2}{#3}
270 }

```

(End definition for __oops_prop_if_exist:nTF.)

```

\__oops_prop_item:nn #1 :  $\langle tl var name \rangle$ 
#2 :  $\langle key \rangle$ 
271 \cs_new:Nn \__oops_prop_item:nn
272 {
273   \prop_item:cn { \__oops_prop_name:n {#1} } {#2}
274 }

```

(End definition for __oops_prop_item:nn.)

```

\__oops_prop_name:n #1 :  $\langle tl var name \rangle$ 
275 \cs_new:Npn \__oops_prop_name:n #1{ __oops_#1 }

```

(End definition for __oops_prop_name:n.)

```

\__oops_prop_new:n #1 :  $\langle tl var name \rangle$ 
276 \cs_new_protected:Nn \__oops_prop_new:n
277 {
278   \prop_new:c{ \__oops_prop_name:n {#1} }
279 }

```

(End definition for __oops_prop_new:n.)

8 seq

```

\__oops_seq_from_prop:NNn #1 :  $\langle seq_1 \rangle$ 
#2 :  $\langle seq_2 \rangle$  (keys)
#3 :  $\langle prop \rangle$ 
280 \cs_new_protected:Nn \__oops_seq_from_prop:NNn
281 {
282   \cs_set_protected:Nn \__oops_seq_from_prop:n
283   {
284     \seq_gput_right:No #1 { \prop_item:cn{#3}{##1} }
285   }
286   \seq_map_function:NN #2 \__oops_seq_from_prop:n
287 }

```

(End definition for __oops_seq_from_prop:NNn.)

```

\__oops_erw_seq_use:Nn
288 % \begin{arguments}
289 % \item \meta{ seq }
290 % \item \meta{ tokens }
291 % \end{arguments}
292 \cs_new:Nn \__oops_seq_use:Nn
293 {

```

```

294 \exp_last_unbraced:NNf
295 \seq_use:Nnnn #1
296 \__oops_aux_separ:n{#2}
297 }

```

(End definition for __oops_erw_seq_use:Nn.)

9 Front-end

```

298 \keys_define:nn { __oops }
299 {
300   Expans .multichoices:nn =
301   { eo, ee, ex, xo, xe, xx }
302   { \tl_gset_eq:NN \g__oops_option_expans_tl \l_keys_choice_tl },
303   Expans .default:n = { xo },
304   Expans .initial:n = { xo },
305   Name .code:n={
306     \__oops_option_name:n{#1}
307     \exp_last_unbraced:Nf
308     \__oops_make_oops:nnnn
309     {
310       { \g__oops_option_name_tl }
311       { \g__oops_option_inner_tl }
312       { \g__oops_option_separ_tl }
313       { \g__oops_option_outer_tl }
314     }
315   },
316   Name .value_required:n = false,
317   Name .default:n = { Math },
318   Name .initial:n = { Math },
319   Inner .code:n={
320     \__oops_option_inner:n{#1}
321     \exp_last_unbraced:Nf
322     \__oops_make_oops:nnnn
323     {
324       { \g__oops_option_name_tl }
325       { \g__oops_option_inner_tl }
326       { \g__oops_option_separ_tl }
327       { \g__oops_option_outer_tl }
328     }
329   },
330   Inner .value_required:n = false,
331   Inner .default:n = {####1},
332   Inner .initial:n = {####1},
333   Outer .code:n={
334     \__oops_option_outer:n{#1}
335     \exp_last_unbraced:Nf
336     \__oops_make_oops:nnnn
337     {
338       { \g__oops_option_name_tl }
339       { \g__oops_option_inner_tl }
340       { \g__oops_option_separ_tl }
341       { \g__oops_option_outer_tl }
342     }

```

```

343 },
344 Outer .value_required:n = false,
345 Outer .default:n = { \ensuremath{####1} },
346 Outer .initial:n = { \ensuremath{####1} },
347 Write .code:n = {
348   \bool_if:nTF{#1}
349   {\__oops_log_open:}
350   {\__oops_log_close:}
351 },
352 Write .value_required:n = false,
353 Write .default:n = \BooleanFalse,
354 Write .initial:n = \BooleanFalse,
355 Separ .code:n={
356   \__oops_option_separ:n{#1}
357   \exp_last_unbraced:Nf
358   \__oops_make_oops:nnnn
359   {
360     { \g__oops_option_name_tl }
361     { \g__oops_option_inner_tl }
362     { \g__oops_option_separ_tl }
363     { \g__oops_option_outer_tl }
364   }
365 },
366 Separ .value_required:n = false,
367 Separ .default:n = { {\ }and{\ } } { ,{\ } } { ,{\ }and{\ } },
368 Separ .initial:n = { {\ }and{\ } } { ,{\ } } { ,{\ }and{\ } }
369 }

```

\OpsClear #1 : $\langle \text{tl var name} \rangle$

```

370 \NewDocumentCommand{ \OpsClear }
371 { D<>{\g__oops_option_name_tl} }
372 {
373   \__oops_prop_clear_new_map:n{#1}
374 }

```

(End definition for \OpsClear. This function is documented on page 5.)

\OpsDebug

```

375 \NewDocumentCommand\OpsDebug{m}
376 {
377   \__oops_prop_if_exist:nTF{#1}
378   { \c_empty_tl }
379   { \__oops_prop_new:n{#1} }
380   \__oops_make_key:Nn \KeyA{KeyA}
381   \gappto{\OpsHook}
382   {
383     \__oops_prop_if_exist:nTF{#1}
384     { \c_empty_tl }
385     { \__oops_prop_new:n{#1} }
386     \__oops_make_key:Nn \KeyA{KeyA}
387   }
388 }

```

(End definition for \OpsDebug. This function is documented on page 5.)

\OpsOption

```
389 \NewDocumentCommand{ \OpsOption }  
390 { m }  
391 {  
392   \keys_set:nn{ __oops }{#1}  
393 }
```

(End definition for \OpsOption. This function is documented on page 5.)

\OpsRead

```
394 \NewDocumentCommand{\OpsRead}  
395 {o}  
396 {  
397   \IfValueTF{#1}  
398   {\__oops_log_read:e{#1}}  
399   {\__oops_log_read:}  
400 }
```

(End definition for \OpsRead. This function is documented on page 5.)

10 Misc

```
401 \ExplSyntaxOff
```