

The ccool package*

Erwann Rogard[†]

Released 2020/04/12

Abstract

ccool stands for Custom COntent Oriented for L^AT_EX, a concept pioneered by cool[1]¹. This is done using a minimalist interface built upon xparse[4]. Specifically, `\Ccool<name>` begins a series of instructions alternating between ‘text’ and macro definitions, that themselves optionally expand using predefined or inline rules. For example,

```
\Ccool<Math>[Let~]
i{\mathbb{#1}}{ Nat = N, Real = R }*s{{~\rm{and}}~}}
[~denote the natural and real numbers.]{}
```

expands to: “Let \mathbb{N} and \mathbb{R} denote the natural and real numbers.” As a side effect, `$_\text{Nat}<Math>$` encodes “N” (and likewise for `\Real`). `Math` being the default for `<name>`, `<Math>` can be dropped. Optionally, the macros can be written to a file, and read, which can be useful for typesetting documents sharing the same notation.

Contents

I	Usage	4
0	Convention	4
1	Loading the package	4
2	\Ccool	4
2.1	<code><tl₁></code>	4
2.2	<code>[tl₂]</code>	4
2.3	<code>i{<code₁>}</code>	4
2.4	<code>{<kv₁>}</code>	5
2.5	<code>+</code>	5
2.6	<code>*</code>	5
2.7	<code>s{{<tl₃>}{<tl₃>}{<tl₄>}{<tl₃>}{<tl₄>}{<tl₅>}}</code>	5
2.8	<code>o{<code₂>}</code>	5
2.9	<code>[tl₆]</code>	5
3	\CcoolClear	5

*This file describes version v1.8, last revised 2020/04/12.

[†]firstname dot lastname AusTria gmail dot com

¹Whereas cool provided predefined macros, ccool is tool for making macros, hence “custom”.

4	\CcoolHook	5
5	\CcoolLambda	6
6	\CcoolOption	6
6.1	Expans	6
6.2	File	6
6.3	Inner	6
6.4	Name	6
6.5	Outer	6
6.6	Separ	6
6.7	Write	6
7	\CcoolRead	7
8	\CcoolVers	7
9	Do's and dont's	7
 II Listing		8
Listing 1. Version.		8
Listing 2. Preamble.		8
Listing 3. Separators.		8
Listing 4. Hello, world!		8
Listing 5. Listing 4 read from file.		9
Listing 6. Probability space.		9
Listing 7. Listing 6 read from file.		9
Listing 8. Mittelwertsatz für n Variable.		10
Listing 9. Listing 8 read from file.		10
Listing 10. Lambda expression.		10
Listing 11. Listing 10 read from file.		11
Listing 12. CUSUM statistic.		11
Listing 13. Listing 12 read from file.		12
 III Other		13
1	Acknowledgment	13

2	Install	13
3	Issue	13
4	Support	13
5	Testing	13
5.1	Technicality	13
5.2	Platform	13
5.3	Engine	13
5.4	Results	13
5.5	Other	14
	References	14
	Change History	14
	Index	15
IV	Implementation	19
1	aux	19
2	lambda	21
3	log	22
4	make_key	23
5	make_ccool	23
6	msg	25
7	option	25
8	prop	26
9	seq	28
10	Front-end	28

Part I Usage

Convention

1. Loosely, those of [2] and [4], for example as to the meaning of $\langle token\ list \rangle$.
2. If unspecified, the environment in which a macro must be declared is `document`.

<code>\usepackage</code>	<code>\usepackage{ccool}</code>
--------------------------	---------------------------------

Requirement

1. `ccool.sty` is in the path of the L^AT_EX engine. See [Part III, section 4](#).
2. Declare it in the *preamble*

<code>\Ccool</code>	$\Ccool\langle tl_1 \rangle$ $[\langle tl_2 \rangle]$ $i\{\langle code_1 \rangle\}$ $\{\langle kvl_1 \rangle\}$ $+$ $*$ $s\{\{\langle tl_3 \rangle\} \{\langle tl_3 \rangle\}\{\langle tl_4 \rangle\} \{\langle tl_3 \rangle\}\{\langle tl_4 \rangle\}\{\langle tl_5 \rangle\}\}$ $o\{\langle code_2 \rangle\}$ $[\langle tl_6 \rangle]$
---------------------	--

Requirement $\langle kvl_1 \rangle$ is specified (all others optional).

$\langle tl_1 \rangle$

Example `Math, ModelA, ModelB`

Semantics Identifies a group of macros

$\langle tl_2 \rangle$

Example `Let~`

Semantics Expands $\langle tl_2 \rangle$

$\langle code_1 \rangle$

Example `\mathbb{#1}`

Semantics

1. $\langle val_i \rangle \leftarrow \langle code_1 \rangle$ applied to $\langle val_i \rangle$

$\langle kvl_1 \rangle$

Example $\text{Elms}=\{\backslash\omega_1, \backslash\text{dots}, \backslash\omega_n\}$, $\text{Sample}=\backslash\Omega$

Semantics

2. $\backslash\langle key_i \rangle \langle tl_1 \rangle \leftarrow \langle val_i \rangle$ defined in step 1, using **Expans** for expansion.
3. If **Write**, writes the input used by step 2 to **File**

+

Other Needed to make **\Ccool**'s side effect within a *local group* persist thereafter

Semantics Appends step 2 and step 3 to **\CcoolHook**

*

Semantics

4. Expands $\langle code_2 \rangle$ applied to the list created in step 1, using the separator specified by $\langle tl_3 \rangle$, $\langle tl_4 \rangle$, $\langle tl_5 \rangle$.

$\langle tl_3 \rangle$

Example $\{\sim\backslash\text{in}\sim\}$

$\langle tl_4 \rangle$

Example $\{\sim\}$

$\langle tl_5 \rangle$

Example $\{\sim\backslash\&\sim\}$

$\langle code_2 \rangle$

Example $\$\backslash\text{left}\backslash\{\#1\backslash\text{right}\backslash\}\$$

$\langle tl_6 \rangle$

Semantics **\Ccool** $\langle tl_1 \rangle \rightarrow [\langle tl_6 \rangle]$

\CcoolClear **\CcoolClear** $\langle keyval list \rangle$

Semantics Clears any data created by **\Ccool** $\{\langle tl_1 \rangle\}$, for all $\langle tl_1 \rangle$ in $\langle keyval list \rangle$

\CcoolHook **\CcoolHook**

Example **\AfterEndEnvironment** $\{\text{theorem}\}\{\backslash\text{CcoolHook}\}$

<hr/> <hr/>	$\backslash\text{CcoolLambda}[\langle integer \rangle]{\langle code \rangle}$
	Example $\backslash\text{Ccool}\{ \text{EvalAt} = \backslash\text{CcoolLambda}\{(\#1)\} \}$
	Semantics Creates a lambda expression with $\langle integer \rangle$ arguments for $\langle code \rangle$
<hr/> <hr/>	$\backslash\text{CcoolOption}\{\langle kv10 \rangle\}$
	Semantics Set default options for $\backslash\text{Ccool}$
Expans	
	Default xo
	Syntax Either of eo , ee , ex , xe , xo , xe , xx
File	
	Default $\text{ccool}\backslash\text{pdfcreationdate}$
	Syntax Expands to a valid <i>path</i>
Inner	
	Default ####1
	Semantics Default for $\langle code_1 \rangle$
	Syntax Use ####1 as the argument to be replaced
Name	
	Default Math
	Semantics Default for $\langle tl_1 \rangle$
Outer	
	Default $\backslash\text{ensuremath}\{\text{####1}\}$
	Semantics Default for $\langle code_2 \rangle$
	Syntax Use ####1 as the argument to be replaced
Separ	
	Default $\{ \{ \backslash \} \text{and} \{ \backslash \} \} \{ , \{ \backslash \} \} \{ , \{ \backslash \} \text{and} \{ \backslash \} \}$
	Semantics Default for separators' <i>parameter</i>
	Syntax That of 'separators' in [2, Section 8 of l3seq]
Write	

Default `\BooleanFalse`

Syntax *Boolean*

`\CcoolRead` `\CcoolRead[⟨path⟩]`

Other The default for $\langle path \rangle$ is the last write-file (see $\langle kul_1 \rangle$)

Semantics

1. Reads the definitions in $\langle path \rangle$.
2. Writes to `ccool.log`: ‘read from $\langle path \rangle$ ’

`\CcoolVers` `\CcoolVers`

Semantics Expands to the package’s version

Do’s and dont’s

1.

Don’t: `\Ccool{ A = a, B = b }[Hello, world!]`.

Do: `\Ccool{ A = a, B = b }[Hello, world!]{}`, or
`\Ccool{ A = a, B = b } Hello, world!`

2.

Don’t: $\$ \langle key_i \rangle < x \$$.

Do: $\$ \langle key_i \rangle \{ < \} x \$$

3.

Don’t: `[a, b)`

Do: `{[]a, b{)}`

4.

Don’t: `\Ccool{ F = \cal F }`.

Do: `\Ccool{ F = \cal{F} } }` or `\Ccool{ F = \mathcal{F} } }`

5. Also see [Part III, section 3](#)

Part II

Listing

Listing 1.

```
% \CcoolVers
%
```

2020/04/12 v1.8 cool — A tool for encoding mathematical notation

Listing 2. Preamble^a

^aThese are the settings to replicate the listings. For exhaustivity, check the **documentation** section of `ccool.dtx`.

```
% \usepackage{amsmath, amsthm, commath}
% \usepackage[T1]{fontenc}% \char`[
%
```

Listing 3. Separators

```
% \CcoolOption{
% ^^A% spaces betw. inner and outer brackets matter!->
% Separ={\ \char`@\ }{\ \% \ }{\ \char`@\ }}
% \Ccool<Test>{ X = x, Y = y }*[\]
% { X = x, Y = y, Z = z }*[\]
% { X = x, Y = y }*s{\ \&\ }{[\]}
% { X = x, Y = y }*s{\ \&\ }{,\ }{[\]}
% { X = x, Y = y, Z = z }*s{\ \&\ }{[\]}
% { X = x, Y = y, Z = z }*s{\ \&\ }{,\ }{[\]}
% { X = x, Y = y, Z = z }*s{\ \&\ }{,\ }{,\ }{[\]}
% { X = x, Y = y, Z = z }*s{\ \&\ }{,\ }{,\ }{,\ }{[\]}
%
```

```
x @ y
x \% y @ z
x & y
x & y
x & y & z
x, y & z
x, y & z
```

Listing 4. Hello, world!^a

^aIf this looks arcane, it's for the purpose of testing.

```
% \CcoolOption{ Separ = {\}{.}{.}}, Outer = {####1} }
% \CcoolOption{ Write = \BooleanTrue }
```



```

% \Ccool<Test>
% { KeyA = {.}, KeyB = {!}, KeyC = {\%} }[]
% { KeyD = {d}, KeyE = {\%} }[]i{\#1\}
% { KeyF = {H}, KeyG = {e}, KeyH = {l} }*[]
% { KeyI = {\%}, KeyJ = {\%}, KeyK = {\%} }[.\{l\}.\{o\}]
% { KeyL = {l}, KeyM = {\char`[]}, KeyN = {\char`[] } }[]
% { KeyO = {o}, KeyP = {\%}, KeyQ = {\%} }[{, \ }]
% { KeyR = {w}, KeyS = {o}, KeyT = {r} }*s{{}{}}o{{\char`[]\#1}[]
% { KeyU = {\%}, KeyV = {\%}, KeyW = {\%} }[]
% { KeyX = {\%}, KeyY = {\%}, KeyZ = {\KeyB<Test>} }\nobreak
% \KeyL<Test>\KeyD<Test>\KeyZ<Test>\KeyN<Test>\
% \CcoolOption{ Write = \BooleanFalse }
%

```

{H}.\{e}.\{l}.\{l}.\{o}, [world!]

Listing 5. Listing 4 read from file.

```

% \CcoolRead
% \KeyF<Test>\KeyA<Test>\nobreak
% \KeyG<Test>\KeyA<Test>\nobreak
% \KeyH<Test>\KeyA<Test>\nobreak
% \KeyH<Test>\KeyA<Test>\nobreak
% {\{} \nobreak \KeyO<Test>\{\}, {\ } \nobreak
% \KeyM<Test>\KeyR<Test>\nobreak
% \KeyO<Test>\nobreak
% \KeyT<Test>\nobreak
% \KeyL<Test>\nobreak
% \KeyD<Test>\nobreak
% \KeyZ<Test>\nobreak
% \KeyN<Test>\nobreak
%

```

{H}.\{e}.\{l}.\{l}.\{o}, [world!]

Listing 6. Probability space

```

% \CcoolOption{ Write = \BooleanTrue }
% \Ccool[Let~]
% { Space = \Omega, Field = \mathcal{F}, Meas = \mathcal{P} }
% *s{{,}}o{{\#1\}}
% [~denote the probability space, where~]{ PowerSet = { 2^{\Space} } }
% [{$\Field\subset \PowerSet$.}
% {
% \CcoolOption{ Write = \BooleanFalse }
%

```

Let $\{\Omega, \mathcal{F}, \mathcal{P}\}$ denote the probability space, where $\mathcal{F} \subset 2^\Omega$.

Listing 7. Listing 6 read from file.

```
% \CcoolRead \tab $\Omega$ $\mathcal{F}$ $\mathcal{P}$
%
```

$$\Omega \mathcal{F} \mathcal{P}$$

Listing 8. Mittelwertsatz für n Variable[1, 17.3]

```
% \CcoolOption{ Write = \BooleanTrue }
% \newtheorem{theorem}{Theorem}
% \AfterEndEnvironment{theorem}{\CcoolHook}
% \Ccool i{\mathbb{#1}}
% { N = { N } , R = { R } }+[]
% { Grad = { \operatorname{grad} } }+
% [\begin{theorem}
% [Mittelwertsatz f\"ur $n$ Variable]Es~sei~]
% { OffMenge = {D}, Ci = {C^{1}}, Strecke = { [x_0,x] } }+
% [$n\in\mathbb{N}, \sim\mathcal{O}ffMenge\subseteq\mathbb{R}^n$ eine offene Menge und
% $f\in C^1(\mathcal{O}ffMenge, \mathbb{R})$.
% Dann gibt es auf jeder Strecke $\mathcal{S}\subseteq\mathcal{O}ffMenge$ einen
% Punkt $\xi\in\mathcal{S}$,~]
% { Steig = { \frac{ f(x)-f(x_0) }{ x-x_0 } }, Punkt = { \xi } }+
% [so dass gilt
% \begin{equation*}
% \Steig = \operatorname{grad} f(\xi)
% \end{equation*}
% \end{theorem}]
% {}
% (Check: $N$, $\xi$)
% \CcoolOption{ Write = \BooleanFalse }
%
```

Theorem 1 (Mittelwertsatz für n Variable) Es sei $n \in \mathbb{N}$, $D \subseteq \mathbb{R}^n$ eine offene Menge und $f \in C^1(D, \mathbb{R})$. Dann gibt es auf jeder Strecke $[x_0, x] \subset D$ einen Punkt $\xi \in [x_0, x]$, so dass gilt

$$\frac{f(x) - f(x_0)}{x - x_0} = \operatorname{grad} f(\xi)^\top$$

(Check: \mathbb{N} , ξ)

Listing 9. Listing 8 read from file.

```
% \CcoolRead \tab $N$ $R$ $\mathcal{O}ffMenge$ $Ci$ $\mathcal{S}$
%
```

$$\mathbb{N} \mathbb{R} D C^1 [x_0, x]$$

Listing 10. Lambda expression.

```
% \CcoolOption{ Write = \BooleanTrue }
% \Ccool{ EvalAt = \CcoolLambda{(#1)}, ApplyOp =
% \CcoolLambda[2]{#1[#2]} }
% [Supposons une fonction  $f$ \EvalAt{t}$, et \etudions le probl\eme
% o\`u la fonctionnelle  $S$ \ApplyOp{S}{f}$ est donn\`ee par\dots]{
% \CcoolOption{ Write = \BooleanFalse }
%
```

Supposons une fonction $f(t)$, et étudions le problème où la fonctionnelle $S[f]$ est donnée par...

Listing 11. Listing 10 read from file.

```
% \CcoolRead \tab  $f$ \EvalAt{t}$,  $S$ \ApplyOp{S}{f}$
%
```

$$f(t), S[f]$$

Listing 12. CUSUM statistic

```
% \newtheorem{definition}{Definition}
% \AfterEndEnvironment{definition}{\CcoolHook}
%
% \CcoolOption{ Write = \BooleanTrue }
% \Ccool{ SuchThat = { ;~ }, Time = { t }, Process = { \xi }, StopT =
% { T }, EvalAt = \CcoolLambda{(#1)} }
% [The CUSUM statistic process and the corresponding one-sided CUSUM
% stopping time are defined as follows:
% \begin{definition}\label{the CUSUM statistic}. Let~
% { Scale = { \lambda }, Real = {\mathcal{R}} }+*s{{~\in~}}[~and~
% { CUSUMthresh = { \nu } }+*o{#1\in\Real^{+}}$.}
% [~Define the following processes:]
% { LogWald = { u }, CUSUMst = { \StopT_{c} }, CUSUM = { y },
% LogWaldInf = { m } }+
% [\begin{enumerate}
% \item{ $\LogWald_{\Time}\EvalAt{ \Scale } = \Scale\Process_{\Time}
% - \frac{1}{2}\Scale^2\Time$ ;
%  $\LogWaldInf_{\Time}\EvalAt{ \Scale } = \inf_{0 \leq s \leq \Time}
% \CUSUM_{s}\EvalAt{ \Scale }$ .}
% \item{ $\CUSUM_{\Time}\EvalAt{ \Scale } =
% \LogWaldInf_{\Time}\EvalAt{ \Scale } - \LogWald_{\Time}\EvalAt{
% \Scale } \geq 0$ , which is the CUSUM statistic process.}
% \item{ $\CUSUMst \EvalAt{ \Scale, \LogWaldInf } = \inf\left[ \Time
% \geq 0 \text{ \textit{SuchThat} } \CUSUM_{\Time}\EvalAt{\Scale} \geq \LogWaldInf
% \right]$ , which is the CUSUM stopping time.}
% \end{enumerate}\end{definition}\par{}
%
% (Check:  $\Scale$ ,  $\CUSUM$ )
% \CcoolOption{ Write = \BooleanFalse }
```

%

The CUSUM statistic process and the corresponding one-sided CUSUM stopping time are defined as follows:

Definition 1 . Let $\lambda \in \mathcal{R}$ and $\nu \in \mathcal{R}^+$. Define the following processes:

1. $u_t(\lambda) = \lambda \xi_t - \frac{1}{2} \lambda^2 t$; $m_t(\lambda) = \inf_{0 \leq s \leq t} y_s(\lambda)$.
2. $y_t(\lambda) = m_t(\lambda) - u_t(\lambda) \geq 0$, which is the CUSUM statistic process.
3. $T_c(\lambda, m) = \inf [t \geq 0; y_t(\lambda) \geq m]$, which is the CUSUM stopping time.

(Check: λ, y)

Listing 13. Listing 12 read from file.

```
%      \CcoolRead \tab $Time$ $Process$ $Scale$ $Real$ $CUSUMthresh$
      $LogWald$ $CUSUMst$ $CUSUM$ $LogWaldInf$
%
```

$t \xi \lambda \mathcal{R} \nu u T_c y m$

Part III

Other

1 Acknowledgment

This work has benefited from Q&A's from the L^AT_EXcommunity[6]. Specific attributions are made in the implementation and [References](#).

2 Install

Compiling `ccool.dtx`² will generate `ccool.sty` and `ccool.pdf`

3 Issue

1. **Don't:** `Inner={\{####1\}}`
Symptom: `\CcoolRead` fails
Do: `Inner={\char'\{####1\char'}}`

4 Support

This package is available from <https://www.ctan.org/pkg/ccool> and <https://github.com/rogard/ccool>.

5 Testing

5.1 Technicality

Not possible to compile-check the expansion of a certain class of macros against predefined values[8]. Instead, one can visually check [Part II](#), as generated in [section 2](#) on one's own machine, against that [of the repository](#) for the same version.

5.2 Platform

1. Linux laptop 4.15.0-20-generic #21-Ubuntu SMP Tue Apr 24
↪ 06:16:15 UTC 2018 x86_64 x86_64 x86_64 GNU/Linux

5.3 Engine

1. pdfTeX 3.14159265-2.6-1.40.20 (TeX Live 2019)

5.4 Results

1. `ccool v1.8` satisfactory on platform [1](#) and engine [1](#)

²Under Unix, `$tex ccool.dtx`

5.5 Other

Check [5] for using ccool with llncs

References

- [1] Nick Setzer *The cool package*, 2005, <https://www.ctan.org/pkg/cool>
- [2] The L^AT_EX3 Project Team *The L^AT_EX3 interfaces*, 2019, <http://ftp.math.purdue.edu/mirrors/ctan.org/macros/latex/contrib/l3kernel/interface3.pdf>
- [3] Thomas F. Sturm *The tcolorbox package*, 2019, <http://www.texdoc.net/texmf-dist/doc/latex/tcolorbox/tcolorbox.pdf>
- [4] The L^AT_EX3 Project Team *The xparse package*, 2020, <http://ftp.math.purdue.edu/mirrors/ctan.org/macros/latex/contrib/l3packages/xparse.pdf>
- [5] Erwann Rogard and Olympia Hadjiliadis *Typesetting a math thesis with ccool*, 2020, <https://github.com/rogard/ccool/blob/master/thesis.pdf>
- [6] <https://tex.stackexchange.com/users/112708/erwann?tab=questions>
- [7] @sean-allred’s answer to “How to create lambda expressions?”, <https://tex.stackexchange.com/a/188053/112708>
- [8] “Checking a function’s expansion against a string”, <https://tex.stackexchange.com/a/534100>
- [9] @frougon’s answer to “Journaling calls to a function []”, <https://tex.stackexchange.com/a/536620>

Change History

v1.0		Replaced: <code>GenericObject</code> by <code>Name</code>	14
General: Initial version	14	Replaced: <code>Separators</code> by <code>Separ</code>	14
v1.1		Revamped: much of the	
General: Added: <code>Save</code>	14	implementation	14
Added: Listing 1., 2., 3., 4., 6., and			
9.	14	v1.2	
Added: <code>\OpsRestore</code>	14	General: Deleted: <code>\OpsTest</code>	14
Added: <code>\OpsTest</code>	14	Deleted: <code>\kvl_2</code> and <code>\code_2</code>	14
Deleted: Listing 1-5 from v1.0	14	Deleted: Listing 2-3 from v1.1.	14
Fixed: apparent anomaly in v1.0’s		Replaced: <code>\OpsClear{\tl_1}</code> by	
Listing 4, see Listing 3	14	<code>\OpsClear[\keyval list]</code>	14
Replaced:		Replaced: <code>\Restore</code> by <code>\Read</code>	14
<code>\OpsOptions</code> by <code>\OpsOption</code>	14	Replaced: <code>\Save</code> by <code>\Write</code>	14
Replaced:		v1.3	
<code>\{ \kvl_2 \}</code> by <code>\kvl_2</code> given that		General: Replaced: <code>\OpsNew</code> by <code>\Ops</code>	14
option type G not recommended[4]	14	Replaced: <code>\{ \tl_1 \}</code> and <code>[\tl_1]</code> by	
		<code>\< \tl_1 \></code>	14

G		$\langle tl_5 \rangle$ 5
<code>\gappto</code>	201	$\langle tl_6 \rangle$ 5
I		Expans 5
<code>\IfBooleanT</code>	195	File 6
<code>\IfValueT</code>	193, 207	Inner 6
<code>\IfValueTF</code>	398	Name 6
int commands:		Outer 6
<code>\int_case:nnTF</code>	55	Separ 6
iow commands:		Write 6
<code>\iow_close:N</code>	94, 98	
<code>\iow_new:N</code>	93	P
<code>\iow_now:Nn</code>	123	<code>\pdfcreationdate</code> 314, 315
<code>\iow_open:Nn</code>	105	prg commands:
<code>\item</code>	297, 298	<code>\prg_replicate:nn</code> 58, 89
K		prop commands:
keys commands:		<code>\prop_clear_new:N</code> 268
<code>\l_keys_choice_tl</code>	310	<code>\prop_gclear_new:N</code> 46
<code>\keys_define:nn</code>	306	<code>\prop_gput:Nnn</code> 29, 257
<code>\keys_set:nn</code>	393	<code>\prop_if_exist:NTF</code> 277
M		<code>\prop_item:Nn</code> 257, 281, 292
<code>\meta</code>	297, 298	<code>\prop_map_function:NN</code> 259
msg commands:		<code>\prop_new:N</code> 26, 286
<code>\msg_error:nnn</code>	126, 233	<code>\ProvideDocumentCommand</code> 132, 386
<code>\msg_error:nnnn</code>	69	
<code>\msg_new:nnn</code> 213, 214, 215, 216, 217, 218		Q
<code>\msg_warning:nnn</code>	225, 243, 251	quark commands:
N		<code>\q_stop</code> 9, 15, 33, 42
<code>\NeedsTeXFormat</code>	2	
<code>\NewDocumentCommand</code>	381, 390, 395, 402	R
O		<code>\Read</code> 27
<code>\Ops</code>	27	<code>\Restore</code> 27
<code>\OpsClear</code>	27	
<code>\OpsDebug</code>	27	S
<code>\OpsHook</code>	27	<code>\Save</code> 27
<code>\OpsNew</code>	27	seq commands:
<code>\OpsOption</code>	27	<code>\seq_gclear_new:N</code> 19, 82
<code>\OpsOptions</code>	27	<code>\seq_gput_right:Nn</code> 11, 292
<code>\OpsRead</code>	27	<code>\seq_if_empty:NTF</code> 47
<code>\OpsRestore</code>	27	<code>\seq_map_function:NN</code>
<code>\OpsTest</code>	27 20, 50, 146, 273, 294
options:		<code>\seq_set_from_clist:Nn</code> 166, 272
<code>*</code>	5	<code>\seq_use:Nnnn</code> 303
<code>+</code>	4	T
$\langle code_1 \rangle$	4	tl commands:
$\langle code_2 \rangle$	5	<code>\c_empty_tl</code> 48, 67, 163, 183, 185, 206
$\langle kvl_1 \rangle$	4	<code>\tl_count:n</code> 78
$\langle tl_1 \rangle$	4	<code>\tl_gset:Nn</code> 104, 221, 229, 239, 313
$\langle tl_2 \rangle$	4	<code>\tl_gset_eq:NN</code> 310
$\langle tl_3 \rangle$	5	<code>\tl_log:n</code> 111, 124
$\langle tl_4 \rangle$	5	<code>\tl_new:N</code> 32, 101, 118
		<code>\tl_trim_spaces:n</code> 11, 37, 38

	U		<code>\use_ii:nn</code>	62
use commands:			<code>\usepackage</code>	4
	<code>\use:N</code>	36, 404	W	
	<code>\use_i:nn</code>	61, 63	<code>\Write</code>	27

Part IV

Implementation

```

1 <@@=ccool>
2 \NeedsTeXFormat{LaTeX2e}[2019/10/01]
3 \ExplSyntaxOn

```

1 aux

```

\__ccool_aux_inner_set:n #1: <code>

4 \cs_new_protected:Nn \__ccool_aux_inner_set:n
5 {
6   \cs_gset:Npn \__ccool_aux_inner:n ##1 {#1}
7   \cs_generate_variant:Nn \__ccool_aux_inner:n { e }
8 }

(End definition for \__ccool_aux_inner_set:n.)

\__ccool_aux_key:w #1: <key>
#2: <value>

9 \cs_new_protected:Npn \__ccool_aux_key:w #1 = #2 \q_stop
10 {
11   \seq_gput_right:Nx \g__ccool_aux_key_seq { \tl_trim_spaces:n{#1} }
12 }

(End definition for \__ccool_aux_key:w.)

\__ccool_aux_key:n #1: <key = value>

13 \cs_new_protected:Nn \__ccool_aux_key:n
14 {
15   \__ccool_aux_key:w #1 \q_stop
16 }

(End definition for \__ccool_aux_key:n.)

\__ccool_aux_key:N #1: <seq>

17 \cs_new_protected:Nn \__ccool_aux_key:N
18 {
19   \seq_gclear_new:N \g__ccool_aux_key_seq
20   \seq_map_function:NN #1 \__ccool_aux_key:n
21 }

(End definition for \__ccool_aux_key:N.)

\__ccool_aux_outer_set:n #1: <inline code>

22 \cs_new_protected:Nn \__ccool_aux_outer_set:n
23 {
24   \cs_gset:Npn \__ccool_aux_outer:n ##1 {#1}
25 }

(End definition for \__ccool_aux_outer_set:n.)

```

```

\__ccool_aux_prop:nn
26 \prop_new:N \g__ccool_aux_prop
27 \cs_new_protected:Nn \__ccool_aux_prop:nn
28 {
29   \prop_gput:Nnn \g__ccool_aux_prop{#1}{#2}
30 }
31 \cs_generate_variant:Nn \__ccool_aux_prop:nn { eo, ee, ex, xo, xe, xx }

(End definition for \__ccool_aux_prop:nn.)

```

```

\__ccool_aux_prop:w #1 : < key >
#2 : < value >

32 \tl_new:N \g__ccool_option_expans_tl
33 \cs_new_protected:Npn \__ccool_aux_prop:w #1 = #2 \q_stop
34 {
35   \exp_args:Nx
36   \use:c{\__ccool_aux_prop:\g__ccool_option_expans_tl}
37   { \tl_trim_spaces:n{#1} }
38   { \__ccool_aux_inner:n{ \tl_trim_spaces:n{#2} } }
39 }

(End definition for \__ccool_aux_prop:w.)

```

```

\__ccool_aux_prop:n #1 : < key = value >

40 \cs_new_protected:Nn \__ccool_aux_prop:n
41 {
42   \__ccool_aux_prop:w #1 \q_stop
43 }

(End definition for \__ccool_aux_prop:n.)

```

```

\__ccool_aux_prop:N #1 : < keyval list >

44 \cs_new_protected:Nn \__ccool_aux_prop:N
45 {
46   \prop_gclear_new:N \g__ccool_aux_prop
47   \seq_if_empty:NTF #1
48   { \c_empty_tl }
49   {
50     \seq_map_function:NN #1 \__ccool_aux_prop:n
51   }
52 }

(End definition for \__ccool_aux_prop:N.)

```

```

\__ccool_aux_separ:nn #1 : < int >
#2 : < tokens >

53 \cs_new:Nn \__ccool_aux_separ:nn
54 {
55   \int_case:nnTF {#1}
56   {
57     {1}
58     { \prg_replicate:nn{ 3 }{#2} }
59     {2}
60     {

```

```

61     { \use_i:nn #2 }
62     { \use_ii:nn #2 }
63     { \use_i:nn #2 }
64   }
65   {3}{#2}
66 }
67 { \c_empty_tl }
68 {
69   \msg_error:nnnn { __erw }
70   { separ }
71   { \exp_not:N \__ccool_aux_separ:nn }
72   {#2}
73 }
74 }
75 \cs_generate_variant:Nn \__ccool_aux_separ:nn { e }

```

(End definition for __ccool_aux_separ:nn.)

```

\__ccool_aux_separ:n #1: < tokens >
76 \cs_new:Nn \__ccool_aux_separ:n
77 {
78   \__ccool_aux_separ:en{ \tl_count:n{#1} }{#1}
79 }

```

(End definition for __ccool_aux_separ:n.)

```

\__ccool_aux_val:Nn #1: < seq >
#2: < tl var name >
80 \cs_new_protected:Nn \__ccool_aux_val:Nn
81 {
82   \seq_gclear_new:N \g__ccool_aux_val_seq
83   \__ccool_seq_from_prop:NNn \g__ccool_aux_val_seq #1 { \__ccool_prop_name:n{#2} }
84 }

```

(End definition for __ccool_aux_val:Nn.)

2 lambda

```

\__ccool_lambda:nn [7]
85 \cs_new_protected:Npn \__ccool_lambda:nn #1 #2
86 {
87   \exp_args:NNx
88   \DeclareDocumentCommand \__ccool_lambda_expression
89   { \prg_replicate:nn { #1 } { m } }
90   {#2}
91   \__ccool_lambda_expression
92 }

```

(End definition for __ccool_lambda:nn.)

3 log

_ccool_log_close:

```

93 \iow_new:N \g__ccool_log_iow
94 \AtEndDocument{\iow_close:N \g__ccool_log_iow}
95 \bool_set_false:N \g__ccool_log_open_bool
96 \cs_new_protected:Nn \_ccool_log_close:
97 {
98   \iow_close:N \g__ccool_log_iow
99   \bool_gset_false:N \g__ccool_log_open_bool
100 }

```

(End definition for _ccool_log_close:.)

_ccool_log_open:

```

101 \tl_new:N \g__ccool_log_file_tl
102 \cs_new_protected:Nn \_ccool_log_open:
103 {
104   \tl_gset:Nx \g__ccool_log_to_tl{\g__ccool_log_file_tl}
105   \iow_open:Nn \g__ccool_log_iow {\g__ccool_log_to_tl}
106   \bool_gset_true:N \g__ccool_log_open_bool
107 }

```

(End definition for _ccool_log_open:.)

_ccool_log_read:n #1 : $\langle path \rangle$

```

108 \cs_new_protected:Nn \_ccool_log_read:n
109 {
110   \file_input:n{#1}
111   \tl_log:n{read~from~#1}
112 }
113 \cs_generate_variant:Nn \_ccool_log_read:n { e }

```

(End definition for _ccool_log_read:n.)

_ccool_log_read:

```

114 \cs_new_protected:Nn \_ccool_log_read:
115 {
116   \_ccool_log_read:e{\g__ccool_log_to_tl}
117 }

```

(End definition for _ccool_log_read:.)

_ccool_log_write:n

```

118 \tl_new:N \g__ccool_log_to_tl
119 \cs_new_protected:Nn \_ccool_log_write:n
120 {
121   \bool_if:nTF{ \g__ccool_log_open_bool }
122   {
123     \iow_now:Nn \g__ccool_log_iow {#1}
124     \tl_log:n{ write~to~#1 }
125   }
126   { \msg_error:nnnn{ __ccool }{ iow }{ \g__ccool_log_iow } }
127 }
128 \cs_generate_variant:Nn \_ccool_log_write:n { e }

```

(End definition for _ccool_log_write:n.)

4 make_key

```
__ccool_make_key:Nn #1 : < token >
#2 : < key >

129 \cs_new_protected:Nn __ccool_make_key:Nn
130 {
131   \exp_args:NNx
132   \ProvideDocumentCommand{#1}
133   { D<>{\g__ccool_option_name_tl} }
134   {
135     \__ccool_prop_item:nn{#1}{#2}
136   }
137 }
138 \cs_generate_variant:Nn __ccool_make_key:Nn {c}

(End definition for __ccool_make_key:Nn.)

__ccool_make_key:n #1 : < key >

139 \cs_new_protected:Nn __ccool_make_key:n
140 {
141   \__ccool_make_key:cn{#1}{#1}
142 }
143 \cs_generate_variant:Nn __ccool_make_key:n { e }

(End definition for __ccool_make_key:n.)

__ccool_make_key:N #1 : < seq >

144 \cs_new_protected:Nn __ccool_make_key:N
145 {
146   \seq_map_function:NN #1 __ccool_make_key:e
147 }

(End definition for __ccool_make_key:N.)
```

5 make_ccool

```
__ccool_make_ccool_exp:nnn

148 \cs_new_protected:Nn __ccool_make_ccool_exp:nnn
149 {
150   \__ccool_aux_val:Nn \g__ccool_aux_key_seq {#1}
151   \__ccool_aux_outer_set:n{#3}
152   \__ccool_aux_outer:n
153   {
154     \exp_args:NNf
155     \__ccool_seq_use:Nn
156     \g__ccool_aux_val_seq
157     {#2}
158   }
159 }

(End definition for __ccool_make_ccool_exp:nnn.)
```

`_ccool_make_ccool_key:nnn`

```

160 \cs_new_protected:Nn \_ccool_make_ccool_key:nnn
161 {
162   \_ccool_prop_if_exist:nTF{#1}
163   { \c_empty_tl }
164   { \_ccool_prop_new:n{#1} }
165   \exp_args:No \_ccool_aux_inner_set:n{#2}
166   \seq_set_from_clist:Nn \g__ccool_aux_keyval_seq {#3}
167   \_ccool_aux_prop:N \g__ccool_aux_keyval_seq
168   \_ccool_prop_append:Nn \g__ccool_aux_prop {#1}
169   \_ccool_aux_key:N \g__ccool_aux_keyval_seq
170   \_ccool_make_key:N \g__ccool_aux_key_seq
171 }

```

(End definition for `_ccool_make_ccool_key:nnn`.)

`_ccool_make_ccool_sideeffect:nnn` [9]

```

172 \cs_new_protected:Nn \_ccool_make_ccool_sideeffect:nnn
173 {
174   \_ccool_make_ccool_key:nnn{#1}{#2}{#3}
175   \bool_if:nTF{ \g__ccool_log_open_bool }
176   {%~A https://tex.stackexchange.com/questions/536597
177     \_ccool_log_write:n
178     {
179       \begingroup
180       \def \_ccool_log_entry { \Ccool<#1>i{#2}{#3} } \expandafter
181       \endgroup \_ccool_log_entry
182     }
183   }{\c_empty_tl}
184 }

```

(End definition for `_ccool_make_ccool_sideeffect:nnn`.)

`_ccool_make_ccool:nnnn`

```

#1 : < token list >
#2 : < seq1 >
#3 : < seq2 >
#4 : < prop >

185 \def\CcoolHook{\c_empty_tl}
186 \cs_new_protected:Npn \_ccool_make_ccool:nnnn #1 #2 #3 #4
187 {
188   \exp_args:NNx \DeclareDocumentCommand \Ccool
189   {%~A      2      3      4 5 6      7 8      9
190     D<>{#1} +o E{ i }{{#2}} m t+ s E{ s o }{{#3}{#4}} +o
191   }
192   {
193     \IfValueT{##2}{##2}
194     \_ccool_make_ccool_sideeffect:nnn{##1}{##3}{##4}
195     \IfBooleanT{##6}
196     {
197       \_ccool_make_ccool_exp:nnn{##1}{##7}{##8}
198     }
199     \bool_if:nTF{##5}
200     {
201       \gappto{\CcoolHook}

```



```

202     {
203       \__ccool_make_ccool_sideeffect:nnn{##1}{##3}{##4}
204     }
205   }
206   {\c_empty_tl}
207   \IfValueT{##9}
208   {
209     \exp_not:n{ \Ccool<##1>[##9] }
210   }
211 }
212 }

```

(End definition for __ccool_make_ccool:nnnn.)

6 msg

```

213 \msg_new:nnn {\__ccool}{ generic }{#1}
214 \msg_new:nnn {\__ccool}{ iow }{#1~is~closed~can't~write}
215 \msg_new:nnn {\__ccool}{ keyonly }{#1~does~not~take~values;~keyval~is~#2}
216 \msg_new:nnn {\__ccool}{ keywrong }{#1~does~not~recognize~key~#2}
217 \msg_new:nnn {\__ccool}{ separ }{#1~expects~1~to~3~items,~#2}
218 \msg_new:nnn {\__ccool}{ unset }{#1~unset}

```

7 option

__ccool_aux_inner:n #1 : *<code>*

```

219 \cs_new_protected:Nn \__ccool_option_inner:n
220 {
221   \tl_gset:Nn \g__ccool_option_inner_tl {#1}
222 }
223 \__ccool_option_inner:n
224 {
225   \msg_warning:nnn{ __ccool }{ unset }{ \exp_not:N \g__ccool_option_inner_tl }
226 }

```

(End definition for __ccool_aux_inner:n.)

__ccool_option_name:n #1 : *<token list>*

```

227 \cs_new:Nn \__ccool_option_name:n
228 {
229   \tl_gset:Nn \g__ccool_option_name_tl{#1}
230 }
231 \__ccool_option_name:n
232 {
233   \msg_error:nnx{ __ccool }
234   { generic }
235   { \exp_not:N\g__ccool_option_name_tl~undefined }
236 }

```

(End definition for __ccool_option_name:n.)

```

\__ccool_option_outer:n #1 :  $\langle inline\ code \rangle$ 
237 \cs_new_protected:Nn \__ccool_option_outer:n
238 {
239   \tl_gset:Nn \g__ccool_option_outer_tl {#1}
240 }
241 \__ccool_option_outer:n
242 {
243   \msg_warning:nnn{__ccool}{unset}{\exp_not:N \g__ccool_option_outer_tl}
244 }

```

(End definition for __ccool_option_outer:n.)

```

\__ccool_option_separ:n #1 :  $\{\langle tl_1 \rangle\}\{\langle tl_2 \rangle\}\{\langle tl_3 \rangle\}$ 
245 \cs_new_protected:Nn \__ccool_option_separ:n
246 {
247   \cs_gset:Npn \g__ccool_option_separ_tl {#1}
248 }
249 \__ccool_option_separ:n
250 {
251   \msg_warning:nnn{__ccool}{unset}{\exp_not:N \g__ccool_option_separ_tl}
252 }

```

(End definition for __ccool_option_separ:n.)

8 prop

```

\__ccool_prop_append:NN #1 :  $\langle prop_1 \rangle$ 
#2 :  $\langle prop_2 \rangle$ 
253 \cs_new_protected:Npn \__ccool_prop_append:NN #1 #2
254 {
255   \cs_set:Nn \__ccool_prop_append:nn
256   {
257     \prop_gput:Nnx #1 {##1}{\prop_item:Nn #2{##1}}
258   }
259   \prop_map_function:NN #2 \__ccool_prop_append:nn
260 }
261 \cs_generate_variant:Nn \__ccool_prop_append:NN {cN}

```

(End definition for __ccool_prop_append:NN.)

```

\__ccool_prop_append:Nn #1 :  $\langle prop \rangle$ 
#2 :  $\langle tl\ var\ name \rangle$ 
262 \cs_new_protected:Nn \__ccool_prop_append:Nn
263 {
264   \__ccool_prop_append:cN{ \__ccool_prop_name:n {#2} } #1
265 }

```

(End definition for __ccool_prop_append:Nn.)

```

\__ccool_prop_clear_new:n #1 :  $\langle tl\ var\ name \rangle$ 
266 \cs_new_protected:Nn \__ccool_prop_clear_new:n
267 {
268   \exp_args:No \prop_clear_new:c{ \__ccool_prop_name:n {#1} }
269 }

```

(End definition for _ccool_prop_clear_new:n.)

```
\_ccool_prop_clear_new_map:n #1 : < keyval list >
270 \cs_new_protected:Nn \_ccool_prop_clear_new_map:n
271 {
272   \seq_set_from_clist:Nn \g__ccool_aux_key_seq {#1}
273   \seq_map_function:NN \g__ccool_aux_key_seq \_ccool_prop_clear_new:n
274 }
```

(End definition for _ccool_prop_clear_new_map:n.)

```
\_ccool_prop_if_exist:nTF #1 : < tl_1 >
#2 : < tl_2 >
#3 : < tl_3 >
275 \cs_new:Nn \_ccool_prop_if_exist:nTF
276 {
277   \prop_if_exist:cTF{ \_ccool_prop_name:n {#1} }{#2}{#3}
278 }
```

(End definition for _ccool_prop_if_exist:nTF.)

```
\_ccool_prop_item:nn #1 : < tl var name >
#2 : < key >
279 \cs_new:Nn \_ccool_prop_item:nn
280 {
281   \prop_item:cn { \_ccool_prop_name:n {#1} } {#2}
282 }
```

(End definition for _ccool_prop_item:nn.)

```
\_ccool_prop_name:n #1 : < tl var name >
283 \cs_new:Npn \_ccool_prop_name:n #1{ __ccool_#1 }
```

(End definition for _ccool_prop_name:n.)

```
\_ccool_prop_new:n #1 : < tl var name >
284 \cs_new_protected:Nn \_ccool_prop_new:n
285 {
286   \prop_new:c{ \_ccool_prop_name:n {#1} }
287 }
```

(End definition for _ccool_prop_new:n.)

9 seq

```

\__ccool_seq_from_prop:NNn #1: < seq1 >
#2: < seq2 > (keys)
#3: < prop >

288 \cs_new_protected:Nn \__ccool_seq_from_prop:NNn
289 {
290   \cs_set_protected:Nn \__ccool_seq_from_prop:n
291   {
292     \seq_gput_right:No #1 { \prop_item:cn{#3}{##1} }
293   }
294   \seq_map_function:NN #2 \__ccool_seq_from_prop:n
295 }

```

(End definition for __ccool_seq_from_prop:NNn.)

```

\__ccool_erw_seq_use:Nn

296 % \begin{arguments}
297 % \item \meta{ seq }
298 % \item \meta{ tokens }
299 % \end{arguments}
300 \cs_new:Nn \__ccool_seq_use:Nn
301 {
302   \exp_last_unbraced:NNf
303   \seq_use:Nnnn #1
304   \__ccool_aux_separ:n{#2}
305 }

```

(End definition for __ccool_erw_seq_use:Nn.)

10 Front-end

```

306 \keys_define:nn { __ccool }
307 {
308   Expans .multichoices:nn =
309   { eo, ee, ex, xo, xe, xx }
310   { \tl_gset_eq:NN \g__ccool_option_expans_tl \l_keys_choice_tl },
311   Expans .default:n = { xo },
312   Expans .initial:n = { xo },
313   File .code:n = { \tl_gset:Nn \g__ccool_log_file_tl{ \exp_not:n{ #1 } } },
314   File .default:n = { ccool\pdfcreationdate },
315   File .initial:n = { ccool\pdfcreationdate },
316   Name .code:n={
317     \__ccool_option_name:n{#1}
318     \exp_last_unbraced:Nf
319     \__ccool_make_ccool:nnnn
320     {
321       { \g__ccool_option_name_tl }
322       { \g__ccool_option_inner_tl }
323       { \g__ccool_option_separ_tl }
324       { \g__ccool_option_outer_tl }
325     }
326   },

```

```

327 Name .value_required:n = false,
328 Name .default:n = { Math },
329 Name .initial:n = { Math },
330 Inner .code:n={
331   \__ccool_option_inner:n{#1}
332   \exp_last_unbraced:Nf
333   \__ccool_make_ccool:nnnn
334   {
335     { \g__ccool_option_name_tl }
336     { \g__ccool_option_inner_tl }
337     { \g__ccool_option_separ_tl }
338     { \g__ccool_option_outer_tl }
339   }
340 },
341 Inner .value_required:n = false,
342 Inner .default:n = {####1},
343 Inner .initial:n = {####1},
344 Outer .code:n={
345   \__ccool_option_outer:n{#1}
346   \exp_last_unbraced:Nf
347   \__ccool_make_ccool:nnnn
348   {
349     { \g__ccool_option_name_tl }
350     { \g__ccool_option_inner_tl }
351     { \g__ccool_option_separ_tl }
352     { \g__ccool_option_outer_tl }
353   }
354 },
355 Outer .value_required:n = false,
356 Outer .default:n = { \ensuremath{####1} },
357 Outer .initial:n = { \ensuremath{####1} },
358 Write .code:n = {
359   \bool_if:nTF{#1}
360   {\__ccool_log_open:}
361   {\__ccool_log_close:}
362 },
363 Write .value_required:n = false,
364 Write .default:n = \BooleanFalse,
365 Write .initial:n = \BooleanFalse,
366 Separ .code:n={
367   \__ccool_option_separ:n{#1}
368   \exp_last_unbraced:Nf
369   \__ccool_make_ccool:nnnn
370   {
371     { \g__ccool_option_name_tl }
372     { \g__ccool_option_inner_tl }
373     { \g__ccool_option_separ_tl }
374     { \g__ccool_option_outer_tl }
375   }
376 },
377 Separ .value_required:n = false,
378 Separ .default:n = { {\ }and{\ } } { ,{\ } } { ,{\ }and{\ } },
379 Separ .initial:n = { {\ }and{\ } } { ,{\ } } { ,{\ }and{\ } }
380 }

```

\CcoolClear #1 : $\langle \text{tl var name} \rangle$

```
381 \NewDocumentCommand{ \CcoolClear }
382 { D<>{\g__ccool_option_name_tl} }
383 {
384   \__ccool_prop_clear_new_map:n{#1}
385 }
```

(End definition for \CcoolClear. This function is documented on page 5.)

\CcoolLambda

```
386 \ProvideDocumentCommand \CcoolLambda { 0{1} m }
387 {
388   \__ccool_lambda:nn { #1 } { #2 }
389 }
```

(End definition for \CcoolLambda. This function is documented on page 6.)

\CcoolOption

```
390 \NewDocumentCommand{ \CcoolOption }
391 { m }
392 {
393   \keys_set:nn{ __ccool }{#1}
394 }
```

(End definition for \CcoolOption. This function is documented on page 6.)

\CcoolRead

```
395 \NewDocumentCommand{\CcoolRead}
396 {o}
397 {
398   \IfValueTF{#1}
399   {\__ccool_log_read:e{#1}}
400   {\__ccool_log_read:}
401 }
```

(End definition for \CcoolRead. This function is documented on page 7.)

\CcoolVers

```
402 \NewDocumentCommand{\CcoolVers}
403 {}
404 {\use:c{ver@ccool.sty}}
```

(End definition for \CcoolVers. This function is documented on page 7.)

11 Misc

```
405 \ExplSyntaxOff
```