

OTHER PUBLISHER APIS

Analytics Standard API

The PubMatic Analytics API lets you view and interact with data insights to improve ad performance. You can easily integrate PubMatic APIs using simple HTTP GET requests to the PubMatic Analytics API Server. Mandatory and optional parameters in the query string, such as dimensions, metrics, and filters, let you control the scope of the JSON results PubMatic returns.

Getting started

Before using PubMatic APIs, first, generate your API Access Token. For more information, see [Getting Started](#).

Time-To-Live for Data (TTL)

Daily: The API Data Pull supports daily data for the last 90 days.

Monthly: The API Data Pull supports monthly data for the last 13 months.

Reporting data availability

Yesterday's data is available by **5 AM local time**, with the following exceptions:

Available at 9 AM local time:

Identity reporting
Wrapper reporting
Video metrics

Available at 1 PM PST:

Viewability metrics

Accounts sending more than 2,000 requests per day may get throttled

Contact your PubMatic account manager, if you need to send more than 2,000 requests a day. For WebHook data pull, a user can submit up-to 12 data pull requests per calendar hour - more details on the WebHook page.

See [Webhook data pull](#) for our Webhook guide. WebHook provides more flexibility because it can retrieve bulk-data for multiple topics.

Request

URI: `http://${URI_PREFIX}/v1/analytics/data/publisher/{publisherId}`

HTTP METHOD: GET

Remember

To complete your API endpoint, replace the placeholder `${URL_PREFIX }` with your actual target domain; for example, replace `${URL_PREFIX}` with, `api.pubmatic.com`.

Request Headers

Header name	Type	Value	Required	Description
Authorization	String	<code>`Bearer \${access_token} Y`</code>	Yes	Send your generated access token in place of <code>\${access_token}</code> for authentication. Example: <code>curl "http://api.pubmatic.com/v1/analytics/data/publisher/xxxxx?dateUnit=date&dimensions=siteld&filters=&fromDate=2015-01-01T00:00&metrics=revenue,paidImpressions,ecpm&pageSize=10&sort=-revenue&toDate=2015-01-31T23:59" -H "Authorization: Bearer BDxxx9d"</code>

Request Path Parameters

Name	Type	Required	Validations	Description
<code>publisherId</code>	Integer	Yes	Publishers can only query their own data.	Indicates the publisher ID.

Request Query Parameters

The following table lists parameters you can use to build requests.

Parameter name	Type	Required	Description
<code>fromDate</code>	string	Yes	Start date of data retrieval. Example: <code>2013-03-01T00:00</code> PubMatic uses this standard date format even if the <code>dateUnit</code> parameter is different.
<code>toDate</code>	string	Yes	End date of data retrieval. Example: <code>2015-03-29T23:59</code> The conclusion time on the final end date (in this example, 3-29) should be 23:59. A date and time format of <code>03-30T00:00</code> would return some data from 3-30.
<code>compFromDate</code>	string	No	Comparison period start date.
<code>compToDate</code>	string	No	Comparison period end date. The <code>compFromDate/compToDate</code> period should be within the same timespan as the original <code>fromDate/toDate</code> period.
<code>dimensions</code>	string	No	Dimensions are attributes available in the PubMatic system. Acceptable values: <code>date</code> <code>adFormatId</code> <code>adSizeId</code> <code>subAdFormatId</code> <code>advertiserId</code> <code>bundledDealMetaId</code>

Parameter name	Type	Required	Description
			atdId dspId dealMetaId channelId platformId countryId Example: <dim1>,<dim2>
metrics	string	Yes	Metrics measure specified dimensions. Acceptable values: ctr clicks paidImpressions revenue ecpm In case of multiple entries, use a comma-separated format. Example: <metric1>,<metric2>
sort	string	No	By default, the sort order is ascending. To change to descending, prefix a minus sign to the requested field. Example: To determine which sites provide the most paidImpressions with the fewest zero bids, use sort=-paidImpressions,totalBidRequests Use the sort parameter only with measurements included in the metrics list.
filters	string	No	For more information on filters, see Using Filters and Search to Locate a Rule
dateUnit	string	No	The date unit to query in the aggregation. Possible options are: hour date month Not all dimensions are supported for the hourly view. If your query returns null results when you include hours in the fromDate and toDate fields try using the date range only. Start date of data retrieval Example: 2020-01-25 End date of data retrieval Example: 2020-01-25
dataType	string	No	Send dataType=wrapper to pull OpenWrap data.
pageSize	integer	No	The maximum number of rows to include in the response. Example: "40" returns up to 40 rows If page size is unspecified, then page size defaults to 256000 rows.
fluidTimezone	string	No	indicates the timezone in which you want to receive data. By default, data is returned in the Pacific Standard Time (PST)

Parameter name	Type	Required	Description
			timezone. If you want data in another timezone, you should set 'isFluidTimezoneSupported' to 'true' and specify your timezone ID in the <code>fluidTimezone</code> parameter, e.g., America/New_York .

Response

Header Name	Type	Description
Content-Type	application/json	JSON response Response Body Parameters

Response Body Parameters

The following table lists parameters returned in API responses.

Body Parameter	Type	Description
alert	string	Alert message from server. In most cases, it will be null. Example: "alert": null
columns	string	Dimension and metrics columns. Please see the relevant reference section for a complete list of dimensions and metrics and their limitations. Example: "columns": ["dealMetald", "revenue", "paidImpressions", "ecpm"]
dataFreshness	object	The date on which the settings of the dataset were last updated. Example: "dataFreshness": { "dataFreshnessHour": "2015-03-12T04", "timeZone": "PST" },
displayValue	object	The display value of the "ID." Example: dealMetald "13497" has a description (name) of "xxx" "displayValue": { "dealMetald": { "13497": "xxx", "16083": "yyy",
rows	array of array	The records below would be presented in columns, ["dealMetald","publisherDealId," "revenue," "paidImpressions," "ecpm"] "rows": [["16651", "PM-XXX339", 83365.114596, 10126407.0, 8.232448],

Body Parameter	Type	Description
		Example: <pre> "columns": ["dealMetaId", "publisherDealId", "revenue"], "rows": [["10534", "PM-SUU63339", 0]] </pre>

HTTP Status Codes

The table below lists common HTTP status codes sent in REST API responses from the PubMatic API platform.

Status	Message	Type	Description
200	Ok	success	The request has been successfully processed; check contents of body.
400	Bad Request	client-side error	There is some validation failure; check the response body for error details.
401	Unauthorized		There is an authentication or authorization failure; check the response body for specific details.
403	Forbidden		You are not subscribed to this feature of the Platform.
404	Not found		The server does not have this resource.
413	Request Entity Too Large		The request content exceeds the size limit. This may be the number of records or the actual content size.
500	Internal Server Error	API-side error	There is problem in the PubMatic API Platform. Please contact the PubMatic API support team.

Available Dimensions

Dimensions are attributes, such as Country, Platform, and Site, available in the PubMatic system. The following tables provide information about dimension grouping.

Update for supported dimensions

PubMatic continuously adds new data points to meet industry demands and deprecates less relevant ones. As of October 4, 2022, PubMatic's Analytics API no longer supports the dimensions `foldPositionId` and `secureStatus` for Publisher data.

Dimensions for Historic Data

Dimension	Data type	Description
adFormatId	numeric	Type of Ad associated with the impression (e.g., video display).
adNetworkGroupId	numeric	Name of the parent Ad Network that monetized the impression.

Dimension	Data type	Description
adNetworkVariantId	numeric	Name of the parent Ad Network's campaign that monetized the impression.
adSizeId	numeric	Size of the ad associated with the impression (e.g., 200 × 800)
adTagId	numeric	Name of the ad tag used when an impression was requested.
advertiserCategoryId	numeric	Category of the advertiser.
advertiserId	numeric	Name of the advertiser associated with the ad. Advertisers spending on "Reseller" will appear as "Reseller - Advertiser" for DSP and Buyers.
appDomain	string	The URL, app ID, or bundle ID from which the ad request originated. Note This dimension can only be combined with the following dimensions: Date Month Advertiser Publisher Buyer Channel Country Deal DSP Platform This dimension can only be combined with the following metrics: Clicks Click through rate Revenue Net Revenue Paid Impressions eCPM Net eCPM Video through rate Formula:(video complete count * 100)/ paid impressions 25% view 50% view 75% view Completed
atdId	numeric	Name of the agency, ATD or buyer associated with the DSP that won the impression.
campaignId	numeric	Campaign of the advertiser associated with the ad.
categoryId	numeric	Category of the site from which an impression was requested.
channelId	numeric	Sales channel through which the impression was won (e.g., RTB, PMP).
channelTypeId	alphanumeric	Channel type through which the impression was won (example: PMP, PMP Preferred, PG). Supported only with dealMetad.
cookied	boolean	Indicates whether or not the DSP's cookies were dropped when an impression was requested.

Dimension	Data type	Description
countryId	numeric	Country from which an impression was requested. (Refer to How Countries are Reported in Analytics Reports for more information) This dimension is not available in hourly view. You must query using date range only.
creativeId	numeric	The creative id delivered in the ad response. This applies to video ads ONLY.
date	string	Date (YYYY-MM-DD format) on which an impression was requested.
dealCategoryId	alphanumeric	Deal type through which the impression was won (example: Auction Package, PMP). Supported only with dealMetaId.
dealMetaId	numeric	Name of the Marketplace Deal that won the impression. This is the numeric ID that the PubMatic system uses to track the Deal. Note This dimension can only be combined with the following dimensions: Ad Format Ad Size Advertiser appDomain Buyer Category Channel Type Deal Source Deal Type DSP Platform Site Date Hour
dealSourceId	alphanumeric	Source of deal through which the impression was won (example: PubMatic, Publisher). Supported only with dealMetaId.
domainId	numeric	Domain name (web addresses) of the advertiser. The domains are identified by the landing page of the impression displayed.
dspId	numeric	Name of the DSP that won the impression.
hour	string	Time (YYY-MM-DD'T'HH format) at which an impression was received.
mobDeviceIdFlag	boolean	Indicates whether the visitor's Device ID is present in the impression requests.
mobDeviceIdTypeId	boolean	Type of Device ID used by the visitor to generate an impression request.
mobDeviceTypeId	boolean	Type of Device used by the visitor to generate an impression request.
mobGeoSourceFlag	boolean	Source that provided the visitor's geographical location.
mobLatLongFlag	boolean	Indicates whether the visitor's latitude/longitude details were included in the impression request.

Dimension	Data type	Description
mobMakeModelId	numeric	Mobile Make/Model Id.
mobOsId	numeric	Mobile Operating System Id.
month	string	Month (YYYY-MM format) at which an impression was received .
pageURL	string	Specifies the Uniform Resource Locator for the page.
pbReason	numeric	Reason for Passback.
platformId	numeric	Platform through which an impression was requested (e.g., Web, Mobile Web)
publisherDealId	string	The Publisher Deal Id. This is the alphanumeric value that is used by publishers which is also sent over RTB pipes. publisherDealId is currently only supported when the request also contains dealMetad. Example: dimensions=dealMetad,publisherDealId will return a column for dealMetad another for publisherDealId and then the metrics. Sending this dimension standalone isn't currently supported.
sectionId	numeric	Section of the site from which an impression was requested.
siteId	numeric	ID of the site from which an impression was requested.
tldEntity	numeric	Top level domain Entity. Applicable in the case of mobile impressions.
tldId	numeric	Top level domain.
videoClientId	numeric	This will be present when a video tracker (e.g. event, impression, error) is fired by the PubMatic VPAID component. This ID will represent whether it is a Flash VPAID component (1) or HTML/JS VPAID component (2), otherwise if not present (NULL) it means the PubMatic VPAID component was not present.
videoErrorId	numeric	Video Error Code. Includes the IAB VAST error codes along with PubMatic custom video error codes that provide more granularity for debugging.
videoEventId	numeric	Event id represents the type of video tracker event that was fired by the video player. Events can include start event, click event, 25%, 50%, completion, etc.

Not all dimensions and metrics are supported together...

For more information and verification, log in to PubMatic Analytics UI.

Dimensions for Rule Data (RTB Rules Report)

Dimension ID	Data type	Description
campaignId	numeric	Campaign of the advertiser associated with the ad.
date	string	Date (YYYY-MM-DD format) on which an impression was requested.
pubId	integer	Publisher associated with the impression requests.
ruleId	numeric	Winning Rule ID and Ad Server logs.
ruleMetaId	numeric	Rule Meta ID for PMPF rule type.

Dimension ID	Data type	Description
siteId	numeric	ID of the site from which an impression was requested.

Dimensions for Identity data

Dimension	Data type	Description
date	string	Date (YYYY-MM-DD format) on which an impression was requested.
pubId	integer	Publisher associated with the impression requests.
adFormatId	numeric	Type of Ad associated with the impression (e.g., video display).
platformId	numeric	Platform through which an impression was requested (e.g., Web, Mobile Web).
BrowserId	numeric	Browser through which an impression was requested (e.g., Chrome, Safari, Firefox).
GDPRConsent	numeric	Indicates whether GDPR consent is provided or not (where applicable).
PartnerId	numeric	Identity Partner (for example, TTD ID, Criteo ID, PubCommon ID).
IdentityPartnerFlag	string	Indicates whether the Identity information is received in the impression (Yes/No).
PubToPubmaticCookie	numeric	Indicates whether the publisher to PubMatic cookie data is received in the impression (Yes/No).
dspid	integer	Indicates the DSP ID.
PubmaticToDspCookie	string	indicates whether the DSP cookie data is available for the impression (Yes/No).

Available Metrics

The following tables list available metrics for publisher bulk-data.

Metrics for Historic Data

avgPubmaticBidsEcpm	numeric	Average CPM of the bid responses from Pubmatic
averageBidEcpmAdv	numeric	Average CPM of the bid responses associated with an advertiser.
averageBidEcpmAtd	numeric	Average CPM of the bid responses associated with a buyer.
averageBidEcpmDsp	numeric	Average CPM of the bid responses received from a DSP.
pbImpressions	numeric	Number of impressions sent back to the publisher's passback networks because they were not monetized by the ad networks configured in the PubMatic system.
bidPercentageDsp	numeric	Number of bids responded as % of bid request sent. Formula : $\text{bidPercentageDsp} = (\text{nonZeroBidResponses} / \text{totalBidsRequests}) * 100$
bidWinRateAdv	numeric	Rate of won bids expressed as a percentage of total bids for advertiser. Formula : $\text{bidWinRateAdv} = \text{paidImpressions} * 100 / \text{nonZeroBidReceived}$
bidWinRateAtd	numeric	A buyer's paid impressions divided by non-zero bids received, expressed as a percentage. Formula : $(\text{Paid} / \text{nonZeroBidsReceived}) * 100$

		Impressions * 100) / Non-Zero Bids Received
bidWinRateDsp	numeric	A DSP's paid impressions divided by non-zero bid responses, expressed as a percentage. Formula: (Paid Impressions * 100) / Non-Zero Bid Responses
clicks	numeric	Number of paid impressions clicked by users.
ctr	numeric	Effectiveness of an ad based on the number of clicks it receives compared to the number of times it is displayed. Formula :clicks / paidImpressions *100
defaults	numeric	Number of impressions not served (defaulted) by an ad network configured in the PubMatic system.
ecpm	numeric	Average CPM (cost per thousand) for the impressions.
fillRate	numeric	Percentage of times an ad is displayed to the visitor. Higher rates are better.
gEcpm	numeric	Gross eCPM.
lostBidsAmountByAuction	numeric	Amount of the bid responses that lost to the winning bid response in the auction.
lostBidsAmountByBlockList	numeric	Amount of the bid responses that lost to the winning bid response in the Brand Control blocklist.
lostBidsAmountByCBLK	numeric	Lost Bid Amount (Creative Block).
lostBidsAmountByDWLF	numeric	Amount of the bid responses that lost because the advertiser's associated category/name/domain was not included in the Marketplace deals.
lostBidsAmountByFloor	numeric	Amount of the bid responses that lost because their value was below the floor set in the Marketplace Rule Manager.
lostBidsByAuction	numeric	Number of bid responses that did not win the impression (lost to other bid responses from DSPs and ad networks).
lostBidsByBlockList	numeric	Number of bid responses that did not win the impression because the attributes were either included in the publisher's blocklist or not included in the publisher's allowlist.
lostBidsByCBLK	numeric	Lost Bid Count (Creative Block).
lostBidsByDWLF	numeric	Number of bid responses that did not win the impression because the associated Marketplace deal's allowlist did (DWLF) not include the advertiser.
lostBidsByFloor	numeric	Number of bid responses that did not win the impression because the demand partner's bid value was below the floor set in the Marketplace Rule Manager.
lostBidsEcpmAdv	numeric	Average CPM of the bid responses associated with an advertiser.
lostBidsEcpmAtd	numeric	Average CPM of the bid responses associated with a buyer.
lostBidsEcpmByAuction	numeric	eCPM of the bid responses that lost to the winning bid response in the auction.
lostBidsEcpmByBlockList	numeric	eCPM of the bid responses that lost because the advertiser's associated category/name/domain was added in the Brand Control blocklist.

lostBidsEcpmByDWLF	numeric	eCPM of the bid responses that lost because the advertiser's associated category/name/domain was not included in the Marketplace deals' allowlist.
lostBidsEcpmByFloor	numeric	eCPM of the bid responses which lost because their value was below the floor set in the Marketplace Rule Manager.
lostBidsEcpmDsp	numeric	eCPM of the bid responses associated with a DSP that lost the impressions.
lostBidsTotalAmount	numeric	Total amount of the bid responses that lost due to a reason other than that described in the Lost Bids Amount (Auction) metric.
measuredImpressions	numeric	Number of impressions measured by IAS.
netRevenue	numeric	Net Revenue. Applicable to only the publishers with net bidding enabled. This number is not for billing purpose, but an estimate.
neteCpm	numeric	Net eCPM. Applicable to only the publishers with net bidding enabled. This number is not for billing purpose, but an estimate.
nonZeroBidReceived	numeric	Number of bids in responses from demand partners that had a non-zero bid value. In case of multi-bid responses, each non-zero bid in the response is counted individually.
nonZeroBidResponses	numeric	Number of bid responses from demand partners that had a non-zero bid value; indicates bid responses intended to participate in the auction.
paidImpressions	numeric	Number of impressions won by the demand partner.
pbImpressionsBot	numeric	Number of impressions passed back to the publisher because requests came from a Web bot.
pbImpressionsNet	numeric	Number of impressions sent back to the publisher's passback networks because they were not monetized by the ad networks configured in the PubMatic system.
pbImpressionsNonApproved	numeric	Number of impressions passed back to the publisher because its site URL was either not included in the publisher's allowlisted domains or included in the global supply-side blocklist.
percentInViewForMoreThan15sec	numeric	(%) of Ad in viewable area more than 15 seconds.
percentInViewForMoreThan5sec	numeric	(%) of Ad in viewable area more than 5 seconds.
pubmaticBidAmount	numeric	Potential revenue generated by all Pubmatic bid responses.
viewabilityPercent	numeric	(%) of Ad in viewable area.
phantomBids	numeric	How often PubMatic bid response loses to others.
revenue	numeric	Gross Revenue amount generated by the winning impressions.
ssExpectedRevenue	numeric	Gross Potential revenue generated by all PubMatic bid responses.
ssWinningImpressions	numeric	Number of non-zero responses to the publisher. This metric shows the impression requests for which Pubmatic responded with nonzero bid responses.

suspiciousImpressions	numeric	Number of impressions marked as suspicious by IAS
totalBidAmount	numeric	Amount of the total bid responses received by the PubMatic system. Formula: Total bid responses * Avg. bid eCPM
totalBidsRequestsDsp	numeric	Total number of bid requests sent by PubMatic to a DSP.
totalImpressions	numeric	Total number of impressions sent by the publisher to the PubMatic system. This value does not include the number of defaulted impressions.
totalLostBidsAdv	numeric	Total number of advertiser bid responses that did not win the impressions.
totalLostBidsAtd	numeric	Total number of buyer bid responses that did not win the impressions.
totalLostBidsDsp	numeric	Total number of DSP bid responses that did not win the impressions.
totalRequests	numeric	Total Requests.
vctr	numeric	Click Through Rate
video25PercentCount	numeric	25% Video Count
video50PercentCount	numeric	50% Video Count
video75PercentCount	numeric	75% Video Count
videoClicksCount	numeric	Video Click Count
videoCompleteCount	numeric	Video Complete Count
videoErrorCount	numeric	Video Error Count
videoEventCount	numeric	Error Count
videoImpressions	numeric	Video Distinct Impressions
videoStartCount	numeric	Video Start Event Count
vtr	numeric	Video Through Rate
winningBidCount	numeric	Number of non-zero bid responses to publisher. If more than one bid response is received for an impression request, this metric will account for all bid responses.
winningImpressions	numeric	Number of times PubMatic responds with a bid response
winRate	numeric	PubMatic Paid Impressions/Total Requests
spend	numeric	Spend generated by an impression request.

Metrics for Domain Data

Metrics ID	Data type	Description
clicks	numeric	Number of paid impressions clicked by users.
defaults	numeric	Number of impressions not served (defaulted) by an ad network configured in the PubMatic system.
paidImpressions	numeric	Number of impressions won by the demand partner.
pbImpressions	numeric	Number of impressions sent back to the publisher's passback networks because they were not monetized by the ad networks configured in the

Metrics ID	Data type	Description
		PubMatic system.
revenue	numeric	Gross Revenue amount generated by the winning impressions.
totalRequests	numeric	Total Requests

Metrics for Rules Data

Metrics ID	Data Type	Description
paidImpressions	numeric	Number of impressions won by the demand partner.
revenue	numeric	Gross Revenue amount generated by the winning impressions.
totalRequests	numeric	Total Requests.

Metrics for Identity data

Metrics ID	Data Type	Description
PaidImpressions	numeric	Number of impressions won by the demand partner .
Revenue	numeric	Gross Revenue amount generated by the winning impressions.
TotalRequests	numeric	Total number of ad requests from the publisher.
PublisherBasedBidRequestCount	numeric	Total number of bid requests sent by PubMatic to a DSP for the publisher for which the report(s) is being generated.

 Updated 6 months ago

[← HTTP Request Parameters](#)

[Webhook data pull →](#)

Did this page help you?  Yes  No

