

MIPS Instruction Reference

This is a description of the MIPS instruction set, their meanings, syntax, semantics, and bit encodings. The syntax given for each instruction refers to the assembly language syntax supported by the MIPS assembler. Hyphens in the encoding indicate "don't care" bits which are not considered when an instruction is being decoded.

General purpose registers (GPRs) are indicated with a dollar sign (\$). The words SWORD and UWORD refer to 32-bit signed and 32-bit unsigned data types, respectively.

The manner in which the processor executes an instruction and advances its program counters is as follows:

1. execute the instruction at *PC*
2. copy *nPC* to *PC*
3. add 4 or the branch offset to *nPC*

This behavior is indicated in the instruction specifications below. For brevity, the function `advance_pc (int)` is used in many of the instruction descriptions. This function is defined as follows:

```
void advance_pc (SWORD offset)
{
    PC    =  nPC;
    nPC   += offset;
}
```

Note: ALL arithmetic immediate values are sign-extended. After that, they are handled as signed or unsigned 32 bit numbers, depending upon the instruction. The only difference between signed and unsigned instructions is that signed instructions can generate an overflow exception and unsigned instructions can not.

The instruction descriptions are given below:

ADD – Add (with overflow)

Description:	Adds two registers and stores the result in a register
Operation:	$\$d = \$s + \$t$; <code>advance_pc (4)</code> ;
Syntax:	<code>add \$d, \$s, \$t</code>
Encoding:	0000 00ss ssst tttt dddd d000 0010 0000

ADDI -- Add immediate (with overflow)

Description:	Adds a register and a sign-extended immediate value and stores the result in a register
Operation:	$\$t = \$s + \text{imm}$; <code>advance_pc (4)</code> ;
Syntax:	<code>addi \$t, \$s, imm</code>
Encoding:	0010 00ss ssst tttt iiii iiii iiii iiii

ADDIU -- Add immediate unsigned (no overflow)

Description:	Adds a register and a sign-extended immediate value and stores the result in a register
Operation:	\$t = \$s + imm; advance_pc (4);
Syntax:	addiu \$t, \$s, imm
Encoding:	0010 01ss ssst tttt iiii iiii iiii iiii

ADDU -- *Add unsigned (no overflow)*

Description:	Adds two registers and stores the result in a register
Operation:	\$d = \$s + \$t; advance_pc (4);
Syntax:	addu \$d, \$s, \$t
Encoding:	0000 00ss ssst tttt dddd d000 0010 0001

AND -- *Bitwise and*

Description:	Bitwise ands two registers and stores the result in a register
Operation:	\$d = \$s & \$t; advance_pc (4);
Syntax:	and \$d, \$s, \$t
Encoding:	0000 00ss ssst tttt dddd d000 0010 0100

ANDI -- *Bitwise and immediate*

Description:	Bitwise ands a register and an immediate value and stores the result in a register
Operation:	\$t = \$s & imm; advance_pc (4);
Syntax:	andi \$t, \$s, imm
Encoding:	0011 00ss ssst tttt iiii iiii iiii iiii

BEQ -- *Branch on equal*

Description:	Branches if the two registers are equal
Operation:	if \$s == \$t advance_pc (offset << 2)); else advance_pc (4);
Syntax:	beq \$s, \$t, offset
Encoding:	0001 00ss ssst tttt iiii iiii iiii iiii

BGEZ -- *Branch on greater than or equal to zero*

Description:	Branches if the register is greater than or equal to zero
Operation:	if \$s >= 0 advance_pc (offset << 2)); else advance_pc (4);
Syntax:	bgez \$s, offset
Encoding:	0000 01ss sss0 0001 iiii iiii iiii iiii

BGEZAL -- *Branch on greater than or equal to zero and link*

Description:	Branches if the register is greater than or equal to zero and saves the return address in \$31
Operation:	if \$s >= 0 \$31 = PC + 8 (or nPC + 4); advance_pc (offset << 2)); else advance_pc (4);
Syntax:	bgezal \$s, offset
Encoding:	0000 01ss sss1 0001 iiii iiii iiii iiii

BGTZ -- *Branch on greater than zero*

Description:	Branches if the register is greater than zero
Operation:	if \$s > 0 advance_pc (offset << 2)); else advance_pc (4);
Syntax:	bgtz \$s, offset
Encoding:	0001 11ss sss0 0000 iiii iiii iiii iiii

BLEZ -- *Branch on less than or equal to zero*

Description:	Branches if the register is less than or equal to zero
Operation:	if \$s <= 0 advance_pc (offset << 2)); else advance_pc (4);
Syntax:	blez \$s, offset
Encoding:	0001 10ss sss0 0000 iiii iiii iiii iiii

BLTZ -- *Branch on less than zero*

Description:	Branches if the register is less than zero
Operation:	if \$s < 0 advance_pc (offset << 2)); else advance_pc (4);
Syntax:	bltz \$s, offset
Encoding:	0000 01ss sss0 0000 iiii iiii iiii iiii

BLTZAL -- *Branch on less than zero and link*

Description:	Branches if the register is less than zero and saves the return address in \$31
Operation:	if \$s < 0 \$31 = PC + 8 (or nPC + 4); advance_pc (offset << 2)); else advance_pc (4);
Syntax:	bltzal \$s, offset
Encoding:	0000 01ss sss1 0000 iiii iiii iiii iiii

BNE -- *Branch on not equal*

Description:	Branches if the two registers are not equal
Operation:	if \$s != \$t advance_pc (offset << 2)); else advance_pc (4);
Syntax:	bne \$s, \$t, offset

Encoding:	0001 01ss ssst tttt iiii iiii iiii iiii
-----------	---

DIV -- *Divide*

Description:	Divides \$s by \$t and stores the quotient in \$LO and the remainder in \$HI
Operation:	$\$LO = \$s / \$t$; $\$HI = \$s \% \$t$; advance_pc (4);
Syntax:	div \$s, \$t
Encoding:	0000 00ss ssst tttt 0000 0000 0001 1010

DIVU -- *Divide unsigned*

Description:	Divides \$s by \$t and stores the quotient in \$LO and the remainder in \$HI
Operation:	$\$LO = \$s / \$t$; $\$HI = \$s \% \$t$; advance_pc (4);
Syntax:	divu \$s, \$t
Encoding:	0000 00ss ssst tttt 0000 0000 0001 1011

J -- *Jump*

Description:	Jumps to the calculated address
Operation:	$PC = nPC$; $nPC = (PC \& 0xf0000000) (target \ll 2)$;
Syntax:	j target
Encoding:	0000 10ii iiii iiii iiii iiii iiii iiii

JAL -- *Jump and link*

Description:	Jumps to the calculated address and stores the return address in \$31
Operation:	$\$31 = PC + 8$ (or $nPC + 4$); $PC = nPC$; $nPC = (PC \& 0xf0000000) (target \ll 2)$;
Syntax:	jal target
Encoding:	0000 11ii iiii iiii iiii iiii iiii iiii

JR -- *Jump register*

Description:	Jump to the address contained in register \$s
Operation:	$PC = nPC$; $nPC = \$s$;
Syntax:	jr \$s
Encoding:	0000 00ss sss0 0000 0000 0000 0000 1000

LB -- *Load byte*

Description:	A byte is loaded into a register from the specified address.
Operation:	$\$t = \text{MEM}[\$s + \text{offset}]$; advance_pc (4);

Syntax:	lb \$t, offset(\$s)
Encoding:	1000 00ss ssst tttt iiii iiii iiii iiii

LUI -- *Load upper immediate*

Description:	The immediate value is shifted left 16 bits and stored in the register. The lower 16 bits are zeroes.
Operation:	\$t = (imm << 16); advance_pc (4);
Syntax:	lui \$t, imm
Encoding:	0011 11-- ---t tttt iiii iiii iiii iiii

LW -- *Load word*

Description:	A word is loaded into a register from the specified address.
Operation:	\$t = MEM[\$s + offset]; advance_pc (4);
Syntax:	lw \$t, offset(\$s)
Encoding:	1000 11ss ssst tttt iiii iiii iiii iiii

MFHI -- *Move from HI*

Description:	The contents of register HI are moved to the specified register.
Operation:	\$d = \$HI; advance_pc (4);
Syntax:	mfhi \$d
Encoding:	0000 0000 0000 0000 dddd d000 0001 0000

MFLO -- *Move from LO*

Description:	The contents of register LO are moved to the specified register.
Operation:	\$d = \$LO; advance_pc (4);
Syntax:	mflo \$d
Encoding:	0000 0000 0000 0000 dddd d000 0001 0010

MULT -- *Multiply*

Description:	Multiplies \$s by \$t and stores the result in \$LO.
Operation:	\$LO = \$s * \$t; advance_pc (4);
Syntax:	mult \$s, \$t
Encoding:	0000 00ss ssst tttt 0000 0000 0001 1000

MULTU -- *Multiply unsigned*

--

Description:	Multiplies \$s by \$t and stores the result in \$LO.
Operation:	\$LO = \$s * \$t; advance_pc (4);
Syntax:	multu \$s, \$t
Encoding:	0000 00ss ssst tttt 0000 0000 0001 1001

NOOP -- *no operation*

Description:	Performs no operation.
Operation:	advance_pc (4);
Syntax:	noop
Encoding:	0000 0000 0000 0000 0000 0000 0000 0000

Note: The encoding for a NOOP represents the instruction SLL \$0, \$0, 0 which has no side effects. In fact, nearly every instruction that has \$0 as its destination register will have no side effect and can thus be considered a NOOP instruction.

OR -- *Bitwise or*

Description:	Bitwise logical ors two registers and stores the result in a register
Operation:	\$d = \$s \$t; advance_pc (4);
Syntax:	or \$d, \$s, \$t
Encoding:	0000 00ss ssst tttt dddd d000 0010 0101

ORI -- *Bitwise or immediate*

Description:	Bitwise ors a register and an immediate value and stores the result in a register
Operation:	\$t = \$s imm; advance_pc (4);
Syntax:	ori \$t, \$s, imm
Encoding:	0011 01ss ssst tttt iiii iiii iiii iiii

SB -- *Store byte*

Description:	The least significant byte of \$t is stored at the specified address.
Operation:	MEM[\$s + offset] = (0xff & \$t); advance_pc (4);
Syntax:	sb \$t, offset(\$s)
Encoding:	1010 00ss ssst tttt iiii iiii iiii iiii

SLL -- *Shift left logical*

Description:	Shifts a register value left by the shift amount listed in the instruction and places the result in a third register. Zeroes are shifted in.
Operation:	\$d = \$t << h; advance_pc (4);

Syntax:	sll \$d, \$t, h
Encoding:	0000 00ss ssst tttt dddd dhhh hh00 0000

SLLV -- Shift left logical variable

Description:	Shifts a register value left by the value in a second register and places the result in a third register. Zeroes are shifted in.
Operation:	\$d = \$t << \$s; advance_pc (4);
Syntax:	sllv \$d, \$t, \$s
Encoding:	0000 00ss ssst tttt dddd d--- --00 0100

SLT -- Set on less than (signed)

Description:	If \$s is less than \$t, \$d is set to one. It gets zero otherwise.
Operation:	if \$s < \$t \$d = 1; advance_pc (4); else \$d = 0; advance_pc (4);
Syntax:	slt \$d, \$s, \$t
Encoding:	0000 00ss ssst tttt dddd d000 0010 1010

SLTI -- Set on less than immediate (signed)

Description:	If \$s is less than immediate, \$t is set to one. It gets zero otherwise.
Operation:	if \$s < imm \$t = 1; advance_pc (4); else \$t = 0; advance_pc (4);
Syntax:	slti \$t, \$s, imm
Encoding:	0010 10ss ssst tttt iiii iiii iiii iiii

SLTIU -- Set on less than immediate unsigned

Description:	If \$s is less than the unsigned immediate, \$t is set to one. It gets zero otherwise.
Operation:	if \$s < imm \$t = 1; advance_pc (4); else \$t = 0; advance_pc (4);
Syntax:	sltiu \$t, \$s, imm
Encoding:	0010 11ss ssst tttt iiii iiii iiii iiii

SLTU -- Set on less than unsigned

Description:	If \$s is less than \$t, \$d is set to one. It gets zero otherwise.
Operation:	if \$s < \$t \$d = 1; advance_pc (4); else \$d = 0; advance_pc (4);
Syntax:	sltu \$d, \$s, \$t
Encoding:	0000 00ss ssst tttt dddd d000 0010 1011

SRA -- Shift right arithmetic

Description:	Shifts a register value right by the shift amount (shamt) and places the value in the destination register. The sign bit is shifted in.
Operation:	\$d = \$t >> h; advance_pc (4);
Syntax:	sra \$d, \$t, h
Encoding:	0000 00-- ---t tttt dddd dhhh hh00 0011

SRL -- *Shift right logical*

Description:	Shifts a register value right by the shift amount (shamt) and places the value in the destination register. Zeroes are shifted in.
Operation:	\$d = \$t >> h; advance_pc (4);
Syntax:	srl \$d, \$t, h
Encoding:	0000 00-- ---t tttt dddd dhhh hh00 0010

SRLV -- *Shift right logical variable*

Description:	Shifts a register value right by the amount specified in \$s and places the value in the destination register. Zeroes are shifted in.
Operation:	\$d = \$t >> \$s; advance_pc (4);
Syntax:	srlv \$d, \$t, \$s
Encoding:	0000 00ss ssst tttt dddd d000 0000 0110

SUB -- *Subtract*

Description:	Subtracts two registers and stores the result in a register
Operation:	\$d = \$s - \$t; advance_pc (4);
Syntax:	sub \$d, \$s, \$t
Encoding:	0000 00ss ssst tttt dddd d000 0010 0010

SUBU -- *Subtract unsigned*

Description:	Subtracts two registers and stores the result in a register
Operation:	\$d = \$s - \$t; advance_pc (4);
Syntax:	subu \$d, \$s, \$t
Encoding:	0000 00ss ssst tttt dddd d000 0010 0011

SW -- *Store word*

Description:	The contents of \$t is stored at the specified address.
Operation:	MEM[\$s + offset] = \$t; advance_pc (4);
Syntax:	sw \$t, offset(\$s)

Encoding:	1010 11ss ssst tttt iiii iiii iiii iiii
-----------	---

SYSCALL -- *System call*

Description:	Generates a software interrupt.
Operation:	advance_pc (4);
Syntax:	syscall
Encoding:	0000 00-- ---- ---- ---- ---- --00 1100

The syscall instruction is described in more detail on the [System Calls](#) page.

XOR -- *Bitwise exclusive or*

Description:	Exclusive ors two registers and stores the result in a register
Operation:	\$d = \$s ^ \$t; advance_pc (4);
Syntax:	xor \$d, \$s, \$t
Encoding:	0000 00ss ssst tttt dddd d--- --10 0110

XORI -- *Bitwise exclusive or immediate*

Description:	Bitwise exclusive ors a register and an immediate value and stores the result in a register
Operation:	\$t = \$s ^ imm; advance_pc (4);
Syntax:	xori \$t, \$s, imm
Encoding:	0011 10ss ssst tttt iiii iiii iiii iiii

Updated on September 10, 1998