

An UltraEdit SAS DMS Editor for SAS Compatible Systems

Roger J. DeAngelis

Table of Contents

Preface

CHAPTER I: CONFIGURATION AND ULTRAEDIT SETUP FOR SAS COMPATIBLE SYSTEMS

- I. Jenner Analytics Configuration Win 11 64-bit
 - a. Create environment variable
 - * 1. Open the environment variables dialog
 - * 2. Select Edit environment variables
 - * 3. User variables > Edit/Add
 - * 4. Enter the variable and value
 - * 5. Refresh the environment variable
 - * 6. Check the environment variable
 - b. Create a path environment variable
 - * 1. Open the environment variables dialog
 - * 2. Select edit environment variables
 - * 3. Select Environment variables
 - * 4. Add to Path in System variables
 - c. Create folder structures (sandbox)
 - * 1. c:/jnr/
 - * 2. c:/wpsoto
 - * 3. c:/wpscfig
 - * 4. d:/wpswrk
 - * 5. d:/wpswrkx
 - d. Key files
 - * 1. Copy the config file
 - * 2. Edit the local config file
 - e. Create c:/wpsoto/autoexec.sas
 - * 1. The autoexec file
 - * 2. Completion message
- II. UltraEdit Configuration Win 11 64-bit
 - a. Download and install UltraEdit
 - b. Make the Windows clipboard your default clipboard

- c. Create SAS DMS window vertical layout
- III. Run a Simple SAS Compatible Program
 - a. Turn line numbers on
 - b. Run the program
 - c. Immediate output
 - d. Save all user customizations

CHAPTER II: ULTRAEDIT KEY MAPPING FOR SAS COMPATIBLE SYSTEMS

- I. Miscellaneous
 - a. Turn line numbers on
 - b. Turn Windows clipboard on
 - c. List all default key mappings
 - d. Toggle Insert Mode and Column Mode
 - e. Automatically Update Changed Files
 - f. SAS highlighting
- II. Default Key-Mappings
 - a. Missing block copy/paste
 - b. List of default key mappings
- III. User Key Mapping — Advanced > Settings > Key Mappings
 - a. Create DMS layout lst/pgm/log
 - b. Versioning
 - c. Automatic save every minute
 - d. Assign four spaces to the Tab key
 - e. Right, Left and Center Justify
 - f. Left Align a Block of Lines
 - g. Comment a Block of SAS Code
- IV. List of Key Mappings

CHAPTER III: ULTRAEDIT MACROS AND JAVASCRIPT FOR SAS COMPATIBLE SYSTEMS

- I. Macros and Updated Move/Overlay/Insert Blocks of Code
 - a. Move/Overlay/Insert Blocks of code
 - b. Reduce multiple spaces to a single space
 - c. Using Templates to insert a box comment
- II. JavaScript Tools
 - a. Clear log and list
 - b. Setup Jenner CLI
 - c. Run highlighted code
 - d. Save program using path in line 2 of editor
- III. List of Enhanced Functionality (Full Cheat Sheet)
 - a. Block moves, shared windows hotkeys and mouse actions
 - * 1. Move/overlay a block of text
 - * 2. Copy, Paste, Cut, Undo, Redo
 - * 3. Shift text left and right
 - b. Enhanced Key Mapping

- * 1. Run Highlighted Code
- * 2. Run entire program with Jenner Analytics
- * 3. Save Program using line 2 of program
- * 4. Clear any window
- * 5. Save
- * 6. Save as
- * 7. Docked small persistent find box
- * 8. Find
- * 9. Find/replace
- * 10. Go to line
- * 11. Convert selected text to lowercase
- * 12. Convert selected text to uppercase
- * 13. Duplicate line
- * 14. Delete Line
- * 15. Multiple consecutive spaces to one space
- * 16. Select matching brackets
- * 17. Search forward
- * 18. Search backward
- * 19. Cursor to top of editor
- * 20. Cursor to bottom of editor
- * 21. Delete all lines to end of file
- * 22. Toggle Hex Mode
- * 23. Trim leading spaces
- * 24. Open an additional editor window
- * 25. Spell Check
- * 26. Find in files
- * 27. Insert datetime at cursor
- * 28. Capitalize the first letter of each word
- * 29. Word count for entire program
- * 30. Quick File Open
- * 31. Open a File
- * 32. Close all Files Open
- * 33. Save All Open Files
- * 34. Command Palette
- * 35. Help
- * 36. Run DOS Command
- * 37. Run Windows Program
- * 38. Trim Leading Spaces
- * 39. Print
- * 40. Play Macro
- * 41. Compare files
- * 42. Flow lines
- * 43. Create command box using autocomplete
- * 44. Clear log and list
- * 45. Tab 4 spaces
- * 46. Center Justify

- * 47. Left Justify
- * 48. Right Justify
- * 49. Comment out a block of existing code
- c. JavaScript and User Tools
 - * 1. Run SAS program via Jenner Analytics
 - * 2. Execute selected text via the Jenner CLI
 - * 3. Clear log and list
 - * 4. Save program using line 2 of the program
 - * 5. Multiple consecutive spaces to one
- d. Macros
 - * 1. Reduce multiple blanks to a single blank
- e. Templates
- IV. Miscellaneous
 - a. Autosave all open files every minute
 - b. Assign four spaces to the Tab key
 - c. Right, Left or Center Text
 - d. Left Align a Block of Lines
 - e. Comment a Block of SAS Code

Index

Preface

Use this ebook as an overview and spend more time with the repositories. This ebook a complete workflow for turning **UltraEdit** into a SAS Display Manager System (DMS)-style editor for SAS-compatible engines — Jenner Analytics(jnr) and Altair SLC among them — as implemented by Roger J. DeAngelis across three GitHub repositories. All three chapters assume **UltraEdit Version 2025.1.0.31 64-bit** running in the **Contemporary** menu mode (ribbon: File, Home, Edit, Format, View, Coding, Project, Layout, Window, Advanced).

GitHub: [utl-chapter-I-configuration-and-ultraedit-setup-for-sas-compatible-systems](#)

GitHub: [utl-chapter-II-ultraedit-key-mapping-for-sas-compatible-systems](#)

GitHub: [utl-chapter-III-ultraedit-macros-javascript-for-sas-compatible-systems](#)

CHAPTER I: CONFIGURATION AND ULTRAEDIT SETUP FOR SAS COMPATIBLE SYSTEMS

C:\jnr\current.lst, c:\jnr\current.sas, and c:\jnr\current.log form a sandbox. To save production code elsewhere, press **Ctrl+Alt+2** to save the program to the path given on line 2 of the editor (see Chapter III for the JavaScript behind this).

Although UltraEdit does not have a true command line, it offers three levels of automation of increasing power: (1) macro record, (2) JavaScript scripting with UltraEdit's own commands, (3) JavaScript combined with external programs like SAS, Altair SLC, or Jenner Analytics. Note: submitting a program without making any changes to it will do nothing.

I. Jenner Analytics Configuration Win 11 64-bit

a. Create environment variable

1. Open the environment variables dialog Windows 11 search box → type environment variables.

2. Select Edit environment variables

3. User variables > Edit/Add

4. Enter the variable and value

Variable	Value
Jenner Analyticsjnr_CONFIG	C:\wpscfg\ Jenner Analyticsj_local.cfg

5. Refresh the environment variable Open Task Manager (Ctrl+Alt+Delete), find *Windows Explorer*, right-click → **Restart** (this activates the path). If UltraEdit is open, close and restart it too.

6. Check the environment variable Open a DOS command window (cmd.exe) and run `echo % Jenner Analytics_CONFIG%` — it should print `C:\wpscfg\ Jenner Analytics_local.cfg`.

b. Create a path environment variable

1. Open the environment variables dialog Windows 11 search box → type environment variables.

2. Select edit environment variables

3. Select Environment variables

4. **Add to Path in System variables** Click **Path** under System variables → **Edit** → **New** → add C:\Program Files\ Jenner Analytics\jnr\2026\bin → OK → Apply. Refresh Explorer the same way as in a.5 to activate the path.

c. Create folder structures (sandbox)

1. **c:/jnr/** **current.sas** (frozen left panel), **current.log** (frozen center panel), **current.lst** (frozen right panel) in UltraEdit.

2. **c:/wpsoto** For autocall macros.

3. **c:/wpscfg** For the config file.

4. **d:/wpswrk** Temporary work directory.

5. **d:/wpswrkx** Permanent work directory.

d. Key files

1. **Copy the config file** Copy C:\Program Files\ Jenner Analytics\jnr\2026\ Jenner Analyticsjnr.cfg to C:\wpscfg\ Jenner Analyticsjnr_local.cfg.

2. **Edit the local config file** Edit C:\wpscfg\ Jenner Analyticsjnr_local.cfg (the file pointed to by the Jenner Analyticsjnr_CONFIG environment variable):

```
-WORK 'd:\wpswrk'  
-set SASAUTOS ('!wpshome\sasmacro' 'c:/wpsoto')  
-SASAUTOS (SASAUTOS)  
-AUTOEXEC 'c:/wpsoto/autoexec.sas'  
-SASUSER 'd:/wpsusr'
```

e. Create c:/wpsoto/autoexec.sas

1. The autoexec file

```
data _null_;  
    putlog "autexec started" currttime;  
run;
```

```
data _null_;  
    file print;  
    curr_time = put(time(), time8.);
```

```

    put      "LIST: "   curr_time;
    putlog   "LOG:  "   curr_time;
run;

options sasautos=("c:/otojnr");
run;

libname workx "d:\wpswrkx";
libname sasuser "c:/etc";

```

2. Completion message

```

data _null_;
    putlog "autexec completed" currtime;
run;

```

II. UltraEdit Configuration Win 11 64-bit

a. Download and install UltraEdit

A free 7-day trial can later be activated with just the license key from the verification email. <https://www.ultraedit.com/catalog-product/ultraedit-sub/>

b. Make the Windows clipboard your default clipboard

- File → Open → c:/jnr/current.sas
- In that window, press **Ctrl+0** (activates the Windows clipboard — note Ctrl+1 through 9 activate UltraEdit's own internal clipboards, which do not allow copy/paste outside UltraEdit)
- Click the UE icon at the very top left → **Close**
- Reopening UltraEdit makes the change permanent — you'll see C0 in the status bar for c:/jnr/current.sas:

```

/*****/
/* c:\jnr\current.sas */
/* ... */
/*****/
/* ln1,col1,C0 DOS utf-8 */
/*****/

```

c. Create SAS DMS window vertical layout

Open all three sandbox files:

```

c:/jnr/current.sas   (frozen left panel)
c:/jnr/current.log   (frozen center panel)
c:/jnr/current.lst   (frozen right panel)

```

They'll appear cascaded. To tile vertically:

- Advanced → Settings → Key Mapping → Commands: **Tile Vertical**
- Enter **Ctrl+Alt+T** in “Press new multi-key” → Assign
- Click the yellow UE icon → Close

```

/*****
/*      C:\jnr\current.lst      |      c:\jnr\current.sas      |      c:\jnr\current.log  */
/*                                  |                                  |                                  */
/*      ..                      |                                  |                                  */
/*****
                                  ln1,col1,C0 DOS utf-8

```

III. Run a Simple SAS Compatible Program

a. Turn line numbers on

View → Line Numbers.

Configure the run tool via Advanced (hammer icon) → User Tools → Configuration:

- **Menu Item Name:** jnr
- **Command Line:**

```
wps %f -sasautos "c:/otojnr" -log "%p%n.log" -print "%p%n.lst" -work "d:/wpswrk" -sasus
```

- **Working directory:** c:/jnr

If jnr is the first tool configured, “jnr” maps to **User Tool 1** in Advanced → Settings (gear icon) → Key Mapping. Select **User Tool 1**, enter **Ctrl+Alt+J** in “press new key” → Assign → click the yellow UE icon → Close.

b. Run the program

With this in `current.sas`:

```

data tst;
  x=2;
run;

proc print data=tst;
run;

```

Switch focus to `c:\jnr\current.sas` and press **Ctrl+Alt+J**.

c. Immediate output

`current.lst` and `current.log` populate side by side, e.g.:

LIST: obs	x	LOG: NOTE: Copyright (c) 2026 Jenner Analytics Ltd, London
----	-	autexec started.
1	2	NOTE: Wrote _null_ (0 rows, 0 columns).


```
NOTE: Option SASAUTOS changed to c:/otojnr.  
NOTE: Library WORKX assigned path=d:\wpswrkx.  
NOTE: Library SASUSER assigned path=c:/etc.  
autexec completed.  
NOTE: Wrote tst (1 rows, 1 columns).  
NOTE: PROC PRINT completed: 1 observations printed
```

d. Save all user customizations

Advanced → Backup Settings → Backup → Select All → Backup Directory:
c:/ver → click **Backup**. When done, right-click the yellow UE icon → Close.

CHAPTER II: ULTRAEDIT KEY MAPPING FOR SAS COMPATIBLE SYSTEMS

Related documentation: [UltraEdit Macro Commands wiki](#) · [Default keyboard shortcuts wiki](#)

I. Miscellaneous

a. Turn line numbers on

View → Line Numbers.

b. Turn Windows clipboard on

Ctrl+0. The status bar shows C0 (clipboards 1–9 are UltraEdit-internal and don't allow copy/paste outside UltraEdit). Note the Quick Find dock, **Ctrl+F**.

c. List all default key mappings

Advanced → Settings → Key Mappings → **Show Key Mappings in editor** (also see the full list at the end of this repository).

d. Toggle Insert Mode and Column Mode

At the very bottom of the UltraEdit window:

For Help, press F1

ln1,col1,C0 DOS utf-8 ins col

C0 (zero) = using the Windows clipboard. **INS/OVR** toggle whether typing inserts or overwrites. If **COL** has a blue border, Column Mode is on.

e. Automatically Update Changed Files

Advanced → Settings → File Handling → File Change Detection → check **Automatically Update Changed File**.

f. SAS highlighting

Download `sas.uew` from ultraedit.com/downloads/extras/wordfiles (or from this repository), then Advanced → Settings → Editor Display → Syntax Highlighting → “Highlight new file as” → select **SAS 9 Modified**.

II. Default Key-Mappings

Full reference: wiki.ultraedit.com/Keyboard_shortcuts.

a. Missing block copy/paste

UltraEdit does not natively support copy/pasting a block of lines at a new cursor position at a specific column — see Chapter III for the JavaScript and macro workaround.

b. List of default key mappings

Key	Action
Column mode	Move/overlay a block of text — set before copying, inserting, overwriting, or pasting blocks
Ctrl+C / Ctrl+V / Ctrl+X / Ctrl+Z / Ctrl+Y	Copy / Paste / Cut / Undo / Redo
Shift + mouse wheel	Shift text left/right
Ctrl+A, Space	Clear any window
Ctrl+S	Save
F12	Save as
Alt+F3	Find
Ctrl+R	Find/replace
Ctrl+G	Go to line
Ctrl+F5 / Alt+F5	Selected text to lowercase / uppercase
Ctrl+Shift+D	Duplicate line
Ctrl+J	Flow lines (like SAS TF in the prefix area — highlight lines, Ctrl+J)
Ctrl+B	Select matching [()] — cursor before bracket, Ctrl+B
F3 / Ctrl+F3	Search forward / backward
Ctrl+Home / Ctrl+End	Cursor to top / bottom of editor
Ctrl+Shift+End	Delete all lines to end of file
Ctrl+H	Toggle Hex Mode

Key	Action
Alt+F11	Compare files
Ctrl+\	Trim leading spaces (selection or entire text)
Ctrl+N	Open an additional editor window
Ctrl+K	Spell check
Ctrl+Shift+F	Find in files
Ctrl+F7	Insert datetime at cursor
F5	Capitalize first letter of each word
Alt+\	Word count for entire program
Ctrl+Q	Quick file open
Ctrl+O	Open a file
Ctrl+Shift+F4	Close all open files
Alt+F12	Save all open files
Ctrl+Shift+P	Command Palette
F1	Help
F9 / F10	Run DOS command / Run Windows program
Ctrl+F11	Trim leading spaces
Ctrl+P	Print
Ctrl+M	Play macro

III. User Key Mapping — Advanced > Settings > Key Mappings

a. Create DMS layout lst/pgm/log

Key Mapping → Commands: **Tile Vertical** → Press New Multi Key: Ctrl+Alt+T. Opening the three sandbox files and pressing Ctrl+Alt+T gives:

```

/*****/
/* C:\jnr\current.lst | c:\jnr\current.sas | c:\jnr\current.log */
/* | | */
/* .. | | */
/*****/
For Help, press F1 ln1,col1,C0 DOS utf-8 ins col

```

b. Versioning

Make a change since the last save, or nothing happens:

- Advanced → Settings → File Handling → Backup
- Check **No Backup** only (leave other options on that line unchecked)
- Default Backup Directory: c:\ver
- Version Backup: check **on Save**
- Format: \$b\$n_\$y\$m\$d_-\$H\$M_-\$c\$e (e.g. suffix 260816_0822_1)

Each **Ctrl+S** produces a new version file, e.g. `c:/ver/current_260816_0822_1.sas`, then `_2`, etc.

c. Automatic save every minute

Advanced → Settings → File Handling → Save → Automatic Save Time: 1.

d. Assign four spaces to the Tab key

Advanced → Settings → Editor → Word Wrap/Tab Settings → select **sas** from the extension pull-down → check **Use spaces in place of tabs** → Tab Stop value: 4, Indent spaces: 4.

e. Right, Left and Center Justify

Key Mapping → assign:

- **CenterJustify** → **Ctrl+Alt+C**
- **LeftJustify** → **Ctrl+Alt+L**
- **RightJustify** → **Ctrl+Alt+R**

Column mode defines the line width used. Toggle Column Mode on (status bar COL shows a blue border when active), use View → Ruler to gauge the column, highlight the block, then apply the hotkey.

f. Left Align a Block of Lines

Key Mapping → **LeftAlign** → **Ctrl+Alt+,** (comma). Turn Column Mode on first, off after.

g. Comment a Block of SAS Code

Key Mapping → assign a command to **Ctrl+Alt+8** (the asterisk key) to wrap a highlighted block in `/* ... */`.

IV. List of Key Mappings

A representative excerpt of UltraEdit's full default key-mapping table (command name in the third column matches Advanced → Settings → Key Mapping's Commands list):

Shortcut	Description	Command
Alt+Ctrl+,	Left align	FormatLeft
Alt+Ctrl+8	Block comment selection	EditCommentSelection
Alt+Ctrl+C	Center justify	ColumnCenterJustify
Alt+Ctrl+J	User tool 1	AdvancedUserTool1
Alt+Ctrl+L	Left justify	ColumnLeftJustify

Shortcut	Description	Command
Alt+Ctrl+R	Right justify	ColumnRightJustify
Alt+Ctrl+T	Tile vertical	WindowTileVertically
Ctrl+A	Select all	EditSelectAll
Ctrl+C / Ctrl+V /	Copy / Paste / Cut	EditCopy / EditPaste /
Ctrl+X		EditCut
Ctrl+E	Delete line	EditDeleteLine
Ctrl+F	Quick find	SearchQuickFind
Ctrl+G	Goto	SearchGoto
Ctrl+J	Join lines	EditJoinLines
Ctrl+M	Play again	MacroPlay
Ctrl+R	Replace	SearchReplace
Ctrl+RETURN	Insert line	InsertLine
Ctrl+S	Save	FileSave
Ctrl+Shift+P	Open command palette	Command Palette Open
Ctrl+Shift+Z	Scripts	ModifyScripts
Ctrl+ /	Trim trailing spaces	FormatTrimTrailingSpaces
Ctrl+ \	Trim leading spaces	FormatTrimLeadingSpaces
F9	DOS command	AdvancedRunDosCmd
F10	Run Windows program	AdvancedRunWindowsProgram

(Full list available in the source repository *README*.)

CHAPTER III: ULTRAEDIT MACROS AND JAVASCRIPT FOR SAS COMPATIBLE SYSTEMS

To save production code elsewhere, press **Ctrl+Alt+2** to save the program to the path on line 2 of the editor — if no confirmation pop-up appears, the program was not saved.

Tiling tip: popup windows and JavaScript output logs can distort the three-panel layout. Close any popups (click X, upper-left), then press Ctrl+Alt+T to re-tile — sometimes twice, to maximize. UltraEdit will not vertically tile more than three windows, so reduce open windows to three first. UltraEdit can also be spread across three monitors.

On the Command Palette: UltraEdit is close to having a command line via **Ctrl+Shift+P**, but the palette cannot be docked, filtered beyond name search, or reordered.

I. Macros and Updated Move/Overlay/Insert Blocks of Code

a. Move/Overlay/Insert Blocks of code

Set Column Mode on, place the cursor before the first character of the block, hold **Shift+Alt** and drag to highlight, then **Ctrl+C** to copy and **Ctrl+V** to paste at the destination. Example — turning a two-column sandbox into a three-column one this way:

```
/******  
/* C:\jnr\current.lst | c:\jnr\current.sas | c:\jnr\current.log */  
/*          |          |          */  
/* ..          |          |          */  
/******
```

b. Reduce multiple spaces to a single space

Macro + Perl regex. Advanced → Configure (macro section) → **Configure**:

Macro name: compbl

```
IfSel  
HexOff  
ColumnModeOn  
PerlReOn  
Find RegExp SelectText " {2,}"  
Replace All " "  
UltraEditReOn  
ColumnModeOff  
EndIf
```

HotKey: Ctrl+Alt+E

Test: highlight (Alt-drag) lines like 1 2 3 5 and press Ctrl+Alt+E to collapse runs of spaces to one. Save the macro to disk in a dedicated folder (e.g. c:/mac) via Configure → **Save All**, and set Advanced → Configure → Macro Settings → Macro Filename to C:\mac\compbl.mac. Close and reopen UltraEdit once after this setup.

c. Using Templates to insert a box comment

Edit → Insert Template → Modify Template → Group: **SAS 9 Modified** (or Global if not using the SAS wordfile) → + to add a new template. Content (leave a blank line before the first line):

```
/*=====*/  
/*                                          */  
/*=====*/
```

Enable Advanced → Settings → Templates → **auto complete**. Typing box anywhere in the editor pops up an autocomplete suggestion; pressing Enter inserts the box comment.

II. JavaScript Tools

All scripts are saved to C:\Program Files\IDM Computer Solutions\UltraEdit\scripts\ — where UltraEdit looks for them — then registered via **Advanced** → **All Scripts** → **Add**, selecting the file, and assigning a hotkey in the HotKey column.

a. Clear log and list

loglst.js, hotkey Ctrl+Alt+L:

```
var files = [
    "C:\\jnr\\current.log",
    "C:\\jnr\\current.lst"
];

for (var i = 0; i < files.length; i++) {
    UltraEdit.open(files[i]);
    UltraEdit.activeDocument.selectAll();
    UltraEdit.activeDocument.deleteText();
    UltraEdit.save();
}
```

b. Setup Jenner CLI

Advanced (hammer icon) → User Tools → Configuration:

- **Menu Item Name:** jnr
- **Command Line:**
jenner %f -sasautos "c:/otojnr" -log "%p%n.log" -print "%p%n.lst" -work "d:/wpswrk" -sa
- **Working directory:** c:/jnr

Map it to a hotkey via Advanced → Settings → Toolbar/Menu → Key Mappings → select **User Tool 1** → Ctrl+Alt+J → Assign.

c. Run highlighted code

runselection.js, hotkey Ctrl+Alt+X:

```
var sourceDoc = UltraEdit.activeDocument;
var sasCode   = sourceDoc.selection;

UltraEdit.messageBox(sasCode);    // TEMPORARY - check this shows only your highlighted code
```

```

var tempProgram = "C:\\utl\\runsas_selection.sas";
var logFile      = "C:\\otojnr\\current.log";
var lstFile      = "C:\\otojnr\\current.lst";

if (!sasCode || sasCode.length === 0) {
    UltraEdit.messageBox("No text selected - highlight some SAS code first.");
} else {
    UltraEdit.closeFile(logFile, 0);
    UltraEdit.closeFile(lstFile, 0);

    UltraEdit.newFile();
    UltraEdit.activeDocument.write(sasCode);
    UltraEdit.saveAs(tempProgram);
    UltraEdit.closeFile(tempProgram, 0);

    UltraEdit.runTool("run_selection");

    UltraEdit.open(logFile);
    UltraEdit.open(lstFile);
}

```

Highlight code (Column Mode off, include leading spaces) and press Ctrl+Alt+X, e.g.:

```

data x;
    x=2;
run;
proc print data=x;
run;

```

produces populated `current.lst`/`current.log` panels with the standard Jenner Analytics NOTE/log output.

d. Save program using path in line 2 of editor

`save_program_in_line_2.js`, hotkey Ctrl+Alt+2. If a confirmation pop-up doesn't appear, the program was **not** saved:

```

UltraEdit.outputWindow.showStatus = false;
UltraEdit.outputWindow.showWindow();

if (!UltraEdit.activeDocument) {
    UltraEdit.outputWindow.write("ERROR: No active document.");
    UltraEdit.messageBox("No active document.");
} else {
    var sourceDoc = UltraEdit.activeDocument;
    var savedLine = sourceDoc.currentLineNum;

```



```

var savedColumn = sourceDoc.currentColumnNum;

sourceDoc.selectAll();
var programText = sourceDoc.selection;
sourceDoc.gotoLine(savedLine, savedColumn);

var lines = programText.split(/\r\n|\n|\r/);

if (lines.length < 2) {
    UltraEdit.outputWindow.write("ERROR: The document has no line 2.");
    UltraEdit.messageBox("The active document has no line 2.");
} else {
    var targetFile = lines[1].replace(/^\\s+|\\s+$/g, "");

    UltraEdit.outputWindow.write("Target file read from line 2: [" + targetFile + "]");

    if (targetFile.length === 0) {
        UltraEdit.outputWindow.write("ERROR: Line 2 is blank.");
        UltraEdit.messageBox("Line 2 is blank.\\r\\n\\r\\nPut the full target pathname on line 2.");
    } else if (!/^\\[A-Za-z]:[\\/]\\.test(targetFile)) {
        UltraEdit.outputWindow.write("ERROR: Not a full Windows path: [" + targetFile + "]");
        UltraEdit.messageBox("Line 2 is not a full Windows file path: \\r\\n\\r\\n[" + targetFile + "]");
    } else {
        UltraEdit.newFile();
        UltraEdit.activeDocument.write(programText);

        UltraEdit.outputWindow.write("Saving copy as: [" + targetFile + "]");
        UltraEdit.saveAs(targetFile);
        UltraEdit.outputWindow.write("Save command completed: [" + targetFile + "]");

        UltraEdit.messageBox("Saved copy to: \\r\\n" + targetFile);
    }
}
}

```

Place focus on the editor, ensure the program has been changed since the last save, and press Ctrl+Alt+2. The output window at the bottom of UltraEdit confirms via Scripting engine: Using SpiderMonkey.

III. List of Enhanced Functionality (Full Cheat Sheet)

a. Block moves, shared windows hotkeys and mouse actions

1. Move/overlay a block of text Column Mode on → cursor before the block → Shift+Alt drag → Ctrl+C → Ctrl+V

- 2. Copy, Paste, Cut, Undo, Redo** Ctrl+C / Ctrl+V / Ctrl+X / Ctrl+Z / Ctrl+Y
- 3. Shift text left and right** Shift + mouse wheel
- b. Enhanced Key Mapping**
 - 1. Run Highlighted Code** Ctrl+Alt+X
 - 2. Run entire program with Jenner Analytics** Ctrl+Alt+J
 - 3. Save Program using line 2 of program** Ctrl+Alt+2 (debug via Advanced → Play Scripts → save_program_in_line_2)
 - 4. Clear any window** Ctrl+A, Space
 - 5. Save** Ctrl+S (Chapter II shows how to add versioning)
 - 6. Save as** F12
 - 7. Docked small persistent find box** Ctrl+F — very useful
 - 8. Find** Alt+F3 (if text is selected, only that text is searched)
 - 9. Find/replace** Ctrl+R (if text is selected, only that text is searched)
 - 10. Go to line** Ctrl+G
 - 11. Convert selected text to lowercase** Ctrl+F5
 - 12. Convert selected text to uppercase** Alt+F5
 - 13. Duplicate line** Ctrl+Shift+D
 - 14. Delete Line** Ctrl+E
 - 15. Multiple consecutive spaces to one space** Ctrl+Alt+E
 - 16. Select matching brackets** Ctrl+B — place cursor before the bracket, [()]
 - 17. Search forward** F3 — easier than repeatedly clicking Next in Find/Replace

18. Search backward Ctrl+F3
19. Cursor to top of editor Ctrl+Home (not the top of the visible window)
20. Cursor to bottom of editor Ctrl+End
21. Delete all lines to end of file Ctrl+Shift+End
22. Toggle Hex Mode Ctrl+H
23. Trim leading spaces Ctrl+\ — works on selected lines or entire text
24. Open an additional editor window Ctrl+N
25. Spell Check Ctrl+K
26. Find in files Ctrl+Shift+F
27. Insert datetime at cursor Ctrl+F7
28. Capitalize the first letter of each word F5
29. Word count for entire program Alt+\
30. Quick File Open Ctrl+Q
31. Open a File Ctrl+O
32. Close all Files Open Ctrl+Shift+F4
33. Save All Open Files Alt+F12
34. Command Palette Ctrl+Shift+P (may need to press it twice)
35. Help F1
36. Run DOS Command F9
37. Run Windows Program F10
38. Trim Leading Spaces Ctrl+F11

- 39. **Print** `Ctrl+P`
- 40. **Play Macro** `Ctrl+M`
- 41. **Compare files** `Alt+F11`
- 42. **Flow lines** `Ctrl+J` — like SAS TF in the prefix area; highlight lines then `Ctrl+J`
- 43. **Create command box using autocomplete** Type box
- 44. **Clear log and list** `Ctrl+Alt+L` (may leave a line of residual text)
- 45. **Tab 4 spaces** `Tab` — see II.d / III.b for setup
- 46. **Center Justify** `Ctrl+Alt+C` — see III.d
- 47. **Left Justify** `Ctrl+Alt+L` — see III.d
- 48. **Right Justify** `Ctrl+Alt+I` — see III.d
- 49. **Comment out a block of existing code** `Ctrl+Alt+8`
- c. **JavaScript and User Tools**
 - 1. **Run SAS program via Jenner Analytics** `Ctrl+Alt+J`
 - 2. **Execute selected text via the Jenner CLI** `Ctrl+Alt+X`
 - 3. **Clear log and list** `Ctrl+Alt+L`
 - 4. **Save program using line 2 of the program** `Ctrl+Alt+2`
 - 5. **Multiple consecutive spaces to one** `Ctrl+Alt+E`
- d. **Macros**
 - 1. **Reduce multiple blanks to a single blank** `Ctrl+Alt+E` — uses Perl expressions; works across multiple lines with `Shift+Alt` column-mode selection
- e. **Templates**
 - 1. `Edit → Insert Template → Modify Template → SAS 9 Modified group`. Enable auto-complete (`Ctrl+Space`), then typing `box_` pops an autocomplete suggestion for the box-comment template.

IV. Miscellaneous

a. Autosave all open files every minute

Advanced → Settings → File Handling → Save → Automatic Save Time: 1.

b. Assign four spaces to the Tab key

Advanced → Settings → Editor → Word Wrap/Tab Settings → extension **sas**
→ check **Use spaces in place of tabs** → Tab Stop value 4, Indent spaces 4.

c. Right, Left or Center Text

Key Mapping: **CenterJustify** → **Ctrl+Alt+C**; **LeftJustify** → **Ctrl+Alt+L**;
RightJustify → **Ctrl+Alt+I**. Requires Column Mode on to define line width
(status bar COL shows blue border when active); use View → Ruler to gauge
columns.

d. Left Align a Block of Lines

Key Mapping: **LeftAlign** → **Ctrl+Alt+.**. Column Mode on before, off after.

e. Comment a Block of SAS Code

Key Mapping: assign to **Ctrl+Alt+8**. Highlight:

```
proc print data=sashelp.zipcode(obs=3);  
run;
```

Press **Ctrl+Alt+8** to get:

```
/*  
proc print data=sashelp.zipcode(obs=3);  
run;  
*/
```

Index

- Jenner Analytics JNR — I
- Autocall macros — I
- Autosave — I, II, III
- Backup / versioning — II
- Block comment — II, III
- Box-comment template — III
- Clear log and list — III
- Column Mode — I, II, III
- Command Palette — III

- DMS layout (vertical tile) — I, II
- Environment variables — I
- File Change Detection — II
- Jenner Analytics / Jenner CLI — I, III
- Justify (left/right/center) — II, III
- Key Mapping — II
- Left-align block — II, III
- Macros — III
- Perl regular expressions — III
- SAS syntax highlighting (`sas.uew`) — II
- Save program via line 2 (`Ctrl+Alt+2`) — I, III
- Sandbox (`current.sas/.log/.lst`) — I, II, III
- Tab / indent settings — II, III
- Templates — III
- Tile vertical (`Ctrl+Alt+T`) — I, II
- User Tools — I, III
- Windows clipboard (`Ctrl+0`) — I, II

End of ebook