

← Go Back to Pre Work

Course Content

1.1 Test Your Understanding

Type	:	Practice Assessment
Questions	:	8
Scoring Policy	:	Highest Score
Your Marks	:	8/8

Instructions

RETAKE

Attempt History

Attempt #4
Nov 08, 9:54 AM

Marks: 8

Q No: 1 Correct Answer

Marks: 1/1

What is default file extension of Jupyter Notebook?

- .py
- .npy
- .ipynb — You Selected
- pynb

.ipynb is a document created using Jupyter Notebook. This file can be handled and edited in any other system using Jupyter Notebook or Google Colaboratory.

Q No: 2 Correct Answer

Marks: 1/1

Which of the following app is used to open .ipynb file?

- (●) Colaboratory — You Selected
- ( ) Python
- ( ) Collabrify
- ( ) None of the mentioned

Colaboratory is the app used or installed to open a Jupyter Notebook file (.ipynb) using Google Drive. We can also create our own Notebook or Python script and execute it using this app popularly known as Google Colaboratory.

Q No: 3 Correct Answer

Marks: 1/1

Identify the advantage of Google Colaboratory among the following

- ( ) Google Colaboratory consists of many pre-installed libraries
- ( ) It becomes easy to share the work using Google Colaboratory
- ( ) Google Colaboratory uses the cloud for computation
- (●) All of the mentioned — You Selected

Google Colaboratory consists of many pre-installed libraries, so we don't have to worry about installation errors , it uses the cloud for computation so tyour system specifications

does not comes in the way of performance. It is also very easy to share the work using Google Colaboratory.

Q No: 4 Correct Answer

Marks: 1/1

Which of the following cell can execute Python code?

- ○ Text cells
- ◉ Code cells You Selected

Code cells are used to write the codes whereas text cells are used to specify heading, descriptions etc.

Q No: 5 Correct Answer

Marks: 1/1

at the start of text cell is used to create different levels of headers such as header, sub-header, sub-sub-header, etc

- ◉ True You Selected
- ○ False

We can create different level of headers or sections, sub-sections etc. by using multiple # (such as #, ##, ###)

Q No: 6 Correct Answer

Marks: 1/1

What will be the output of the following code?

```
print(4*4)
```

- 4*4
- 16 — You Selected
- Error
- 256

Python will first calculate the value of 4*4 as 16, and then the calculated value will be printed as the output.

Q No: 7 Correct Answer

Marks: 1/1

What will be the output of the following code?

```
print("I am",25,"years old")
```

- I am25years old
- I am 25 years old — You Selected
- "I am",25,"years old"
- None of the above

By default, Python considers whitespace as the separator between the different values passed to the print() function. Therefore, the values in the code will be printed with whitespace between the values passed. The output of the code will be

I am 25 years old

Q No: 8 Correct Answer

Marks: 1/1

What will be the output of the following code?

```
print("I am " + "25 years old")
```

- (●) I am 25 years old — You Selected
- ( ) I am25 years old
- ( ) "I am " + "25 years old"

In Python two strings can be added together using the + operator.

Attempt #3
Aug 06, 6:01 PM — Marks: 8

Attempt #2
Aug 06, 2:14 PM — Marks: 7

Previous Next

Attempt #1
Aug 04, 9:10 PM — Marks: 7

Proprietary content.©Great Learning. All Rights Reserved. Unauthorized use or distribution prohibited.

© 2023 All rights reserved. Help