

← Go Back to Pre Work

Course Content

1.9 Test Your Understanding

Type	:	Practice Assessment
Questions	:	6
Scoring Policy	:	Highest Score
Your Marks	:	6/6

Instructions

RETAKE

Attempt History

Attempt #2
Aug 07, 3:15 PM

Marks: 6

Q No: 1 Correct Answer

Marks: 1/1

What will be the output of the following code?

```
def total_addition(*numbers):
    addition = 0
    for number in numbers:
        addition += number
    return addition

total_addition(1,2,3)
```

addition

1, 2, 3

6 You Selected

0

As we have specified *numbers, Python will expect one or more positional arguments. The for loop will iterate over these arguments and keep multiplying them to the variable result. The final value of result will be returned by the function.

Q No: 2 Correct Answer

Marks: 1/1

Which of the following is the correct function declaration that can execute both the function calls mentioned below ?

```
fun(1, 2, 3)
fun(23, 24)
```

def fun(args*):return args

def fun(args):return args

def fun(*args):return args You Selected

def fun(*args*):return args

We need to specify args in the function to account for one or more positional arguments. The correct way to do so is by putting an asterisk (*) to specify one or more positional arguments as function input. Syntax will be as follows:

```
def fun(*args):return args
```

or

```
def fun(*args):
    return args
```

Q No: 3 Correct Answer

Marks: 1/1

What will be the output of the code below?

```
def fun(*int):
    result = 1
    for x in int:
        result *= x
    return result

fun(1,2,3,4,5)
```

- 1*2*3*4*5
- 1, 2, 3, 4, 5
- 120 You Selected
- 1

As we have specified *int, Python will expect one or more positional arguments. The for loop will iterate over these arguments and keep multiplying them to the variable result. The final value of result will be returned by the function.

Q No: 4 Correct Answer

Marks: 1/1

What will be the output of the following code?

```
def function(var1=2, var2=4):
    var2 = 6
    var1 = 5
    print(var1, var2)
```

```
function(10, 20)
```

- 2 4
- 5 6 — You Selected
- 10 24
- 12 20

The function will take two arguments, set the first argument's value to 5, set the second argument's value to 6, and then return the arguments. Irrespective of the arguments passed to the function, the output will always be

5 6

Q No: 5 Correct Answer

Marks: 1/1

What will be the output of the code below?

```
def my_function(a, b, **kwargs, *args):
    return a+b
my_function(5,6)
```

- Error — You Selected
- 5+6
- a+b
- 11

The code in the question raises an error the keyword arguments (kwargs) are specified before the positional arguments (args).

The correct way to declare a function with kwargs and args is as follows:

```
def my_function(a, b, *args, **kwargs):
    return a+b
my_function(5,6)
```

Q No: 6 Correct Answer

Marks: 1/1

Which of the following statements is correct for the code below?

```
def fun(A, B=30):
    return A + B
```

- ○ A is a keyword argument and B is a positional argument
- ○ A and B are both keyword arguments
- ◉ A is a positional argument and B is a keyword argument — You Selected
- ○ A and B are both positional arguments

Argument A does not have a default value and is specified first, so it is a positional argument.

Argument B has a default value specified, so it is a keyword argument.

Attempt #1

Aug 07, 3:13 PM

Marks: 5

Previous Next

Proprietary content.©Great Learning. All Rights Reserved. Unauthorized use or distribution prohibited.

© 2023 All rights reserved. Help