

← Go Back to Pre Work

Course Content

Practice Quiz - Introduction to Python

Type	:	Practice Assessment
Attempts	:	1/1
Questions	:	10
Time	:	1h
Your Marks	:	9/10

Instructions

Attempt History

Attempt #1
Aug 10, 4:48 PM

Marks: 9

Q No: 1 Correct Answer

Marks: 1/1

For which of the following pairs of datatypes does the addition operation raise an error?

- ○ float and int
- ◉ int and string — You Selected
- ○ string and string
- ○ int and int

- int and int: Adding two integers in Python will return the sum of the two integers.
- string and string: Adding two strings in Python will return a string which will be a concatenation of the two strings.
- float and int: Adding a float and an integer in Python will return a float due to implicit type conversion.
- int and string: This will raise an error as a string in Python can only be added to another string. It cannot be added to other datatypes.

Q No: 2 Correct Answer

Marks: 1/1

Which of the following is NOT true regarding loops in Python?

- Loops are used to perform certain tasks repeatedly
- while loop is used when multiple statements are to be executed repeatedly until the given condition becomes False
- while loop is used when multiple statements are to be executed repeatedly until the given condition becomes True — You Selected
- for loop can be used to iterate through the elements of lists

Looping statements in Python are used to perform a certain task continuously until the given condition becomes False. For example,

```
while a > 5:
```

This loop will go on performing iterations as long as the variable 'a' takes values greater than 5. It will stop when the value of 'a' becomes less than or equal to 5.

Q No: 3 Correct Answer

Marks: 1/1

What will be the type of the variable 'c' after running the following code snippet?

```
a = 10
b = 2.3
c = a*b
```

- ○ int
- ◉ float — You Selected
- ○ decimal
- ○ complex

Here, a is of type int and b is of type float. When any mathematical operation happens between int and float type variables, the output is always typecasted to float to store the decimal point values. This is known as implicit type conversion.

Here, even though the multiplication of 10*2.3 results in 23, the value stored will be 23.0 due to implicit type conversion.

The type of variable c can be confirmed using the following code:

```
type(c)
```

Q No: 4 Correct Answer

Marks: 1/1

What will be the output of the following code snippet?

```
i = '20'
if i > 20:
    print(1)
else:
    print(2)
```

1

2

'2'

TypeError You Selected

```
TypeError: '>' not supported between instances of 'str' and 'int'
```

The error message generated by above code will be of TypeError, Here, i='20' is a variable of string datatype (as the value denoted is inside quotation marks). So, when the i>20 condition is encountered by Python, it throws an error message because, we are trying to compare a string to an integer (i.e. 20).

Q No: 5 Incorrect Answer

Marks: 0/1

What will be the value of the variable 'a' after the fourth iteration of the following for loop?

```
a = 1
for i in range(1,6):
    a = a*i
print(a)
```

120 You Selected

1

24 Correct Option

720

range(start, step, stop) returns a sequence that starts from the number start (is inclusive), increments in the step of the number step, and ends before the number stop (is exclusive). By default, the sequence starts from 0 and increments with a step of 1.

As per the given code, range(1,6) returns a sequence starting from 1 and ending at 5 (because 6 is excluded), with increments of 1 (by default). The loop will iterate over the numbers 1, 2, 3, 4, and 5 (5 iterations).

The result of each iteration will be as follows:

1st iteration: a =1 and i=1

a = a*i =>1*1 =1

New value of a is 1

2nd iteration: a =1 and i=2

a = a*i =>1*2 =2

New value of a is 2

3rd iteration: a =2 and i=3

a = a*i =>2*3 =6

New value of a is 6

4th iteration: a =6 and i=4

a = a*i =>6*4 =24

New value of a is 24

5th iteration: a =24 and i=5

a = a*i =>24*5 =120

New value of a is 120

So, the value for the fourth iteration will be 24.

Q No: 6 Correct Answer

Marks: 1/1

Which of the following codes will fetch the third element from the start of a list named new_list containing 4 elements?

```
new_list[3]
```

```
new_list['3']
```

```
new_list[-2]
```

You Selected

```
new_list[-1]
```

Negative Index	-4	-3	-2	-1
Elements	a	b	c	d
Index	0	1	2	3

Python programming language supports negative indexing of arrays. The negative indexing starts from where the array ends. This means that the last element of the array is the first element in the negative indexing, which is -1. So, the third element in the list will be the second element from the end. Hence, new_list[-2] will fetch the required element.

Q No: 7

Correct Answer

Marks: 1/1

Following is a dictionary named alphabets:

```
alphabets = {'1':'A','2':'B','3': ['C','D','E']}
```

Which statement among the following will fetch the element 'E'?

- [x] `alphabets['3'][2]` — You Selected
- [ ] `alphabets['3']['E']`
- [ ] `alphabets['3']['2']`
- [ ] `alphabets[3][2]`

Here, the list ['C','D','E'] is stored inside a dictionary under key '3'. So to fetch the 'E' we have to first call key '3' and then call the 'E' by index(since ['C','D','E'] is a list).

To achieve this we can call it by the following code.

```
alphabets['3'][2]
```

Q No: 8 Correct Answer

Marks: 1/1

How will you fetch [True, 46] from the list below?

```
list = ["Great", 51, True, 46, "Hi"]
```

- list[3:5]
- list[2:-1] — You Selected
- list[2:3]
- list[1:3]

True and 46 are at index positions 2 and 3 (or -3 and -2) respectively of the given list.
So, list[2:-1] will return [True, 46] from the given list.

Q No: 9 Correct Answer

Marks: 1/1

What will be the output of the following code?

```
list_mul = ['2','2','2']
list_mul*2
```

- `[4, 4, 4]`
- `[2, 2, 2, 2, 2, 2]`
- `['4', '4', '4', '4', '4', '4']`
- `['2', '2', '2', '2', '2', '2']` — You Selected

The * operator multiplies numbers of elements rather than multiplication of individual elements. So, 2 times of ['2', '2', '2'] will create the list ['2', '2', '2', '2', '2', '2'].

Q No: 10 Correct Answer

Marks: 1/1

Which of the following pairs of functions yield the same output?

You Selected

```
def fun(n):
    return n*n*n
```

```
lambda_cube = lambda n: n*n*n
```

```
def fun(n):
    n*n*n
```

```
lambda_cube = lambda n: n*n*n
```

```
def fun(n):
```

Previous Next

Proprietary content.©Great Learning. All Rights Reserved. Unauthorized use or distribution prohibited.

© 2023 All rights reserved. Help