

← Go Back to Pre Work

Course Content

Practice Quiz 1.1 - Intro to Variables

Type	:	Practice Assessment
Questions	:	9
Time	:	1h
Scoring Policy	:	Highest Score
Your Marks	:	10/10

Instructions

RETAKE

Attempt History

Attempt #1
Aug 08, 3:54 PM

Marks: 10

Q No: 1 Correct Answer

Marks: 1/1

What will be the datatype of the variable *add*?

```
a = 10
b = 5.1
add = a + b
```

- int
- float — You Selected
- string
- long

When any mathematical operation happens between int and float type variables, the output is always typecasted to float to store the decimal point values. This is known as implicit type conversion.

In the given question, one variable is an integer and the other is a float. So, Python automatically converts the final output to float due to implicit type conversion.

The below snippet can be used to verify the result.

```
type(add)
```

Q No: 2 Correct Answer

Marks: 1/1

What will be the output of the following code?

```
5 == (3 + 2)
```

- SyntaxError: cannot assign to literal
- False
- True — You Selected
- SyntaxError: unexpected EOF while parsing

== operator compares the equality of two objects. The output of the given code will be **True** as the value of the left side expression (5) is equal to the right side expression (3 + 2 = 5).

Q No: 3 Correct Answer

Marks: 1/1

What will be the output of the following snippet?

```
a = 3
print(a + (33))
```

- ○ 3 + 33
- ◉ 36 You Selected
- ○ 3 + (33)
- ○ TypeError: 'int' object is not callable

In Python, the + operator can be used to add two numbers. The value of variable *a* is 3. *a* + 33 will be 36. The print() method prints the specified message to the screen.

Q No: 4 Correct Answer

Marks: 1/1

Which of the following snippets can be used to convert an float variable '*a*' to integer?

```
a = 3.5
```

```
float(a)
```

```
type(a)
```

```
int(a)
```

You Selected

```
a = int
```

In Python, the int() method is used to convert a string or floating-point value into an integer value.

Q No: 5 Correct Answer

Marks: 1/1

What will be the output of the following code snippet?

```
a = '5a'
int(a)
```

'5a'

5a

5

invalid literal for int() with base 10: '5a' You Selected

In Python, the int() method is used to convert a variable from a given datatype to an integer, provided the value stored in the variable consists of numbers only (should not include any characters).

Q No: 6 Correct Answer

Marks: 1/1

Which of the following code snippet can be used to calculate the area of a triangle with base = 10 and height = 5?

Hint : Area of triangle = (base*height)/2

```
area = 0.5 ** 10 * 5
print("Area of triangle:", area)
```

```
area = 0.5 * 10 * 5
print("Area of triangle:", area)
```

You Selected

```
area = 10 * 5
print("Area of triangle:", area)
```

```
area = 10 * 5 ** 0.5
print("Area of triangle:", area)
```

The area of the triangle is calculated using the formula 0.5 * base * height. Here, base = 10 and height = 5. Hence, the area of the triangle will be 0.5 * 10 * 5.

Q No: 7 Correct Answer

Marks: 1/1

What will be the value of *z* in the following expression?

```
v = 10
w = 25
x = 70
y = 2
z = (v + w) * (x / y)
```

- 1255.0
- 1225
- 1225.0 — You Selected
- 1.225

The precedence of operators in python is defined as PEMDAS. P having the highest precedence and S having the lowest.

P - Parentheses ()

E - Exponents, (**)

MD - Multiplication and division (*, /, //, %)

AS - Addition and Subtraction (+, -)

The value of the z will be equal to (10 + 25) * (70 / 2) = 35 * 35.0 = 1225.0

So , the value of the z is calculated based on this precedence.

So first, 10+25 and 70/2 will be solved(since, they are in parentheses)

Next, both the values will be multiplied to get the final value

---

Q No: 8 Correct Answer

Marks: 2/2

Which of the following snippets can be used to complete the code to swap the values of two variables *a* and *b*?

```
a = 10
b = 5
print("A and B before swapping {},{}".format(a,b))
temp = a #create a third variable and assign the value of a to it
#write the missing code(code missing here)
b = temp #value of a is in third variable so assign the value to b
print("A and B after swapping {},{}".format(a,b))
```

- b = a
- a = b — You Selected
- a = temp
- temp = b

The value of the variable *a* is stored in the third variable *temp*. To swap the values, we must assign the value of *b* to *a*. Then, the value of *a* stored in the third variable *temp* can be assigned to *b*.

Q No: 9 Correct Answer

Marks: 1/1

Which of the below snippets can be used to convert 35 degrees Celsius temperature to Fahrenheit?

Hint: To convert temperatures in degrees Celsius to Fahrenheit, multiply Celsius with 1.8 (or 9/5) and add 32(as a constant)

You Selected

```
celsius = 35
fah = 1.8 * celsius + 32
print("Temperature in Fahrenheit =", fah)
```

```
celsius = 35
fah = (5/9) * celsius + 32
print("Temperature in Fahrenheit =", fah)
```

```
sius = 35
fah = 1.8 * celsius + 9/5
print("Temperature in Fahrenheit =", fah)
```

Previous Next

Proprietary content.©Great Learning. All Rights Reserved. Unauthorized use or distribution prohibited.

© 2023 All rights reserved. Help