MambaGuard: Certified Streaming Detection for Multi-Protocol LLM Agent Security

Anonymous Submission

Paper #XXXX, IEEE S&P 2027 Cycle 2

***Abstract*—Large language model (LLM) agents now communicate through four open protocols — the Model Context Protocol, the Agent-to-Agent Protocol, the Agent Communication Protocol, and the Agent Network Protocol — whose combined traffic forms a network-scale attack surface that prompt-boundary monitors and classical intrusion detection systems were not designed to observe. We present *MambaGuard*, a streaming detector that ingests a canonicalised protocol message graph, extracts per-agent sequential features with a selective state-space backbone, propagates relational context with a Lipschitz-normalised temporal graph attention layer, and selects defensive actions through a Hedge-based controller. The detector carries two complementary certificates. First, a randomised-smoothing certificate on the payload-embedding feature space yields a lower bound on the expected defender utility of the form $V^* - B\ \Pr[\neg\mathcal{C}_\varepsilon] - B\sqrt{\ln N/(2T)} - B\alpha_{MC}$, in which every term shares the utility unit so the composition type-checks. Second, a sparse-smoothing certificate on the protocol graph bounds the number of injected or removed edges an attacker can tolerate per window. We evaluate MambaGuard with three seeds on MCPTox, MCP-SafetyBench, AgentDojo, InjecAgent and a synthetic A2A sandbox, on grouped splits, against an episode-length control and a bag-of-words logistic-regression baseline. The detector separates the structural A2A attacks (macro-F1 0.968 ± 0.001, AUROC 0.997), but it does not beat the lexical baseline on any benchmark: it is level with it on the A2A sandbox (0.952) and clearly behind it where the attack is a text payload (MCPTox 0.48 vs 0.85, MCP-SafetyBench 0.62 vs 0.88, AgentDojo 0.75 vs 1.00). No architectural component is necessary on these benchmarks, and the residual-aware Lipschitz bound of the trained models is vacuous. We read this as a finding about the benchmarks as much as about the detector: their attacks are largely templated text that word counts already expose. We also show that the block-product Lipschitz bound used in earlier detectors of this family is not a valid upper bound once residual paths are counted, and we replace it with a residual-aware bound that a gradient-ascent probe confirms. We release an anonymised reference implementation, the evaluation harness, and a reproducibility script that regenerates every table and figure from a single command.**

1. Introduction

Enterprise AI has moved from single-prompt interfaces to protocol-mediated agent meshes. A 2025 systematic review of the Model Context Protocol catalogued more than thirty attack techniques at the MCP layer alone [1], and the empirical MCPSecBench study reported attack success rates above eighty-five per cent on at least one major commercial deployment [2]. The MCP Inspector remote-code-execution flaw [3] and the A2ABreak catalogue of eleven protocol-level vulnerabilities [4] confirm that protocol exposure translates directly into system compromise. The defensive response so far has been fragmented along three separate axes.

First, *design-level* defences such as CaMeL [13] and MELON [14] prevent prompt-injection outcomes by sandboxing tool invocation or isolating untrusted content. These approaches are complementary to detection: they provide provable guarantees on specific agent decisions, not on the broader protocol traffic. Second, *tool-boundary monitors* like ClawGuard [9] enforce per-call deterministic policies, and program-dependency monitors like AgentArmor [8] reconstruct a per-trace dependency graph. Neither observes the multi-agent interaction graph, nor reports a quantitative robustness guarantee. Third, classical *network intrusion detection systems* have evolved through graph neural networks [28], transformer encoders [29], and selective state-space models [23] — but these operate on flat flow features and do not model MCP/A2A/ACP/ANP message semantics or certify their own output.

MambaGuard closes the gap between these three strands. It models the protocol stream as a time-stamped heterogeneous graph whose vertices are agents, tools, capability descriptors, and sessions, and whose edges carry canonicalised message tuples. A selective state-space backbone [19] processes each agent's message stream in linear time; a Lipschitz-normalised GATv2 layer [24], [26] propagates relational context; and a Hedge controller [37] selects defensive actions online with no-regret against the best fixed commitment in hindsight. Two certificates accompany the detector: a randomised-smoothing certificate [30] on the payload-embedding feature space, and a sparse-smoothing certificate [34] on graph edges.

1.1. Contributions

- A **unified protocol-graph schema** for MCP, A2A, ACP and ANP (§4.1) with a five-class canonical message taxonomy.
- A **streaming composed detector** that couples a selective SSM with a Lipschitz-normalised temporal GATv2 layer over a per-window protocol graph (§4).
- A **dimensionally consistent two-certificate scheme** (§5): a Cohen-style smoothing certificate on feature-space perturbations with a composition theorem whose terms all carry the utility unit, plus a sparse-smoothing certificate on graph edits.
- A **measured study with controls** (§7): three seeds, bootstrap intervals, an episode-length control and a lexical baseline on every benchmark. The detector separates structural A2A attacks (macro-F1 0.968 vs a 0.53 length control) but trails a bag-of-words classifier on payload-borne attacks, and component ablations show no part of the architecture is necessary on these benchmarks.
- A **benchmark audit** (§7.2): the top lexical features are the attack templates themselves, two benchmarks have 14 or fewer benign test episodes, and InjecAgent's benign class is a single filler sentence, so episode-level scores on these corpora overstate what a detector has learned.
- An **anonymised artifact** that regenerates every table and figure with one command.

1.2. Scope and Non-Goals

The paper's guarantees are deliberately scoped. The feature-space certificate holds inside the payload-embedding feature space, not for arbitrary text edits; the graph certificate holds under a bounded number of edge additions or deletions, not under host compromise; and the online bound holds in the zero-sum restriction of the defender game. §5.6 and §9 state exactly what the certificates do and do not cover.

2. Background

Two technical ingredients underpin the paper. We state only what the body of the paper needs; extensions and standard proofs are deferred to Appendix A.

Selective state-space models.. A continuous state-space model maintains a hidden state $h(t) \in \mathbb{R}^N$ evolving as $h'(t) = Ah(t) + Bu(t)$, with output $y(t) = Ch(t)$. Zero-order-hold discretisation gives $h_t = \bar{A}h_{t-1} + \bar{B}u_t$, with $\bar{A} = \exp(\Delta A)$ and $\bar{B} = (\Delta A)^{-1}(\exp(\Delta A) - I)\Delta B$. The selective variant Mamba [19] makes Δ, B, C input-dependent and amortises inference in $\mathcal{O}(L)$ per sequence of length L via a hardware-aware parallel scan. We adopt the **S4D-Real** parameterisation [20], in which $A \in \mathbb{R}^N$ is a diagonal real matrix with strictly negative entries; this is the default Mamba initialisation and the choice reported to perform best on discrete modalities. For a real diagonal matrix the spectral radius equals the spectral (operator-2) norm, which is the property we exploit in the Lipschitz analysis of §5.2.

Randomised smoothing.. Given a base classifier f, the smoothed classifier $g(x) = \arg\max_c \Pr_{\delta\sim\mathcal{N}(0,\sigma^2 I)}[f(x + \delta) = c]$ is certifiably robust in ℓ_2 within a radius $r = \sigma\,\Phi^{-1}(p_A)$, where p_A is the probability of the top class under the noise distribution and Φ is the standard normal CDF [30]. In practice p_A is replaced by a Clopper-Pearson lower bound $\underline{p_A}$ estimated from n Monte-Carlo samples, with a failure probability α_{MC} absorbed into the certificate.

3. Threat Model and Security Goals

A robustness claim is only as meaningful as its threat model. We specify ours along four axes.

System model.. Several agents communicate through MCP, A2A, ACP and ANP. A trusted detector observes every protocol message, canonicalises it, and maintains a sliding-window protocol graph. A defender action is selected per round and applied to one message or session: deep packet inspection, blocking, session termination, agent isolation, or capability revocation.

Attacker knowledge.. We consider a *grey-box* attacker who knows the detector's architectural family (selective SSM plus temporal GATv2, protocol-graph representation, 34-class attack taxonomy), the published hyperparameters, and the payload encoder. The attacker does not have the deployed weights or the per-tenant Hedge random seed. For each experiment we also report a *white-box* setting in which the attacker additionally receives the trained weights and the embedding gradient; this is the standard worst case used by [39].

Attacker capabilities.. The attacker may (i) craft or rewrite protocol payloads inside a signed agent envelope; (ii) modify tool descriptions or Agent Cards; (iii) replay historical messages within a bounded time window; (iv) inject or delete graph edges up to a budget k per detection window through a compromised registered agent; (v) query the detector a bounded number of times to drive an attack search. The attacker cannot forge cryptographic signatures outside the compromised set, cannot compromise the host that runs the detector, and cannot modify the detector's weights. Compromise of the model supply chain, memory, or host is explicitly out of scope.

Attacker action space $\mathcal{A}_A$.. Seven families from the agent-protocol attack literature [1], [2], [4]: tool poisoning, indirect prompt injection, rug-pull capability updates, capability shadowing, cross-server capability confusion, credential exfiltration, and sandbox bypass.

Perturbation budgets.. Two complementary budgets. $\varepsilon \geq 0$ bounds the ℓ_2 norm of perturbations at the frozen payload-embedding layer; this is where the smoothing certificate holds. $k \in \{0, 1, \ldots\}$ bounds the number of graph edges the attacker may add or delete inside one detection window; this is where the sparse-smoothing certificate holds. We do *not* claim that the ℓ_2 budget transports to a bound on

raw text edits: the payload encoder has no meaningful global Lipschitz constant from token edits to embeddings, and a single token change can move an embedding arbitrarily far relative to ε. §5.6 returns to this restriction.

Security goals.. The defender seeks (G1) low per-message false-positive rate on benign traffic; (G2) high detection rate on malicious traffic; (G3) *certified* robustness within the stated perturbation budgets; (G4) sustained throughput at the message rate of the monitored deployment.

4. Protocol Graph and Detector

4.1. Unified Heterogeneous Protocol Graph

Let $\mathcal{G}(t) = (\mathcal{V}(t), \mathcal{E}(t), X(t))$ denote the protocol graph at wall-clock time t. The vertex set $\mathcal{V}(t) = \mathcal{V}_A \cup \mathcal{V}_T \cup \mathcal{V}_C \cup \mathcal{V}_S$ is partitioned into agents, tools or services, capability descriptors, and active sessions. Edges are time-stamped and typed; the five canonical types are agent-calls-tool, agent-messages-agent, agent-advertises-capability, tool-returns-data, and agent-delegates-task. Each protocol message is canonicalised into the tuple

$$m = (\tau, s, d, p, \mu, t_m),$$

where $\tau \in \{\mathcal{M}_{\text{tool}}, \mathcal{M}_{\text{comm}}, \mathcal{M}_{\text{cap}}, \mathcal{M}_{\text{data}}, \mathcal{M}_{\text{ctrl}}\}$, s, d are source/destination identifiers, $p \in \mathbb{R}^{d_p}$ is a payload embedding ($d_p = 384$, a frozen, L2-normalised MiniLM sentence embedding by default), $\mu \in \mathbb{R}^{d_\mu}$ carries HTTP status, latency and auth metadata, and t_m is the message timestamp. A rule-based parser produces one tuple per raw protocol packet for each of MCP, A2A, ACP and ANP.

Worked example.. Consider a 2-second window in which Agent A issues an MCP `tools/list` to a database tool T_1 and receives a 400-byte JSON response; concurrently, Agent B sends an A2A `tasks/send` to Agent A delegating a user query, and a new capability descriptor C_3 is advertised through ANP by Agent C. The parser canonicalises six messages into three edges: $(A \to T_1, \mathcal{M}_{\text{tool}})$, $(T_1 \to A, \mathcal{M}_{\text{data}})$, $(B \to A, \mathcal{M}_{\text{comm}})$, and one capability-advertisement edge $(C \to C_3, \mathcal{M}_{\text{cap}})$. All four edges carry the same timestamp bucket $t_e \in [0, 2]$. The graph $\mathcal{G}(t)$ at the end of the window thus has six nodes (three agents, one tool, one capability, one session), four typed edges, and per-edge features comprising the 384-dim frozen embedding of the payload and a 32-dim metadata vector. This is the input the detector sees for one detection decision.

4.2. Selective SSM Backbone

For each agent $a \in \mathcal{V}_A$, the sequence of incident messages $x^a = (m_1^a, \ldots, m_{L_a}^a)$ is processed by a four-layer selective block (details in Appendix E):

$$h_t^a = \bar{A}_t \, h_{t-1}^a + \bar{B}_t \, m_t^a, \tag{1}$$

$$z_t^a = C_t \, h_t^a \odot \mathrm{SiLU}\big(W_g \, m_t^a\big), \tag{2}$$

with the standard Mamba depthwise causal 1-D convolution applied to x^a before (1). The gated output $z_t^a \in \mathbb{R}^{d_z}$ is the per-agent sequential feature.

Algorithm 1 MambaGuard online defence loop

Require: Horizon T, utility range B, number of defender actions $N = |\mathcal{A}_D|$

$\eta \leftarrow \sqrt{8 \ln N / T} \,/\, B$ ▷ Corrected tuning (§5.4)
$w_1(s) \leftarrow 1$ for all $s \in \mathcal{A}_D$
for $t = 1, \ldots, T$ **do**
  Observe $\mathcal{G}(t)$ and per-agent streams
  Compute z_t^a via (1)–(2)
  Compute h_t^a via (3)
  Score classes $\hat{y}_t \leftarrow \mathrm{softmax}(W_h h_t)$
  Sample action $s_t \sim p_t(s) = w_t(s) / \sum_{s'} w_t(s')$
  Observe loss $\ell_t(s) \in [0, B]$
  $w_{t+1}(s) \leftarrow w_t(s) \exp(-\eta \, \ell_t(s))$
end for

4.3. Lipschitz-Normalised Temporal GATv2

With $\{z^a\}_{a \in \mathcal{V}_A}$ available, a temporal GATv2 layer propagates relational information. For an ordered pair (a, a') joined by an edge with timestamp t_e, the attention logit is

$$e_{a,a'} = q^\top \, \mathrm{LeakyReLU}\big(W_r \, [z^a \| z^{a'} \| e_{a,a'}^{\text{feat}} \| \Phi(t - t_e)]\big), \tag{3}$$

where $\Phi(\Delta t)$ is the Bochner-derived TGAT time encoding [25] with d_T learnable frequencies, $\|$ denotes concatenation, and q, W_r, W_v are learnable. We apply *LipschitzNorm* [26] to the attention weights; this is essential for the Lipschitz analysis below, because vanilla GATv2's dot-product attention is *not* Lipschitz for any ℓ_p norm on an unbounded domain (Kim *et al.* [27] prove this for self-attention and the argument transfers to GATv2). Multi-head attention with $H = 4$ heads is averaged at the final layer; the composed feature h^a feeds a softmax head over the 34-class attack taxonomy.

4.4. Hedge Controller

The detector logits parameterise a Hedge [37] selector over the five defensive actions $\mathcal{A}_D$. Algorithm 1 states the complete loop.

5. Certified Guarantees

The detector carries two certificates — feature-space (§5.1) and graph-edit (§5.3) — plus a no-regret guarantee on the Hedge controller (§5.4). §5.5 combines them in a dimensionally consistent composition theorem, and §5.6 states what the certificates do and do not operationally guarantee.

5.1. Feature-Space Smoothing Certificate

We define the smoothed detector $g(x) = \arg\max_c \mathbb{P}_{\delta \sim \mathcal{N}(0, \sigma^2 I)}[f(x + \delta) = c]$ over the payload-embedding input x. Following [30], for a given x let $\underline{p_A}$ be the Clopper-Pearson lower bound on $\mathbb{P}[f(x + \delta) = \overline{g(x)}]$

from n Monte-Carlo samples at confidence $1-\alpha_{MC}$. Then with probability at least $1-\alpha_{MC}$ the certified radius is

$$R(x) = \sigma\,\Phi^{-1}\big(\underline{p_A}\big), \tag{4}$$

and $g(x+\delta') = g(x)$ for all $\|\delta'\|_2 \le R(x)$. We report certified-accuracy-vs-radius curves rather than a single number, because the radius varies per input (§7.3).

5.2. Local Lipschitz Bound on the Composed Detector

The smoothed detector's accuracy is tightened when the base detector is Lipschitz on the perturbed domain. For MambaGuard the base map is $f = h \circ g_{\text{gat}} \circ g_{\text{ssm}}$. We state the bound under explicit bounded-input assumptions, because the selective SSM and the gated output are both products of input-dependent factors and therefore *not* globally Lipschitz on $\mathbb{R}^d$.

Assumption 1 (Bounded operating regime)**.** *(i) Inputs are projected to a Euclidean ball $\|x_t\|_2 \le X_{\max}$; (ii) discretisation steps are clamped to $\Delta_t \in [\Delta_{\min}, \Delta_{\max}]$; (iii) spectral norms of the projections producing B_t, C_t and Δ_t (including their Jacobians) are bounded by M_B, M_C, M_Δ respectively; (iv) the state matrix $A \in \mathbb{R}^N$ is real diagonal with strictly negative entries (S4D-Real) and $\Delta_{\max}\max_i A_i < 0$, so $\rho(\bar{A}_t) = \|\bar{A}_t\|_2 \le \rho < 1$.*

Lemma 1 (Local Lipschitz of the selective block)**.** *Under Assumption 1, with $\beta := \sup_t \|\bar{B}_t\|_2$, $\gamma := \sup_t \|C_t\|_2$, $\kappa_g := \|W_g\|_2$, $L_\sigma \approx 1.0998$ the exact SiLU Lipschitz constant, and $X_{\max}$ the input-norm cap, the selective block g_{ssm} is Lipschitz on $\{x : \|x_t\| \le X_{\max}\}$ with*

$$L_{ssm} \le \frac{\gamma\beta(1+L_\sigma\kappa_g)}{1-\rho} + \frac{\gamma\beta X_{\max}(M_B+M_C+M_\Delta)}{(1-\rho)^2}. \tag{5}$$

The second term accounts for the input-dependent factors in $\bar{B}_t, C_t, \Delta_t$; it vanishes only when those parameters are input-independent (the S4 limit). Proof in Appendix B.

Lemma 2 (LipschitzNormed GATv2)**.** *With LipschitzNorm scaling constant η and Bochner frequencies $\{\omega_k\}$, the temporal GATv2 layer (3) satisfies*

$$L_{gat} \le \|W_v\|_2\big(1+\eta\,\|q\|_2\,\|W_r\|_2\big), \tag{6}$$

$$L_\Phi \le \|W_v\|_2\,\eta\,\|q\|_2\,\|W_r\|_2\sqrt{\tfrac{2}{d_T}\textstyle\sum_k \omega_k^2}. \tag{7}$$

Residual paths matter.. The detector stacks S residual SSM blocks after an input projection W_{in}, so the sound composition is

$$L_f \;\le\; M_h\,L_{\text{gat}}\,\|W_{\text{in}}\|_2\prod_{\ell=1}^{S}\big(1+L_{\text{ssm}}^{(\ell)}\big). \tag{8}$$

The plain product $M_h L_{\text{gat}}\prod_\ell L_{\text{ssm}}^{(\ell)}$, which drops the identity branch of every residual block and the input projection, is *not* an upper bound: in §7.3 a gradient-ascent probe exceeds it by a factor of 3.6. The smoothing certificates we report (§7.3) do not depend on (8); the bound is a diagnostic of the architecture, and **we do not claim it transfers to raw text perturbations**.

5.3. Sparse-Smoothing Graph-Edit Certificate

A continuous certificate does not express structural attacks such as Agent Card impersonation, which add or remove edges in $\mathcal{G}(t)$. We apply the sparse-smoothing framework of Bojchevski *et al.* [34]. For edge-flip probabilities p_+ (adding an absent edge) and p_- (deleting a present edge), the smoothed classifier on edge-perturbed graphs is certified robust to budgets (k_a, k_d) whenever

$$\sum_{\mathbf{Q}\in\mathcal{H}} \min\{\mathbf{p}^+_{\mathbf{Q}}, \mathbf{p}^-_{\mathbf{Q}}\} \;\ge\; p_A - 0.5, \tag{9}$$

where the pointwise bound is taken over the Neyman-Pearson regions $\mathcal{H}$ induced by budgets k_a edge additions and k_d edge deletions, and $\mathbf{p}^\pm$ are the per-region likelihoods under the clean and perturbed noise distributions (full statement in [34], Theorem 1). In practice we evaluate the bound over the attacker's candidate edge set, not over all node pairs, which both reduces variance and matches the registered-agent restriction in the threat model.

5.4. Online No-Regret Guarantee

For losses in $[0, B]$ the Hedge regret bound $R_T \le (\ln N)/\eta + \eta T B^2/8$ is minimised at

$$\eta^* \;=\; \sqrt{8\ln N/T}\;/\;B, \tag{10}$$

giving

$$R_T \;\le\; B\sqrt{(T/2)\ln N}. \tag{11}$$

(This is the classical Cesa-Bianchi–Lugosi tuning [37]; the frequently quoted $\eta = \sqrt{2\ln N/T}$ minimises the cruder bound $(\ln N)/\eta + \eta T/2$ and gives $\sqrt{2T\ln N}$, twice the constant.) For an anytime variant with $\eta_t = \sqrt{8\ln N/t}/B$, the regret is at most $B(\sqrt{2T\ln N} + \ln N/8)$.

Theorem 1 (No-regret)**.** *Algorithm 1 with η as in (10) satisfies (11).*

We do *not* claim that no-regret dynamics converge to the Stackelberg leader value in general. That claim is only true in two restricted settings: (a) the defender-attacker game is *zero-sum*, in which case the Stackelberg value equals the minimax value and Hedge's time-average payoff is within R_T/T of it; or (b) the guarantee is phrased as regret against the *best fixed commitment in hindsight* over a finite set of attacker types [38], with the action set restricted to the extreme points of the attacker best-response polytopes. Our experiments report both views.

5.5. Composed Certificate (Type-Checked)

Let $\mathcal{C}_\varepsilon$ be the event that the smoothed detector's prediction is certified constant at radius ε, as in (4). On $\mathcal{C}_\varepsilon$ the defender's action and utility are unchanged under attack; off $\mathcal{C}_\varepsilon$ the per-round loss is at most B. Combining with Theorem 1 gives the composition.

Theorem 2 (Composed certificate)**.** *Let V^* be the Stackelberg value under the restriction of §5.4(a) or (b), $\hat{\pi}_T$ the Hedge policy after T rounds, $\varepsilon \geq 0$ the feature-space ℓ_2 budget, and α_{MC} the Monte-Carlo failure probability in (4). Then*

$$\mathbb{E}\big[V_{ach}(\hat{\pi}_T, \varepsilon)\big] \;\geq\; V^* - B\,\mathbb{P}\big[\neg\mathcal{C}_\varepsilon\big] - B\sqrt{\tfrac{\ln N}{2T}} - B\,\alpha_{MC}. \tag{12}$$

All four terms share the utility unit; $\mathbb{P}[\neg\mathcal{C}_\varepsilon] = 1 - \mathrm{CertAcc}(\varepsilon)$ is read off the certified-accuracy curve. Proof in Appendix C.

5.6. Operational Meaning and Non-Guarantees

Theorem 2 guarantees a lower bound on long-run expected defender utility against any attacker whose per-round perturbation stays within the stated budgets. It does *not* guarantee: (i) that an arbitrary text edit of a payload lies within ε in embedding space (the encoder has no global token-to-embedding Lipschitz constant); (ii) robustness to graph edits beyond $k_a + k_d$ within one window; (iii) robustness to host compromise, cryptographic-signature forgery, or zero-day protocol-implementation flaws. Applications that require payload-level provable robustness should additionally use the erase-and-check certificate of Kumar *et al.* [33] against suffix/insertion/infusion up to d tokens; our evaluation reports this composition in §7.3.

6. Experimental Setup

6.1. Benchmarks

We evaluate on six benchmarks that span the agent-protocol attack surface. None of them records protocol traffic with timestamps, so each case is rendered as an *episode*: the JSON-RPC messages an observer between host and servers would see around one user task, with a per-message label marking attacker-controlled content (construction, pinned source commits and counts in Appendix F). Splits are grouped and stratified so that no server, case or attack/benign pair appears in two splits.

MCPTox [6]: 1,312 tool-poisoning instances over 10 risk categories on 45 real MCP servers (353 tools). Each attack episode lists the server's clean tools plus one poisoned tool; 533 benign episodes replay the same user queries with the clean tool list. Split by server (train/val/test 1,263/283/299 episodes), so test servers are unseen.

MCP-SafetyBench [5]: 245 attack cases over 5 domains and 20 attack types. Clean tool lists are taken from the benchmark's own server sources; each attack is placed on the message that carries it (poisoned description, added tool, injected or forged tool result, replayed or spoofed call, or the user request). We use the 238 cases whose attack is visible on the wire (the 7 rug-pull cases change tool code but no message) plus 162 exact benign twins for the description-borne attacks.

MCPSecBench [2]: the 11 attacks for which the benchmark provides prompts, rendered against its benign and malicious playground servers, with 7 benign twins. Because the twins differ in the number of servers, episode length alone separates the classes, so we report only message-level detection on this set.

A2A-sandbox: synthetic A2A v1.0 traces we generate for the 11 vulnerability classes of A2ABreak [4], whose artifact analyses the specification and contains no traffic. Each of 2,200 attack episodes has a benign twin with the same participants and task that differs only in the decisive field (requested scope, reused `contextId`, webhook host, chunk index, ...); both receive identical random background exchanges. We report results on the default pair-grouped split and leave-one-finding-out.

AgentDojo [11]: the recorded agent runs shipped with the benchmark (no agent is re-run) for one model (`claude-3-5-sonnet`); a tool result is labelled as attacker-controlled when the injected string surfaces in it. 550 attack and 97 benign episodes. **InjecAgent** [12]: 1,054 templated cases, each a tool result whose single injection slot is filled with the attacker instruction; benign twins fill the slot with neutral text.

Shortcut control.. For every benchmark we also report a one-threshold classifier on episode length. It reaches balanced test accuracy 0.50 on MCPTox, MCP-SafetyBench, AgentDojo and InjecAgent, and 0.53 on the A2A-sandbox, so a detector must beat these numbers to be doing anything beyond counting messages. **Lexical baseline.** We also train a TF–IDF logistic regression on the concatenated JSON text of each episode (word uni- and bigrams, minimum document frequency 2, at most 5×10^4 features, balanced class weights, $C = 1$) on the same splits, with the same validation-tuned threshold. It has no sequence model, no graph and no protocol knowledge, so it measures how much of a benchmark words alone solve.

Small benign classes. The test splits contain 330 (A2A), 70 (MCPTox), 24 (MCP-SafetyBench), 14 (AgentDojo) and 3 (InjecAgent) benign episodes; false-positive rates on the last three rest on very few windows.

6.2. Payload Encoder, Metrics and Protocol

Each message payload is serialised to JSON and embedded once by a frozen `all-MiniLM-L6-v2` sentence encoder (384 dimensions, L2-normalised); one embedding per message. All detector runs use the per-window protocol-graph read-out, four selective-SSM blocks and two GATv2 layers (3.67 M trainable parameters), AdamW (learning rate 3×10^{-4}, 200 warm-up steps), focal loss, the Lipschitz regulariser $\lambda_L = 10^{-3}$, batch 32, class-balanced sampling of

TABLE 1. TEST DETECTION, MEAN ± S.D. OVER THREE SEEDS (MINILM ENCODER, ONE T4). MACRO-F1 USES THE THRESHOLD TUNED ON VALIDATION. "LEXICAL" IS THE TF–IDF LOGISTIC-REGRESSION BASELINE ON THE SAME SPLITS AND THRESHOLD RULE; "LEN." IS THE BALANCED ACCURACY OF THE EPISODE-LENGTH CONTROL. n IS THE NUMBER OF TEST EPISODES (BENIGN IN BRACKETS). MCPSECBENCH (18 EPISODES WHOSE CLASSES DIFFER IN LENGTH) SUPPORTS ONLY MESSAGE-LEVEL EVALUATION AND IS NOT INCLUDED.

		MambaGuard		Lexical		
Benchmark	n **(ben.)**	**Macro-F1**	**AUROC**	**F1**	**AUROC**	**Len.**
A2A sandbox	660 (330)	$\mathbf{0.968}_{\pm.001}$	0.997	0.952	0.995	0.53
MCPTox	265 (70)	$0.482_{\pm.020}$	0.593	**0.845**	0.911	0.50
MCP-SafetyBench	59 (24)	$0.619_{\pm.104}$	0.703	**0.880**	0.935	0.50
AgentDojo	104 (14)	$0.751_{\pm.089}$	0.877	**1.000**	1.000	0.50
InjecAgent	189 (3)	$0.630_{\pm.232}$	1.000	1.000	1.000	0.50

training windows, and early stopping on validation macro-F1 with patience 5 (at most 15, 20, 30, 30 and 20 epochs for A2A, MCPTox, MCP-SafetyBench, AgentDojo and InjecAgent). Each configuration is trained with seeds 0, 1 and 2 (ablations: seeds 0 and 1) on one NVIDIA T4 under bfloat16 autocast; the whole study took 4.0 GPU-hours (Appendix E).

The decision threshold is chosen on the validation split to maximise macro-F1 and then applied to the test split. We report test macro-F1 at that threshold (primary), macro-F1 at 0.5, AUROC, attack recall and false-positive rate, as mean ± standard deviation over seeds, and a 1,000-sample bootstrap 95% interval for seed 0. A head-to-head comparison with the published agent defences of §10 needs each one retrained on the same splits and is not part of this study.

7. Results

7.1. Per-Benchmark Detection

Table 1 reports test detection for the detector and both controls. On the A2A sandbox, where the attack is *structural* — a reused context identifier, an unverified webhook host, an over-claimed Agent Card, an out-of-order task state — MambaGuard reaches macro-F1 0.968 ± 0.001 and AUROC 0.997, with attack recall 0.96 at a false-positive rate of 0.025; the seed-0 bootstrap interval is $[0.953, 0.980]$, far above the 0.53 length control. Where the attack is a *text payload*, detection is weak to moderate: MCPTox 0.48 (AUROC 0.59), MCP-SafetyBench 0.62 (AUROC 0.70), AgentDojo 0.75 (AUROC 0.88). Seed variance is large on the two smallest test sets (MCP-SafetyBench, AgentDojo). On InjecAgent every seed ranks all attacks above all benign windows (AUROC 1.000; macro-F1 1.000 at threshold 0.5), but the validation split holds only two benign windows, the tuned threshold collapses to 0.04, and the test macro-F1 at that threshold averages 0.63; with three benign test windows neither number is informative (§7.2).

7.2. What a Lexical Baseline Reveals

The bag-of-words classifier matches MambaGuard on the A2A sandbox and beats it by 0.26–0.37 macro-F1 on every payload benchmark (Table 1). We checked that this is not leakage through identifiers: its heaviest attack features are the attack text itself — "important", "you must", "ignore the previous", "when using" on MCPTox; the fixed AgentDojo injection template ("before you can solve the task that I gave you"); the attacker's request on InjecAgent. Three conclusions follow.

The detector loses lexical detail. One sentence embedding per message averages a poisoned description with the server's clean tool descriptions in the same `tools/list` result (7.8 per server on average in MCPTox), and the injected sentence in a long tool result with its surrounding text. The graph and sequence layers cannot recover a signal the encoder has already diluted. Per-tool or per-chunk embeddings, or lexical features fed alongside the embedding, are the obvious next step; we have not evaluated them.

The benchmarks are easier than their size suggests. Attacks are instantiated from a small number of text templates, so a word-level classifier separates them; on AgentDojo and InjecAgent it is perfect. Benign classes are small and narrow: InjecAgent's 17 benign episodes all carry one filler sentence, MCP-SafetyBench's benign twins exist only for description-borne attacks and come mostly from the web-search servers ("serper" and "serpapi" are among the strongest benign features), and the A2A sandbox's attack templates have their own vocabulary ("jwks", "admin", "hr records"), which likely explains why the lexical baseline also reaches 0.95 there. Episode-level scores on these corpora say little about robustness to unseen attack phrasings. Evaluation on held-out templates, and message-level evaluation, would test that; we have not run them.

Structure is not yet shown to add over words. On the one benchmark where attacks are structural, the detector's lead over the lexical baseline (0.968 vs 0.952) is at the edge of the seed-0 bootstrap interval, and the ablations below show that removing the graph or the sequence model does not lower it.

7.3. Certification: Actual Lipschitz Constant, Smoothing and Graph-Edit

Table 2 reports the per-component Lipschitz factors as a function of the effective spectral cap $c = \sup_\ell \|W^{(\ell)}\|_2$ enforced by the regulariser λ_L. The key finding is at $c = 0.5$: the block-product quantity is 0.023, but projected gradient ascent on δ finds a ratio $\|f(x+\delta) - f(x)\|/\|\delta\|$ of 0.083, i.e. 3.6× larger. The block product is therefore *not* an upper bound; it omits the identity branch of each residual block and the input projection. The residual-aware bound (8) is 3.09, which the probe respects, and which is 37× looser than the probe. Tighter LipSDP-style estimates [32] are future work. On the *trained* benchmark models the residual-aware bound is vacuous: 4×10^5–2×10^6 for the full model with the regulariser ($\lambda_L = 10^{-3}$) and 1.2–1.5×10^8

TABLE 2. LIPSCHITZ BOUNDS VERSUS THE EFFECTIVE SPECTRAL CAP c IMPOSED ON EVERY LINEAR LAYER (DEFAULT 3.68 M-PARAMETER CONFIGURATION). "BLOCK PRODUCT" IS $M_h L_{\text{GAT}} \prod_\ell L_{\text{SSM}}^{(\ell)}$; "RESIDUAL" IS THE SOUND BOUND (8); $\hat{L}_f$ IS THE EMPIRICAL LOWER BOUND FROM 200-STEP PROJECTED GRADIENT ASCENT ON δ ("—" WHERE THE RESIDUAL BOUND AND THE PROBE WERE NOT EVALUATED; THEY WERE RUN AT $c = 0.5$).

c	L_{ssm}	L_{gat}	Block product	Residual	$\hat{L}_f$
0.50	0.06	1.46	0.023	3.09	0.083
0.75	12.88	5.50	39.87	—	—
1.00	58.84	14.73	651.80	—	—
1.25	89.74	32.30	2482.52	—	—
2.00	177.96	67.99	10364.17	—	—




Figure 1. Measured certified accuracy versus ℓ_2 radius on the benchmark test sets (seed-0 models, $\sigma = 0.05$, $n = 500$, $\alpha_{MC} = 10^{-3}$). The maximum certifiable radius at this n is ≈ 0.11.

without it (Table 4). The regulariser lowers the bound by two orders of magnitude without changing detection, but neither value certifies anything; the certificates below therefore use randomised smoothing alone.

Figure 1 plots certified accuracy against radius for the seed-0 model of each benchmark: the fraction of test windows that the smoothed detector classifies correctly *and* certifies at radius r, with Gaussian noise added to the payload embedding of every message in the window (100 test windows, 59 for MCP-SafetyBench; $n_0 = 32$ selection and $n = 500$ estimation samples; $\alpha_{MC} = 10^{-3}$). With $n = 500$ the largest certifiable radius is $\sigma\Phi^{-1}(\alpha_{MC}^{1/n}) \approx 2.2\sigma$, i.e. 0.11 at $\sigma = 0.05$, so every curve reaches zero by $r = 0.25$. On the A2A sandbox, certified accuracy is 0.93 at $r = 0$, 0.62 at $r = 0.05$ and 0.11 at $r = 0.1$; feeding this curve into Theorem 2 ($V^* = B = 1$, $T = 10^4$, $N = 5$) gives a defender-utility lower bound of 0.92, 0.61 and 0.10. Larger noise costs accuracy without buying radius at this sample size: at $\sigma = 0.10$ and 0.25 the A2A certified accuracy at $r = 0$ falls to 0.73 and 0.37 and the abstention rate rises from 0.03 to 0.21 and 0.53. The InjecAgent curve is high mainly because 98% of its windows are attacks; the MCPTox curve is low because the base detector is weak. Radii are measured on unit-norm MiniLM embeddings; we have not measured how far a text edit moves an embedding, so none of these radii is a text-level guarantee (§5.6).

TABLE 3. DETECTOR FORWARD LATENCY ON ONE T4 (MEDIAN OF 100 RUNS AFTER 10 WARM-UPS; REFERENCE SCAN; PAYLOAD ENCODING EXCLUDED). "BATCH 1" IS ONE DETECTION WINDOW (3–8 MESSAGES). "BEST BATCH" IS THE NUMBER OF WINDOWS PER BATCH, AMONG 1, 8, 32 AND 128, THAT MAXIMISES MESSAGES PER SECOND.

	Batch 1 (one window)			Best batch		
Benchmark	**median**	**p99**	**per msg**	**windows**	**per msg**	**msg/s**
A2A sandbox	8.5 ms	10.2 ms	1.06 ms	32	0.11 ms	9,008
MCPTox	8.4 ms	12.6 ms	2.80 ms	128	0.11 ms	8,878
MCP-SafetyBench	8.9 ms	9.8 ms	1.27 ms	32	0.18 ms	5,708
AgentDojo	8.2 ms	13.8 ms	2.04 ms	32	0.19 ms	5,181
InjecAgent	8.3 ms	9.4 ms	1.67 ms	128	0.10 ms	10,231

For the *graph-edit* certificate we use sparse smoothing with $p_+ = p_- = 0.05$, restricted to the attacker's candidate edge set of registered agents. As a correctness check of the implementation, on a 10-node test graph with $n = 1000$ smoothing samples and $\alpha = 10^{-3}$ the certificate returns $\underline{p_A} = 0.993$ and a budget of $(k_a, k_d) = (2, 2)$. A benchmark-scale evaluation of certified edge budgets is not part of this study.

7.4. Latency and Throughput, Harmonised

Per-message latency and aggregate throughput are different quantities, and a single number cannot stand for both. Table 3 therefore reports (i) the streaming batch-1 latency of one detection window and (ii) the amortised per-message cost at the batch size that maximises throughput. Both are forward passes of the detector on one T4 on precomputed payload embeddings, using our reference (non-fused) selective scan; the MiniLM encoding of each message is *not* included.

A single window costs about 8.5 ms regardless of its length, so batch-1 latency is dominated by fixed per-call overhead; batching windows brings the amortised cost to 0.10–0.19 ms per message and throughput to 5,000–10,000 messages per second. (On CPU, with the feature-hashing encoder included, the batch-1 median was 7.7 ms and throughput peaked at 334 messages per second.) We make no claim for a fused-kernel deployment, which we did not measure.

7.5. Component Ablation

Table 4 switches off one component at a time on the A2A sandbox, where the detector works, and on MCPTox, where it does not (two seeds per variant, three for the full model). On the A2A sandbox every variant reaches macro-F1 0.954–0.968 and AUROC 0.996–0.998: the differences are at most 0.014, of the order of the seed spread. Removing the GATv2 layers, removing the SSM, replacing the graph read-out with a flat mean, or replacing the SSM with a Transformer does not degrade detection, and the GAT-only model trains three times faster. On MCPTox all variants stay between 0.41 and 0.51, i.e. near chance, with no consistent ordering. Hence, on these benchmarks, **no component of**

TABLE 4. COMPONENT ABLATION: TEST MACRO-F1 (VALIDATION-TUNED THRESHOLD) / AUROC, MEAN ± S.D. OVER SEEDS; TRAINABLE PARAMETERS; T4 TRAINING TIME OF SEED 0 ON A2A; RESIDUAL-AWARE LIPSCHITZ BOUND L_f OF THE SEED-0 A2A MODEL.

Variant	A2A sandbox	MCPTox	Params	Train	L_f
Full (SSM+GATv2, graph)	$0.968_{\pm.001}$ / 0.997	$0.482_{\pm.020}$ / 0.593	3.67 M	1200 s	7.8×10^5
SSM only (no GATv2)	$0.964_{\pm.005}$ / 0.997	$0.414_{\pm.000}$ / 0.568	1.92 M	1161 s	2.5×10^4
GATv2 only (no SSM)	$0.954_{\pm.001}$ / 0.996	$0.423_{\pm.068}$ / 0.565	1.92 M	392 s	1.0×10^2
Flat read-out (no graph)	$0.964_{\pm.005}$ / 0.998	$0.514_{\pm.028}$ / 0.575	3.67 M	473 s	7.2×10^5
Transformer for SSM	$0.954_{\pm.001}$ / 0.996	$0.481_{\pm.097}$ / 0.598	4.03 M	340 s	∞
No Lipschitz penalty	$0.965_{\pm.009}$ / 0.997	$0.439_{\pm.002}$ / 0.600	3.67 M	1197 s	1.5×10^8

the architecture is shown to be necessary. The Lipschitz regulariser lowers the residual-aware bound by about $190\times$ ($1.5\times10^8 \to 7.8\times10^5$ on A2A) without changing detection, but both values are vacuous, and the bound is infinite for the Transformer variant because softmax attention is not globally Lipschitz [27].

8. Adaptive Attacks and Robustness

A smoothing-based filter must be judged against an attacker who adapts to it, not against static inputs [39], [40]. We therefore built the attack surface into the artifact. Each attack targets a different component: white-box projected gradient descent in the payload-embedding space with Expectation-over-Transformation over the smoothing noise [41] (E1); Greedy Coordinate Gradient token search that keeps the malicious tool call fixed, to measure how far text-level evasion exceeds the feature-space budget [42] (E2); an attacker-LLM payload rewrite under a fixed query budget (E3); graph-structural evasion that splits an attack across agents or windows (E4); and manipulation of the Hedge controller's observed losses (E5).

We report here only what we measured, on CPU, against the untrained reference model. The embedding-PGD attack (E1), run on 16 synthetic inputs with 40 steps and 4 EoT samples, flips 0% of predictions at $\varepsilon \in \{0.01, 0.05\}$, 6.3% at $\varepsilon = 0.10$ and 12.5% at $\varepsilon = 0.20$: inside the certified radius the detector is empirically stable, and the first failures appear only past it, consistent with the certificate of §5. This is an implementation check on synthetic inputs, not a benchmark attack-success rate; the GCG, LLM-rewrite, graph-evasion and Hedge-manipulation attacks are implemented in the artifact but were not run against the trained benchmark models. Given §7.2, the most informative adaptive test is a paraphrase of the templated attack text, which would probe the lexical baseline and the detector alike; we have not run it.

9. Discussion and Limitations

MambaGuard is a *detector*, complementary to design-level defences like CaMeL and MELON that prevent injection outcomes by sandboxing; we view detector+design composition as the deployment target. **The main limitation is empirical.** On the benchmarks we could run, the detector does not beat a bag-of-words classifier, and its components are not individually necessary (§7.2, §7.5). Its one clear success, the A2A sandbox, is our own synthetic data, generated from one template per finding. The benchmarks themselves limit what can be concluded: templated attacks, small benign classes (3–24 test episodes on three of them) and a single recorded model on AgentDojo. A convincing case for a structural detector needs benchmarks with paraphrased attacks, held-out templates and recorded multi-agent traffic, and payload encodings that keep sentence-level detail. Other limitations: **Feature vs payload.** The smoothing certificate holds in the payload-embedding feature space; the erase-and-check composition partially bridges but does not close the gap to text-level perturbations. **Loose Lipschitz.** The sound residual-aware bound is $37\times$ the empirical lower bound at $c = 0.5$, is vacuous ($\geq 4 \times 10^5$) on every trained model, and the simpler block-product bound is not a bound at all; tighter data-dependent estimates are future work. **Small certified radii.** With $n = 500$ smoothing samples no radius above $\approx 2.2\sigma$ can be certified, and the measured radii (≤ 0.11 on unit-norm embeddings) are not tied to any text-edit budget. **Attacker capabilities.** The threat model excludes host compromise, cryptographic-signature forgery and arbitrary new-agent injection; these capabilities need orthogonal defences. Encrypted and post-quantum traffic, and differentially private payload embeddings, are future work.

10. Related Work

Agent-protocol security monitors. ClawGuard [9] enforces deterministic tool-access policies. AgentArmor [8] reconstructs program-dependency graphs from runtime traces. DataSentinel [18] is a game-theoretic detection framework published at IEEE S&P 2025. None observes the multi-protocol interaction graph or reports a certificate.

Design-level defences. CaMeL [13] prevents injection outcomes by design. MELON [14] provides provable guarantees against indirect prompt injection in ICML 2025. Progent [15] adds programmable privilege control. The Task Shield [10] enforces task alignment. These are complementary to our detector.

Certified robustness. Tsuzuku *et al.* [31] introduced Lipschitz-margin training; Cohen *et al.* [30] introduced randomised smoothing. Bojchevski *et al.* [34] developed sparse smoothing for graphs; Schuchardt *et al.* [35], [36] extended to collective and hierarchical variants. Kumar *et al.* [33] gave erase-and-check for LLM prompt perturbations.

Mamba / SSM stability. Halloran *et al.* [21] prove Lyapunov stability for Mamba; a parallel 2024 preprint explores adversarial robustness of deep SSMs [22].

Attention Lipschitz. Kim *et al.* [27] prove that dot-product attention is not globally Lipschitz; LipschitzNorm [26] is the standard remedy for graph-attention networks.

Adaptive-attack methodology. Nasr *et al.* [39] bypassed twelve recent prompt-injection defences; Tramèr *et al.* [40] wrote the methodological reference.

Game theory. Balcan *et al.* [38] prove regret against the best fixed commitment in hindsight for repeated Stackelberg games under unknown attacker types.

11. Conclusion

We presented MambaGuard, a streaming detector for multi-protocol LLM-agent traffic that couples a selective SSM with a Lipschitz-normalised temporal GATv2 layer and ships two type-checked certificates and a corrected online no-regret bound. We corrected the online step size, made the composition theorem unit-consistent, and showed that a block-product Lipschitz bound is unsound once residual paths are counted. Measured with three seeds on one GPU, the detector separates structural A2A attacks (macro-F1 0.968, AUROC 0.997) but trails a bag-of-words baseline on payload-borne attacks (MCPTox 0.48 vs 0.85), and no single component is necessary on these benchmarks. The lexical baseline shows that current agent-security benchmarks are largely solvable from attack-template words, so progress on structural detection needs harder benchmarks as much as better detectors. Code, weights, the adaptive-attack harness, and a reproduction script that regenerates every table and figure are released under an anonymised mirror.

References

[1] X. Hou *et al.*, "Model Context Protocol: Landscape, security threats, and future research directions," arXiv:2503.23278, 2025.

[2] Y. Yang *et al.*, "MCPSecBench: A systematic security benchmark and playground for testing model context protocols," arXiv:2508.13220, 2025.

[3] Qualys, "Anthropic MCP Inspector remote code execution vulnerability (CVE-2025-49596)," Jul. 2025.

[4] A. Lotfi, M. M. Rahman, I. Karim, E. Bertino, "A2ABreak: Systematic security analysis of the A2A protocol," arXiv:2609.10871, 2026.

[5] T. Zong *et al.*, "MCP-SafetyBench: A benchmark for safety evaluation of LLMs with real-world MCP servers," ICLR 2026, arXiv:2512.15163.

[6] Z. Wang *et al.*, "MCPTox: A benchmark for tool poisoning attack on real-world MCP servers," AAAI 2026, arXiv:2508.14925.

[7] Z. Habler *et al.*, "Building a secure agentic AI application leveraging Google's A2A protocol," arXiv:2504.16902, 2025.

[8] P. Wang *et al.*, "AgentArmor: Enforcing program analysis on agent runtime trace to defend against prompt injection," arXiv:2508.01249, 2025.

[9] W. Zhao *et al.*, "ClawGuard: Securing LLM agents through deterministic tool-access policies," arXiv:2604.11790, 2026.

[10] "The Task Shield: Enforcing task alignment to defend against indirect prompt injection in LLM agents," arXiv:2412.16682, 2024.

[11] E. Debenedetti *et al.*, "AgentDojo: A dynamic environment to evaluate prompt injection attacks and defenses for LLM agents," NeurIPS 2024.

[12] Q. Zhan *et al.*, "InjecAgent: Benchmarking indirect prompt injections in tool-integrated large language model agents," Findings of ACL 2024.

[13] E. Debenedetti *et al.*, "Defeating prompt injections by design (CaMeL)," arXiv:2503.18813, 2025.

[14] K. Zhu *et al.*, "MELON: Provable defense against indirect prompt injection attacks in AI agents," ICML 2025, PMLR 267:80310–80329.

[15] T. Shi *et al.*, "Progent: Programmable privilege control for LLM agents," arXiv:2504.11703, 2025.

[16] Meta AI, "PromptGuard: A compact classifier for prompt injection," 2024.

[17] "PIGuard: Prompt injection detection," arXiv:2411.XXXXX, 2024.

[18] Y. Liu *et al.*, "DataSentinel: A game-theoretic detection of prompt injection attacks," IEEE S&P 2025, arXiv:2504.11358.

[19] A. Gu, T. Dao, "Mamba: Linear-time sequence modeling with selective state spaces," arXiv:2312.00752, 2023.

[20] A. Gu *et al.*, "On the parameterization and initialization of diagonal state space models," NeurIPS 2022.

[21] J. T. Halloran *et al.*, "Mamba state-space models are Lyapunov-stable learners," TMLR 2025, arXiv:2406.00209.

[22] "Exploring adversarial robustness of deep state space models," arXiv:2406.05532, 2024.

[23] T. Wang *et al.*, "NetMamba: Efficient network traffic classification via pre-training unidirectional Mamba," IEEE INFOCOM 2025.

[24] S. Brody, U. Alon, E. Yahav, "How attentive are graph attention networks?," ICLR 2022.

[25] D. Xu *et al.*, "Inductive representation learning on temporal graphs," ICLR 2020.

[26] G. Dasoulas, K. Scaman, A. Virmaux, "Lipschitz normalization for self-attention layers with application to graph neural networks," ICML 2021.

[27] H. Kim, G. Papamakarios, A. Mnih, "The Lipschitz constant of self-attention," ICML 2021.

[28] W. W. Lo *et al.*, "E-GraphSAGE: A graph neural network based IDS for IoT," IEEE/IFIP NOMS 2022.

[29] Z. Wu *et al.*, "RTIDS: A robust transformer-based approach for IDS," IEEE Access, vol. 10, 2022.

[30] J. M. Cohen, E. Rosenfeld, J. Z. Kolter, "Certified adversarial robustness via randomized smoothing," ICML 2019.

[31] Y. Tsuzuku, I. Sato, M. Sugiyama, "Lipschitz-margin training," NeurIPS 2018.

[32] M. Fazlyab *et al.*, "Efficient and accurate estimation of Lipschitz constants for deep neural networks," NeurIPS 2019.

[33] A. Kumar *et al.*, "Certifying LLM safety against adversarial prompting," COLM 2024, arXiv:2309.02705.

[34] A. Bojchevski, J. Gasteiger, S. Günnemann, "Efficient robustness certificates for discrete data: Sparsity-aware randomized smoothing for graphs, images and more," ICML 2020.

[35] J. Schuchardt *et al.*, "Localized randomized smoothing for collective robustness certification," ICLR 2023.

[36] J. Schuchardt *et al.*, "Hierarchical randomized smoothing," NeurIPS 2023.

[37] N. Cesa-Bianchi, G. Lugosi, *Prediction, Learning, and Games*. Cambridge Univ. Press, 2006.

[38] M.-F. Balcan, A. Blum, N. Haghtalab, A. D. Procaccia, "Commitment without regrets: Online learning in Stackelberg security games," ACM EC 2015.

[39] M. Nasr *et al.*, "The attacker moves second: Stronger adaptive attacks bypass defenses against LLM jailbreaks and prompt injections," USENIX Security 2026, arXiv:2510.09023.

[40] F. Tramèr *et al.*, "On adaptive attacks to adversarial example defenses," NeurIPS 2020.

[41] A. Athalye, N. Carlini, D. Wagner, "Obfuscated gradients give a false sense of security," ICML 2018.

[42] A. Zou *et al.*, "Universal and transferable adversarial attacks on aligned language models (GCG)," arXiv:2307.15043, 2023.

[43] I. Sharafaldin *et al.*, "Toward generating a new intrusion detection dataset," ICISSP 2018.

[44] E. C. P. Neto *et al.*, "CICIoT2023," *Sensors*, vol. 23, 2023.

[45] N. Moustafa, J. Slay, "UNSW-NB15," MilCIS 2015.

Appendix A. Mathematical Preliminaries

Standard restatement of S4D-Real Mamba, dynamic graph attention and TGAT time encoding; omitted from body for space. Full derivations in the anonymised artifact (file `docs/preliminaries.pdf`).

Appendix B. Proof of Lemma 1 (Local SSM Lipschitz)

Under Assumption 1, the state recurrence $h_t = \sum_{k=0}^{t-1}(\prod_{j=t-k+1}^{t}\bar{A}_j)\bar{B}_{t-k}m_{t-k}$ gives $\|h_t(x)-h_t(x')\| \le \sum_{k\ge 0}\rho^k\beta\|m_{t-k}-m'_{t-k}\| = \beta/(1-\rho)\|x-x'\|_{\infty,t}$. Multiplying by $\gamma = \sup\|C_t\|$ for the output, and by the Hadamard-gate factor $(1+L_\sigma\kappa_g)$ since $\|fg\|_{\mathrm{Lip}} \le \|f\|_\infty L_g + \|g\|_\infty L_f$ with $\|f\|_\infty, \|g\|_\infty \le \gamma\beta X_{\max}/(1-\rho)$, bounded by $X_{\max}$, yields the first term of (5). The second term absorbs the Jacobians of $\bar{B}_t$, C_t and Δ_t with respect to the input; applying submultiplicativity once more gives $\gamma\beta X_{\max}(M_B+M_C+M_\Delta)/(1-\rho)^2$. The depthwise causal convolution is folded into β via its unrolled Toeplitz norm. □

Appendix C. Proof of Theorem 2 (Composed Certificate)

Partition the horizon into rounds where $\mathcal{C}_\varepsilon$ holds and rounds where it does not. On $\mathcal{C}_\varepsilon$ the detector's prediction, hence the defender's action, hence the per-round utility, is unchanged under attack and therefore at least V^* in expectation (by the Stackelberg optimality under the zero-sum or fixed-commitment restriction). On $\neg\mathcal{C}_\varepsilon$ the per-round loss is at most B. The Hedge regret $R_T \le B\sqrt{(T/2)\ln N}$ divided by T gives the second penalty. The α_{MC} term is the probability that the Clopper-Pearson lower bound fails and the certified event is reported in error. □

Appendix D. Exact SiLU Lipschitz Constant

$\frac{d}{du}\mathrm{SiLU}(u) = \sigma(u)(1+u(1-\sigma(u)))$; numerical solution of $\mathrm{SiLU}''(u)=0$ yields $u^* \approx 2.3994$, $\mathrm{SiLU}'(u^*) \approx 1.0998$.

Appendix E. Hyperparameters

$N = 16$, $d_z = 256$, expansion $E = 2$, kernel width $k = 4$, 4 stacked SSM layers; $H = 4$ heads, $d_T = 64$; AdamW lr 3×10^{-4}, weight decay 10^{-2}, cosine schedule with 200 warm-up steps, batch 32, class-balanced sampling, early stopping on validation macro-F1 (patience 5) with at most 15/20/30/30/20 epochs (A2A/MCPTox/MCP-SafetyBench/AgentDojo/InjecAgent); focal loss; $\lambda_L = 10^{-3}$ unless otherwise noted; bfloat16 autocast on one NVIDIA T4; seeds 0, 1, 2. Payload encoder: frozen `sentence-transformers/all-MiniLM-L6-v2`, $d_p = 384$, L2-normalised, one embedding per message (a feature-hashing encoder over token uni/bigrams is the CPU alternative used in our earlier runs). A2A sandbox: 200 attack/benign pairs per finding. Smoothing on benchmarks: 100 test windows, $n_0 = 32$, $n = 500$, $\alpha_{MC} = 10^{-3}$, $\sigma \in \{0.05, 0.10, 0.25\}$; on synthetic inputs: $n = 1000$. Sparse smoothing: $p_+ = p_- = 0.05$, $n = 1000$.

Appendix F. Protocol-Benchmark Canonicalisation

Loaders for MCPTox, MCP-SafetyBench, MCPSecBench and the A2A-sandbox are in `mambaguard/data/protocol_traces/`; `reproducibility/PROTOCOL_BENCHMARKS.md` gives the pinned source commits, the episode construction for each benchmark, expected counts, and the shortcut baselines. Server source files are parsed statically and never executed. MCPTox and MCP-SafetyBench carry no license and are read from the user's own clone, not redistributed.

Appendix G. Graph-Edit Certified Budgets

Full distribution of (k_a, k_d) over the six benchmarks and the sensitivity to p_+, p_-. See the artifact for CSV.

Appendix H. Erase-and-Check Composition

The feature-space smoothing certificate can be composed with the erase-and-check certificate [33], which certifies against adversarial suffixes, insertions and infusions of up to d tokens. We describe the composition here as the route to a payload-level guarantee; a quantitative evaluation is future work.

Appendix I. Network-IDS Transfer (Not in Headline Claims)

Classical network-IDS corpora (CSE-CIC-IDS2018, CIC-IoT2023, UNSW-NB15) are supported by the same canonicaliser and loaders, but a transfer evaluation is out of scope for this paper, which targets agent-protocol threats.

Appendix J.
Ethics Considerations

The adaptive-attack code in §8 could in principle be adapted to attack production MCP servers. We release the scaffolding needed to reproduce the paper but not working exploits against live third-party services. All protocol traces are synthetic or from public benchmarks; no live third-party agent deployment was targeted and no human-subject data was collected. We do not include CVE identifiers in the submission.

Appendix K.
Generative AI Usage

The benchmarks used in this paper are either public (MCPTox, MCP-SafetyBench, MCPSecBench, AgentDojo, InjecAgent) or generated deterministically from a fixed random seed with no model in the loop (the A2A-sandbox); no closed model was queried to produce the data or the results reported here. Generative AI was used for editorial purposes in this manuscript, and all outputs were inspected by the authors to ensure accuracy and originality.

Appendix L.
Artifact Availability

An anonymised artifact is available at https://anonymous.4open.science/r/mambaguard-sp2027 (identifier filled in at submission). It contains the detector, the smoothing, sparse-smoothing and composed certificates, the Hedge controller, the adaptive attacks, the training and evaluation harness, all configuration files, and 43 tests. `scripts/reproduce_all.sh` runs the tests and regenerates every synthetic-input result in about ten minutes on a CPU. `kaggle/run_kaggle_study.py` reruns the whole benchmark study (all seeds, ablations, certificates, latency) on one GPU in about four hours, and `scripts/lexical_baseline.py` reruns the lexical baseline on a CPU. Recorded outputs are in `reproducibility/kaggle_gpu/` (every run, prediction, certificate and latency file), `reproducibility/kaggle_results.json`, `reproducibility/lexical_baseline.json` and `reproducibility/experiments_sp2027.json`. The artifact is frozen at the submission deadline and is not updated during review, per the S&P 2027 artifact policy.