

[301] Advanced Functions

Tyler Caraza-Harter

Learning Objectives Today

Iterators

- what is an iterable?
- how to read files, with sequences or iterators
- advantages of laziness
- writing your own generators

References to functions

- ways to get a reference
- callbacks
- sort/map

Learning Objectives Today

Iterators

- what is an iterable?
- how to read files, with sequences or iterators
- advantages of laziness
- writing your own generators

References to functions

- ways to get a reference
- callbacks
- sort/map

Revisiting the For Loop

for loops can iterate over **sequences**

- list values
- string characters
- other sequences

```
for letter in "hello":  
    print(letter)
```

```
for num in [1,2,3]:  
    print(num)
```

Revisiting the For Loop

for loops can iterate over **sequences**

- list values
- string characters
- other sequences

More precisely...

```
for letter in "hello":  
    print(letter)
```

```
for num in [1,2,3]:  
    print(num)
```

Revisiting the For Loop

for loops can iterate over **sequences**

- list values
- string characters
- other sequences

More precisely...

for loops can iterate over **iterables**


- **sequences** are **iterable**
- **other things** (like dict values) are also **iterable**

Example: Dictionary Values

```
d = {1:"one", 2:"two", 3:"three"}  
d.values() # type is <class 'dict_values'>
```

Example: Dictionary Values


```
d = {1:"one", 2:"two", 3:"three"}  
d.values() # type is <class 'dict_values'>
```



```
vals = list(d.values())
```


Example: Dictionary Values

```
d = {1:"one", 2:"two", 3:"three"}  
d.values() # type is <class 'dict_values'>
```



```
vals = list(d.values())
```

```
for v in vals:  
    print(v)
```

Prints (or other order):


two
one
three

Example: Dictionary Values

```
d = {1:"one", 2:"two", 3:"three"}  
d.values() # type is <class 'dict_values'>
```



```
vals = list(d.values())
```



```
it = iter(d.values())
```

```
for v in vals:  
    print(v)
```


Example: Dictionary Values

```
d = {1:"one", 2:"two", 3:"three"}  
d.values() # type is <class 'dict_values'>
```




```
vals = list(d.values())
```

```
for v in vals:  
    print(v)
```



```
it = iter(d.values())
```



if you can call **iter(x)**,
then **x** is *iterable*,
by definition

Example: Dictionary Values

```
d = {1:"one", 2:"two", 3:"three"}  
d.values() # type is <class 'dict_values'>
```

```
vals = list(d.values())
```

```
for v in vals:  
    print(v)
```

```
it = iter(d.values())
```

d.values() is iterable, and **it** is an iterator


Example: Dictionary Values

```
d = {1:"one", 2:"two", 3:"three"}  
d.values() # type is <class 'dict_values'>
```



```
vals = list(d.values())
```

```
for v in vals:  
    print(v)
```



```
it = iter(d.values())
```

```
for v in it:  
    print(v)
```

Both print the same:

```
two  
one  
three
```


Example: Dictionary Values

```
d = {1:"one", 2:"two", 3:"three"}  
d.values() # type is <class 'dict_values'>
```



```
vals = list(d.values())
```

```
for v in vals:  
    print(v)
```



```
it = iter(d.values())
```

```
for v in it:  
    print(v)
```

Both print the same:

```
two  
one  
three
```

NOTE: the for loop automatically calls iter if necessary, so we could have written this instead:

```
for v in d.values():  
    print(v)
```

Example: Dictionary Values


```
d = {1:"one", 2:"two", 3:"three"}  
d.values() # type is <class 'dict_values'>
```



```
vals = list(d.values())
```

```
for v in vals:  
    print(v)
```

```
print(vals[2])
```



```
it = iter(d.values())
```

```
for v in it:  
    print(v)
```

We can index over a sequence.

Example prints:

three

Example: Dictionary Values


```
d = {1:"one", 2:"two", 3:"three"}  
d.values() # type is <class 'dict_values'>
```



```
vals = list(d.values())
```

```
for v in vals:  
    print(v)
```

```
print(vals[2])
```



```
it = iter(d.values())
```

```
for v in it:  
    print(v)
```

```
print(it[2]) # BAD!
```


Example: Dictionary Values


```
d = {1:"one", 2:"two", 3:"three"}  
d.values() # type is <class 'dict_values'>
```



```
vals = list(d.values())
```

```
for v in vals:  
    print(v)
```

```
print(vals[2])
```



```
it = iter(d.values())
```

```
for v in it:  
    print(v)
```

```
print(it[2]) # BAD!
```

```
Traceback (most recent call last):  
  File "<stdin>", line 1, in <module>  
TypeError: 'dict_valueiterator' object is not subscriptable
```

You can only loop over
iterators, not index with them

Comparison

	sequence	iterator
can use for loop	✓	✓
can do indexing	✓	✗

Comparison

	sequence	iterator
can use for loop	✓	✓
can do indexing	✓	✗

why ever use the less-capable iterator?

Comparison

	sequence	iterator
can use for loop	✓	✓
can do indexing	✓	✗

why ever use the less-capable iterator?

it's often faster (as we'll see later)

Learning Objectives Today

Iterators

- what is an iterable?
- how to read files, with sequences or iterators
- advantages of laziness
- writing your own generators

References to functions

- ways to get a reference
- callbacks
- sort/map

Reading Files

```
path = "file.txt"  
f = open(path)
```

Reading Files

```
path = "file.txt"  
f = open(path)
```



open(...) function is built in

Reading Files

```
path = "file.txt"  
f = open(path)
```



it takes a string argument,
which contains path to a file

file.txt

```
This is a test!  
3  
2  
1  
Go!
```

c:\users\tyler\my-doc.txt

/var/log/events.log

../data/input.csv

Reading Files

```
path = "file.txt"  
f = open(path)
```



it returns a file object

file.txt

This is a test!

3

2

1

Go!

Reading Files

```
path = "file.txt"  
f = open(path)
```



it returns a file object

file objects are iterable!

file.txt

This is a test!

3

2

1

Go!

Reading Files

```
path = "file.txt"
f = open(path)

for line in f:
    print(line)
```



Output

This is a test!

3

2

1

Go!

file.txt

This is a test!

3

2

1

Go!

Reading Files

```
path = "file.txt"
f = open(path)

for line in f:
    print(line.strip())
```



Output

```
This is a test!
3
2
1
Go!
```

file.txt

```
This is a test!
3
2
1
Go!
```

Reading Files

```
path = "file.txt"
f = open(path)

for line in f:
    print(line.strip())
```

file.txt

This is a test!
3
2
1
Go!

Another option: use the
iterable file object to create a list

Reading Files

```
path = "file.txt"
f = open(path)
lines = list(f) # create list from iterable

for line in f:
    print(line.strip())
```


file.txt

This is a test!
3
2
1
Go!

Another option: use the
iterable file object to create a list

Reading Files

```
path = "file.txt"
f = open(path)
lines = list(f) # create list from iterable
for line in f:
    print(line.strip())
```



file.txt

```
This is a test!
3
2
1
Go!
```

Another option: use the
iterable file object to create a list

lines is a list:

```
["This is a test\n", "3\n", "2\n", "1\n", "Go!\n"]
```

Reading Files

```
path = "file.txt"
f = open(path)
lines = list(f) # create list from iterable

for line in f lines:
    print(line.strip())
```

file.txt

```
This is a test!
3
2
1
Go!
```

Another option: use the
iterable file object to create a list

Reading Files

```
path = "file.txt"
f = open(path)
lines = list(f) # create list from iterable

for line in lines:
    print(line.strip())
```

file.txt

This is a test!
3
2
1
Go!

Another option: use the
iterable file object to create a list

Learning Objectives Today

Iterators

- what is an iterable?
- how to read files, with sequences or iterators
- **advantages of laziness**
- writing your own generators

References to functions

- ways to get a reference
- callbacks
- sort/map

Demo 1: Add numbers in a file

Goal: read all lines from a file as integers and add them

Input:

- file containing **50 million numbers** between 0 and 100

Output:

- The sum of the numbers

Example:

```
prompt> python sum.py  
2499463617
```

Demo 1: Add numbers in a file

Goal: read all lines from a file as integers and add them

Input:

- file containing **50 million numbers** between 0 and 100

Output:

- The sum of the numbers

Example:

```
prompt> python sum.py  
2499463617
```

Two ways:

- Put all lines in a list first
- Directly use iterable file

Learning Objectives Today

Iterators

- what is an iterable?
- how to read files, with sequences or iterators
- advantages of laziness
- writing your own generators

References to functions

- ways to get a reference
- callbacks
- sort/map

Reviewing Return

```
def f():  
    return "A"  
    return "B"  
    return "C"  
  
print("Got", f())
```

What is printed?

Reviewing Return

```
def f():  
    return "A"  
    return "B"  
    return "C"  
  
print("Got", f())
```

What is printed?

Got A

Reviewing Return

```
def f():  
    return "A"  
    return "B"  
    return "C"  
  
print("Got", f())
```

What is printed?

Got A

Let's say we want to return 3 values

Reviewing Return

```
def f():  
    items = []  
    items.append("A")  
    items.append("B")  
    items.append("C")  
    return items  
  
for item in f():  
    print("Got", item)
```

What is printed?

Reviewing Return

```
def f():  
    items = []  
    items.append("A")  
    items.append("B")  
    items.append("C")  
    return items  
  
for item in f():  
    print("Got", item)
```

What is printed?

Got A
Got B
Got C

Reviewing Return

```
def f():  
    items = []  
    print("Produce A")  
    items.append("A")  
    print("Produce B")  
    items.append("B")  
    print("Produce C")  
    items.append("C")  
    return items
```

What is printed?

```
for item in f():  
    print("Got", item)
```

Reviewing Return

```
def f():  
    items = []  
    print("Produce A")  
    items.append("A")  
    print("Produce B")  
    items.append("B")  
    print("Produce C")  
    items.append("C")  
    return items
```

```
for item in f():  
    print("Got", item)
```

What is printed?

Produce A
Produce B
Produce C

Got A
Got B
Got C

everything is produced...

Reviewing Return

```
def f():  
    items = []  
    print("Produce A")  
    items.append("A")  
    print("Produce B")  
    items.append("B")  
    print("Produce C")  
    items.append("C")  
    return items
```

```
for item in f():  
    print("Got", item)
```

What is printed?

Produce A
Produce B
Produce C

everything is produced...

Got A
Got B
Got C

...before anything is used

Reviewing Return

```
def f():  
    items = []  
    print("Produce A")  
    items.append("A")  
    print("Produce B")  
    items.append("B")  
    print("Produce C")  
    items.append("C")  
    return items
```

```
for item in f():  
    print("Got", item)
```

What is printed?

Produce A
Produce B
Produce C

everything is produced...

Got A
Got B
Got C

...before anything is used

Sometimes we want to be “lazy” and only produce values right before they’re needed

Introducing Yield

```
def f():  
    print("Produce A")  
    yield "A"  
    print("Produce B")  
    yield "B"  
    print("Produce C")  
    yield "C"  
  
items = f()
```

Introducing Yield

```
def f():  
    print("Produce A")  
    yield "A"  
    print("Produce B")  
    yield "B"  
    print("Produce C")  
    yield "C"  
  
items = f()
```

what is yield?

- produce results, like return
- can yield multiple values, unlike return

Introducing Yield

```
def f():  
    print("Produce A")  
    yield "A"  
    print("Produce B")  
    yield "B"  
    print("Produce C")  
    yield "C"
```

```
items = f()
```

what is yield?

- produce results, like return
- can yield multiple values, unlike return

What is printed?

Introducing Yield

```
def f():  
    print("Produce A")  
    yield "A"  
    print("Produce B")  
    yield "B"  
    print("Produce C")  
    yield "C"
```

```
items = f()
```

what is yield?

- produce results, like return
- can yield multiple values, unlike return

What is printed?

nothing

Introducing Yield

```
def f():  
    print("Produce A")  
    yield "A"  
    print("Produce B")  
    yield "B"  
    print("Produce C")  
    yield "C"
```

```
items = f()
```

what is yield?

- produce results, like return
- can yield multiple values, unlike return
- functions with yield are lazy
(don't run until result is needed)

What is printed?

nothing

Introducing Yield

```
def f():  
    print("Produce A")  
    yield "A"  
    print("Produce B")  
    yield "B"  
    print("Produce C")  
    yield "C"
```

```
items = f()
```

what is yield?

- produce results, like return
- can yield multiple values, unlike return
- functions with yield are lazy
(don't run until result is needed)

What is printed?

nothing

type of items is:
<class 'generator'>



Introducing Yield

```
def f():  
    print("Produce A")  
    yield "A"  
    print("Produce B")  
    yield "B"  
    print("Produce C")  
    yield "C"
```

```
items = f()
```

what is yield?

- produce results, like return
- can yield multiple values, unlike return
- functions with yield are lazy (don't run until result is needed)

What is printed?

nothing

type of items is:
<class 'generator'>

weird, no?
we don't return anything

Introducing Yield

```
def f():  
    print("Produce A")  
    yield "A"  
    print("Produce B")  
    yield "B"  
    print("Produce C")  
    yield "C"
```

```
items = f()
```

what is yield?

- produce results, like return
- can yield multiple values, unlike return
- functions with yield are lazy (don't run until result is needed)
- functions with yield automatically return a *generator*, a type of iterator

What is printed?

nothing

type of items is:
<class 'generator'>

weird, no?
we don't return anything

Introducing Yield

```
def f():  
    print("Produce A")  
    yield "A"  
    print("Produce B")  
    yield "B"  
    print("Produce C")  
    yield "C"
```

➔

```
items = f()  
for item in items:  
    print(item)
```

what is yield?

- produce results, like return
- can yield multiple values, unlike return
- functions with yield are lazy (don't run until result is needed)
- functions with yield automatically return a *generator*, a type of iterator

What is printed?

Introducing Yield

```
def f():  
→ print("Produce A")  
  yield "A"  
  print("Produce B")  
  yield "B"  
  print("Produce C")  
  yield "C"
```

```
items = f()  
for item in items:  
    print(item)
```

what is yield?

- produce results, like return
- can yield multiple values, unlike return
- functions with yield are lazy (don't run until result is needed)
- functions with yield automatically return a *generator*, a type of iterator

What is printed?

Produce A

Introducing Yield

```
def f():  
    print("Produce A")  
    ➔ yield "A"  
    print("Produce B")  
    yield "B"  
    print("Produce C")  
    yield "C"
```

```
items = f()  
for item in items:  
    print(item)
```

what is yield?

- produce results, like return
- can yield multiple values, unlike return
- functions with yield are lazy (don't run until result is needed)
- functions with yield automatically return a *generator*, a type of iterator

What is printed?

Produce A

Introducing Yield

```
def f():  
    print("Produce A")  
    yield "A"  
    print("Produce B")  
    yield "B"  
    print("Produce C")  
    yield "C"
```

```
items = f()  
for item in items:  
    ➡ print(item)
```

what is yield?

- produce results, like return
- can yield multiple values, unlike return
- functions with yield are lazy (don't run until result is needed)
- functions with yield automatically return a *generator*, a type of iterator

What is printed?

Produce A

A

Introducing Yield

```
def f():  
    print("Produce A")  
    yield "A"  
    print("Produce B")  
    yield "B"  
    print("Produce C")  
    yield "C"
```

```
→ items = f()  
for item in items:  
    print(item)
```

what is yield?

- produce results, like return
- can yield multiple values, unlike return
- functions with yield are lazy (don't run until result is needed)
- functions with yield automatically return a *generator*, a type of iterator

What is printed?

Produce A

A

Introducing Yield

```
def f():  
    print("Produce A")  
    yield "A"  
→ print("Produce B")  
    yield "B"  
    print("Produce C")  
    yield "C"  
  
items = f()  
for item in items:  
    print(item)
```

what is yield?

- produce results, like return
- can yield multiple values, unlike return
- functions with yield are lazy (don't run until result is needed)
- functions with yield automatically return a *generator*, a type of iterator


What is printed?

Produce A

A

Produce B

Introducing Yield

```
def f():  
    print("Produce A")  
    yield "A"  
    print("Produce B")  
     yield "B"  
    print("Produce C")  
    yield "C"  
  
items = f()  
for item in items:  
    print(item)
```

what is yield?

- produce results, like return
- can yield multiple values, unlike return
- functions with yield are lazy (don't run until result is needed)
- functions with yield automatically return a *generator*, a type of iterator

What is printed?

Produce A


A

Produce B

Introducing Yield

```
def f():  
    print("Produce A")  
    yield "A"  
    print("Produce B")  
    yield "B"  
    print("Produce C")  
    yield "C"
```

```
items = f()  
for item in items:
```

 print(item)

what is yield?

- produce results, like return
- can yield multiple values, unlike return
- functions with yield are lazy (don't run until result is needed)
- functions with yield automatically return a *generator*, a type of iterator

What is printed?

Produce A


A

Produce B

B

Introducing Yield

```
def f():  
    print("Produce A")  
    yield "A"  
    print("Produce B")  
    yield "B"  
    print("Produce C")  
    yield "C"
```

```
items = f()  
 for item in items:  
    print(item)
```

what is yield?

- produce results, like return
- can yield multiple values, unlike return
- functions with yield are lazy (don't run until result is needed)
- functions with yield automatically return a *generator*, a type of iterator

What is printed?

Produce A

A

Produce B

B

Introducing Yield

```
def f():  
    print("Produce A")  
    yield "A"  
    print("Produce B")  
    yield "B"  
→ print("Produce C")  
    yield "C"  
  
items = f()  
for item in items:  
    print(item)
```

what is yield?

- produce results, like return
- can yield multiple values, unlike return
- functions with yield are lazy (don't run until result is needed)
- functions with yield automatically return a *generator*, a type of iterator

What is printed?

Produce A

A

Produce B

B

Produce C

Introducing Yield

```
def f():  
    print("Produce A")  
    yield "A"  
    print("Produce B")  
    yield "B"  
    print("Produce C")  
    ➡ yield "C"  
  
items = f()  
for item in items:  
    print(item)
```

what is yield?

- produce results, like return
- can yield multiple values, unlike return
- functions with yield are lazy (don't run until result is needed)
- functions with yield automatically return a *generator*, a type of iterator

What is printed?

Produce A

A

Produce B

B

Produce C

Introducing Yield

```
def f():  
    print("Produce A")  
    yield "A"  
    print("Produce B")  
    yield "B"  
    print("Produce C")  
    yield "C"
```

```
items = f()  
for item in items:  
    ➡ print(item)
```

what is yield?

- produce results, like return
- can yield multiple values, unlike return
- functions with yield are lazy (don't run until result is needed)
- functions with yield automatically return a *generator*, a type of iterator

What is printed?

Produce A

A

Produce B

B

Produce C

C

Introducing Yield

```
def f():  
    print("Produce A")  
    yield "A"  
    print("Produce B")  
    yield "B"  
    print("Produce C")  
    yield "C"
```

```
items = f()  
for item in items:  
    ➡ print(item)
```

observations

- we bounce in and out of a generator function
- the function starts producing values even before it finishes

what is yield?

- produce results, like return
- can yield multiple values, unlike return
- functions with yield are lazy (don't run until result is needed)
- functions with yield automatically return a *generator*, a type of iterator

What is printed?

Produce A

A

Produce B

B

Produce C

C

Demo 2: Squares

Goal: generate sequence of squares

Input:

- none

Output:

- Squares

Example:

```
prompt> python squares.py
```

```
1
```

```
4
```

```
9
```

```
16
```

```
25
```

```
...
```

Iterator/Generator Vocabulary Recap

Sequence: object we can loop over (with for) **AND** index into

Iterator: object we can loop over (with for)

Iterable: object **x** that can give us an iterator if we call **iter(x)**

Generator: simple iterator returned by a function that **yields**

Generator function: function that returns a generator

Learning Objectives Today

Iterators

- what is an iterable?
- how to read files, with sequences or iterators
- advantages of laziness
- writing your own generators

References to functions

- ways to get a reference
- callbacks
- sort/map

Learning Objectives Today

Iterators

- what is an iterable?
- how to read files, with sequences or iterators
- advantages of laziness
- writing your own generators

References to functions

- ways to get a reference
- **callbacks**
- sort/map

Learning Objectives Today

Iterators

- what is an iterable?
- how to read files, with sequences or iterators
- advantages of laziness
- writing your own generators

References to functions

- ways to get a reference
- callbacks
- **sort/map**