

# Cluster algorithms for the Ising model

Monte Carlo methods which overcome the problem of critical slowing down close to second order phase transitions

# Contents

- ▶ Ising model
- ▶ Single spin flip metropolis
- ▶ Autocorrelation, Binning Analysis
- ▶ Wolff algorithm
- ▶ Swensen-Wang algorithm

# Ising model

# Ising model

- ▶ Phase transitions

# Ising model

- ▶ Phase transitions
- ▶ One of the simplest statistical models that show a phase transition

# Ising model

- ▶ Phase transitions
- ▶ One of the simplest statistical models that show a phase transition
- ▶ Magnetic systems, opinion models, binary mixtures

# Ising model

- ▶ Phase transitions
- ▶ One of the simplest statistical models that show a phase transition
- ▶ Magnetic systems, opinion models, binary mixtures




Figure : Ernst Ising (1900 - 1998)

# Ising model - Definition



# Ising model - Definition

- ▶ Discrete integer spins  $\sigma_i = \pm 1$  on each lattice site

# Ising model - Definition


- Discrete integer spins  $\sigma_i = \pm 1$  on each lattice site

$$\mathcal{H}(\sigma) = -J \sum_{\langle i,j \rangle} \sigma_i \sigma_j - H \sum_i \sigma_i$$

# Ising model - Definition

- Discrete integer spins  $\sigma_i = \pm 1$  on each lattice site



$$\mathcal{H}(\sigma) = -J \sum_{\langle i,j \rangle} \sigma_i \sigma_j - H \sum_i \sigma_i$$



# Ising model - Definition

- Discrete integer spins  $\sigma_i = \pm 1$  on each lattice site

$$\mathcal{H}(\sigma) = -J \sum_{\langle i,j \rangle} \sigma_i \sigma_j - H \sum_i \sigma_i$$



# Ising model - Canonical ensemble

# Ising model - Canonical ensemble

$$p(\sigma, T) = \frac{e^{-\beta \mathcal{H}(\sigma)}}{\mathcal{Z}(T)}, \quad \beta = \frac{1}{k_B T}$$

# Ising model - Canonical ensemble

$$p(\sigma, T) = \frac{e^{-\beta \mathcal{H}(\sigma)}}{\mathcal{Z}(T)}, \quad \beta = \frac{1}{k_B T}$$

$$\langle M \rangle_T = \sum_{\sigma} M(\sigma) p(\sigma, T)$$

# Ising model - Monte Carlo




# Ising model - Monte Carlo

- ▶ We can't compute all configurations ( $2^N$ )


# Ising model - Monte Carlo

- ▶ We can't compute all configurations ( $2^N$ )
- ▶ We can't sample uniformly distributed over energy



# Ising model - Monte Carlo

- ▶ We can't compute all configurations ( $2^N$ )
- ▶ We can't sample uniformly distributed over energy



- ▶ Solution: Importance sampling using Metropolis algorithm

# Single spin flip metropolis - Algorithm

# Single spin flip metropolis - Algorithm

1. Choose one site (uniformly randomly)

# Single spin flip metropolis - Algorithm

1. Choose one site (uniformly randomly)
2. Generate new trial configuration  $Y$  by flipping spin

# Single spin flip metropolis - Algorithm

$$A(X \rightarrow Y) = \min \left( 1, \frac{p(Y)}{p(X)} \right)$$

1. Choose one site (uniformly randomly)
2. Generate new trial configuration  $Y$  by flipping spin
3. Accept new configuration with transition probability above

## Single spin flip metropolis - Algorithm

$$\begin{aligned} A(X \rightarrow Y) &= \min \left( 1, \frac{p(Y)}{p(X)} \right) \\ &= \min \left( 1, e^{-\beta[E(Y)-E(X)]} \right) \end{aligned}$$

1. Choose one site (uniformly randomly)
2. Generate new trial configuration  $Y$  by flipping spin
3. Accept new configuration with transition probability above



# Single spin flip metropolis - Results

## Single spin flip metropolis - Results


$$\text{Magnetization } M(T) = \left\langle \frac{1}{N} \sum_{i=1}^N \sigma_i \right\rangle_T$$

# Single spin flip metropolis - Results

$$\text{Magnetization } M(T) = \left\langle \frac{1}{N} \sum_{i=1}^N \sigma_i \right\rangle_T$$

Expected

Magnetization




# Single spin flip metropolis - Results

$$\text{Magnetization } M(T) = \left\langle \frac{1}{N} \sum_{i=1}^N \sigma_i \right\rangle_T$$


Expected

Magnetization



Obtained

Magnetization



# Ising model - 2 spins


# Single spin flip metropolis - To flip or not to flip

## Single spin flip metropolis - To flip or not to flip

$$\mathcal{H}(\sigma) = -J \sum_{\langle i,j \rangle} \sigma_i \sigma_j$$

# Single spin flip metropolis - To flip or not to flip

$$\mathcal{H}(\sigma) = -J \sum_{\langle i,j \rangle} \sigma_i \sigma_j$$






# Autocorrelation time

# Autocorrelation time

$$\phi_A(t) = \frac{\langle A(t_0)A(t) \rangle - \langle A \rangle^2}{\langle A(t_0)^2 \rangle - \langle A \rangle^2}$$



# Autocorrelation time

$$\phi_A(t) = \frac{\langle A(t_0)A(t) \rangle - \langle A \rangle^2}{\langle A(t_0)^2 \rangle - \langle A \rangle^2}$$



# Autocorrelation time

$$\phi_A(t) = \frac{\langle A(t_0)A(t) \rangle - \langle A \rangle^2}{\langle A(t_0)^2 \rangle - \langle A \rangle^2}$$



## Binning analysis I

$$\text{Var}X := E[X^2] - E[X]^2$$

$$\begin{aligned}(\Delta X)^2 &= \frac{1}{N^2} \sum_{i,j=1}^N \left( E[X_i X_j] - E[X]^2 \right) \\&= \frac{\text{Var}X}{N} + \frac{1}{N^2} \sum_{i \neq j} \left( E[X_i X_j] - E[X]^2 \right) \\&= \frac{\text{Var}X}{N} + \frac{2}{N^2} \sum_{i=1}^N \sum_t \left( E[X_i X_{i+t}] - E[X]^2 \right) \\&:= \frac{\text{Var}X}{N} (1 + 2\tau_X)\end{aligned}$$

## Binning analysis II

$$A_i^{(l)} = \frac{1}{2} \left( A_{2i-1}^{(l-1)} + A_{2i}^{(l-1)} \right)$$

$$\Delta^{(l)} = \sqrt{\text{Var}A^{(l)} / M^{(l)}} \xrightarrow{l \rightarrow \infty} \Delta = \sqrt{(1 + 2\tau_A) \text{Var}A / M}$$

$$\tau_A = \lim_{l \rightarrow \infty} \left( \frac{2^l \text{Var}A^{(l)}}{\text{Var}A^{(0)}} - 1 \right)$$

# What really happens in the System

## Cluster algorithms: Wolff algorithm

$$P(\sigma_x, \sigma_y) = 1 - \min \left( 1, e^{2\beta\sigma_x\sigma_y} \right)$$



## Cluster algorithms: Wolff algorithm

$$P(\sigma_x, \sigma_y) = 1 - \min \left( 1, e^{2\beta\sigma_x\sigma_y} \right)$$

1. Choose one site (uniformly randomly)

## Cluster algorithms: Wolff algorithm

$$P(\sigma_x, \sigma_y) = 1 - \min \left( 1, e^{2\beta\sigma_x\sigma_y} \right)$$


1. Choose one site (uniformly randomly)
2. Flip its spin and add it to the cluster

## Cluster algorithms: Wolff algorithm


$$P(\sigma_x, \sigma_y) = 1 - \min \left( 1, e^{2\beta\sigma_x\sigma_y} \right)$$

1. Choose one site (uniformly randomly)
2. Flip its spin and add it to the cluster
3. For all sites in the cluster:
  - 3.1 Visit every unknown neighbour, flip its spin and add it to the cluster with probability given above

# Why cluster algorithms are better



# Energy



# Cluster size

# Magnetization

# Magnetization squared



# Computation time per spin flip

# Swendsen-Wang

# Questions

# Wolff or Swendsen-Wang?

Swendsen-Wang better for parallelization because it touches the whole lattice.