

RSyslog TLS Configuration and Setup

Last updated by | Naser Mohammed | Mar 19, 2023 at 7:18 AM CDT

Contents

- How to set up TLS from one Syslog Client to a Syslog Server
 - Summary of the process
 - Prerequisites:
 - Required packages
- (STEP ONE) Generate a Self-Signing Certificate Authority C...
 - Build the CA-Key file
 - Now create the (self-signed) CA certificate:
- (STEP TWO) Syslog Server Machine cert
 - Build the Server machine private key
 - Build the Server machine request for public key from CA C...
 - Generate the Server Machine Certificate (this file will be us...
- (STEP THREE) Client Server Machine certificate
 - Build the Client machine private key
 - Build the Client machine request for public key from CA Ce...
 - Generate the Client Machine Certificate
- (STEP FOUR) Copy client files to client machine and Server ...
 - Client Files
 - Server Files (If you ran the files on this server you will not n...
 - Convert to other formats (P12 PKS)
 - Check Point configuration
- (STEP FIVE) Rsyslog.conf Configurations
 - rsyslog.conf - Client Setup
 - rsyslog.conf - Central Rsyslog Server
- load TCP listener
- start up listener at port 6514
- provides UDP syslog reception
- provides TCP syslog reception
- module(load="imtcp")
- (STEP SIX) Restart the Rsyslog Server on both the client an...
- Debugging

How to set up TLS from one Syslog Client to a Syslog Server

Summary of the process

- As we need to establish trust between client/server we would need to generate the CA certificates for each of the server/client.
- We will copy the respective client certificate to client node and server certificate to rsyslog server.
- Certificate Authority server can be rsyslog server or an another server.
- To accept the logs over tls we will add some more modules to rsyslog server configuration file.
- To send the logs over tls we will add some more modules to rsyslog client configuration file.
- Make sure order of the modules are correct in both server/client configuration files.

Prerequisites:

```
sudo apt-get install rsyslog-gnutls
```

Required packages

```
rsyslog-gnutls-5.8.10-10.0.1.el6_6.x86_64  
rsyslog-5.8.10-10.0.1.el6_6.x86_64  
gnutls-utils-2.8.5-19.el6_7.x86_64  
gnutls-2.8.5-19.el6_7.x86_64
```

(STEP ONE) Generate a Self-Signing Certificate Authority Certificate

Build the CA-Key file

```
certtool --generate-privkey --outfile ca-key.pem
```

This takes a short while. Be sure to do some work on your workstation, it waits for random input. Switching between windows is sufficient 😊

Now create the (self-signed) CA certificate:

```
certtool --generate-self-signed --load-privkey ca-key.pem --outfile ca.pem
```

This generates the CA certificate. This command queries you for a number of things. Use appropriate responses. When it comes to certificate validity, keep in mind that you need to recreate all certificates when this one expires. So it may be a good idea to use a long period, eg. 3650 days (roughly 10 years). You need to specify that the certificates belongs to an authority. The certificate is used to sign other certificates.

Certificate Authority Certificate Demo

Common name: CACert
UID:
Organizational unit name: CACertOU
Organization name: CACertOrg
Locality name: Grapevine
State or province name: TX
Country name (2 chars): Us
Enter the subject's domain component (DC): CAAuthority
Enter an additional domain component (DC):
This field should not be used in new certificates.
E-mail: someone@somewhere.com
Enter the certificate's serial number in decimal (123) or hex (0xabcd)
(default is 0x324ccfaaf99550f907d882af6a3da1ccf0f26dd)
value:

Activation/Expiration time.
The certificate will expire in (days): 3650

Extensions.
Does the certificate belong to an authority? (y/N): y
Path length constraint (decimal, -1 for no constraint): -1
Is this a TLS web client certificate? (y/N): n
Will the certificate be used for IPsec IKE operations? (y/N):
Is this a TLS web server certificate? (y/N):
Enter a dnsName of the subject of the certificate:
Enter a URI of the subject of the certificate:
Enter the IP address of the subject of the certificate:
Enter the e-mail of the subject of the certificate:
Will the certificate be used for signing (required for TLS)? (Y/n):
Will the certificate be used for data encryption? (y/N):
Will the certificate be used to sign OCSP requests? (y/N):
Will the certificate be used to sign code? (y/N):
Will the certificate be used for time stamping? (y/N):
Will the certificate be used for email protection? (y/N):
Will the certificate be used to sign other certificates? (Y/n): Y
Will the certificate be used to sign CRLs? (y/N):
Enter the URI of the CRL distribution point:

(STEP TWO) Syslog Server Machine cert

Build the Server machine private key

```
certtool --generate-privkey --outfile server-key.pem --bits 2048
```

Build the Server machine request for public key from CA Certificate

```
certtool --generate-request --load-privkey server-key.pem --outfile request.pem
```

Demo

```
Common name: ServerCert
Organizational unit name: ServerCertOU
Organization name: ServerCertOrg
Locality name: Grapevine
State or province name: TX
Country name (2 chars): US
Enter the subject's domain component (DC): 192.168.1.179
Enter an additional domain component (DC):
UID:
Enter a dnsName of the subject of the certificate: 192.168.1.179 <-- the Syslog Server's IP
Enter an additional dnsName of the subject of the certificate:
Enter a URI of the subject of the certificate:
Enter the IP address of the subject of the certificate:
Enter the e-mail of the subject of the certificate:
Enter a challenge password:
Does the certificate belong to an authority? (y/N): n
Will the certificate be used for signing (DHE ciphersuites)? (Y/n):
Will the certificate be used for encryption (RSA ciphersuites)? (Y/n):
Will the certificate be used to sign code? (y/N):
Will the certificate be used for time stamping? (y/N):
Will the certificate be used for email protection? (y/N):
Will the certificate be used for IPsec IKE operations? (y/N):
Will the certificate be used to sign OCSP requests? (y/N):
Is this a TLS web client certificate? (y/N): Y
Is this a TLS web server certificate? (y/N): Y
```

Generate the Server Machine Certificate (this file will be used on both the client and server machines)

```
certtool --generate-certificate --load-request request.pem --outfile server-cert.pem --load-ca-certificate ca.pem --load-ca-privkey ca-key.pem
```

Demo

```
Generating a signed certificate...
Enter the certificate's serial number in decimal (123) or hex (0xabcd)
(default is 0x1e5b71b3b6ee00f0530f3526460d715dcaca4762)
value:
```

```
Activation/Expiration time.
The certificate will expire in (days): 3649
```

```
Extensions.
Do you want to honour all the extensions from the request? (y/N): Y
Does the certificate belong to an authority? (y/N):
Is this a TLS web client certificate? (y/N): Y
Will the certificate be used for IPsec IKE operations? (y/N):
Is this a TLS web server certificate? (y/N): Y
Enter a dnsName of the subject of the certificate: 192.168.1.179 <-- the Syslog Server's IP Address
Enter an additional dnsName of the subject of the certificate:
Enter a URI of the subject of the certificate:
Enter the IP address of the subject of the certificate:
Will the certificate be used for signing (DHE ciphersuites)? (Y/n):
Will the certificate be used for encryption (RSA ciphersuites)? (Y/n):
Will the certificate be used for data encryption? (y/N):
Will the certificate be used to sign OCSP requests? (y/N):
Will the certificate be used to sign code? (y/N):
Will the certificate be used for time stamping? (y/N):
Will the certificate be used for email protection? (y/N):
```

```
rm request.pem < delete the last request >
```

(STEP THREE) Client Server Machine certificate

Build the Client machine private key

```
certtool --generate-privkey --outfile client-key.pem --bits 2048
```

Build the Client machine request for public key from CA Certificate

```
certtool --generate-request --load-privkey client-key.pem --outfile request.pem
```

Demo

```
Common name: ClientCert
Organizational unit name: ClientCertOU
Organization name: ClientCertOrg
Locality name: Grapevine
State or province name: TX
Country name (2 chars): US
Enter the subject's domain component (DC):
UID:
Enter a dnsName of the subject of the certificate: 192.168.1.166 <-- the Syslog Client's IP Address
Enter an additional dnsName of the subject of the certificate:
Enter a URI of the subject of the certificate:
Enter the IP address of the subject of the certificate:
Enter the e-mail of the subject of the certificate:
Enter a challenge password:
Does the certificate belong to an authority? (y/N): n
Will the certificate be used for signing (DHE ciphersuites)? (Y/n):
Will the certificate be used for encryption (RSA ciphersuites)? (Y/n):
Will the certificate be used to sign code? (y/N):
Will the certificate be used for time stamping? (y/N):
Will the certificate be used for email protection? (y/N):
Will the certificate be used for IPsec IKE operations? (y/N):
Will the certificate be used to sign OCSP requests? (y/N):
Is this a TLS web client certificate? (y/N): Y
Is this a TLS web server certificate? (y/N): Y
```

Generate the Client Machine Certificate

```
certtool --generate-certificate --load-request request.pem --outfile client-cert.pem --load-ca-certificate ca.pem --load-ca-privkey ca-key.pem
```

Demo

Generating a signed certificate...

Enter the certificate's serial number in decimal (123) or hex (0xabcd)
(default is 0x4816b1ddd3320dea219895d706aba965f7abe23f)
value:

Activation/Expiration time.

The certificate will expire in (days): 3649

Extensions.

Do you want to honour all the extensions from the request? (y/N): Y

Does the certificate belong to an authority? (y/N): n

Is this a TLS web client certificate? (y/N): Y

Will the certificate be used for IPsec IKE operations? (y/N):

Is this a TLS web server certificate? (y/N): Y

Enter a dnsName of the subject of the certificate: 192.168.1.166 <-- the Syslog Client's IP Address

Enter an additional dnsName of the subject of the certificate:

Enter a URI of the subject of the certificate:

Enter the IP address of the subject of the certificate:

Will the certificate be used for signing (DHE ciphersuites)? (Y/n):

Will the certificate be used for encryption (RSA ciphersuites)? (Y/n):

Will the certificate be used for data encryption? (y/N):

Will the certificate be used to sign OCSP requests? (y/N):

Will the certificate be used to sign code? (y/N):

Will the certificate be used for time stamping? (y/N):

Will the certificate be used for email protection? (y/N):

(STEP FOUR) Copy client files to client machine and Server files to Rsyslog Collector

Client Files

ca.pem

client-cert.pem

client-key.pem

Server Files (If you ran the files on this server you will not need to move them, just point to the directory)

ca.pem

server-cert.pem

server-key.pem

use WinSCP to copy files over in Binary mode

Convert to other formats (P12 PKS)

```
certtool --load-certificate client-cert.pem --load-privkey client-key.pem --to-p12 --outder --outfile client-key.p12
```

Check Point configuration

Demo

```
cp log export set name ubuntu20 ca-cert /var/log/syslogcert/ca.pem client-cert /var/log/syslogcert/client-key.p12 client-secret R4n9er*10
```

(STEP FIVE) Rsyslog.conf Configurations

rsyslog.conf - Client Setup

```
# make gtls driver the default and set certificate files
global(
    DefaultNetstreamDriver="gtls"
    DefaultNetstreamDriverCAFile="/var/log/syslogcert/ca.pem" <- this should be the file location of the file
    DefaultNetstreamDriverCertFile="/var/log/syslogcert/client-cert.pem" <- this should be the file location of the
    DefaultNetstreamDriverKeyFile="/var/log/syslogcert/client-key.pem" <- this should be the file location of the
)
#
# set up the action for all messages
action(
    type="omfwd"
    target="192.168.1.179"
    protocol="tcp"
    port="6514"
    StreamDriver="gtls"
    StreamDriverMode="1" # run driver in TLS-only mode
    StreamDriverAuthMode="x509/name"
    StreamDriverPermittedPeers="192.168.1.179"
)
```

rsyslog.conf - Central Rsyslog Server

```
` global( DefaultNetstreamDriver="gtls" DefaultNetstreamDriverCAFile="/var/log/syslogcert/ca.pem" <- this
should be the file location of the file DefaultNetstreamDriverCertFile="/var/log/syslogcert/server-cert.pem" <-
this should be the file location of the file DefaultNetstreamDriverKeyFile="/var/log/syslogcert/server-key.pem"
<- this should be the file location of the file )
```

load TCP listener

```
module( load="imtcp" StreamDriver.Name="gtls" StreamDriver.Mode="1" StreamDriver.Authmode="anon" )
```

start up listener at port 6514

```
input( type="imtcp" port="6514" )
```

provides UDP syslog reception

```
module(load="imudp") input(type="imudp" port="514")
```

provides TCP syslog reception

```
module(load="imtcp")
```

```
input(type="imtcp" port="514") `
```

(STEP SIX) Restart the Rsyslog Server on both the client and server

```
systemctl restart rsyslog
```

Debugging

They will need to run `tail -f /var/log/messages` and see if there is TLS errors, if there is they will need to redo their certificates. `tail -f /var/log/messages`