

ORIFICE PLATE

APPLICATION: RESTRICTION / GENERAL

ILLUSTRATIVE CHAMFER VALUES - NOT DEFAULTS

MARKING: HOLD

METHOD: HOLD
LOCATION: HOLD

Ø1.548

BORE TOLERANCE: NOT SPECIFIED - HOLD

4X R 0.03125

PLAN - NTS

Ø5.000

2.000

A

10.500 C/L TO HANDLE END

SECTION A-A - NTS
THROUGH HANDLE / BORE

FLOW

B

t = 0.125

CHAMFER: CONFIGURED


BORE FINISH: HOLD

NO. REQ'D.	1
ORIFICE PLATE	0.125 THK.
MATERIAL	304 STAINLESS STEEL

EDGE / FINISH: HOLD
SURFACE FINISH: HOLD
INSPECTION: HOLD

DETAIL B - BORE EDGE - NTS
DOWNSTREAM / ANGLE FROM FACE

45°



AXIAL DEPTH 0.0400 / LAND 0.0850

ROGUE MACHINE / O-PLATES

ORIFICE PLATE

UNLESS OTHERWISE SPECIFIED:

.X HOLD
.XX HOLD
.XXX HOLD
ANGLES HOLD

DO NOT SCALE DRAWING

PART NO.
EXAMPLE-CHAMFER-NOT-DEFAULT

MATERIAL
304 STAINLESS STEEL

REV
P3E

UNITS
INCHES

SCALE
NTS

DWG NO.
OP-EXAMPLE-CHAMFER-NOT-DEFAULT

THICKNESS
0.125

QUANTITY
1

SHEET
1 OF 1

DRAFTING BASIS
ASME Y14.5-2018

GEN: op-drawing-v3e

SPEC REV: HOLD

GEOMETRY: straight-handle-r03125-v2-prototype

PROTOTYPE - NOT RELEASED FOR MANUFACTURE