

ORIFICE PLATE

APPLICATION: RESTRICTION / GENERAL

MARKING: HOLD

METHOD: HOLD
LOCATION: HOLD

Ø1.548

BORE TOLERANCE: NOT SPECIFIED - HOLD

4X R 0.03125

PLAN - NTS

2.000

A →

10.500 C/L TO HANDLE END

Ø5.000

A →

SECTION A-A - NTS
THROUGH HANDLE / BORE



t = 0.125

CHAMFER: NOT SPECIFIED - HOLD

NO. REQ'D. 2
ORIFICE PLATE 0.125 THK.
MATERIAL 304 STAINLESS STEEL
ORDER OP-PROTOTYPE-001

BORE FINISH: HOLD

ORDER/LINE REV: L1-R2
EDGE / FINISH: HOLD
SURFACE FINISH: HOLD
INSPECTION: HOLD

ROGUE MACHINE / O-PLATES

ORIFICE PLATE

UNLESS OTHERWISE SPECIFIED:

.X HOLD
.XX HOLD
.XXX HOLD
ANGLES HOLD

DO NOT SCALE DRAWING

PART NO.
PROTOTYPE-001

DWG NO.
OP-PROTOTYPE-001

MATERIAL
304 STAINLESS STEEL

THICKNESS
0.125

QUANTITY
2

REV R2 UNITS INCHES SCALE NTS SHEET 1 OF 1

DRAFTING BASIS
ASME Y14.5-2018

GEN: op-drawing-v3e SPEC REV: R2
GEOMETRY: straight-handle-r03125-v2-prototype

CUSTOMER CONFIRMATION - NOT RELEASED FOR MANUFACTURE