
Lab Week – 2

SQL Operators, Restricting and Sorting Data

SQL operators

- In this session
 - Character strings
 - Comparison operators
 - Rules of precedence
 - Sorting and ordering

Character Strings and Dates

- Character strings and date values are enclosed in single quotation marks.
- Character values are case sensitive and date values are format sensitive.
- The default date format is DD-MON-YY.

```
SELECT last_name, job_id, department_id
FROM   employees
WHERE  last_name = 'Whalen' ;
```

Comparison Operators

Operator	Meaning
=	Equal to
>	Greater than
>=	Greater than or equal to
<	Less than
<=	Less than or equal to
<> or !=	Not equal to

Using the Comparison Operators

```
SELECT last_name, salary
FROM employees
WHERE salary <= 3000 ;
```

LAST_NAME	SALARY
Matos	2600
Vargas	2500

Other Comparison Operators

Operator	Meaning
BETWEEN ...AND...	Between two values (inclusive)
IN(list)	Match any of a list of values
LIKE	Match a character pattern
IS NULL	Is a null value

Using the BETWEEN Operator

- Use the BETWEEN operator to display rows based on a range of values.

```
SELECT last_name, salary
FROM employees
WHERE salary BETWEEN 2500 AND 3500 ;
```

Lower limit

Upper limit

LAST_NAME	SALARY
Rajs	3500
Davies	3100
Matos	2600
Vargas	2500

Using the IN Operator

- Use the IN operator to test for values in a list.

```
SELECT employee_id, last_name, salary, manager_id
FROM   employees
WHERE  manager_id IN (100, 101, 201) ;
```

EMPLOYEE_ID	LAST_NAME	SALARY	MANAGER_ID
202	Fay	6000	201
200	Whalen	4400	101
205	Higgins	12000	101
101	Kochhar	17000	100
102	De Haan	17000	100
124	Mourgos	5800	100
149	Zlotkey	10500	100
201	Hartstein	13000	100

8 rows selected.

Using the LIKE Operator

- Use the LIKE operator to perform wildcard searches of valid search string values.
- Search conditions can contain either literal characters or numbers.
- % denotes zero or many characters.
- _ denotes one character.

```
SELECT    first_name  
FROM      employees  
WHERE     first_name LIKE 'S%';
```

Using the LIKE Operator

- You can combine pattern-matching characters:

```
SELECT last_name  
FROM employees  
WHERE last_name LIKE '_o%' ;
```

LAST_NAME
Kochhar
Lorentz
Mourgos

- You can use the `ESCAPE` identifier to search for the actual `%` and `_` symbols.

Using the IS NULL Operator

- Test for nulls with the IS NULL operator.

```
SELECT last_name, manager_id  
FROM employees  
WHERE manager_id IS NULL ;
```

LAST_NAME	MANAGER_ID
King	

Logical Operators

Operator	Meaning
AND	Returns TRUE if <i>both</i> component conditions are TRUE
OR	Returns TRUE if <i>either</i> component condition is TRUE
NOT	Returns TRUE if the following condition is FALSE

Using the AND Operator

AND requires both conditions to be true:

```
SELECT employee_id, last_name, job_id, salary
FROM employees
WHERE salary >=10000
AND job_id LIKE '%MAN%' ;
```

EMPLOYEE_ID	LAST_NAME	JOB_ID	SALARY
149	Zlotkey	SA_MAN	10500
201	Hartstein	MK_MAN	13000

Using the OR Operator

OR requires either condition to be true:

```
SELECT employee_id, last_name, job_id, salary
FROM   employees
WHERE  salary >= 10000
OR     job_id LIKE '%MAN%' ;
```

EMPLOYEE_ID	LAST_NAME	JOB_ID	SALARY
100	King	AD_PRES	24000
101	Kochhar	AD_VP	17000
102	De Haan	AD_VP	17000
124	Mourgos	ST_MAN	5800
149	Zlotkey	SA_MAN	10500
174	Abel	SA_REP	11000
201	Hartstein	MK_MAN	13000
205	Higgins	AC_MGR	12000

8 rows selected.

Using the NOT Operator

```
SELECT last_name, job_id
FROM employees
WHERE job_id
      NOT IN ('IT_PROG', 'ST_CLERK', 'SA_REP') ;
```

LAST_NAME	JOB_ID
King	AD_PRES
Kochhar	AD_VP
De Haan	AD_VP
Mourgos	ST_MAN
Zlotkey	SA_MAN
Whalen	AD_ASST
Hartstein	MK_MAN
Fay	MK_REP
Higgins	AC_MGR
Gietz	AC_ACCOUNT

10 rows selected.

Rules of Precedence

Order Evaluated	Operator
1	Arithmetic operators
2	Concatenation operator
3	Comparison conditions
4	IS [NOT] NULL, LIKE, [NOT] IN
5	[NOT] BETWEEN
6	NOT logical condition
7	AND logical condition
8	OR logical condition

Note: Override rules of precedence by using parentheses.

Rules of Precedence

```
SELECT last_name, job_id, salary
FROM employees
WHERE job_id = 'SA_REP'
OR job_id = 'AD_PRES'
AND salary > 15000;
```

1

LAST_NAME	JOB_ID	SALARY
King	AD_PRES	24000
Abel	SA_REP	11000
Taylor	SA_REP	8600
Grant	SA_REP	7000

```
SELECT last_name, job_id, salary
FROM employees
WHERE (job_id = 'SA_REP'
OR job_id = 'AD_PRES')
AND salary > 15000;
```

2

LAST_NAME	JOB_ID	SALARY
King	AD_PRES	24000

ORDER BY Clause

- Sort retrieved rows with the ORDER BY clause:
 - ASC: ascending order, default
 - DESC: descending order
- The ORDER BY clause comes last in the SELECT statement:

```
SELECT    last_name, job_id, department_id, hire_date
FROM      employees
ORDER BY  hire_date ;
```

Sorting in Descending Order

- Sorting in descending order:

```
SELECT last_name, job_id, department_id, hire_date
FROM employees
ORDER BY hire_date DESC ;
```

1

- Sorting by column alias:

```
SELECT employee_id, last_name, salary*12 annsal
FROM employees
ORDER BY annsal ;
```


2

- Sorting by multiple columns:

```
SELECT last_name, department_id, salary
FROM employees
ORDER BY department_id, salary DESC ;
```

3

Substitution Variables



Substitution Variables

- Use *iSQL*Plus* substitution variables to:
 - Temporarily store values with single-ampersand (&) and double-ampersand (&&) substitution
- Use substitution variables to supplement the following:
 - WHERE conditions
 - ORDER BY clauses
 - Column expressions
 - Table names
 - Entire SELECT statements

Using the & Substitution Variable

- Use a variable prefixed with an ampersand (&) to prompt the user for a value:

```
SELECT employee_id, last_name, salary, department_id
FROM   employees
WHERE  employee_id = &employee_num ;
```

Lab Activities

- Complete SQL lab exercise