

TravelVIP B2B — QA Booking Flow Guide (Postman)

For: QA team · **Products:** Hotel, Flight, Cab

Base URL (staging): `https://api-staging.travelvip.ai`

Postman collection: `postman/TravelVIP-Dynamic-Flights-Hotels.postman_collection.json`

Environment: `postman/B2B Dev.postman_environment.json`

Before you start (one time)

1. Import **collection** + **environment** in Postman.
2. Fill environment variables:
 - `base_url` , `partner_id` , `partner_secret` , `signing_key` , `tier_id`
3. Run **Auth** folder in order:
 - **Partner Token** → saves `access_token`
 - **User Auth (Session)** → saves `auth_token`
4. Pin one `correlation_id` for the whole session (do not change mid-flow).

Headers used everywhere

Header	Value	When
Authorization	Bearer {{auth_token}}	All product APIs
X-Partner-Key	{{access_token}}	Hotel finalize, Flight issue-ticket, Cab finalize/cancel
X-Correlation-ID	{{correlation_id}}	All calls (same ID)
X-Signature, X-Timestamp, X-Request-Id	Auto from collection	POST bodies (signed)

Quick cheat sheet — what to copy where

HOTEL:	<code>details.requestId + details.bookingCode → prebook → finalize → status(BR)</code>
FLIGHT:	<code>search.searchId → pricing → issue-ticket → status(BR)</code>
CAB:	<code>search.searchId → fare → finalize → status(BR)</code>

HOTEL booking flow

Auth → Search → Details → Prebook → Finalize → Status

Step 0 — Auth (same for all products)

Step	API	Save from response
0a	POST <code>/auth/partner/token</code>	<code>access_token</code>

0b	POST /v1/auth/session + header X-Partner-Key: access_token	auth_token
----	--	------------

Step 1 — Search

POST /v1/hotels/search · Query: pid=vgm , lang=en , currency=INR

Body (example):

```
{
  "checkin": "2026-09-23",
  "checkout": "2026-09-24",
  "entityId": "39627872",
  "nationality": "IN",
  "type": "HOTEL",
  "rooms": [{ "adults": 1, "children": 0, "childAges": [] }]
}
```

Copy to next step	From response
Same dates + entity + rooms	Use same values in Details and Finalize
(optional) requestId	May appear — do not use for book ; use Details requestId instead

Test hotel: Hilltop Mumbai · entityId = 39627872

Step 2 — Details

POST /v1/hotels/details · Query: pid=vgm

Body: Same as Search **without** "type" field.

Copy to next step	From response
requestId	Top-level requestId → Prebook + Finalize
bookingCode	results[0].rooms[0].bookingCode → Prebook + Finalize

Important: Always use **Details** requestId , not Search requestId .

Step 3 — Prebook

POST /v1/hotels/prebook

Body:

```
{
  "bookingCode": "<from Details>",
  "requestId": "<from Details>"
}
```

Copy to next step	From response
bookingContext	bookingContext → Finalize

Step 4 — Finalize (BOOK — live)

POST /v1/hotels/finalize-booking · Query: pid=vgm

Extra header: X-Partner-Key: {{access_token}}

Body (key fields):

```
{
  "bookingContext": "<from Prebook>",
  "bookingCode": "<from Details>",
  "requestId": "<from Details>",
  "checkin": "<same as Search>",
  "checkout": "<same as Search>",
  "rooms": [{
    "guests": [{
      "title": "Mr", "firstName": "Rohan", "lastName": "Bhagat",
      "type": "Adult", "isLead": true, "gender": "Male"
    }]
  }],
  "contact": {
    "email": "qa.test@example.com",
    "mobile": "9876543210",
    "countryCode": "+91",
    "panCardNumber": "EUIPB1672M",
    "panCardName": "Rohan Bhagat"
  }
}
```

Copy to next step	From response
bookingRefId	bookingRefId OR bookingReferenceId → Status

Step 5 — Booking status

GET /v1/hotels/bookings/{{bookingRefId}}/status

Poll until status = **Confirmed**, **Failed**, or **Inprogress** (do not stop on Pending).

FLIGHT booking flow

```
Auth → Search (poll) → Details → Pricing → Issue-ticket → Status
```

Step 1 — Search

POST /v1/flights/search · Query: sortBy=fare,asc

Body (OW example DEL→BOM):

```
{
  "itinerary": [{ "origin": "DEL", "destination": "BOM", "date": "2026-09-15" }],
  "travellers": { "adults": 1, "children": 0, "infants": 0 },
  "cabinClass": "ECONOMY",
  "journeyType": "ONE_WAY",
  "currency": "INR",
  "language": "en",
  "fareType": "CORPORATE"
}
```

Poll until search completes and options appear.

Copy to next step	From response
searchId	results[ONWARD].options[0].searchId → all next steps

For **Round Trip**: copy **two** IDs (ONWARD + RETURN).

Step 2 — Details

POST /v1/flights/details

```
{
  "journeyType": "ONE_WAY",
  "selection": { "selectedSearchIds": ["<searchId>"] }
}
```

Same `searchId` reused — mainly for itinerary display. No new ID required for book.

Step 3 — Pricing

POST /v1/flights/pricing

```
{
  "journeyType": "ONE_WAY",
  "selection": { "selectedSearchIds": ["<searchId>"] }
}
```

Copy to next step	From response
priceId	priceId → Issue-ticket
bookingContext	bookingContext → Issue-ticket as bookingReference

Step 4 — Issue ticket (BOOK — live)

POST /api/v2/flights/booking/issue-ticket

Extra header: X-Partner-Key: {{access_token}}

```
{
  "type": "ticket",
  "currency": "INR",
  "language": "en",
  "timezone": "Asia/Calcutta",
  "journeyType": "ONE_WAY",
  "bookingReference": "<pricing.bookingContext>",
  "searchIds": [<searchId>],
  "data": {
    "priceId": "<pricing.priceId>",
    "passportType": "NONE",
    "includeGst": false,
    "contact": {
      "email": "qa.test@example.com",
      "mobile": "9876543210",
      "countryCode": "+91"
    },
    "passengers": [{
      "paxId": "1",
      "type": "ADULT",
      "isLead": true,
      "profile": {
        "title": "Mr", "firstName": "Rohan", "lastName": "Bhagat",
        "gender": "Male", "dateOfBirth": "1990-01-15", "nationality": "IN"
      },
      "city": { "cityCode": "DEL", "cityName": "New Delhi" },
      "passport": { "type": "NONE" }
    }]
  }
}
```

Note: field name is **bookingReference** but value comes from **pricing.bookingContext** .

Copy to next step	From response
bookingReference	bookingReference OR bookingReferenceId → Status

Step 5 — Booking status

GET /v1/flights/booking/{{bookingReference}}/status

Poll until **Confirmed**, **Inprogress**, **Failed**, or **Cancelled**.

CAB booking flow

Auth → Search → Fare → Finalize → Status

Step 1 — Search

POST /v1/airportServices/cabs/search

AIRPORT departure example (DEL):

```
{
  "journeyType": "AIRPORT",
  "travelType": "DEPARTURE",
  "airportCode": "DEL",
  "pickupDatetime": "2026-09-20T10:00:00+05:30",
  "distanceKm": 25,
  "durationMin": 45,
  "pickup": { "latitude": 28.5562, "longitude": 77.1000, "address": "Home, Delhi" },
  "drop": { "latitude": 28.5562, "longitude": 77.1000, "address": "DEL Airport" }
}
```

Copy to next step	From response
searchId	Pick a cab with tag RECOMMENDED → cabs[].searchId → Fare

Step 2 — Fare

POST /v1/airportServices/cabs/fare

```
{ "searchId": "<from Cab Search>" }
```

Copy to next step	From response
bookingReference	bookingReference → Finalize
priceId	priceId → Finalize

Step 3 — Finalize (BOOK — live)

POST /v1/airportServices/cabs/finalize-booking

Extra header: X-Partner-Key: {{access_token}}

```
{
  "bookingReference": "<from Fare>",
  "priceId": "<from Fare>",
  "passengers": [{
    "title": "Mr", "firstName": "Rohan", "lastName": "Bhagat",
```

```
    "email": "qa.test@example.com", "mobile": "9876543210", "isLead": true
  }],
  "contact": {
    "email": "qa.test@example.com",
    "mobile": "9876543210", "countryCode": "+91"
  },
  "otherDetails": { "flightNumber": "AI101", "remarks": "QA test" }
}
```

Copy to next step	From response
bookingRefId	bookingRefId → Status

Step 4 — Booking status

GET /v1/airportServices/cabs/{{bookingRefId}}/status

One-page summary table

Product	Step 1 → 2	Step 2 → 3	Step 3 → 4 (Book)	After book
Hotel	Search → Details: same body	Details → Prebook: requestId, bookingCode	Prebook → Finalize: bookingContext	bookingRefId → status
Flight	Search → Pricing: searchId	Pricing → Issue: priceId, bookingContext	Issue-ticket (needs X- Partner-Key)	bookingReference → status
Cab	Search → Fare: searchId	Fare → Finalize: bookingReference, priceId	Finalize (needs X- Partner-Key)	bookingRefId → status

Postman tips for QA

1. **Run top to bottom** inside each scenario folder — collection scripts auto-save variables.
2. **Do not reuse** old `requestId` / `bookingCode` / `priceId` — they expire.
3. **Hotel:** if finalize stays Inprogress, that BR cannot be used for price/cancel tests.
4. **Flight:** issue-ticket books a **live ticket** on staging — use only when needed.
5. **Cab:** finalize books live — cancel after test if required.
6. **Secrets:** never commit `partner_secret` or `signing_key` to git.

Generated for TravelVIP B2B QA · Staging default · Update dates/entityId for your test data.