

Cab API Error Contract

Every client-facing error the cab endpoints can return — HTTP status, error code, and message — plus the shared response envelope.

Service `catalog-platform` Base `/api/v1/cabs` Provider `Mojoboxx`

! Scope is **catalog-platform** only — the three endpoints below. `finalize-booking` and the wallet codes (`FARE_EXPIRED`, `WALLET_*`, `INSUFFICIENT_BALANCE`) live in **travelx-backend** and are not covered here.

RESPONSE ENVELOPE

Every error — validation or upstream — is returned in this exact shape. `details` is `null` unless the row says otherwise.

```
"error": {  
  "code": "VALIDATION_ERROR",  
  "message": "searchId is required.",  
  "details": null  
}
```

400 validation / bad input **404** not found **5xx** upstream / vendor

1 · LOCATION SEARCH

GET `/api/v1/cabs/locations` → `cityList`

Free-text lookup of pickup / drop points. **No client-side validation** — `search`, `latitude`, `longitude` are all optional and passed straight through; no params returns the whole list.

No 4xx validation errors. Only the shared upstream errors below can occur.

POST /api/v1/cabs/search → fareSearch Query param pid required · body CabSearchRequest.		
HTTP	CODE	MESSAGE
400	VALIDATION_ERROR	pid is required. Missing <code>pid</code> query param.
400	VALIDATION_ERROR	Malformed JSON request body. Unparseable body or wrong field type; <code>details</code> carries path + expectedType.
400	VALIDATION_ERROR	Request validation failed. One or more required body fields missing – <code>journeyType</code> , <code>travelType</code> , <code>airportCode</code> , <code>pickup</code> , <code>drop</code> , <code>pickupDatetime</code> . Offending fields under <code>details.fieldErrors</code> .
400	VALIDATION_ERROR	airportCode is required. airportCode present but blank.
404	NOT_FOUND	Unknown airportCode: <code><v></code> Not a recognised airport.

POST `/api/v1/cabs/fare` → `getSearchResult`

Query param `pid` required · body `CabFareRequest`.

HTTP	CODE	MESSAGE
400	VALIDATION_ERROR	pid is required. Missing <code>pid</code> query param.
400	VALIDATION_ERROR	Malformed JSON request body.
400	VALIDATION_ERROR	Request validation failed. <code>searchId</code> blank or missing; field under <code>details.fieldErrors</code> .
400	VALIDATION_ERROR	Invalid searchId. Expected a searchId returned by <code>/search</code> . Fails the <code><uuid> <hash></code> format — e.g. <code>ROHAN</code> , <code>abc</code> , <code><script></code> , a bare UUID.
404	NOT_FOUND	No fare found for searchId= <code><v></code> . The quote may have expired; re-run <code>/search</code> . Well-formed id that is unknown or expired at the vendor.

SHARED · UPSTREAM & VENDOR ERRORS

Applies to **all three** endpoints when the provider call fails after input passes.

HTTP	CODE	MESSAGE
503	VENDOR_TIMEOUT	Cab provider took too long to respond. Please retry.
502	VENDOR_REJECTED_REQUEST	Cab provider could not process this search. Vendor answered with a 4xx.
503	VENDOR_UNAVAILABLE	Cab provider is temporarily unavailable. Please retry.
500	INTERNAL_SERVER_ERROR	Something went wrong. Unexpected / uncaught error.

SAMPLE PAYLOADS

400 · single-field validation

```
"error": {  
  "code": "VALIDATION_ERROR",  
  "message": "Invalid searchId. Expected a  
             searchId returned by /search.",  
  "details": null  
}
```

400 · body field errors

```
"error": {  
  "code": "VALIDATION_ERROR",  
  "message": "Request validation failed.",  
  "details": {  
    "fieldErrors": {  
      "airportCode": "must not be null",  
      "pickupDatetime": "must not be null"  
    }  
  }  
}
```

Note on field messages. Required-field checks (`journeyType`, `travelType`, `pickupDatetime`, ...) come from bean validation and surface as the generic `Request validation failed.` with the fields under `details.fieldErrors` — not one message per field. Per-field messages can be added if the frontend prefers them.