

TravelVIP — Webhook integration guide

Cab booking and trip events — payload reference

Payload version	1
Events covered	12 (5 booking, 7 trip & dispatch)
Issued	28 August 2026
Updated	3 September 2026
Status	Initial release

Confidential — for integration partners

Contents

1. [How to read this document](#)
2. [Event catalogue](#)
3. [Cab booking events](#)
 - 3.1 [booking.pending](#)
 - 3.2 [booking.confirmed](#)
 - 3.3 [booking.failed](#)
 - 3.4 [booking.cancelled](#)
 - 3.5 [booking.cancellation_failed](#)
4. [Trip and dispatch events](#)
 - 4.1 [driver.assigned](#)
 - 4.2 [driver.departed](#)
 - 4.3 [driver.enroute](#)
 - 4.4 [driver.arrived](#)
 - 4.5 [trip.started](#)
 - 4.6 [cab.location](#)
 - 4.7 [trip.ended](#)
5. [Shared booking objects](#)
 - 5.1 [transaction](#)
 - 5.2 [contact](#)
 - 5.3 [passengers](#)
 - 5.4 [details \(core trip fields\)](#)
 - 5.5 [details.vehicle and details.operator](#)
 - 5.6 [details.assignment](#)
 - 5.7 [details.trip](#)
 - 5.8 [salesSummary](#)
 - 5.9 [cancellation](#)
6. [Amount reconciliation](#)
7. [Appendix A — change log](#)

1. How to read this document

Every TravelVIP webhook is delivered as a single JSON object over HTTPS POST. The outer envelope is identical across all events; only **data** varies. Route on **event**, and read **version** before parsing **data**.

Field	Type	Description
version	integer	Contract version of the payload. Always 1 for the schema described here. A breaking change ships as version: 2 ; additive fields do not increment it.
event	string	Event identifier — see the event catalogue in section 2. Route on this field, not on data.status .
timestamp	string (ISO 8601, UTC)	When the event was generated by TravelVIP.
type	string	Event category. cab for booking lifecycle events, dispatch for trip and driver-tracking events.
data	object	Event-specific body. Shape depends on type .

Alignment with the REST API. **data** mirrors the shape TravelVIP's own cabs REST API returns from **GET /v1/airportServices/cabs/{bookingReference}/status** and **GET /v1/airportServices/cabs/booking/{bookingReference}** — **contact**, **details**, and **salesSummary** are the same objects, with the same field names, that those endpoints return. A few fields exist only in this webhook and have no REST equivalent: **transaction[]**, **tripStage**, **sequenceNumber**, and **cancellation**. Each is called out inline below.

Conventions

- **Keys are camelCase** throughout the payload, at every nesting level.
- **Event names are identifiers, not keys.** Match the dot-delimited lowercase value of **event** exactly (e.g. **booking.cancellation_failed**, **driver.enroute**, **cab.location**).
- **bookingReference is standardized.** The REST API uses three different key names for this same identifier depending on endpoint — **bookingRefId** (Book, Cancel Booking), **bookingReferenceId** (Fetch Booking Status, Fetch Booking Details), **bookingId** (Fetch Cab Location). This webhook always uses **bookingReference**, matching the hotel and flight event contracts. Do not expect this exact key name back from the polling endpoints.
- **Timestamps mostly come in one shape, with two documented exceptions.** Envelope, **transaction**, and **tripTracking.syncedAt** timestamps are ISO 8601 in UTC with a trailing **Z**. **details.pickupDatetime** is also UTC but is written with an explicit **+00:00** offset instead of **Z** — both denote the same instant; don't assume the **Z** form appears everywhere. **details.assignment.assignedAt**, **details.assignment.syncedAt**, and **details.trip.startedAt / endedAt** are naive **YYYY-MM-DD HH:mm:ss** strings (no **T**, no offset) in the underlying REST responses — this webhook normalizes all three to ISO 8601 UTC for consistency with the rest of the contract; treat the naive format as a quirk of the polling endpoints only, not something you'll see here.

- **Amounts** are numbers in the major unit of the accompanying currency (ISO 4217). There are no minor-unit integers on the wire.
- **tripTracking normalizes types found in the raw tracking endpoint.** GET `/v1/airportServices/cabs/tracking/{bookingReference}/location` returns `latitude/longitude` as strings and its sync timestamp as an epoch-milliseconds string (e.g. `"1750935000000"`). This webhook emits `latitude/longitude` as numbers and `syncedAt` as ISO 8601 UTC, matching every other coordinate and timestamp in this contract.
- **Absent data.** Event-conditional objects (`details.assignment`, `details.trip`, `cancellation`) and `data.providerBookingId` (before the fleet partner accepts the booking) are omitted entirely rather than sent as `null`; other optional scalars are `null`; unset strings such as `details.otp` before `booking.confirmed` are the empty string. Handle all three forms.
- **High-frequency events.** `driver.enroute` and `cab.location` fire repeatedly — potentially dozens of times per trip — each carrying a monotonically increasing `sequenceNumber` (webhook-only; there is no equivalent on the polling tracking endpoint). Dedupe and order on `sequenceNumber`, not on arrival order or `timestamp`; mobile network retries can deliver pings out of sequence. If you only need the latest position, it is safe to discard superseded pings rather than persist every one. Their payload is also leaner than the other dispatch events — see section 4.
- **details.assignment keeps driver and vehicle identity in different shapes.** Driver identity is flat-only (`driverName`, `driverMobile`) — there is no nested `driver` object. Vehicle identity is nested-only (`vehicle.type`, `vehicle.registrationNo`, `vehicle.color`, ...) — there is no flat `vehicleRegistrationNo` mirror. Don't expect the two to be symmetric.
- **details.assignment.trip0tp supersedes details.otp once a driver is assigned.** From `driver.assigned` onward, `details.otp` is dropped from the payload — `trip0tp` carries that same pickup verification value forward (see the OTP callout in section 3.2).
- **data.providerBookingId** is the fleet partner's own reference for this booking — useful when raising a support ticket with them directly. It's assigned once the fleet partner accepts the booking, so it's absent on `booking.pending` and `booking.failed`, and present on every other event (`booking.confirmed` onward, and every dispatch event).
- **details.operator and details.assignment.partner are not always the same value.** `details.operator` is the customer-facing brand shown at search and booking time (e.g. TravelVIP). `details.assignment.partner` is the backend fleet/dispatch partner that actually fulfilled the trip (e.g. MERU) — TravelVIP can white-label another fleet's inventory. Don't assume they match.
- **Identifiers.** `bookingReference` is a stable string reference. `passengers[].paxId` and `cancellation.id` are integers. `sequenceNumber` is an integer.
- **Forward compatibility.** Ignore keys you do not recognise. Additive fields will not change `version`.

Reconciliation rule. Treat `salesSummary.totalAmount` as the amount charged at booking confirmation; it is not recalculated after the trip runs. Extra distance and night charges settle separately — see section 6. Treat `cancellation.refundAmount` as the credited amount on cancellation, `cancellation.penaltyAmount` as what was withheld, and `salesSummary.refund.amount` as the credited amount when confirmation fails outright.

2. Event catalogue

Twelve events are in scope. `data.status` describes the state of the *booking* after the event; `data.tripStage` (dispatch events only) is a webhook-only convenience string identifying the current dispatch milestone — see section 4. Neither is a substitute for `event`.

Event	Type	data.status	Fired when
<code>booking.pending</code>	<code>cab</code>	Pending	Booking request received; payment captured and handed to the fleet partner for confirmation.
<code>booking.confirmed</code>	<code>cab</code>	Confirmed	Booking confirmed with the rider. <code>details.otp</code> is generated on this event.
<code>booking.failed</code>	<code>cab</code>	Failed	Confirmation failed. The debit has been reversed in full.
<code>booking.cancelled</code>	<code>cab</code>	Cancelled	Cancellation completed. <code>cancellation.refundAmount</code> credited net of <code>penaltyAmount</code> .
<code>booking.cancellation_failed</code>	<code>cab</code>	Confirmed	Cancellation attempt failed. The booking is still live.
<code>driver.assigned</code>	<code>dispatch</code>	Confirmed	A driver and vehicle have been allocated to the booking. <code>details.assignment</code> is populated for the first time.
<code>driver.departed</code>	<code>dispatch</code>	Confirmed	Fired once when the driver starts moving towards the pickup point.
<code>driver.enroute</code>	<code>dispatch</code>	Confirmed	Fired repeatedly while the driver travels towards the pickup point.
<code>driver.arrived</code>	<code>dispatch</code>	Confirmed	Fired once when the driver reaches the pickup location.
<code>trip.started</code>	<code>dispatch</code>	Confirmed	Fired when the rider boards and the trip begins.
<code>cab.location</code>	<code>dispatch</code>	Confirmed	Fired repeatedly from trip start until trip end.
<code>trip.ended</code>	<code>dispatch</code>	Completed	Fired when the trip finishes. Carries <code>details.trip</code> , the settlement summary.

Ordering. A booking's first event is `booking.pending`, followed by `booking.confirmed` or `booking.failed`. Do not assume arrival order — compare `timestamp` (or `sequenceNumber` for dispatch events) and ignore an event older than the state you already hold.

The dispatch sequence. On a confirmed booking, dispatch events fire in this order: `driver.assigned` → `driver.departed` → `driver.enroute` (×N) → `driver.arrived` → `trip.started` → `cab.location` (×N) → `trip.ended` — each one advances `data.tripStage` to the next milestone. `driver.assigned` can recur mid-trip only in a reassignment (driver breakdown, no-show) — check `details.assignment.isReassigned` before treating a second `driver.assigned` as an error.

Cancellation has no acknowledgement step. Unlike hotel and flight bookings, a cab cancellation attempt fires exactly one event — `booking.cancelled` or `booking.cancellation_failed` — never a separate `booking.cancellation_requested` first. Don't build integration logic that waits on a request/acknowledgement event before the outcome. A cancellation can be attempted at any point up to `trip.started`.

3. Cab booking events

All five booking events share one envelope and one `data` skeleton: `status`, `reason`, `bookingReference`, `transaction[]`, `contact`, `passengers[]`, `details`, and `salesSummary`. The two cancellation-family events (`booking.cancelled`, `booking.cancellation_failed`) add `cancellation.details.assignment` and `details.trip` are never present on booking events — they're introduced by the dispatch events in section 4. The shared objects are documented once in section 5; each event below lists only what is specific to it.

3.1 booking.pending

Fired as soon as payment is captured and the booking request is handed to the fleet partner for confirmation — this is the first event a booking receives. The booking is not yet confirmed with a rider: `details.otp` is still the empty string. Wait for `booking.confirmed` or `booking.failed` before treating the booking as final; do not issue pickup instructions on this event.

Event-specific values

Field	Type	Description
<code>data.status</code>	string	Always <code>Pending</code> .
<code>data.details.otp</code>	string	Empty string — not yet generated. Populated by <code>booking.confirmed</code> .
<code>data.transaction</code>	array<object>	The original debit, with <code>status</code> set to <code>success</code> .
<code>data.providerBookingId</code>	—	Absent — the fleet partner hasn't accepted the booking yet; see section 1.
<code>cancellation</code>	object	Absent.

Payload

```
{
  "version": 1,
  "event": "booking.pending",
```

```
"timestamp": "2026-08-24T05:30:12Z",
"type": "cab",
"data": {
  "status": "Pending",
  "reason": null,
  "bookingReference": "BR2608241730214",
  "transaction": [
    {
      "id": "32608241730214001",
      "amount": 1113,
      "currency": "INR",
      "paymentMethod": "wallet",
      "createdAt": "2026-08-24T05:30:11Z",
      "completedAt": "2026-08-24T05:30:11Z",
      "type": "debit",
      "status": "success"
    }
  ],
  "contact": {
    "name": "Chaitanya Patil",
    "email": "chaitanya@travelvip.ai",
    "countryCode": "+91",
    "mobile": "9921862715"
  },
  "passengers": [
    {
      "paxId": 1,
      "paxType": "ADT",
      "isLead": true,
      "profile": {
        "title": "Mr",
        "firstName": "Chaitanya",
        "lastName": "Patil",
        "gender": "male"
      }
    }
  ],
  "details": {
    "journeyType": "AIRPORT",
    "travelType": "DEPARTURE",
    "airportCode": "DEL",
    "pickupDatetime": "2026-08-24T09:15:00+00:00",
    "pickup": {
      "name": "Vasant Kunj, Delhi",
      "city": "Delhi",
      "latitude": 28.5201,
      "longitude": 77.1591
    },
    "drop": {
      "name": "IGI Airport-T1",
      "city": "Delhi",
      "latitude": 28.5588,
      "longitude": 77.0814
    }
  },
}
```

```

    "distanceKm": 15,
    "durationMin": 15,
    "extraKmFare": 25,
    "freeCancellationTillMin": 30,
    "inclusions": [
      "15 Kms Ride",
      "GST Included"
    ],
    "exclusions": [
      "Waiting Charges (after 30 mins) ₹100/30min",
      "Toll Charges",
      "Extra Km Fare (₹25/Km)"
    ],
    "vehicle": {
      "type": "SEDAN",
      "category": "ECONOMY",
      "model": "Dzire or Similar",
      "makeYear": 2016,
      "seatingCapacity": 4,
      "luggageCapacity": 2,
      "airConditioned": true,
      "fuelType": "CNG",
      "imageUrl":
        "https://cdn.bookairportcab.com/logos/travel_vip_84X84.png",
      "imageAppUrl": null,
      "imageMobileUrl": null
    },
    "operator": {
      "name": "TravelVIP",
      "logoUrl":
        "https://cdn.bookairportcab.com/logos/travel_vip_84X84.png",
      "rating": 3.6,
      "ratingCount": 190
    },
    "otp": ""
  },
  "salesSummary": {
    "basePrice": 1060,
    "subTotal": 1060,
    "tax": 53,
    "convenienceFee": 0,
    "totalAmount": 1113,
    "totalDiscount": 0,
    "currency": "INR"
  }
}

```

3.2 booking.confirmed

Fired once the fleet partner confirms the booking with the rider. This is the event to act on for booking confirmation messaging — `details.otp` is populated for the first time and must be shown to the rider

for verification at pickup.

Event-specific values

Field	Type	Description
<code>data.status</code>	string	Always <code>Confirmed</code> .
<code>data.details.otp</code>	string	4-digit pickup verification code. Present for the lifetime of the booking; unchanged by reassignment.
<code>data.transaction</code>	array<object>	The original debit, with <code>status</code> set to <code>success</code> .
<code>data.providerBookingId</code>	string	The fleet partner's own booking reference, assigned now that they've accepted the booking. Present from this event onward — see section 1.
<code>cancellation</code>	object	Absent.

Handle the OTP carefully. `details.otp` is sensitive: display it to the rider, do not log it in plaintext analytics, and mask it in support tooling. The driver's app validates it against this same value at pickup. Once a driver is assigned, `details.assignment.tripOtp` carries this same value forward — `details.otp` itself is dropped from the payload from `driver.assigned` onward (it is never reissued); see section 5.6.

Payload

```
{
  "version": 1,
  "event": "booking.confirmed",
  "timestamp": "2026-08-24T05:31:02Z",
  "type": "cab",
  "data": {
    "status": "Confirmed",
    "reason": null,
    "bookingReference": "BR2608241730214",
    "providerBookingId": "TVIPWE100726174646EQEW",
    "transaction": [
      {
        "id": "32608241730214001",
        "amount": 1113,
        "currency": "INR",
        "paymentMethod": "wallet",
        "createdAt": "2026-08-24T05:30:11Z",
        "completedAt": "2026-08-24T05:30:11Z",
        "type": "debit",
        "status": "success"
      }
    ]
  },
  "contact": {
    "name": "Chaitanya Patil",
    "email": "chaitanya@travelvip.ai",
    "countryCode": "+91",
```

```
    "mobile": "9921862715"
  },
  "passengers": [
    {
      "paxId": 1,
      "paxType": "ADT",
      "isLead": true,
      "profile": {
        "title": "Mr",
        "firstName": "Chaitanya",
        "lastName": "Patil",
        "gender": "male"
      }
    }
  ],
  "details": {
    "journeyType": "AIRPORT",
    "travelType": "DEPARTURE",
    "airportCode": "DEL",
    "pickupDatetime": "2026-08-24T09:15:00+00:00",
    "pickup": {
      "name": "Vasant Kunj, Delhi",
      "city": "Delhi",
      "latitude": 28.5201,
      "longitude": 77.1591
    },
    "drop": {
      "name": "IGI Airport-T1",
      "city": "Delhi",
      "latitude": 28.5588,
      "longitude": 77.0814
    },
    "distanceKm": 15,
    "durationMin": 15,
    "extraKmFare": 25,
    "freeCancellationTillMin": 30,
    "inclusions": [
      "15 Kms Ride",
      "GST Included"
    ],
    "exclusions": [
      "Waiting Charges (after 30 mins) ₹100/30min",
      "Toll Charges",
      "Extra Km Fare (₹25/Km)"
    ],
    "vehicle": {
      "type": "SEDAN",
      "category": "ECONOMY",
      "model": "Dzire or Similar",
      "makeYear": 2016,
      "seatingCapacity": 4,
      "luggageCapacity": 2,
      "airConditioned": true,
      "fuelType": "CNG",
    }
  }
}
```

```

        "imageUrl":
"https://cdn.bookairportcab.com/logos/travel_vip_84X84.png",
        "imageAppUrl": null,
        "imageMobileUrl": null
    },
    "operator": {
        "name": "TravelVIP",
        "logoUrl":
"https://cdn.bookairportcab.com/logos/travel_vip_84X84.png",
        "rating": 3.6,
        "ratingCount": 190
    },
    "otp": "4522"
},
"salesSummary": {
    "basePrice": 1060,
    "subTotal": 1060,
    "tax": 53,
    "convenienceFee": 0,
    "totalAmount": 1113,
    "totalDiscount": 0,
    "currency": "INR"
}
}
}

```

3.3 booking.failed

Fired when confirmation fails at the supplier/dispatch layer. The debit has been reversed in full.

Event-specific values

Field	Type	Description
<code>data.status</code>	string	Always Failed .
<code>data.reason</code>	string	Failure reason, e.g. No cabs available .
<code>data.transaction</code>	array<object>	The original debit plus a matching credit reversal for <code>salesSummary.totalAmount</code> .
<code>salesSummary.refund</code>	object	Present — a full reversal. See below.
<code>salesSummary.refund.amount</code>	number	Equals <code>salesSummary.totalAmount</code> .
<code>salesSummary.refund.destinationType</code>	string	Where the money was returned, e.g. wallet .
<code>data.providerBookingId</code>	—	Absent — confirmation never completed, so the fleet partner

Field	Type	Description
		never accepted the booking; see section 1.
cancellation	object	Absent.

Payload

```
{
  "version": 1,
  "event": "booking.failed",
  "timestamp": "2026-08-24T05:33:40Z",
  "type": "cab",
  "data": {
    "status": "Failed",
    "reason": "No cabs available",
    "bookingReference": "BR2608241730214",
    "transaction": [
      {
        "id": "32608241730214001",
        "amount": 1113,
        "currency": "INR",
        "paymentMethod": "wallet",
        "createdAt": "2026-08-24T05:30:11Z",
        "completedAt": "2026-08-24T05:30:11Z",
        "type": "debit",
        "status": "success"
      },
      {
        "id": "32608241730214002",
        "amount": 1113,
        "currency": "INR",
        "paymentMethod": "wallet",
        "createdAt": "2026-08-24T05:33:40Z",
        "completedAt": "2026-08-24T05:33:40Z",
        "type": "credit",
        "status": "success"
      }
    ],
    "contact": {
      "name": "Chaitanya Patil",
      "email": "chaitanya@travelvip.ai",
      "countryCode": "+91",
      "mobile": "9921862715"
    },
    "passengers": [
      {
        "paxId": 1,
        "paxType": "ADT",
        "isLead": true,
        "profile": {
          "title": "Mr",

```

```
        "firstName": "Chaitanya",
        "lastName": "Patil",
        "gender": "male"
    }
}
],
"details": {
    "journeyType": "AIRPORT",
    "travelType": "DEPARTURE",
    "airportCode": "DEL",
    "pickupDatetime": "2026-08-24T09:15:00+00:00",
    "pickup": {
        "name": "Vasant Kunj, Delhi",
        "city": "Delhi",
        "latitude": 28.5201,
        "longitude": 77.1591
    },
    "drop": {
        "name": "IGI Airport-T1",
        "city": "Delhi",
        "latitude": 28.5588,
        "longitude": 77.0814
    },
    "distanceKm": 15,
    "durationMin": 15,
    "extraKmFare": 25,
    "freeCancellationTillMin": 30,
    "inclusions": [
        "15 Kms Ride",
        "GST Included"
    ],
    "exclusions": [
        "Waiting Charges (after 30 mins) ₹100/30min",
        "Toll Charges",
        "Extra Km Fare (₹25/Km)"
    ],
    "vehicle": {
        "type": "SEDAN",
        "category": "ECONOMY",
        "model": "Dzire or Similar",
        "makeYear": 2016,
        "seatingCapacity": 4,
        "luggageCapacity": 2,
        "airConditioned": true,
        "fuelType": "CNG",
        "imageUrl":
https://cdn.bookairportcab.com/logos/travel\_vip\_84X84.png,
        "imageAppUrl": null,
        "imageMobileUrl": null
    },
    "operator": {
        "name": "TravelVIP",
        "logoUrl":
https://cdn.bookairportcab.com/logos/travel\_vip\_84X84.png,
    }
```

```

    "rating": 3.6,
    "ratingCount": 190
  },
  "otp": ""
},
"salesSummary": {
  "basePrice": 1060,
  "subTotal": 1060,
  "tax": 53,
  "convenienceFee": 0,
  "totalAmount": 1113,
  "totalDiscount": 0,
  "currency": "INR",
  "refund": {
    "id": "32608241730214002",
    "amount": 1113,
    "destinationType": "wallet"
  }
}
}
}
}

```

3.4 booking.cancelled

Fired when a cancellation completes. There is no separate acknowledgement event for a cab booking — a cancellation attempt fires exactly one outcome, this event or `booking.cancellation_failed` (section 3.5). `cancellation` combines the request that was made and the outcome the fleet partner returned — its financial fields mirror the shape returned by `GET`

`.../cabs/bookings/{bookingReference}/cancel`; `refundAmount` is `totalPrice` minus `penaltyAmount`.

Event-specific values

Field	Type	Description
<code>data.status</code>	string	Always <code>Cancelled</code> .
<code>data.providerBookingId</code>	string	The fleet partner's own booking reference — see section 1.
<code>data.transaction</code>	array<object>	The original debit plus a credit for <code>cancellation.refundAmount</code> .
<code>cancellation.id</code>	integer	Stable identifier for this cancellation attempt.
<code>cancellation.status</code>	string	Always <code>Cancellation Successful</code> .
<code>cancellation.requestedBy</code>	string	<code>RIDER</code> , <code>PARTNER</code> , or <code>SYSTEM</code> .
<code>cancellation.reason</code>	string	Free-text reason supplied by the requester.
<code>cancellation.totalPrice</code>	number	Equals <code>salesSummary.totalAmount</code> .

Field	Type	Description
<code>cancellation.penaltyAmount</code>	number	Cancellation charge withheld. <code>0</code> when the request landed inside the free-cancellation window.
<code>cancellation.refundAmount</code>	number	<code>totalPrice</code> minus <code>penaltyAmount</code> . This is what's credited.

Payload

```
{
  "version": 1,
  "event": "booking.cancelled",
  "timestamp": "2026-08-24T07:05:52Z",
  "type": "cab",
  "data": {
    "status": "Cancelled",
    "reason": "Rider cancelled",
    "bookingReference": "BR2608241730214",
    "providerBookingId": "TVIPWE100726174646EQEW",
    "cancellation": {
      "id": 550118,
      "status": "Cancellation Successful",
      "requestedBy": "RIDER",
      "requestedAt": "2026-08-24T07:05:18Z",
      "reason": "Change of plans",
      "message": "Booking cancelled successfully",
      "totalPrice": 1113,
      "penaltyAmount": 0,
      "refundAmount": 1113,
      "currency": "INR"
    },
    "transaction": [
      {
        "id": "32608241730214001",
        "amount": 1113,
        "currency": "INR",
        "paymentMethod": "wallet",
        "createdAt": "2026-08-24T05:30:11Z",
        "completedAt": "2026-08-24T05:30:11Z",
        "type": "debit",
        "status": "success"
      },
      {
        "id": "32608241730214002",
        "amount": 1113,
        "currency": "INR",
        "paymentMethod": "wallet",
        "createdAt": "2026-08-24T07:05:52Z",
        "completedAt": "2026-08-24T07:05:52Z",
        "type": "credit",

```

```
    "status": "success"
  }
],
"contact": {
  "name": "Chaitanya Patil",
  "email": "chaitanya@travelvip.ai",
  "countryCode": "+91",
  "mobile": "9921862715"
},
"passengers": [
  {
    "paxId": 1,
    "paxType": "ADT",
    "isLead": true,
    "profile": {
      "title": "Mr",
      "firstName": "Chaitanya",
      "lastName": "Patil",
      "gender": "male"
    }
  }
],
"details": {
  "journeyType": "AIRPORT",
  "travelType": "DEPARTURE",
  "airportCode": "DEL",
  "pickupDatetime": "2026-08-24T09:15:00+00:00",
  "pickup": {
    "name": "Vasant Kunj, Delhi",
    "city": "Delhi",
    "latitude": 28.5201,
    "longitude": 77.1591
  },
  "drop": {
    "name": "IGI Airport-T1",
    "city": "Delhi",
    "latitude": 28.5588,
    "longitude": 77.0814
  },
  "distanceKm": 15,
  "durationMin": 15,
  "extraKmFare": 25,
  "freeCancellationTillMin": 30,
  "inclusions": [
    "15 Kms Ride",
    "GST Included"
  ],
  "exclusions": [
    "Waiting Charges (after 30 mins) ₹100/30min",
    "Toll Charges",
    "Extra Km Fare (₹25/Km)"
  ],
  "vehicle": {
    "type": "SEDAN",
```

```

        "category": "ECONOMY",
        "model": "Dzire or Similar",
        "makeYear": 2016,
        "seatingCapacity": 4,
        "luggageCapacity": 2,
        "airConditioned": true,
        "fuelType": "CNG",
        "imageUrl":
"https://cdn.bookairportcab.com/logos/travel_vip_84X84.png",
        "imageAppUrl": null,
        "imageMobileUrl": null
    },
    "operator": {
        "name": "TravelVIP",
        "logoUrl":
"https://cdn.bookairportcab.com/logos/travel_vip_84X84.png",
        "rating": 3.6,
        "ratingCount": 190
    },
    "otp": "4522"
},
"salesSummary": {
    "basePrice": 1060,
    "subTotal": 1060,
    "tax": 53,
    "convenienceFee": 0,
    "totalAmount": 1113,
    "totalDiscount": 0,
    "currency": "INR"
}
}
}

```

(In this example the request landed inside the 30-minute free-cancellation window, so *penaltyAmount* is 0 and the full amount is refunded. Outside that window, the fleet partner may withhold a penalty — *refundAmount* will be lower than *totalPrice*.)

3.5 booking.cancellation_failed

Fired when a cancellation attempt fails at the dispatch layer (e.g. a driver was already en route). The booking is still live — no new transaction is emitted, and *cancellation* carries no financial fields. As with *booking.cancelled* in section 3.4, there is no separate acknowledgement event preceding this one.

Event-specific values

Field	Type	Description
<i>data.status</i>	string	Always <i>Confirmed</i> — the booking's current status, unchanged by the failed attempt.

Field	Type	Description
<code>data.providerBookingId</code>	string	The fleet partner's own booking reference — unchanged; see section 1.
<code>cancellation.status</code>	string	Always Cancellation Failed — the outcome of this attempt, not the booking's status; read <code>data.status</code> for that.
<code>cancellation.failureReason</code>	string	Machine-routable failure code, e.g. DRIVER_ALREADY_ENROUTE .
<code>cancellation.message</code>	string	Human-readable failure message, mirroring the message field the REST cancel endpoint returns on a failed attempt.
<code>data.transaction</code>	array<object>	Unchanged — the original debit only.

Payload

```
{
  "version": 1,
  "event": "booking.cancellation_failed",
  "timestamp": "2026-08-24T07:06:01Z",
  "type": "cab",
  "data": {
    "status": "Confirmed",
    "reason": null,
    "bookingReference": "BR2608241730214",
    "providerBookingId": "TVIPWE100726174646EQEW",
    "cancellation": {
      "id": 550119,
      "status": "Cancellation Failed",
      "requestedBy": "RIDER",
      "requestedAt": "2026-08-24T07:05:58Z",
      "reason": "Change of plans",
      "failureReason": "DRIVER_ALREADY_ENROUTE",
      "message": "Cancellation window has closed – the driver is already en
route to pickup."
    },
    "transaction": [
      {
        "id": "32608241730214001",
        "amount": 1113,
        "currency": "INR",
        "paymentMethod": "wallet",
        "createdAt": "2026-08-24T05:30:11Z",
        "completedAt": "2026-08-24T05:30:11Z",
        "type": "debit",
        "status": "success"
      }
    ]
  },
  "contact": {
```

```
"name": "Chaitanya Patil",
"email": "chaitanya@travelvip.ai",
"countryCode": "+91",
"mobile": "9921862715"
},
"passengers": [
  {
    "paxId": 1,
    "paxType": "ADT",
    "isLead": true,
    "profile": {
      "title": "Mr",
      "firstName": "Chaitanya",
      "lastName": "Patil",
      "gender": "male"
    }
  }
],
"details": {
  "journeyType": "AIRPORT",
  "travelType": "DEPARTURE",
  "airportCode": "DEL",
  "pickupDatetime": "2026-08-24T09:15:00+00:00",
  "pickup": {
    "name": "Vasant Kunj, Delhi",
    "city": "Delhi",
    "latitude": 28.5201,
    "longitude": 77.1591
  },
  "drop": {
    "name": "IGI Airport-T1",
    "city": "Delhi",
    "latitude": 28.5588,
    "longitude": 77.0814
  },
  "distanceKm": 15,
  "durationMin": 15,
  "extraKmFare": 25,
  "freeCancellationTillMin": 30,
  "inclusions": [
    "15 Kms Ride",
    "GST Included"
  ],
  "exclusions": [
    "Waiting Charges (after 30 mins) ₹100/30min",
    "Toll Charges",
    "Extra Km Fare (₹25/Km)"
  ],
  "vehicle": {
    "type": "SEDAN",
    "category": "ECONOMY",
    "model": "Dzire or Similar",
    "makeYear": 2016,
    "seatingCapacity": 4,
```

```

        "luggageCapacity": 2,
        "airConditioned": true,
        "fuelType": "CNG",
        "imageUrl":
"https://cdn.bookairportcab.com/logos/travel_vip_84X84.png",
        "imageAppUrl": null,
        "imageMobileUrl": null
    },
    "operator": {
        "name": "TravelVIP",
        "logoUrl":
"https://cdn.bookairportcab.com/logos/travel_vip_84X84.png",
        "rating": 3.6,
        "ratingCount": 190
    },
    "otp": "4522"
},
"salesSummary": {
    "basePrice": 1060,
    "subTotal": 1060,
    "tax": 53,
    "convenienceFee": 0,
    "totalAmount": 1113,
    "totalDiscount": 0,
    "currency": "INR"
}
}
}

```

4. Trip and dispatch events

Trip and dispatch events extend a **booking.confirmed** booking with real-time progress. All seven carry **bookingReference** and **providerBookingId** (see section 1); the milestone events — **driver.assigned**, **driver.departed**, **driver.arrived**, **trip.started**, **trip.ended** — additionally share **contact**, **passengers**, and **details** (the core trip fields from section 3) with the booking events, and add:

- **data.tripStage** — a webhook-only convenience string identifying the current dispatch milestone: **Driver Assigned**, **Driver Departed**, **Driver Enroute**, **Driver Arrived**, **Trip Started**, **Trip In Progress**, **Trip Ended**. This is the single source of truth for dispatch progress.
- **details.assignment** — driver and vehicle, absent until **driver.assigned** (see section 5.6).
- **data.sequenceNumber** — monotonically increasing per booking, webhook-only, used to order and dedupe the high-frequency events.

None of these events carry **transaction** except **trip.ended**, which emits a settlement debit when extra distance or night charges apply. **type** is always **dispatch**.

driver.enroute and **cab.location** carry a lean payload. These two fire from position pings, not booking-state changes, and mirror the raw tracking endpoint's shape rather than the full

status endpoint. They carry only `bookingReference`, `tripStage`, `sequenceNumber`, and `tripTracking`. Correlate against the driver, vehicle, and trip context you already hold from `driver.assigned` (or an earlier booking event) using `bookingReference`.

4.1 driver.assigned

Fired when a driver and vehicle are allocated to the booking. `details.assignment` is populated for the first time — the driver is exposed as flat fields only, the vehicle as a nested object only (see section 5.6). `details.otp` is dropped from this event onward; `details.assignment.tripOtp` carries that same value.

Event-specific values

Field	Type	Description
<code>data.tripStage</code>	string	Always <code>Driver Assigned</code> .
<code>details.assignment</code>	object	Driver and vehicle — see section 5.6.
<code>details.assignment.tripOtp</code>	string	Populated for the first time on this event, carrying forward the same value <code>details.otp</code> had on <code>booking.confirmed</code> .
<code>details.otp</code>	—	Absent from this event onward — superseded by <code>details.assignment.tripOtp</code> .
<code>details.assignment.partner</code>	string	Fleet/dispatch partner that supplied this driver, e.g. <code>MERU</code> . May differ from <code>details.operator.name</code> — see section 1.
<code>details.assignment.isReassigned</code>	boolean	<code>true</code> when this event replaces a previously assigned driver (breakdown, no-show). <code>false</code> on the first assignment.

Payload

```
{
  "version": 1,
  "event": "driver.assigned",
  "timestamp": "2026-08-24T08:50:03Z",
  "type": "dispatch",
  "data": {
    "tripStage": "Driver Assigned",
    "sequenceNumber": 1,
    "bookingReference": "BR2608241730214",
    "providerBookingId": "TVIPWE100726174646EQEW",
    "contact": {
      "name": "Chaitanya Patil",
      "email": "chaitanya@travelvip.ai",
      "countryCode": "+91",
      "mobile": "9921862715"
    }
  },
}
```

```
"passengers": [
  {
    "paxId": 1,
    "paxType": "ADT",
    "isLead": true,
    "profile": {
      "title": "Mr",
      "firstName": "Chaitanya",
      "lastName": "Patil",
      "gender": "male"
    }
  }
],
"details": {
  "journeyType": "AIRPORT",
  "travelType": "DEPARTURE",
  "airportCode": "DEL",
  "pickupDatetime": "2026-08-24T09:15:00+00:00",
  "pickup": {
    "name": "Vasant Kunj, Delhi",
    "city": "Delhi",
    "latitude": 28.5201,
    "longitude": 77.1591
  },
  "drop": {
    "name": "IGI Airport-T1",
    "city": "Delhi",
    "latitude": 28.5588,
    "longitude": 77.0814
  },
  "distanceKm": 15,
  "durationMin": 15,
  "extraKmFare": 25,
  "freeCancellationTillMin": 30,
  "inclusions": [
    "15 Kms Ride",
    "GST Included"
  ],
  "exclusions": [
    "Waiting Charges (after 30 mins) ₹100/30min",
    "Toll Charges",
    "Extra Km Fare (₹25/Km)"
  ],
  "vehicle": {
    "type": "SEDAN",
    "category": "ECONOMY",
    "model": "Dzire or Similar",
    "makeYear": 2016,
    "seatingCapacity": 4,
    "luggageCapacity": 2,
    "airConditioned": true,
    "fuelType": "CNG",
    "imageUrl":
"https://cdn.bookairportcab.com/logos/travel\_vip\_84X84.png",

```

```

        "imageAppUrl": null,
        "imageMobileUrl": null
    },
    "operator": {
        "name": "TravelVIP",
        "logoUrl":
"https://cdn.bookairportcab.com/logos/travel_vip_84X84.png",
        "rating": 3.6,
        "ratingCount": 190
    },
    "assignment": {
        "driverName": "Ramesh Kumar",
        "driverMobile": "9876543210",
        "tripOtp": "4522",
        "assignedAt": "2026-08-24T08:50:03Z",
        "vehicle": {
            "name": "Swift Dzire",
            "color": "White",
            "type": "SEDAN",
            "registrationNo": "KA01AB1234"
        },
        "partner": "MERU",
        "isReassigned": false,
        "syncedAt": "2026-08-24T08:50:03Z"
    }
}
}
}
}

```

4.2 driver.departed

Fired once, immediately after **driver.assigned**, when the driver departs for the pickup point. Marks the start of the journey to the rider — before any of the repeated **driver.enroute** position pings. Unlike **driver.enroute**, this carries the full milestone payload (**contact**, **passengers**, **details**), the same shape as **driver.arrived**.

Event-specific values

Field	Type	Description
data.tripStage	string	Always Driver Departed .
data.tripTracking	object	Driver's position at departure — the starting point for the driver.enroute pings that follow.

Payload

```

{
  "version": 1,
  "event": "driver.departed",
  "timestamp": "2026-08-24T08:51:20Z",

```

```
"type": "dispatch",
"data": {
  "tripStage": "Driver Departed",
  "sequenceNumber": 2,
  "bookingReference": "BR2608241730214",
  "providerBookingId": "TVIPWE100726174646EQEW",
  "tripTracking": {
    "latitude": 28.6304,
    "longitude": 77.2177,
    "syncedAt": "2026-08-24T08:51:18Z"
  },
  "contact": {
    "name": "Chaitanya Patil",
    "email": "chaitanya@travelvip.ai",
    "countryCode": "+91",
    "mobile": "9921862715"
  },
  "passengers": [
    {
      "paxId": 1,
      "paxType": "ADT",
      "isLead": true,
      "profile": {
        "title": "Mr",
        "firstName": "Chaitanya",
        "lastName": "Patil",
        "gender": "male"
      }
    }
  ],
  "details": {
    "journeyType": "AIRPORT",
    "travelType": "DEPARTURE",
    "airportCode": "DEL",
    "pickupDatetime": "2026-08-24T09:15:00+00:00",
    "pickup": {
      "name": "Vasant Kunj, Delhi",
      "city": "Delhi",
      "latitude": 28.5201,
      "longitude": 77.1591
    },
    "drop": {
      "name": "IGI Airport-T1",
      "city": "Delhi",
      "latitude": 28.5588,
      "longitude": 77.0814
    },
    "distanceKm": 15,
    "durationMin": 15,
    "extraKmFare": 25,
    "freeCancellationTillMin": 30,
    "inclusions": [
      "15 Kms Ride",
      "GST Included"
    ]
  }
}
```

```

],
"exclusions": [
  "Waiting Charges (after 30 mins) ₹100/30min",
  "Toll Charges",
  "Extra Km Fare (₹25/Km)"
],
"vehicle": {
  "type": "SEDAN",
  "category": "ECONOMY",
  "model": "Dzire or Similar",
  "makeYear": 2016,
  "seatingCapacity": 4,
  "luggageCapacity": 2,
  "airConditioned": true,
  "fuelType": "CNG",
  "imageUrl":
"https://cdn.bookairportcab.com/logos/travel_vip_84X84.png",
  "imageAppUrl": null,
  "imageMobileUrl": null
},
"operator": {
  "name": "TravelVIP",
  "logoUrl":
"https://cdn.bookairportcab.com/logos/travel_vip_84X84.png",
  "rating": 3.6,
  "ratingCount": 190
},
"assignment": {
  "driverName": "Ramesh Kumar",
  "driverMobile": "9876543210",
  "tripOtp": "4522",
  "assignedAt": "2026-08-24T08:50:03Z",
  "vehicle": {
    "name": "Swift Dzire",
    "color": "White",
    "type": "SEDAN",
    "registrationNo": "KA01AB1234"
  },
  "partner": "MERU",
  "isReassigned": false,
  "syncedAt": "2026-08-24T08:50:03Z"
}
}
}
}

```

4.3 driver.enroute

Fired repeatedly while the driver travels towards the pickup point. Carries the driver's live position — expect many of these per booking.

Event-specific values

Field	Type	Description
<code>data.tripStage</code>	string	Always <code>Driver Enroute</code> .
<code>data.sequenceNumber</code>	integer	Increases with every ping since <code>driver.assigned</code> . Order and dedupe on this, not on delivery order.
<code>data.tripTracking</code>	object	<code>{ latitude, longitude, syncedAt }</code> , mapping to the raw tracking endpoint's <code>tripTracking</code> object, normalized per section 1.

Payload

```
{
  "version": 1,
  "event": "driver.enroute",
  "timestamp": "2026-08-24T08:56:20Z",
  "type": "dispatch",
  "data": {
    "tripStage": "Driver Enroute",
    "sequenceNumber": 7,
    "bookingReference": "BR2608241730214",
    "providerBookingId": "TVIPWE100726174646EQEW",
    "tripTracking": {
      "latitude": 28.5701,
      "longitude": 77.1204,
      "syncedAt": "2026-08-24T08:56:18Z"
    }
  }
}
```

4.4 driver.arrived

Fired once when the driver reaches the pickup location.

Event-specific values

Field	Type	Description
<code>data.tripStage</code>	string	Always <code>Driver Arrived</code> .
<code>data.tripTracking</code>	object	Final position before pickup — should sit at or very near <code>details.pickup.latitude/longitude</code> .

Payload

```
{
  "version": 1,
  "event": "driver.arrived",
  "timestamp": "2026-08-24T09:08:44Z",
```

```
"type": "dispatch",
"data": {
  "tripStage": "Driver Arrived",
  "sequenceNumber": 19,
  "bookingReference": "BR2608241730214",
  "providerBookingId": "TVIPWE100726174646EQEW",
  "tripTracking": {
    "latitude": 28.5201,
    "longitude": 77.1591,
    "syncedAt": "2026-08-24T09:08:44Z"
  },
  "contact": {
    "name": "Chaitanya Patil",
    "email": "chaitanya@travelvip.ai",
    "countryCode": "+91",
    "mobile": "9921862715"
  },
  "passengers": [
    {
      "paxId": 1,
      "paxType": "ADT",
      "isLead": true,
      "profile": {
        "title": "Mr",
        "firstName": "Chaitanya",
        "lastName": "Patil",
        "gender": "male"
      }
    }
  ],
  "details": {
    "journeyType": "AIRPORT",
    "travelType": "DEPARTURE",
    "airportCode": "DEL",
    "pickupDatetime": "2026-08-24T09:15:00+00:00",
    "pickup": {
      "name": "Vasant Kunj, Delhi",
      "city": "Delhi",
      "latitude": 28.5201,
      "longitude": 77.1591
    },
    "drop": {
      "name": "IGI Airport-T1",
      "city": "Delhi",
      "latitude": 28.5588,
      "longitude": 77.0814
    },
    "distanceKm": 15,
    "durationMin": 15,
    "extraKmFare": 25,
    "freeCancellationTillMin": 30,
    "inclusions": [
      "15 Kms Ride",
      "GST Included"
    ]
  }
}
```

```

],
"exclusions": [
  "Waiting Charges (after 30 mins) ₹100/30min",
  "Toll Charges",
  "Extra Km Fare (₹25/Km)"
],
"vehicle": {
  "type": "SEDAN",
  "category": "ECONOMY",
  "model": "Dzire or Similar",
  "makeYear": 2016,
  "seatingCapacity": 4,
  "luggageCapacity": 2,
  "airConditioned": true,
  "fuelType": "CNG",
  "imageUrl":
"https://cdn.bookairportcab.com/logos/travel_vip_84X84.png",
  "imageAppUrl": null,
  "imageMobileUrl": null
},
"operator": {
  "name": "TravelVIP",
  "logoUrl":
"https://cdn.bookairportcab.com/logos/travel_vip_84X84.png",
  "rating": 3.6,
  "ratingCount": 190
},
"assignment": {
  "driverName": "Ramesh Kumar",
  "driverMobile": "9876543210",
  "tripOtp": "4522",
  "assignedAt": "2026-08-24T08:50:03Z",
  "vehicle": {
    "name": "Swift Dzire",
    "color": "White",
    "type": "SEDAN",
    "registrationNo": "KA01AB1234"
  },
  "partner": "MERU",
  "isReassigned": false,
  "syncedAt": "2026-08-24T08:50:03Z"
}
}
}
}

```

4.5 trip.started

Fired when the rider boards and the trip begins.

Event-specific values

Field	Type	Description
<code>data.tripStage</code>	string	Always <code>Trip Started</code> .
<code>details.trip.startedAt</code>	string (ISO 8601, UTC)	When the trip began. Normalized — see section 1.
<code>data.tripTracking</code>	object	Driver's position at trip start.

Payload

```
{
  "version": 1,
  "event": "trip.started",
  "timestamp": "2026-08-24T09:15:32Z",
  "type": "dispatch",
  "data": {
    "tripStage": "Trip Started",
    "sequenceNumber": 20,
    "bookingReference": "BR2608241730214",
    "providerBookingId": "TVIPWE100726174646EQEW",
    "tripTracking": {
      "latitude": 28.5201,
      "longitude": 77.1591,
      "syncedAt": "2026-08-24T09:15:32Z"
    },
    "contact": {
      "name": "Chaitanya Patil",
      "email": "chaitanya@travelvip.ai",
      "countryCode": "+91",
      "mobile": "9921862715"
    },
    "passengers": [
      {
        "paxId": 1,
        "paxType": "ADT",
        "isLead": true,
        "profile": {
          "title": "Mr",
          "firstName": "Chaitanya",
          "lastName": "Patil",
          "gender": "male"
        }
      }
    ],
    "details": {
      "journeyType": "AIRPORT",
      "travelType": "DEPARTURE",
      "airportCode": "DEL",
      "pickupDatetime": "2026-08-24T09:15:00+00:00",
      "pickup": {
        "name": "Vasant Kunj, Delhi",
        "city": "Delhi",

```

```
    "latitude": 28.5201,
    "longitude": 77.1591
  },
  "drop": {
    "name": "IGI Airport-T1",
    "city": "Delhi",
    "latitude": 28.5588,
    "longitude": 77.0814
  },
  "distanceKm": 15,
  "durationMin": 15,
  "extraKmFare": 25,
  "freeCancellationTillMin": 30,
  "inclusions": [
    "15 Kms Ride",
    "GST Included"
  ],
  "exclusions": [
    "Waiting Charges (after 30 mins) ₹100/30min",
    "Toll Charges",
    "Extra Km Fare (₹25/Km)"
  ],
  "vehicle": {
    "type": "SEDAN",
    "category": "ECONOMY",
    "model": "Dzire or Similar",
    "makeYear": 2016,
    "seatingCapacity": 4,
    "luggageCapacity": 2,
    "airConditioned": true,
    "fuelType": "CNG",
    "imageUrl":
"https://cdn.bookairportcab.com/logos/travel\_vip\_84X84.png",
    "imageAppUrl": null,
    "imageMobileUrl": null
  },
  "operator": {
    "name": "TravelVIP",
    "logoUrl":
"https://cdn.bookairportcab.com/logos/travel\_vip\_84X84.png",
    "rating": 3.6,
    "ratingCount": 190
  },
  "assignment": {
    "driverName": "Ramesh Kumar",
    "driverMobile": "9876543210",
    "tripOtp": "4522",
    "assignedAt": "2026-08-24T08:50:03Z",
    "vehicle": {
      "name": "Swift Dzire",
      "color": "White",
      "type": "SEDAN",
      "registrationNo": "KA01AB1234"
    }
  },
}
```

```

    "partner": "MERU",
    "isReassigned": false,
    "syncedAt": "2026-08-24T08:50:03Z"
  },
  "trip": {
    "startedAt": "2026-08-24T09:15:32Z"
  }
}
}
}

```

4.6 cab.location

Fired repeatedly from `trip.started` until `trip.ended`. Same shape as `driver.enroute`, distinguished by `tripStage`.

Event-specific values

Field	Type	Description
<code>data.tripStage</code>	string	Always <code>Trip In Progress</code> .
<code>data.sequenceNumber</code>	integer	Continues incrementing from the <code>driver.enroute</code> stream.
<code>data.tripTracking</code>	object	<code>{ latitude, longitude, syncedAt }</code> .

Payload

```

{
  "version": 1,
  "event": "cab.location",
  "timestamp": "2026-08-24T09:28:07Z",
  "type": "dispatch",
  "data": {
    "tripStage": "Trip In Progress",
    "sequenceNumber": 34,
    "bookingReference": "BR2608241730214",
    "providerBookingId": "TVIPWE100726174646EQEW",
    "tripTracking": {
      "latitude": 28.5450,
      "longitude": 77.1210,
      "syncedAt": "2026-08-24T09:28:05Z"
    }
  }
}

```

4.7 trip.ended

Fired when the trip finishes. `details.trip` carries the settlement summary — actual distance travelled, extra distance, and night charges — and, when any adjustment applies, a settlement transaction. This is

the event to act on for final receipts and post-trip fulfilment.

Event-specific values

Field	Type	Description
<code>data.tripStage</code>	string	Always <code>Trip Ended</code> .
<code>data.status</code>	string	<code>Completed</code> — the only dispatch event that sets <code>data.status</code> .
<code>details.trip.endedAt</code>	string (ISO 8601, UTC)	When the trip finished.
<code>details.trip.totalTravelledKm</code>	number	Actual distance travelled.
<code>details.trip.totalTravelledFare</code>	number	Fare corresponding to <code>totalTravelledKm</code> . Typically close to <code>salesSummary.totalAmount</code> but can differ slightly on real-time re-rating.
<code>details.trip.extraTravelledKm</code>	number	Distance beyond <code>details.distanceKm</code> , if any.
<code>details.trip.extraTravelledFare</code>	number	Charge for <code>extraTravelledKm</code> , at the rate in <code>details.extraKmFare</code> .
<code>details.trip.nightCharges</code>	number	Night surcharge, if the trip crossed a night-fare window. <code>0</code> otherwise.
<code>details.trip.reason</code>	string null	Free-text supplier note on the trip settlement. Usually <code>null</code> .
<code>data.transaction</code>	array<object>	Present only when <code>extraTravelledFare + nightCharges</code> is greater than <code>0</code> — a settlement debit for that delta. See section 6.

Payload

```
{
  "version": 1,
  "event": "trip.ended",
  "timestamp": "2026-08-24T09:44:51Z",
  "type": "dispatch",
  "data": {
    "tripStage": "Trip Ended",
    "status": "Completed",
    "sequenceNumber": 61,
    "bookingReference": "BR2608241730214",
    "providerBookingId": "TVIPWE100726174646EQEW",
    "tripTracking": {
```

```
    "latitude": 28.5588,
    "longitude": 77.0814,
    "syncedAt": "2026-08-24T09:44:51Z"
  },
  "transaction": [
    {
      "id": "32608241730214003",
      "amount": 75,
      "currency": "INR",
      "paymentMethod": "wallet",
      "createdAt": "2026-08-24T09:44:51Z",
      "completedAt": "2026-08-24T09:44:51Z",
      "type": "debit",
      "status": "success"
    }
  ],
  "contact": {
    "name": "Chaitanya Patil",
    "email": "chaitanya@travelvip.ai",
    "countryCode": "+91",
    "mobile": "9921862715"
  },
  "passengers": [
    {
      "paxId": 1,
      "paxType": "ADT",
      "isLead": true,
      "profile": {
        "title": "Mr",
        "firstName": "Chaitanya",
        "lastName": "Patil",
        "gender": "male"
      }
    }
  ],
  "details": {
    "journeyType": "AIRPORT",
    "travelType": "DEPARTURE",
    "airportCode": "DEL",
    "pickupDatetime": "2026-08-24T09:15:00+00:00",
    "pickup": {
      "name": "Vasant Kunj, Delhi",
      "city": "Delhi",
      "latitude": 28.5201,
      "longitude": 77.1591
    },
    "drop": {
      "name": "IGI Airport-T1",
      "city": "Delhi",
      "latitude": 28.5588,
      "longitude": 77.0814
    },
    "distanceKm": 15,
    "durationMin": 15,
```

```
"extraKmFare": 25,
"freeCancellationTillMin": 30,
"inclusions": [
  "15 Kms Ride",
  "GST Included"
],
"exclusions": [
  "Waiting Charges (after 30 mins) ₹100/30min",
  "Toll Charges",
  "Extra Km Fare (₹25/Km)"
],
"vehicle": {
  "type": "SEDAN",
  "category": "ECONOMY",
  "model": "Dzire or Similar",
  "makeYear": 2016,
  "seatingCapacity": 4,
  "luggageCapacity": 2,
  "airConditioned": true,
  "fuelType": "CNG",
  "imageUrl":
"https://cdn.bookairportcab.com/logos/travel_vip_84X84.png",
  "imageAppUrl": null,
  "imageMobileUrl": null
},
"operator": {
  "name": "TravelVIP",
  "logoUrl":
"https://cdn.bookairportcab.com/logos/travel_vip_84X84.png",
  "rating": 3.6,
  "ratingCount": 190
},
"assignment": {
  "driverName": "Ramesh Kumar",
  "driverMobile": "9876543210",
  "tripOtp": "4522",
  "assignedAt": "2026-08-24T08:50:03Z",
  "vehicle": {
    "name": "Swift Dzire",
    "color": "White",
    "type": "SEDAN",
    "registrationNo": "KA01AB1234"
  },
  "partner": "MERU",
  "isReassigned": false,
  "syncedAt": "2026-08-24T08:50:03Z"
},
"trip": {
  "startedAt": "2026-08-24T09:15:32Z",
  "endedAt": "2026-08-24T09:44:51Z",
  "totalTravelledKm": 18,
  "totalTravelledFare": 1113,
  "extraTravelledKm": 3,
  "extraTravelledFare": 75,
```

```
    "nightCharges": 0,
    "reason": null
  },
  "salesSummary": {
    "basePrice": 1060,
    "subTotal": 1060,
    "tax": 53,
    "convenienceFee": 0,
    "totalAmount": 1113,
    "totalDiscount": 0,
    "currency": "INR"
  }
}
```

5. Shared booking objects

5.1 transaction

Webhook-only wallet ledger entry; no REST equivalent.

Field	Type	Description
<code>id</code>	string	Unique transaction identifier.
<code>amount</code>	number	Major-unit amount.
<code>currency</code>	string	ISO 4217.
<code>paymentMethod</code>	string	e.g. <code>wallet</code> .
<code>createdAt</code> / <code>completedAt</code>	string (ISO 8601, UTC)	Equal on synchronous settlement.
<code>type</code>	string	<code>debit</code> or <code>credit</code> .
<code>status</code>	string	<code>success</code> , <code>pending</code> , or <code>failed</code> .

5.2 contact

Field	Type	Description
<code>name</code>	string	Rider's full name.
<code>email</code>	string	Rider contact email.
<code>countryCode</code>	string	E.164 dialling code, e.g. <code>+91</code> .
<code>mobile</code>	string	Rider contact mobile, without the country code.

5.3 passengers

Not echoed back by the REST status/details endpoints (they assume the caller already has this from their own Book request) — this webhook includes it on every event so each payload is self-contained, except `driver.enroute` and `cab.location`, whose lean payload omits it (see section 4).

Field	Type	Description
<code>paxId</code>	integer	Passenger index within the booking.
<code>paxType</code>	string	<code>ADT</code> (adult), <code>CHD</code> (child), or <code>INF</code> (infant).
<code>isLead</code>	boolean	<code>true</code> for the primary passenger on the booking.
<code>profile.title</code> / <code>firstName</code> / <code>lastName</code>	string	Passenger name.
<code>profile.gender</code>	string	<code>male</code> or <code>female</code> .

5.4 details (core trip fields)

Field	Type	Description
<code>journeyType</code>	string	<code>AIRPORT</code> , <code>OUTSTATION</code> , or <code>RENTAL</code> .
<code>travelType</code>	string	<code>DEPARTURE</code> (towards the airport) or <code>ARRIVAL</code> (from the airport) when <code>journeyType</code> is <code>AIRPORT</code> . Empty string ("") for <code>OUTSTATION</code> and <code>RENTAL</code> — see the <code>journeyType</code> examples below.
<code>airportCode</code>	string null	IATA code, present only for <code>journeyType: AIRPORT</code> ; <code>null</code> otherwise.
<code>pickupDatetime</code>	string (ISO 8601, UTC, <code>+00:00</code> offset)	See section 1 for the offset-vs- <code>Z</code> note.
<code>pickup.name</code> / <code>city</code> / <code>latitude</code> / <code>longitude</code>	string / string / number / number	Pickup location — <code>name</code> is a free-text label, not a structured address.
<code>drop.*</code>	object	Same shape as <code>pickup</code> .
<code>distanceKm</code> / <code>durationMin</code>	number	Estimated at booking time.
<code>extraKmFare</code>	number	Per-km overage rate, in <code>salesSummary.currency</code> .
<code>freeCancellationTillMin</code>	integer	Minutes before <code>pickupDatetime</code> free cancellation remains available.
<code>inclusions</code> / <code>exclusions</code>	array<string>	Display-only, supplier-authored line items from the fare quote.

Field	Type	Description
<code>otp</code>	string	See section 3.2. Present on booking events; dropped from <code>details</code> starting at <code>driver.assigned</code> — see <code>details.assignment.tripOtp</code> in section 5.6.

journeyType variants

`travelType` and `airportCode` are populated only for `journeyType: AIRPORT`; every other journey type carries `travelType: ""` and `airportCode: null`. The full `booking.confirmed` payload in section 3.2 shows the `AIRPORT` case; `OUTSTATION` and `RENTAL` follow the same `details` shape with these fields changed:

AIRPORT (departure) — as shown in section 3.2:

```
{
  "journeyType": "AIRPORT",
  "travelType": "DEPARTURE",
  "airportCode": "DEL"
}
```

OUTSTATION:

```
{
  "journeyType": "OUTSTATION",
  "travelType": "",
  "airportCode": null
}
```

RENTAL:

```
{
  "journeyType": "RENTAL",
  "travelType": "",
  "airportCode": null
}
```

5.5 details.vehicle and details.operator

`vehicle` describes the cab **class quoted** at search/booking time — not the specific car that shows up. `operator` is the customer-facing brand for that quote.

Field	Type	Description
<code>vehicle.type</code>	string	e.g. <code>SEDAN</code> , <code>SUV</code> , <code>HATCHBACK</code> .

Field	Type	Description
<code>vehicle.category</code>	string	e.g. <code>ECONOMY</code> , <code>PREMIUM</code> .
<code>vehicle.model</code>	string	Indicative model, e.g. <code>Dzire</code> or <code>Similar</code> .
<code>vehicle.makeYear</code>	integer null	
<code>vehicle.seatingCapacity</code> / <code>luggageCapacity</code>	integer	
<code>vehicle.airConditioned</code>	boolean	
<code>vehicle.fuelType</code>	string	e.g. <code>CNG</code> , <code>PETROL</code> , <code>DIESEL</code> .
<code>vehicle.imageUrl</code> / <code>imageAppUrl</code> / <code>imageMobileUrl</code>	string null	
<code>operator.name</code>	string	Customer-facing brand, e.g. <code>TravelVIP</code> .
<code>operator.logoUrl</code> / <code>rating</code> / <code>ratingCount</code>	string / number / integer	

5.6 details.assignment

Absent from every booking event in section 3. Introduced by `driver.assigned` and repeated on every dispatch event thereafter that carries `details` — `driver.enroute` and `cab.location` omit `details` (and so `details.assignment`) entirely; see section 4. Driver identity is flat-only; vehicle identity is nested-only — see the convention note in section 1 for why.

Field	Type	Description
<code>driverName</code> / <code>driverMobile</code>	string	Driver display details. Flat fields only — there is no nested <code>driver</code> object.
<code>tripOtp</code>	string null	Drop-off verification code. Populated with the same value <code>details.otp</code> had on <code>booking.confirmed</code> , which is then dropped from the payload; <code>null</code> if the fleet partner doesn't require one.
<code>assignedAt</code>	string (ISO 8601, UTC)	When this driver was assigned. Normalized — see section 1.
<code>vehicle.name</code> / <code>color</code> / <code>type</code>	string	Assigned vehicle's model, colour, and class — may differ from the originally quoted <code>details.vehicle.type</code> if the fleet substituted an equivalent car.
<code>vehicle.registrationNo</code>	string	Number plate, shown to the rider for identification.

Field	Type	Description
<code>partner</code>	string	Fleet/dispatch partner, e.g. <code>MERU</code> . See the <code>operator</code> vs. <code>partner</code> note in section 1.
<code>isReassigned</code>	boolean	<code>true</code> when this assignment replaces a prior one.
<code>syncedAt</code>	string (ISO 8601, UTC)	When the fleet partner last synced this assignment. Normalized — see section 1.

5.7 details.trip

Absent until `trip.ended`.

Field	Type	Description
<code>startedAt</code>	string (ISO 8601, UTC)	Present from <code>trip.started</code> onward.
<code>endedAt</code>	string (ISO 8601, UTC)	Present only on <code>trip.ended</code> .
<code>totalTravelledKm / totalTravelledFare</code>	number	Actual distance and its corresponding fare.
<code>extraTravelledKm / extraTravelledFare</code>	number	Overage beyond the quoted <code>details.distanceKm</code> , and its charge.
<code>nightCharges</code>	number	
<code>reason</code>	string null	Supplier note, usually <code>null</code> .

5.8 salesSummary

Not recalculated after the trip — see section 6 for how to combine it with `details.trip`.

Field	Type	Description
<code>basePrice</code>	number	Fare before tax and fees.
<code>subTotal</code>	number	
<code>tax</code>	number	
<code>convenienceFee</code>	number	
<code>totalAmount</code>	number	Amount actually charged at <code>booking.confirmed</code> .
<code>totalDiscount</code>	number	
<code>currency</code>	string	ISO 4217.
<code>refund</code>	object	Present only on <code>booking.failed</code> — a full reversal of <code>totalAmount</code> . Absent otherwise; a cancellation's refund is

Field	Type	Description
		reported in <code>cancellation.refundAmount</code> (section 5.9), not here.
<code>refund.amount</code>	number	Equals <code>totalAmount</code> .
<code>refund.destinationType</code>	string	Where the money was returned, e.g. <code>wallet</code> .

5.9 cancellation

A single webhook-only object combining the cancellation request and its outcome — there is no separate request/acknowledgement event that emits it on its own. Appears inline on `booking.cancelled` and `booking.cancellation_failed` only.

Field	Type	Description
<code>id</code>	integer	Stable identifier for this cancellation attempt.
<code>status</code>	string	<code>Cancellation Successful</code> on <code>booking.cancelled</code> , <code>Cancellation Failed</code> on <code>booking.cancellation_failed</code> . Describes the outcome of this attempt — not the booking's status; read <code>data.status</code> for that.
<code>requestedBy</code> / <code>requestedAt</code> / <code>reason</code>	string / string / string	Who requested the cancellation, when, and why.
<code>failureReason</code>	string	Present only on <code>booking.cancellation_failed</code> . Machine-routable failure code.
<code>message</code>	string	Human-readable outcome message, mirroring the REST cancel endpoint's response.
<code>totalPrice</code> / <code>penaltyAmount</code> / <code>refundAmount</code>	number	Present only on <code>booking.cancelled</code> . See section 3.4.
<code>currency</code>	string	Present only on <code>booking.cancelled</code> . ISO 4217.

6. Amount reconciliation

Stage	Field	Meaning
Booking confirmed	<code>salesSummary.totalAmount</code>	Amount charged upfront. Not recalculated after the trip runs.
Trip completed, adjustment due	<code>details.trip.extraTravelledFare</code> + <code>details.trip.nightCharges</code>	The delta actually owed beyond <code>totalAmount</code> , if positive. Charged as a settlement debit in <code>trip.ended.data.transaction[]</code> .

Stage	Field	Meaning
Trip completed	<code>salesSummary.totalAmount + details.trip.extraTravelledFare + details.trip.nightCharges</code>	The total amount actually paid across the booking's lifetime. There is no single field carrying this precomputed figure — sum it.
Cancellation completed	<code>cancellation.refundAmount</code>	Settled credit: <code>totalPrice</code> minus <code>penaltyAmount</code> . No refund quote is exposed ahead of the outcome — only <code>details.freeCancellationTillMin</code> hints at eligibility beforehand.
Confirmation failed	<code>salesSummary.refund.amount</code>	Settled credit equal to <code>salesSummary.totalAmount</code> . Full reversal — mirrored in <code>data.transaction[]</code> as a credit entry; there is no <code>cancellation</code> object for this path since it isn't a cancellation.

There is currently no under-run credit: if `totalTravelledKm` is less than `distanceKm`, `extraTravelledKm` floors at 0 and no refund is issued on `trip.ended`.

7. Appendix A — change log

Version	Date	Change
1	2026-08-28	Initial release. Covers the 5-event cab booking lifecycle (<code>booking.pending</code> fires first, followed by <code>booking.confirmed</code> or <code>booking.failed</code> ; <code>booking.cancelled</code> and <code>booking.cancellation_failed</code> each carry a single <code>cancellation</code> object — combining the request and its outcome, with its own <code>status</code> reported separately from <code>data.status</code> — since a cancellation attempt fires only its outcome, never a separate acknowledgement) and the 6-event trip/dispatch lifecycle (<code>driver.*</code> , <code>trip.*</code> , <code>cab.location</code>), with <code>data.tripStage</code> (readable strings, e.g. <code>Driver Assigned</code>) as the single source of dispatch progress. Field names and shapes aligned with TravelVIP's cabs REST API (search, fare, book, status, cancel, and tracking endpoints), except <code>profile.dob</code> / <code>profile.nationality</code> , which are omitted — being removed from the underlying API.
1	2026-09-03	Added <code>driver.departed</code> , fired once immediately after <code>driver.assigned</code> and before the repeated <code>driver.enroute</code> pings begin, marking the moment the driver departs for the pickup point. Carries the full milestone payload (<code>contact</code> , <code>passengers</code> , <code>details</code>), the same shape as <code>driver.arrived</code> . Dispatch lifecycle is now 7 events (12 total); additive change, does not increment <code>version</code> .