

Paul Struble  
3038299344  
Special Participation A

## HW3 (Non-Coding Parts) - GPT 5.1 Thinking (Extended)

### Executive Summary

In this investigation, I used GPT 5.1 Thinking (Extended) to solve the non-coding parts of Homework 3. Overall, the model was very effective at solving each problem and explaining its reasoning. It was able to one-shot all parts of all problems. I prompted the model in the ChatGPT web frontend by providing a PDF attachment of the original homework assignment, a brief explanation of the task, and some additional prompts/attachments throughout the conversation to provide additional contextual resources (from the assignment). This is all recorded in the conversation log in this document. I found no misconceptions or hallucinations in the model's output although some responses took a different approach than the reference solutions (ultimately still arriving at a valid solution).

**Link to Conversation:** <https://chatgpt.com/share/693a069f-44a8-8007-bed7-a4db5aceaa8f>


### Model Details:

- Model: ChatGPT 5.1 Thinking (Extended)
- Used ChatGPT web frontend (chatgpt.com)
- Disabled all personalization features
- Used “default” personality
- Chain of thought (“Thinking”) traces can be found in the original conversation (linked above)

## Initial Prompt

### User Prompt:

[Attachment: Homework 3 PDF]


 hw3.pdf  
PDF

Read through the attached problem set for a deep learning / neural networks course. Once you have read through the assignment, you will complete each problem, one at a time. After each problem, stop and wait for a response before moving on to the next problem. Skip problems 2 and 6. For each problem, complete all subparts (a, b, c, etc.). Where appropriate, show your work, provide complete derivations, and give full explanations. Your answers should be rigorous and address all parts of the question. Start with Problem 1: Maximal Update Parameterization.

## Problem 1: Maximal Update Parameterization

### AI Response:

Thought for 53s >

Here's my solution for Problem 1: Maximal Update Parameterization. 

---

**(a) Expected squared RMS norm at initialization**

We have:

- Input  $x \in \mathbb{R}^{d_1}$  with entries  $x_k \sim \mathcal{N}(0, 1)$  i.i.d.
- Weights  $W \in \mathbb{R}^{d_2 \times d_1}$  with entries  $w_{jk} \sim \mathcal{N}(0, 1)$  i.i.d.
- Output  $y = Wx \in \mathbb{R}^{d_2}$ .

Let  $y_j$  be the  $j$ -th coordinate of  $y$ :

$$y_j = \sum_{k=1}^{d_1} w_{jk} x_k.$$

Each product  $w_{jk} x_k$  has:

- $\mathbb{E}[w_{jk} x_k] = 0$  (product of independent zero-mean variables),
- $\mathbb{E}[(w_{jk} x_k)^2] = \mathbb{E}[w_{jk}^2] \mathbb{E}[x_k^2] = 1 \cdot 1 = 1$ .

The terms are independent across  $k$ , so:

$$\text{Var}(y_j) = \sum_{k=1}^{d_1} \text{Var}(w_{jk} x_k) = d_1,$$

and hence

$$\mathbb{E}[y_j^2] = d_1.$$

The squared Euclidean norm is:

$$\|y\|^2 = \sum_{j=1}^{d_2} y_j^2.$$

Taking expectation:

$$\mathbb{E} [\|y\|^2] = \sum_{j=1}^{d_2} \mathbb{E}[y_j^2] = d_2 \cdot d_1.$$

The squared RMS norm over the features is

$$\text{RMS}^2(y) = \frac{1}{d_2} \|y\|^2,$$

so

$$\mathbb{E}[\text{RMS}^2(y)] = \frac{1}{d_2} \mathbb{E} [\|y\|^2] = \frac{1}{d_2} \cdot d_1 d_2 = d_1.$$

Scaling with dimension:

- It scales linearly with  $d_1$  (fan-in).
- It is independent of  $d_2$  (fan-out).

Now suppose we scale  $W$  by a scalar  $c$ , so we use  $\tilde{W} = cW$ . Then  $\tilde{y} = \tilde{W}x = cWx = cy$ , so

$$\mathbb{E}[\text{RMS}^2(\tilde{y})] = \mathbb{E}[\text{RMS}^2(cy)] = c^2 \mathbb{E}[\text{RMS}^2(y)] = c^2 d_1.$$

We want this to be equal to 1:

$$c^2 d_1 = 1 \quad \Rightarrow \quad c = \frac{1}{\sqrt{d_1}}.$$

Answer (a):

- $\mathbb{E}[\text{RMS}^2(Wx)] = d_1$ .
- It scales like  $O(d_1)$ , independent of  $d_2$ .
- We should multiply  $W$  by  $\boxed{1/\sqrt{d_1}}$  to make  $\mathbb{E}[\text{RMS}^2(Wx)] = 1$  for all  $d_1, d_2$ .

## (b) Expected squared RMS norm of the feature *update* under SignGD

We now look at the change in features caused by the update step.

Setup:

- Inputs  $x_i \in \mathbb{R}^{d_1}$  with entries i.i.d.  $\mathcal{N}(0, 1)$ .
- Backpropagated vector  $g_i \in \mathbb{R}^{d_2}$  is treated as a fixed constant vector.
- Gradient for a single example is outer product  $x_i g_i^\top$ .
- SignGD update:

$$W_{t+1} = W_t + \eta \text{sign}(x_i g_i^\top).$$

Ignoring the learning rate  $\eta$  for now, the **weight update matrix** is:

$$\Delta W = \text{sign}(x_i g_i^\top) \in \mathbb{R}^{d_2 \times d_1}.$$

The **change in features** for input  $x_i$  is:

$$y' = \Delta W x_i = \text{sign}(x_i g_i^\top) x_i \in \mathbb{R}^{d_2}.$$

Let's unpack this.

### Step 1: Coordinate-wise expression for $y'$

Let  $x = x_i$ ,  $g = g_i$ . For the  $m$ -th output coordinate:

$$\Delta W_{m,n} = \text{sign}(g_m x_n) = \text{sign}(g_m) \text{sign}(x_n).$$

Then

$$y'_m = \sum_{n=1}^{d_1} \Delta W_{m,n} x_n = \sum_{n=1}^{d_1} \text{sign}(g_m) \text{sign}(x_n) x_n = \text{sign}(g_m) \sum_{n=1}^{d_1} \text{sign}(x_n) x_n.$$

Define

$$S := \sum_{n=1}^{d_1} \text{sign}(x_n) x_n.$$

Then

$$y'_m = \text{sign}(g_m) S.$$

All coordinates of  $y'$  have the same magnitude: they differ only by the sign  $\text{sign}(g_m)$ .

### Step 2: Express the squared RMS norm in terms of $S$

The squared RMS norm across outputs is

$$\text{RMS}^2(y') = \frac{1}{d_2} \sum_{m=1}^{d_2} (y'_m)^2.$$

But since  $y'_m{}^2 = S^2$  for all  $m$ ,

$$\text{RMS}^2(y') = \frac{1}{d_2} \cdot d_2 \cdot S^2 = S^2.$$

So

$$\mathbb{E}[\text{RMS}^2(y')] = \mathbb{E}[S^2].$$

We see already that  $d_2$  cancels out—the dependence will be only on  $d_1$ .

### Step 3: Distribution of $S$

Each input coordinate  $x_n \sim \mathcal{N}(0, 1)$ .

For a standard normal  $X$ ,  $\text{sign}(X)X = |X|$ , so:

$$\text{sign}(x_n)x_n = |x_n|.$$

Thus

$$S = \sum_{n=1}^{d_1} |x_n|.$$

Let  $Z_n = |x_n|$ . The  $Z_n$  are i.i.d., and for  $X \sim \mathcal{N}(0, 1)$ :

$$\mathbb{E}[Z_n] = \mathbb{E}[|X|] = \sqrt{\frac{2}{\pi}}, \quad \text{Var}(Z_n) = 1 - \frac{2}{\pi}.$$

We have:

$$S = \sum_{n=1}^{d_1} Z_n,$$

$$\mathbb{E}[S] = d_1 \sqrt{\frac{2}{\pi}},$$

$$\text{Var}(S) = d_1 \left(1 - \frac{2}{\pi}\right).$$

Therefore,

$$\mathbb{E}[S^2] = \text{Var}(S) + (\mathbb{E}[S])^2 = d_1 \left(1 - \frac{2}{\pi}\right) + d_1^2 \left(\sqrt{\frac{2}{\pi}}\right)^2 = d_1 \left(1 - \frac{2}{\pi}\right) + d_1^2 \frac{2}{\pi}.$$

So

$$\mathbb{E}[\text{RMS}^2(y')] = d_1 \left(1 - \frac{2}{\pi}\right) + d_1^2 \frac{2}{\pi}.$$

For large  $d_1$ , the  $d_1^2$  term dominates:

$$\mathbb{E}[\text{RMS}^2(y')] \sim \frac{2}{\pi} d_1^2,$$

so the squared RMS norm of the feature  $y'$  state scales like  $\Theta(d_1^2)$ , and is independent of  $d_2$ .

**Step 4: What scaling makes  $\mathbb{E}[\text{RMS}^2(y')] = 1$ ?**

Suppose we multiply the update by a scalar  $c$ :

$$\Delta W_{\text{scaled}} = c \text{sign}(xg^\top), \quad y'_{\text{scaled}} = \Delta W_{\text{scaled}} x = cy'.$$

Then:

$$\text{RMS}^2(y'_{\text{scaled}}) = c^2 \text{RMS}^2(y') = c^2 S^2,$$

so

$$\mathbb{E}[\text{RMS}^2(y'_{\text{scaled}})] = c^2 \mathbb{E}[S^2].$$

We want this expectation to be 1:

$$c^2 \mathbb{E}[S^2] = 1 \quad \Rightarrow \quad c = \frac{1}{\sqrt{\mathbb{E}[S^2]}} = \frac{1}{\sqrt{d_1(1 - 2/\pi) + d_1^2(2/\pi)}}.$$

Exactly:

$$c = \frac{1}{\sqrt{d_1 \left(1 - \frac{2}{\pi}\right) + d_1^2 \frac{2}{\pi}}}.$$

In terms of **scaling with width**  $d_1$ , for large  $d_1$ ,

$$c \approx \sqrt{\frac{\pi}{2}} \cdot \frac{1}{d_1},$$

so we should **scale the update as  $O(1/d_1)$**  (up to a distribution-dependent constant) to keep the expected RMS of the feature update  $y'$  at  $O(1)$ , independent of width.

**Answer (b):**

- $\mathbb{E}[\text{RMS}^2(y')] = d_1(1 - 2/\pi) + d_1^2(2/\pi)$ .
- This is  $\Theta(d_1^2)$  and independent of  $d_2$ .
- To make the expected RMS norm of  $y'$  equal to 1, multiply the update by

$$c = \frac{1}{\sqrt{d_1(1 - 2/\pi) + d_1^2(2/\pi)}} \sim O\left(\frac{1}{d_1}\right).$$

**(c) Why does the update rule only depend on  $d_1$ ?**

There are two complementary perspectives:

#### 1. Direct algebraic reason

We found:

$$y'_m = \text{sign}(g_m) S, \quad S = \sum_{n=1}^{d_1} |x_n|.$$

So:

- All  $d_2$  outputs have the *same magnitude*  $|S|$ .
- The squared RMS norm is:

$$\text{RMS}^2(y') = \frac{1}{d_2} \sum_{m=1}^{d_2} y_m'^2 = \frac{1}{d_2} \cdot d_2 \cdot S^2 = S^2.$$

Thus, the factor  $d_2$  cancels out exactly. The only random object left is  $S$ , which is a sum over the inputs  $x_n$ , so the scaling depends purely on  $d_1$  (how many terms are in that sum) and not on  $d_2$ .

#### 2. Feature-space viewpoint (why $\mu P$ depends on fan-in)

We are measuring a norm in output feature space (across the  $d_2$  coordinates of  $y$ ):

$$\text{RMS}^2 = \frac{1}{d_2} \sum_{j=1}^{d_2} y_j^2.$$

At both initialization and under this SignGD update:

- Each output coordinate is treated symmetrically.
- They have equal variance at initialization and equal magnitude of updates under our simplified assumptions.

When you average across  $d_2$  outputs, any linear scaling in  $d_2$  in the numerator is canceled by the  $1/d_2$  in the RMS definition. What remains is the scaling with **fan-in**  $d_1$ , because each output is a sum over  $d_1$  independent input contributions.

So:

- **Initialization:**  $y_j$  is a sum of  $d_1$  terms  $\rightarrow$  variance scales with  $d_1$ .
- **Update:** the feature change is also a sum over  $d_1$  terms  $\rightarrow$  magnitude scales with  $d_1$ .
- **Averaging across outputs** knocks out any dependence on how many outputs  $d_2$  you have.

**Answer (c):**

The update rule only depends on  $d_1$  because both the initialization scale and the feature-update scale are determined by sums over the **input dimension** (fan-in). When we compute the RMS over the  $d_2$  outputs, the dependence on  $d_2$  cancels out, leaving only the dependence on the number of inputs  $d_1$ .

That finishes **Problem 1**.

When you're ready, tell me to move on and I'll start **Problem 3** (skipping 2 as requested).

### Comments & Observations:

**Part A:** The model one-shotted this part. The model first considers a single coordinate of the output, which is the same logic used by the reference solution. It then writes its proof, using some basic natural language to connect each step of its proof, and it summarizes the correct answers.

**Part B:** The model one-shotted this part. It provides a full proof. Interestingly, the model provides the full constant term (not included in the reference solution), but also summarizes its order as  $O(1/d_1)$ , recognizing that only the  $1/d_1$  term is significant here. The model also makes some minor mistake in the formatting of some of its math that causes a slight rendering error in the web frontend, but this is not particularly significant.

**Part C:** The model one-shotted this part. Its explanation is valid/correct but uses a different line of reasoning than the reference solution. The model's explanation is split into two parts: an algebraic justification and an intuitive "feature-space" viewpoint. Both perspectives are still valid explanations that answer the question.

3: Maximal Update Parameterization Research

User Prompt:

[Attachment: PDF of [Arxiv 2203.03466](#)]

[Attachment: Image of Figure 1 from paper]

## AI Response:

Thought for 2m 22s >

(3b)

From Table 3, for Adam LR, hidden weights (rightmost entry of the bottom row):

- $\mu$ P scaling:  $1/\text{fan\_in}$
- **Standard parametrization (SP) scaling:** shown in gray parentheses as 1.


So, under standard parametrization the Adam learning rate for hidden layers does *not* scale with width; it is simply a constant (independent of `fan_in`).

## User Prompt:

[Attachment: PDF of [Arxiv 2310.17813](#)]

[Attachment: Desideratum 1 from paper]

Desideratum 1 (Feature learning). Let  $h_\ell(x) \in \mathbb{R}^{n_\ell}$  denote the features of input  $x$  at layer  $\ell$  of a neural network, and let  $\Delta h_\ell(x) \in \mathbb{R}^{n_\ell}$  denote their change after a gradient step. We desire that:  
 $\|h_\ell\|_2 = \Theta(\sqrt{n_\ell})$  and  $\|\Delta h_\ell\|_2 = \Theta(\sqrt{n_\ell})$ , at layers  $\ell = 1, \dots, L-1$ .

 2310.17813v2.pdf  
PDF

Now move on to Problem 3 Part c. The research paper "A Spectral Condition for Feature Learning" is attached with this message. An image of Desideratum 1 is also attached with this message.

## AI Response:


Thought for 44s >

Desideratum 1 is asking for **non-trivial but well-behaved feature evolution** as width grows.

**Why this behavior is desired for feature learning**

At layer  $\ell$ , the feature vector  $h_\ell(x) \in \mathbb{R}^{n_\ell}$  and its one-step change  $\Delta h_\ell(x)$  satisfy

$$\|h_\ell\|_2 = \Theta(\sqrt{n_\ell}), \quad \|\Delta h_\ell\|_2 = \Theta(\sqrt{n_\ell}). \quad \text{ : contentReference[oaicite : 0]index = 0 }$$

- Dividing by  $\sqrt{n_\ell}$ , each coordinate of  $h_\ell$  and  $\Delta h_\ell$  has **typical size  $\Theta(1)$** , independent of width.  
 2310.17813v2
- So as we widen the network:
  - activations don't explode or vanish (each neuron still sees  $O(1)$  inputs), and
  - each neuron's update is also  $O(1)$ , so features keep changing by a non-zero amount instead of freezing or blowing up.

This is exactly what we want for "feature learning": hidden representations keep changing in a meaningful, width-independent way.

**Rewriting Desideratum 1 in terms of RMS norm**

Define the RMS norm of a layer- $\ell$  feature vector

$$\text{RMS}(h_\ell) := \frac{\|h_\ell\|_2}{\sqrt{n_\ell}}, \quad \text{RMS}(\Delta h_\ell) := \frac{\|\Delta h_\ell\|_2}{\sqrt{n_\ell}}.$$

Then Desideratum 1 is equivalently

$$\text{RMS}(h_\ell) = \Theta(1), \quad \text{RMS}(\Delta h_\ell) = \Theta(1), \quad \ell = 1, \dots, L-1,$$

i.e. per-coordinate magnitude of features and their updates stays order-one with width.



### Rewriting Condition 1 in RMS language

Condition 1 says that for weight matrix  $W_\ell \in \mathbb{R}^{n_\ell \times n_{\ell-1}}$  and its update  $\Delta W_\ell$ :

$$\|W_\ell\|_* = \Theta\left(\sqrt{\frac{n_\ell}{n_{\ell-1}}}\right), \quad \|\Delta W_\ell\|_* = \Theta\left(\sqrt{\frac{n_\ell}{n_{\ell-1}}}\right).$$

If the input to the layer has RMS =  $\Theta(1)$ , i.e.  $\|h_{\ell-1}\|_2 = \Theta(\sqrt{n_{\ell-1}})$ , then

$$\text{RMS}(h_\ell) = \frac{\|W_\ell h_{\ell-1}\|_2}{\sqrt{n_\ell}} \lesssim \frac{\|W_\ell\|_* \|h_{\ell-1}\|_2}{\sqrt{n_\ell}} = \frac{\Theta\left(\sqrt{\frac{n_\ell}{n_{\ell-1}}}\right) \cdot \Theta(\sqrt{n_{\ell-1}})}{\sqrt{n_\ell}} = \Theta(1),$$

and similarly for  $\Delta h_\ell$  using  $\Delta W_\ell$ . So Condition 1 exactly enforces that RMS feature size and RMS update size stay  $O(1)$  across layers.

### How Condition 1 implies the *upper* bounds

Using the usual operator-norm inequality  $\|Av\|_2 \leq \|A\|_* \|v\|_2$  2310.17813v2 :

1. Forward features:

$$h_\ell = W_\ell h_{\ell-1} \Rightarrow \|h_\ell\|_2 \leq \|W_\ell\|_* \|h_{\ell-1}\|_2 = \Theta\left(\sqrt{\frac{n_\ell}{n_{\ell-1}}}\right) \Theta(\sqrt{n_{\ell-1}}) = \Theta(\sqrt{n_\ell}).$$

2. Feature updates (schematically, from Eq. (3) in the paper):

$$\Delta h_\ell = \Delta W_\ell h_{\ell-1} + W_\ell \Delta h_{\ell-1} + \Delta W_\ell \Delta h_{\ell-1}. : \text{contentReference}[\text{qaicite} : 4] \text{index} = 4$$

Applying the triangle inequality and the same operator-norm bound to each term, together with Condition 1 and inductive assumptions on lower layers, gives

$$\|\Delta h_\ell\|_2 \leq \Theta(\sqrt{n_\ell}).$$

So Condition 1 directly yields the **upper** big- $\Theta$  bounds on  $\|h_\ell\|_2$  and  $\|\Delta h_\ell\|_2$ .

### Key assumption needed for the *lower* bounds

To also get **lower** bounds  $\|h_\ell\|_2 = \Omega(\sqrt{n_\ell})$  and  $\|\Delta h_\ell\|_2 = \Omega(\sqrt{n_\ell})$ , we need that those inequalities are not super-loose. The crucial assumption is:

**Alignment of features with the top singular directions of  $W_\ell$  and  $\Delta W_\ell$ , and no perfect cancellation.**

Concretely, the paper argues (Claim 1 & Claim 2) that:

- Random weight matrices and low-rank gradient updates are such that

$$\|W_\ell h_{\ell-1}\|_2 = \Theta(\|W_\ell\|_* \|h_{\ell-1}\|_2), \quad \|\Delta W_\ell h_{\ell-1}\|_2 = \|\Delta W_\ell\|_* \|h_{\ell-1}\|_2,$$

i.e. the upper bounds are tight up to constants. 2310.17813v2

- Additionally, updates don't perfectly cancel existing features:  $\|h_\ell + \Delta h_\ell\|_2$  is of the same order as  $\|h_\ell\|_2 + \|\Delta h_\ell\|_2$ . 2310.17813v2

This **alignment / non-cancellation assumption** turns the upper bounds into matching lower bounds, giving

$$\|h_\ell\|_2 = \Theta(\sqrt{n_\ell}), \quad \|\Delta h_\ell\|_2 = \Theta(\sqrt{n_\ell}),$$

which is exactly Desideratum 1.

## Comments & Observations:

**Part A:** The model one-shotted this part. It provides a correct/complete analysis of the figure that aligns with the reference solution, and provides some additional detail.

**Part B:** The model one-shotted this part. Interestingly, the chain of thought trace reveals that the model had some issues using some of its tools for reading the PDF that caused a long chain of thought time for this subpart (around 2.5 minutes). It's possible that the attached PDF may have caused the conversation to exceed the context window, but I am unsure. Overall, the model was able to recover and still provide a valid solution.

**Part C:** The model one-shotted this part. It gave a valid proof/reasoning for the problem that aligned with the reference solution.

## 4: Policy Gradient and the Reparameterization Gradient Estimator

User Prompt:

Now move on to Problem 4: Policy Gradient and the Reparameterization Gradient Estimator.

AI Response:

Thought for 1m 28s

Here's Problem 4: Policy Gradient and Reparameterization Gradient, all parts (a)–(e).

We're given

$$F(\theta) = \mathbb{E}_{x \sim p_\theta}[f(x)] = \int p_\theta(x) f(x) dx.$$

(a) Gaussian case: score-function / policy-gradient form

Now  $x$  is multivariate Gaussian with mean  $\mu$  and covariance  $\sigma^2 I$ :

$$p_\mu(x) = (2\pi\sigma^2)^{-k/2} \exp\left(-\frac{\|x - \mu\|^2}{2\sigma^2}\right).$$

Start from the definition

$$F(\mu) = \int p_\mu(x) f(x) dx.$$

Differentiate w.r.t.  $\mu$ :

$$\nabla_\mu F(\mu) = \int \nabla_\mu p_\mu(x) f(x) dx.$$

Write  $\nabla_\mu p_\mu(x) = p_\mu(x) \nabla_\mu \log p_\mu(x)$ :

$$\nabla_\mu F(\mu) = \int p_\mu(x) f(x) \nabla_\mu \log p_\mu(x) dx = \mathbb{E}_{x \sim p_\mu}[f(x) \nabla_\mu \log p_\mu(x)].$$

Compute  $\nabla_\mu \log p_\mu(x)$ :

$$\begin{aligned} \log p_\mu(x) &= C - \frac{1}{2\sigma^2} \|x - \mu\|^2, \\ \nabla_\mu \log p_\mu(x) &= -\frac{1}{2\sigma^2} \nabla_\mu \|x - \mu\|^2 = -\frac{1}{2\sigma^2} (-2)(x - \mu) = \frac{x - \mu}{\sigma^2}. \end{aligned}$$

So

$$\nabla_\mu F(\mu) = \mathbb{E}_{x \sim p_\mu} \left[ f(x) \frac{x - \mu}{\sigma^2} \right].$$

Thus in the required form  $\nabla_\mu F(\mu) = \mathbb{E}_{x \sim p_\mu}[g(x)]$ , we have

$$g(x) = \frac{f(x)}{\sigma^2} (x - \mu).$$

This is the score-function / policy-gradient estimator.

**(b) Rewriting  $F(\mu)$  using a standard normal**

If  $x \sim p_\mu(x) = \mathcal{N}(\mu, \sigma^2 I)$ , then

$$x = \mu + \sigma z, \quad z \sim \mathcal{N}(0, I).$$

Therefore we can reparameterize:

$$F(\mu) = \mathbb{E}_{x \sim p_\mu}[f(x)] = \mathbb{E}_{z \sim \mathcal{N}(0, I)}[f(\mu + \sigma z)].$$

Equivalently: if we set  $x_0 \sim \mathcal{N}(0, \sigma^2 I)$  (i.e.  $p_{\mu=0}$ ), then  $x = x_0 + \mu$ , and

$$F(\mu) = \mathbb{E}_{x_0 \sim p_{\mu=0}}[f(x_0 + \mu)].$$

**(c) Reparameterization gradient for  $\nabla_\mu F(\mu)$**

Using the reparameterized form with  $x_0 \sim p_{\mu=0} = \mathcal{N}(0, \sigma^2 I)$ ,

$$F(\mu) = \mathbb{E}_{x_0 \sim p_{\mu=0}}[f(x_0 + \mu)].$$

Now the distribution no longer depends on  $\mu$ , so we can move  $\nabla_\mu$  inside:

$$\nabla_\mu F(\mu) = \mathbb{E}_{x_0 \sim p_{\mu=0}}[\nabla_\mu f(x_0 + \mu)].$$

But  $f$  depends on  $\mu$  only through the argument  $x = x_0 + \mu$ , so by the chain rule,

$$\nabla_\mu f(x_0 + \mu) = \nabla_x f(x) \Big|_{x=x_0+\mu}.$$

Thus

$$\boxed{\nabla_\mu F(\mu) = \mathbb{E}_{x_0 \sim p_{\mu=0}}[\nabla_x f(x) \Big|_{x=x_0+\mu}]}.$$

This is the **reparameterization gradient estimator** (also called the pathwise derivative): we draw  $x_0$  from a fixed distribution and backpropagate through the transformation  $x = x_0 + \mu$ .

**(d) General policy-gradient estimator for arbitrary  $p_\theta$**

Now consider the general case:

$$F(\theta) = \int p_\theta(x) f(x) dx.$$

Differentiate:

$$\nabla_\theta F(\theta) = \int \nabla_\theta p_\theta(x) f(x) dx.$$

Factor  $\nabla_\theta p_\theta(x) = p_\theta(x) \nabla_\theta \log p_\theta(x)$ :

$$\nabla_\theta F(\theta) = \int p_\theta(x) f(x) \nabla_\theta \log p_\theta(x) dx = \mathbb{E}_{x \sim p_\theta}[f(x) \nabla_\theta \log p_\theta(x)].$$

So in the requested form,

$$\boxed{\nabla_\theta F(\theta) = \mathbb{E}_{x \sim p_\theta}[g(x)], \quad g(x) = f(x) \nabla_\theta \log p_\theta(x).}$$

This is the **general score-function / policy gradient**.

**(e) General reparameterization gradient estimator**

We're given:

- A random variable  $z \sim p(z)$ , where  $p(z)$  does not depend on  $\theta$ .
- A deterministic function  $g(z, \theta)$  such that

$$x = g(z, \theta) \text{ has the same distribution as } x \sim p_\theta(x).$$

Then we can re-write:

$$F(\theta) = \mathbb{E}_{x \sim p_\theta}[f(x)] = \mathbb{E}_{z \sim p(z)}[f(g(z, \theta))].$$

Since the distribution over  $z$  does not depend on  $\theta$ , we can differentiate under the expectation:

$$\nabla_\theta F(\theta) = \mathbb{E}_{z \sim p(z)}[\nabla_\theta f(g(z, \theta))].$$

Apply the chain rule to  $f \circ g$ :

$$\nabla_\theta f(g(z, \theta)) = (\nabla_\theta g(z, \theta))^\top \nabla_x f(x)|_{x=g(z, \theta)}.$$

Therefore,

$$\nabla_\theta F(\theta) = \mathbb{E}_{z \sim p(z)} \left[ \nabla_\theta g(z, \theta)^\top \nabla_x f(x)|_{x=g(z, \theta)} \right].$$

This is the **reparameterization (pathwise) gradient estimator** in full generality.

**Special case** (link to parts (b) and (c))

For the Gaussian example:

- Let  $z \sim p(z) = p_{\mu=0}(z) = \mathcal{N}(0, \sigma^2 I)$ .
- Take  $g(z, \mu) = z + \mu$ .

Then  $g(z, \mu)$  has distribution  $\mathcal{N}(\mu, \sigma^2 I) = p_\mu(x)$ , and plugging into the general formula in (e) recovers exactly the expression from part (c).

**Comments & Observations:**

**Part A:** The model one-shotted this part. It used the score function identity and recognized that solution is the “score-function / policy-gradient estimator.” Because it used the score function identity, its work looks a little different from the reference solution, but ultimately its final solution is the same.

**Part B:** The model one-shotted this part. For its final answer, it added a slightly different (but correct) notation compared to the reference solution, and it used this notation in the follow-up in Part C.

**Part C:** The model one-shotted this part. It continued with its Part B notation, and noted that “this is the reparameterization gradient estimator (also called the pathwise derivative).”

**Part D:** The model one-shotted this part. It notes that “this is the general score-function / policy gradient.”

**Part E:** The model one-shotted this part. It was able to identify the correct special cases referenced by the problem (recognizing the link to Part B and Part C).

## 5: Tensor Rematerialization

User Prompt:

Now move on to Problem 5: Tensor Rematerialization

AI Response:

Thought for 5m 1s >

### Problem 5: Tensor Rematerialization

We have a 10-layer network.

Stored in (on-chip) memory after the initial forward pass:

- inputs (layer 0),
- activations of layer 5,
- activations of layer 10.

During the *backward* pass we recompute activations on-the-fly from the most recent stored activation before the current layer.

#### (a) Number of `fwd` operations in one backward pass

For each layer (going from 10 down to 1):

- Layer 10: already stored  $\rightarrow$  0 extra fwd.
- Layer 9: recompute from layer 5  $\rightarrow$  run layers 6,7,8,9  $\rightarrow$  4 fwd.
- Layer 8: recompute from layer 5  $\rightarrow$  layers 6,7,8  $\rightarrow$  3 fwd.
- Layer 7: recompute from layer 5  $\rightarrow$  layers 6,7  $\rightarrow$  2 fwd.
- Layer 6: recompute from layer 5  $\rightarrow$  layer 6  $\rightarrow$  1 fwd.
- Layer 5: stored  $\rightarrow$  0 fwd.
- Layer 4: recompute from input (layer 0)  $\rightarrow$  layers 1–4  $\rightarrow$  4 fwd.
- Layer 3: from input  $\rightarrow$  layers 1–3  $\rightarrow$  3 fwd.
- Layer 2: from input  $\rightarrow$  layers 1–2  $\rightarrow$  2 fwd.
- Layer 1: from input  $\rightarrow$  layer 1  $\rightarrow$  1 fwd.

Total:

$$0 + (4 + 3 + 2 + 1) + 0 + (4 + 3 + 2 + 1) = 20$$

20 fwd operations

#### (b) Number of `loadmem` operations in one backward pass

Each time we `fetch` a stored activation or the inputs from memory counts as one `loadmem`.

- Layer 10: load its stored activation once  $\rightarrow$  1.
- Layers 9,8,7,6: each time we start from stored layer-5 activation  $\rightarrow$  4 more.
- Layer 5: we must also fetch its stored activation once  $\rightarrow$  +1.
- Layers 4,3,2,1: each time we start from the inputs in memory  $\rightarrow$  4 more.

Total `loadmem` ops:

$$1 + 4 + 1 + 4 = 10$$

10 loadmem operations

**(c) Required speed of  $t_{\text{loaddisk}}$  for disk-based scheme**

Alternative scheme: we **don't** rematerialize; instead all activations are stored on local disk and loaded when needed.

During one backward pass we need one activation per layer  $\rightarrow 10$   $t_{\text{loaddisk}}$  operations, and no extra fwd.

**1. Tensor rematerialization time**

$$T_{\text{TR}} = (\# \text{fwd}) \cdot 20 \text{ ns} + (\# \text{loadmem}) \cdot 10 \text{ ns} = 20 \cdot 20 + 10 \cdot 10 = 400 + 100 = 500 \text{ ns}.$$

**2. Disk scheme time**

$$T_{\text{disk}} = 10 \cdot t_{\text{loaddisk}}.$$

Set them equal to match runtime:

$$10 t_{\text{loaddisk}} = 500 \text{ ns} \Rightarrow t_{\text{loaddisk}} = 50 \text{ ns}.$$

**Each loaddisk must be 50 ns or faster.**

**Comments & Observations:**

The model's chain of thought reasoning took a particularly long time to run on this problem (around 5 minutes). It seems that most of the chain of thought time was spent reasoning about the arithmetic required by the problem and performing calculations.

**Part A:** The model one-shotted this part. It first identified the correct number of fwd operations for each individual layer and then calculated the correct total number of fwd operations.

**Part B:** The model one-shotted this part. Its response/reasoning follows a similar structure to its Part A response, and its final answer for the total number of loadmem operations is correct.

**Part C:** The model one-shotted this part. The model again writes out its arithmetic and arrives at the correct final answer (50 ns).