

Your grade: 100%

Your latest: 100% • Your highest: 100% • To pass you need at least 80%. We keep your highest score.

Next item →

1. True/False: Suppose you learn a word embedding for a vocabulary of 60000 words. Then the embedding vectors could be 60000 dimensional, so as to capture the full range of variation and meaning in those words. 1 / 1 point

- ☒ False
- ☐ True

Expand

Correct  
No, the dimension of word vectors is usually smaller than the size of the vocabulary. Most common sizes for word vectors range between 50 and 1000.

2. What is t-SNE? 1 / 1 point

- ☐ A supervised learning algorithm for learning word embeddings
- ☐ A linear transformation that allows us to solve analogies on word vectors
- ☒ A non-linear dimensionality reduction technique
- ☐ An open-source sequence modeling library

Expand

Correct  
Yes

3. Suppose you download a pre-trained word embedding which has been trained on a huge corpus of text. You then use this word embedding to train an RNN for a language task of recognizing if someone is happy from a short snippet of text, using a small training set. 1 / 1 point

x (input text)	y (happy?)
Having a great time!	1
I'm sad it's raining.	0
I'm feeling awesome!	1

Even if the word “wonderful” does not appear in your small training set, what label might be reasonably expected for the input text “I feel wonderful!”?

- ☒ y=1
- ☐ y=0

Expand

Correct  
Yes, word vectors empower your model with an incredible ability to generalize. The vector for “wonderful” would contain a negative/unhappy connotation which will probably make your model classify the sentence as a “1”.

4. Which of these equations do you think should hold for a good word embedding? (Check all that apply) 1 / 1 point

☒  $e_{man} - e_{woman} \approx e_{king} - e_{queen}$

Correct  
The order of words is correct in this analogy.

☐  $e_{man} - e_{woman} \approx e_{queen} - e_{king}$

☐  $e_{man} - e_{king} \approx e_{queen} - e_{woman}$

☒  $e_{man} - e_{king} \approx e_{woman} - e_{queen}$

Typesetting math: 100%

The order of words is correct in this analogy.

Expand

Correct  
Great, you got all the right answers.

5. True/False: The most computationally efficient formula for Python to get the embedding of word 1021, if  $C$  is an embedding matrix, and  $o_{1021}$  is a one-hot vector corresponding to word 1021, is  $C^T * o_{1021}$ . 1 / 1 point

- ☐ True
- ☒ False

Expand

Correct  
It is computationally wasteful because the element-wise multiplication will be extremely inefficient.

6. When learning word embeddings, we create an artificial task of estimating  $P(target \mid context)$ . It is okay if we do poorly on this artificial prediction task; the more important by-product of this task is that we learn a useful set of word embeddings. 1 / 1 point

- ☐ False
- ☒ True

Expand

Correct

7. True/False: In the word2vec algorithm, you estimate  $P(t \mid c)$ , where  $t$  is the target word and  $c$  is a context word.  $t$  and  $c$  are chosen from the training set using  $cas$  the sequence of all the words in the sentence before  $t$ . 1 / 1 point

- ☒ False
- ☐ True

Expand

Correct  
 $t$  and  $c$  are chosen from the training set to be nearby words.

8. Suppose you have a 10000 word vocabulary, and are learning 100-dimensional word embeddings. The word2vec model uses the following softmax function: 1 / 1 point

$$P(t \mid c) = \frac{e^{\theta_t^T c}}{\sum_{i=1}^{10000} e^{\theta_i^T c}}$$

True/False: After training, we should expect  $\theta_t$  to be very close to  $c_c$  when  $t$  and  $c$  are the same word.

- ☐ True
- ☒ False

Expand

Correct  
To review this concept watch the lecture.

9. Suppose you have a 10000 word vocabulary, and are learning 500-dimensional word embeddings. The GloVe model minimizes this objective: 1 / 1 point

$$\min \sum_{i=1}^{10,000} \sum_{j=1}^{10,000} f(X_{ij})(\theta_i^T e_j + b_i + b_j' - \log X_{ij})^2$$

Which of these statements are correct? Check all that apply.

☒  $X_{ij}$  is the number of times word  $j$  appears in the context of word  $i$ .

Correct

☒ Theoretically, the weighting function  $f(\cdot)$  must satisfy  $f(0) = 0$

Correct

☒  $\theta_i$  and  $e_j$  should be initialized randomly at the beginning of training.

Correct

Typesetting math: 100%  
 $b_i$  be initialized to 0 at the beginning of training.

Expand

Correct  
Great, you got all the right answers.

10. You have trained word embeddings using a text dataset of  $s_1$  words. You are considering using these word embeddings for a language task, for which you have a separate labeled dataset of  $s_2$  words. Keeping in mind that using word embeddings is a form of transfer learning, under which of these circumstances would you expect the word embeddings to be helpful? 1 / 1 point

- ☐  $s_1 \ll s_2$
- ☒  $s_1 \gg s_2$

Expand

Correct  
 $s_1$  should transfer to  $s_2$