

## Logical Clocks

- why physical clocks are not adequate
- event ordering, happened-before relation
- Lamport's logical clocks
  - ◆ condition
  - ◆ implementation
  - ◆ limitation
- Vector clocks
  - ◆ condition
  - ◆ implementation

1

## From physical clocks to logical clocks

- Physical clocks (last time)
  - ◆ With a receiver, a clock can be synchronized to within 0.1–10 ms of UTC
  - ◆ On a network, computer clocks can be synchronized to within 30 ms of each other (using NTP)
  - ◆ Quartz crystal clocks drift 1  $\mu$ s per second (1 ms per 16.6 minutes)
  - ◆ In 30 ms, a 100 MIPS machine can execute 3 million instructions
  - ◆ We will refer to these clocks as *physical clocks*, and say they measure *global time*
- Idea — abandon idea of physical time
  - ◆ For many purposes, it is sufficient to know the **order** in which events occurred
  - ◆ Lamport (1978) — introduce logical (*virtual*) time, synchronize *logical clocks*

2

## Events and event ordering

- For many purposes, it is sufficient to know the **order** in which two events occurred
  - ◆ An event may be an instruction execution, may be a function execution, etc.
  - ◆ Events include message send / receive
- Within a single process, or between two processes on the same computer,
  - ◆ the order in which two events occur **can** be determined using the physical clock
- Between two different computers in a distributed system,
  - ◆ the order in which two events occur **cannot** be determined using local physical clocks, since those clocks cannot be synchronized perfectly


3

## The “happened before” relation

- Lamport defined the *happened before* relation (denoted “ $\rightarrow$ ”), which describes a **causal ordering** of events:
  - (1) if  $a$  and  $b$  are events in the same process, and  $a$  occurred before  $b$ , then  $a \rightarrow b$
  - (2) if  $a$  is the event of sending a message  $m$  in one process, and  $b$  is the event of receiving that message  $m$  in another process, then  $a \rightarrow b$
  - (3) if  $a \rightarrow b$ , and  $b \rightarrow c$ , then  $a \rightarrow c$  (i.e., the relation “ $\rightarrow$ ” is transitive)
- Causality:
  - ◆ Past events influence future events
  - ◆ This influence among causally related events (those that can be ordered by “ $\rightarrow$ ”) is referred to a *causal affects*
  - ◆ If  $a \rightarrow b$ , event  $a$  causally affects event  $b$

4

## The “happened before” relation



- Concurrent events;
  - ◆ Two distinct events  $a$  and  $b$  are said to be *concurrent* (denoted “ $a \parallel b$ ”), if neither  $a \rightarrow b$  nor  $b \rightarrow a$
  - ◆ In other words, concurrent events do not causally affect each other
- For any two events  $a$  and  $b$  in a system, either:  $a \rightarrow b$  or  $b \rightarrow a$  or  $a \parallel b$

5

## Lamport's logical clocks

- To implement “ $\rightarrow$ ” in a distributed system, Lamport (1978) introduced the concept of logical clocks, which captures “ $\rightarrow$ ” numerically
- Each process  $P_i$  has a *logical clock*  $C_i$
- Clock  $C_i$  can assign a value  $C_i(a)$  to any event  $a$  in process  $P_i$ 
  - ◆ The value  $C_i(a)$  is called the *timestamp* of event  $a$  in process  $P_i$
  - ◆ The value  $C(a)$  is called the *timestamp* of event  $a$  in whatever process it occurred
- The timestamps have no relation to physical time, which leads to the term *logical clock*
  - ◆ The logical clocks assign monotonically increasing timestamps, and can be implemented by simple counters

6

## Conditions Satisfied by the logical clocks

- **Clock condition:** if  $a \rightarrow b$ , then  $C(a) < C(b)$ 
  - ◆ If event  $a$  happens before event  $b$ , then the clock value (timestamp) of  $a$  should be less than the clock value of  $b$
  - ◆ Note that we can **not** say: if  $C(a) < C(b)$ , then  $a \rightarrow b$
- **Correctness conditions** (must be satisfied by the logical clocks to meet the clock condition above):
  - [C1] For any two events  $a$  and  $b$  in the same process  $P_i$ , if  $a$  happens before  $b$ , then  $C_i(a) < C_i(b)$
  - [C2] If event  $a$  is the event of sending a message  $m$  in process  $P_i$ , and event  $b$  is the event of receiving that same message  $m$  in a different process  $P_k$ , then  $C_i(a) < C_k(b)$

7

## Implementation of logical clocks

- **Implementation Rules** (guarantee that the logical clocks satisfy the correctness conditions):

- [IR1] Clock  $C_i$  must be incremented between any two successive events in process  $P_i$ :  


$$C_i := C_i + d \quad (d > 0) \text{ (usually } d=1)$$
- [IR2] If event  $a$  is the event of sending a message  $m$  in process  $P_i$ , then message  $m$  is assigned a timestamp  $t_m = C_i(a)$   
 When that same message  $m$  is received by a different process  $P_k$ ,  $C_k$  is set to a value greater than or equal to its present value, and greater than  $t_m$ :  

$$C_k := \max(C_k, t_m + d) \quad (d > 0) \text{ (usually } d=1)$$

8

## Example of logical clocks

Updating logical clocks using Lamport's method




- Notes:
  - ◆ Clocks initially 0,  $d=1$
  - ◆ Most clocks incremented due to IR1
  - ◆ Sends e12, e22, e16, and e24 use IR1
  - ◆ Receives e23, e15, and e17 set to  $C_k$
  - ◆ Receive e25 sets to  $t_m + d = 6 + 1 = 7$

9

## Example of logical clocks


The happened before relationship " $\rightarrow$ " defines an irreflexive **partial order** among events



- A **total order** of events (" $\Rightarrow$ ") can be obtained as follows:
  - ◆ If  $a$  is any event in process  $P_i$ , and  $b$  is any event in process  $P_k$ , then  $a \Rightarrow b$  if and only if either:  
 $C_i(a) < C_k(b)$     **or**     $C_i(a) = C_k(b)$  and  $P_i << P_k$   
 where " $<<$ " denotes a relation that totally orders the processes to break ties

10

## Limitation of logical clocks



- With Lamport's logical clocks, if  $a \rightarrow b$ , then  $C(a) < C(b)$ 
  - ◆ The following is **not** necessarily true if events  $a$  and  $b$  occur in different processes: if  $C(a) < C(b)$ , then  $a \rightarrow b$
  - ◆  $C(e11) < C(e22)$ , and  $e11 \rightarrow e22$  is true
  - ◆  $C(e11) < C(e32)$ , but  $e11 \rightarrow e32$  is false
- Cannot determine whether two events are causally related from timestamps

11

## Vector clocks

- Independently proposed by Fidge and by Mattern in 1988
- Vector clocks:
  - ◆ Assume system contains  $n$  processes
  - ◆ Each process  $P_i$  has a clock  $C_i$ , which is an integer vector of length  $n$   


$$C_i = (C_i[1], C_i[2], \dots, C_i[n])$$
  - ◆  $C_i(a)$  is the timestamp (clock value) of event  $a$  at process  $P_i$
  - ◆  $C_i[l](a)$ , entry  $l$  of  $C_i$ , is  $P_i$ 's logical time
  - ◆  $C_i[k](a)$ , entry  $k$  of  $C_i$  (where  $k \neq i$ ), is  $P_i$ 's best guess of the logical time at  $P_k$   
 More specifically, the time of the occurrence of the last event in  $P_k$  which "happened before" the current event in  $P_i$  (based on messages received)

12

# Implementation of vector clocks

- Implementation Rules:
  - [IR1] Clock  $C_i$  must be incremented between any two successive events in process  $P_i$ :  
 $C_i[i] := C_i[i] + d \quad (d > 0, \text{ usually } d=1)$
  - [IR2] If event  $a$  is the event of sending a message  $m$  in process  $P_i$ , then message  $m$  is assigned a vector timestamp  $t_m = C_i(a)$   
When that same message  $m$  is received by a different process  $P_k$ ,  $C_k$  is updated as follows:  
 $\forall p. C_k[p] := \max(C_k[p], t_m[p] + d)$   
(usually  $d=0$  unless needed to model network delay)
- It can be shown that  $\forall i, \forall k : C_i[i] \geq C_k[i]$
- Rules for comparing timestamps can also be established so that if  $t_a < t_b$ , then  $a \rightarrow b$ 
  - Solves the problem with Lamport's clocks

# Implementation of vector clocks



- Notes:
  - Events e11, e21, and e12 updated by IR1
  - Receive e22 updated by IR1 and IR2
  - Receive e13 tells P1 about P2 and P3 (P3 clock is old, but better than nothing!)