Distributed Deadlock Detection Algorithms 3. A Diffusion Computation Based Algorithm - It is diffused through the WFG of the system - For OR request model. - Process determines if its deadlocked by initiating a diffusion computation. T messages used û ui the form of guery (i,j,k)
reply (i,j,k) > It denotes that it is initiated by a process fi & are being sent from Process fi to > Process states > Blocked = process is executing to acquire a nesounce. > Dependent set of the processes: A blocked process initiates deadlock detection by sending query messages to all the processes from whom it is waiting to receive a message. What does an active process do when receives a query or reply message? It discards it (Because it is already communicating with

6

6

When blocked process la receives query (i,j,k) message, it takes following actions:

- a) If this is I query message received by he for the deadlock detection initiated by Pi (known as engaging query), then it propagates the query to all the processes in its dependent set 2 sets a local variable num<sub>k</sub>(i) to the number of query messages sent
- b) If not an engaging query (not first), then he returns a reply message to it immediately, provided he has been continously blocked since it received the corresponding engaging query.

  Otherwise, it discards query.

wait k(i) = local boolean variable -> at process  $P_k$  denotes the fact that it has been continously blocked since it received

the last engaging query from Process Pi.

wait k(i) holds.

→ A process sends a reply message in response to an engaging query only after it has received a reply to every query message it sent out for this engaging query i.e num(i) = 0 at it.

Chandy et al.'s diffusion computation & ased deadlock Algorithm: Pseudocode fer OR request model: Initiale a diffusion computation for a blocked process Pi: send query (-a,jik) (l,i,j) to all processes Pj un the dependent set DS; of P; 3
mum; (i):= |DS; |; wait; (i):= toue; when a blocked process le receives a query (i,j,k): if this is the engaging query for process the. then send query (i, k, m) to all lm in its dependent set DSK;  $num_k(i) := |DS_k|; wait_k(i) := tsue$ else if wait (i) then send a reply (i,f,k) When a process  $P_k$  receives a refly (i, j, k)

if waitkli)
then begin  $num_{\kappa}(i) := num_{\kappa}(i) - 1;$ if  $num_{\kappa}(i) = 0$ then if i=k then declare a deadlock else send (i, k, m) to the process Pm, which sent the engaging query. above, it is assumed that only one diffusion is initiated for a process. computation

Distributed Deadlock Defection Algorithm. 4. A Global State Defection Based Algorithm. There are 3 algorithms in this part: Facts for the Algorithm. · A consistent snapshot of a distributed system can be obtained without freezing the underlying computation. · A consistent snapshot may not represent the system state at any moment in time, but if a stable property holds in the system before the snapshot collection is initiated this property will still hold in the snapshot. A). Bracha & Toneg -> & phases -> I phase - algo records a snapshot & distributed WFG Il phase - simulates the granting of requests to check for generalized checks deadlocks. Il phase is nested within I phase , so it terminates only when I phase is over B) Wang et al also has 2 phase 6 I phase: records a snapshot of the distributed II phase: static WFG recorded unthe phase I is reduced to detect any deadlocks.

Both phases occur serially. c) Kehemkalyani - Sunghal Algorithm. - has single phase - 2 types of messages Fan - in sweep Fan-out sweep invards to the outwards from an initiatos process. initiator process Sweep - gawfgmis a traversal of the WFG in which all mersages are sent in the direction of the WFG edges (an outward sweep) or all messages sent against the direction of the WFG edges (an inward sweep). - Both sweeps are done concurrently. # In outward sweep- algo records a snapshot of a distributed WFG # In mward sweep- neconded distributed wfg is reduced to determine nahether the initiator Limitation - Reduction of the WFG at a process can begun at before all the WFG edges incident at that process have been recorded. Tillictété de singelet és les désires is pieces states the meanand with process

walter to with the tree

11,0 12 L.

white !