BRAC UNIVERSITY

Quiz 3 **Department of Computer Science and Engineering** **SET F**

CSE110: Programming Language I Duration: 35 minutes Marks: 20

Name: (Please write in CAPITAL LETTERS)	ID:	Section: 30

1. Suppose you are given a list of strings. You have to create a dictionary where the key will be the elements of the list in reverse order and its corresponding value will be a list containing each character of the elements. The output must be exactly in the same form as the sample output. **You are not allowed to use reverse functions or slicing to reverse the list.**

   [Marks 10]
   [CO 3 + CO 4+ CO 6]

   Given Input1:
   ['Emma', 'Olivia', 'Amelia']
   Sample Output1:
   {'Amelia': ['A', 'm', 'e', 'l', 'i', 'a'], 'Olivia': ['O', 'l', 'i', 'v', 'i', 'a'], 'Emma': ['E', 'm', 'm', 'a']}

   Given Input2:
   ['1', '6543', '976','23']
   Sample Output2:
   {'23': ['2', '3'], '976': ['9', '7', '6'], '6543': ['6', '5', '4', '3'], '1': ['1']}

2. Illustrate the outputs of the following statements. Provide your workings on the answer script to verify your outputs. Your answer will not be accepted without the workings. All the outputs must be in the question paper.

[Marks 10]
[CO 3 + CO 4+ CO 6]

		Output
1	myList = [5, -1, 7, 2, 0, 4, 7.0, 0, 9, -5]	
2	new_list = []	
3	val1 = 1	
4	val2 = -1	
5	new_list = myList	
6	while (val1 < (19%10)):	
7	myList[val1] = val1 + 4	
8	val2 = 1	
9	while (val2 < val1):	
10	myList[val1] = new_list[val1+1] - myList[val2-1] - val1	
11	val2 = val2 + 1	
12	print(new_list[val1])	
13	val1 = val1 + 1	
14	print(new_list[2])	
15	val = (tuple(myList)[3],)	
16	print(val)	