Project Design Phase-II

Technology Stack (Architecture & Stack)

Date	31 January 3035
Team ID	SWTID-2026-8933
Project Name	Script-Controlled ACL Restrict Record Access Based on Field Value
Maximum Marks	4 Marks

Technology Stack and Application Characteristics

Script-Controlled READ ACL

1. Technology Stack

Category	Technology	Purpose
Platform	ServiceNow	Application platform used to create tables, records, and access controls
Security	Access Control List (ACL)	Controls who can read records
ACL Type	READ ACL	Restricts users from viewing unauthorized records
Scripting	JavaScript	Implements the field-based access condition
Server-Side Logic	ServiceNow ACL Script	Compares the logged-in user with the specified field value
User Identification	gs.getUserID()	Retrieves the current logged-in user's unique ID
Record Access	current.<field>	Retrieves the value of the field from the current record
Database	ServiceNow Platform Database	Stores application records and user-related data
Data Model	Custom Table	Contains the records whose access needs to be controlled
User Management	ServiceNow User (sys_user)	Provides user information used for access validation

Development Interface	ServiceNow Application Navigator	Used to configure tables, ACLs, and other application components
Testing	ServiceNow User/Role Testing	Verifies that authorized users can read records and unauthorized users are denied

2. Application Characteristics

Characteristic	Description
Application Type	Web-based enterprise application
Platform	ServiceNow
Application Purpose	Control access to records based on specific field values
Security Model	Role and record-level access control
Access Control Type	READ ACL
Access Method	Script-controlled authorization
Scripting Language	JavaScript
User Authentication	ServiceNow user authentication
Authorization	Validated by comparing the logged-in user with a record field
Data Storage	ServiceNow platform database
Data Structure	Custom application tables and fields
User Identification	Current logged-in user's unique identifier
Access Decision	Allow or deny READ access based on the configured condition
Record-Level Security	Users can access only records satisfying the defined criteria
Validation	Tested using different users and records
Security Objective	Prevent unauthorized users from viewing restricted records
Scalability	Access rules can be applied consistently across multiple records
Maintainability	Access logic can be modified through the ACL configuration
Reliability	Provides consistent automated access validation
Error Prevention	Denies access when the required field-based condition is not satisfied