

CS 224 Assignment I

Rohan Rajesh Kalbag, 20D170033

LAB

The following trip was performed
and this map was generated.



we see that the color corresponding to yellow indicates moderate signal strength, green indicates strong signal strength.

- o **Green:** corresponds to

$$-84 \text{ dB}_m \leq \text{RSRP}_{\text{green}}$$

- o **Yellow:** corresponds to

$$-96 \text{ dB}_m \leq \text{RSRP}_{\text{yellow}} < -84 \text{ dB}_m$$

- o **Red:** corresponds to

$$\text{RSRP}_{\text{red}} < -96 \text{ dB}_m$$

THEORY

Q1) for BPSK

$$SNR = \frac{(\text{Energy per symbol}) \alpha^2}{(\text{Energy in Noise signal})}$$

$$SNR = \frac{\alpha^2 (s_x^2 + s_y^2)}{(\mathbb{E}(n_x^2) + \mathbb{E}(n_y^2))}$$

for bit is 1 $\underline{s} = (A, 0)$

$$n_x, n_y \sim \mathcal{N}(0, \frac{N_0}{2})$$


$$\mathbb{E}(n_x^2) - (\mathbb{E}(n_x))^2 = \frac{N_0}{2}$$

$$\mathbb{E}(n_x^2) = \frac{N_0}{2} = \mathbb{E}(n_y^2)$$

$$SNR = \frac{\alpha^2 A^2}{\frac{N_0}{2} + \frac{N_0}{2}} = \frac{\alpha^2 A^2}{N_0}$$

is the SNR per symbol.

(Signal to Noise Ratio - SNR)



$$P(\text{error in bit}) = P(0/1) = P(1/0) \\ \text{by symmetry.}$$

$$P(\text{error in bit}) = P(1) \cdot P(0/1) + P(0) \cdot P(1/0) \\ = \frac{1}{2} \cdot P(n_x \leq -\alpha A) + \frac{1}{2} \cdot P(n_x \geq \alpha A)$$


$$\text{since } P(n_x \leq -\alpha A) = P(n_x \geq \alpha A) \\ \text{we have}$$

$$P(\text{error in bit}) = P(n_x \geq \alpha A) \\ = \frac{1}{\sigma \sqrt{2\pi}} \int_{\alpha A}^{\infty} \exp\left(-\frac{x^2}{2\sigma^2}\right) dx \\ = \frac{1}{\sqrt{2\pi}} \int_{\frac{\alpha A}{\sigma}}^{\infty} \exp\left(-\frac{x^2}{2\sigma^2}\right) dx = Q\left(\frac{\alpha A \sqrt{2}}{\sqrt{N_0}}\right)$$

$$\begin{aligned}
 P(\text{error in bit}) &= Q\left(\frac{\alpha A \sqrt{2}}{\sqrt{N_0}}\right) \\
 &= Q\left(\sqrt{2 \cdot \text{SNR}}\right)
 \end{aligned}$$

(Q2)

for a bit to be misinterpreted we require that noise is greater than $\frac{\alpha A}{\sqrt{2}}$



$P(\text{1st bit is wrong})$

$$\begin{aligned}
 &= [P(00) + P(01)] \cdot P(\infty \geq n_x \geq \frac{\alpha A}{\sqrt{2}}) \\
 &\quad + [P(10) + P(11)] \cdot P(-\infty \leq n_x \leq -\frac{\alpha A}{\sqrt{2}})
 \end{aligned}$$

due to $N(0, \frac{N_0}{2})$ is an even function

and $IP(00)$, $IP(01)$, $IP(10)$, $IP(11)$ being equal.

$$\therefore IP(\text{1st bit in wrong}) = \left(\frac{1}{4} + \frac{1}{4}\right) \cdot IP(n\chi \geq \alpha \frac{A}{\sqrt{2}}) + \left(\frac{1}{4} + \frac{1}{4}\right) IP(n\chi \geq \alpha \frac{A}{\sqrt{2}})$$

$$\begin{aligned} \therefore IP(\text{1st bit in wrong}) &= IP(n\chi \geq \alpha \frac{A}{\sqrt{2}}) \\ &= \frac{1}{\sigma \sqrt{2\pi}} \int_{\alpha \frac{A}{\sqrt{2}}}^{\infty} \exp\left(-\frac{x^2}{2\sigma^2}\right) dx \\ &= \frac{1}{\sqrt{2\pi}} \int_{\alpha \frac{A}{\sqrt{2}}}^{\infty} \exp\left(-\frac{p^2}{2}\right) dp \end{aligned}$$

$$\begin{aligned} \therefore P(\text{1st bit in wrong}) &= Q\left(\frac{\alpha A}{\sqrt{2} \cdot \sqrt{N_0}}\right) \\ &= Q(\sqrt{\text{SNR}}) \end{aligned}$$

Similarly probability of second bit in obtained in error.

$$IP' = [IP(00) + IP(10)] \cdot P(n_y \geq \alpha A / \sqrt{2}) \\ + [IP(01) + IP(11)] \cdot P(n_y \leq -\alpha A / \sqrt{2})$$

$$IP' = IP(n_y \geq \alpha A / \sqrt{2})$$

$$\text{as } IP(n_y \geq \alpha A / \sqrt{2}) = P(n_y \leq -\alpha A / \sqrt{2})$$

$$\text{and } IP(00) = IP(01) = IP(11) = IP(10)$$

$$IP' = \frac{1}{\sigma \sqrt{2\pi}} \int_{\frac{\alpha A}{\sqrt{2}}}^{\infty} \exp\left(-\frac{x^2}{2\sigma^2}\right) dx \\ = \frac{1}{\sigma \sqrt{2\pi}} \int_{\frac{\alpha A}{\sqrt{2}}}^{\infty} \exp\left(-\frac{p^2}{2}\right) dp \quad \checkmark$$

$$= Q\left(\frac{\alpha A}{\sigma \sqrt{2}}\right) = Q\left(\frac{\alpha A}{\sqrt{N_0}}\right) \\ = Q(\sqrt{SNR})$$

Yes, the two probabilities are equal

$$P(\text{1st bit is incorrect}) = P(\text{2nd bit is incorrect})$$

The value obtained for (1) was

$$Q(\sqrt{2\text{SNR}}) < Q(\sqrt{\text{SNR}})$$

as $Q(x)$ is a decreasing function of x . as

$$\sqrt{2\text{SNR}} > \sqrt{\text{SNR}} \Rightarrow Q(\sqrt{2\text{SNR}}) < Q(\sqrt{\text{SNR}})$$

$$\therefore P(\text{error in a bit for QPSK}) > P(\text{error in a bit for BPSK})$$