

Chapter 1 Fundamentals

CSCI 6470 Algorithms (Fall 2024)

Liming Cai

School of Computing UGA

August 19, 2024

Chapter 1 Fundamentals

1. Worst-case time complexity
2. The big-O notation
3. Series and recurrence relations
4. Time complexity of recursive algorithms

1. Worst-case time complexity

- ▶ **Basic operations:** arithmetic ops, logic ops, assignment, branching in high-level programming language
- Corresponding operations in assembly (machine) languages and corresponding micro-instructions

Example: $C = A + B$ is compiled into assembly code and executed with micro-instructions

1. Worst-case time complexity

- ▶ **Basic operations:** arithmetic ops, logic ops, assignment, branching in high-level programming language
 - Corresponding operations in assembly (machine) languages and corresponding micro-instructions

Example: $C = A + B$ is compiled into assembly code and executed with micro-instructions

- Concept of machine cycle

real time = the number of machine cycles needed to execute the basic operations in algorithm A

but the number of machine cycles differ across different computers and system platforms, not suitable for measuring time complexity of algorithms

1. Worst-case time complexity

- ▶ **Time (complexity)** of an algorithm A on input x is the number of **basic operations** carried out by A on x , denotes as function $t(n, x)$, where n is the **size** of x .
 - instead of the number of machine cycles required for running the basic operations.
 - however, $t(x, n)$ is input x (content)-dependent
- ▶ **The worst case time** complexity of algorithm A is function $T(n)$, such that for every $n \geq 0$,

$$\forall x, \text{ of size } n, t(n, x) \leq T(n)$$

independent of the content of input

1. Worst-case time complexity


Example 1. Find $T(n)$ for iterative INSERTION SORT algorithm

But first, what is the idea of the insertion sort?

1. Worst-case time complexity

Example 1. Find $T(n)$ for iterative INSERTION SORT algorithm


But first, what is the idea of the insertion sort?




1. Worst-case time complexity

Example 1. Find $T(n)$ for iterative INSERTION SORT algorithm

But first, what is the idea of the insertion sort?



Schematic representation of the dynamic of insertion sort:



1. Worst-case time complexity

Algorithm INSERTION SORT

1. Worst-case time complexity

Algorithm INSERTION SORT

```
Function Insertion Sort(L, n);  
1. for i = 2 to n  
2.     e = L[i];  
3.     j = i-1;  
4.     while (L[j] > e) AND (j>0)  
5.         L[j+1] = L[j];  
6.         j = j - 1;  
7.     L[j+1] = e;  
8. return
```

1. Worst-case time complexity

Algorithm INSERTION SORT

```
Function Insertion Sort(L, n);  
1. for i = 2 to n  
2.   e = L[i];  
3.   j = i-1;  
4.   while (L[j] > e) AND (j>0)  
5.     L[j+1] = L[j];  
6.     j = j - 1;  
7.   L[j+1] = e;  
8. return
```

- Count the number of basic operations:

Line 1: $2 \times n + (n - 1)$

2,3,7: $2 \times (n - 1)$

4: $2 \times t_j$ ← t_j dependent on j , overall on input x

5: $(t_j - 1)$

6: $2 \times (t_j - 1)$

Line 8: 1

1. Worst-case time complexity

- Count the number of basic operations:

$$t(n, x) = an + b + \sum_{j=1}^{n-1} c \times t_j$$

for some constants $c > 0$, a , and b

- Because t_j can only be as worst (big) as j

$$t(n, x) \leq an + b + \sum_{j=1}^{n-1} c \times j = T(n)$$

$$\begin{aligned} T(n) &= c \frac{n-1}{2} n + an + b = \frac{c}{2} n^2 + \left(a - \frac{c}{2}\right)n + b \\ &= c_1 n^2 + c_2 n + c_3 \end{aligned}$$

1. Worst-case time complexity

Additional issues

- About time used for arithmetic operations

e.g., $A + B$, where A and B are of scale $2^{1000000}$;
time needed is $c \times \frac{1000000}{64} = c_1 \times 1000000$,
the time complexity is related to the binary length of data

1. Worst-case time complexity

Additional issues

- About n , the **size** of input x , what does **size** refer to?
 - (1) size n refers to the number of data items in the input as in INSERTION SORT

Consider to sort 4 very large elements, e.g., of scale $2^{1000000}$
 $T(n) = c_1 n^2 + c_2 n + c_3$, then $T(4)$ is a small constant time,
However, this is not an accurate measure because even just
comparison of two large elements takes $c \times 1000000$ steps

1. Worst-case time complexity

(2) size n is the number of binary bits that encode the input x , denoted as $n = |x|$

then for INSERTION SORT on m elements, time is bounded by

$$\begin{aligned} &= c_1 m^2 |x| + c_2 m |x| + c_3 |x| \\ &\leq c_1 n^3 + c_2 n^2 + c_3 n = T(n) \end{aligned}$$

Why?

Exercise: given algorithm

```
Function Fibonacci (x);  
1. F[1] = 1;  
2. F[2] = 1;  
3. for i = 3 to x  
4.     L[i] = L[i-1] + L[i-2];  
5. return L[x];
```

What is $T(n)$ for Fibonacci? Is it really a linear function?

1. Worst-case time complexity

Additional issues

(3) How to find a simple upper bound for time expressions?

e.g., worst case time for INSERTION SORT

$$\begin{aligned}T(n) &= c_1 n^2 + c_2 n + c_3 \\&\leq (c_1 + c_2 + c_3) n^2 \\&= c n^2\end{aligned}$$

Exercise: find a simple upper bound for

$$T(n) = 5n^2 + 4n \log_2 n - 20n + 89$$

2. The big-O notation

Needs for a succinct notation for worst time complexity

- articulate the growth of time function
ignore constant coefficients
- asymptotic of the exact time function

e.g., intuitively $T(n) = 50n^2 + 4n + 8$ is of $O(n^2)$ because $T(n)$ does not grow faster than some function cn^2 .


2. The big-O notation

Definition Let $T(n)$ and $f(n)$ be two functions in n . If there exist two constants $c > 0$ and $n_0 \geq 0$, such that

$$T(n) \leq cf(n)$$

for all $n \geq n_0$, then $T(n)$ is said to be of the order of n^2 , denoted as

$$T(n) = O(f(n))$$



2. The big-O notation

What is the big- O for function $T(n) = 3n^2 - 20n + 100$?


2. The big-O notation

What is the big-O for function $T(n) = 3n^2 - 20n + 100$?

$$\begin{aligned} 3n^2 - 20n + 100 &\leq 3n^2 + 100 \\ &\leq 3n^2 + 100n^2 \text{ when } n \geq 1 \\ &= 103n^2 \end{aligned}$$

We have found $c = 103$ and $n_0 = 1$ such that $T(n) \leq cn^2$.

By definition, $T(n) = O(n^2)$.



2. The big-O notation

- Is there another way to show

$$T(n) = 3n^2 - 20n + 100 = O(n^2) \text{ ?}$$

- Proving big-O (by finding constants c and n_0)

(1) $3n^3 + 2n - 6 = O(?)$

(2) $3n \log_2 n + 5n + 7 \log_2 n = O(?)$

(3) $2^{2n} + 3 \cdot 2^n = O(?)$

(4) $5 \ln n + 7 \log_{10} n + 2 \log_2 n = O(?)$

2. The big-O notation

Summary: deriving big-O for iterative algorithms:

- count the worst-case total number of basic operations, and formulate $T(n)$ as an expression in n
- rule of thumb: choose $f(n)$ to be the highest-order term in $T(n)$ expression
- identify constants c and n_0 to allow

$$T(n) \leq cf(n)$$

then by big-O definition, $T(n) = O(f(n))$

Take-home exercises I(A)

1. Write/find pseudo codes for the following algorithms:
 - (1) Iterative algorithm that searches a list for a key and returns its index in the list;
 - (2) iterative **selection Sort** algorithm;
 - (3) iterative algorithm that returns the n^{th} Fibonacci number, given n ;
 - (4) iterative binary search algorithm;
2. Derive a worst-case time function $T(n)$ from each of the pseudo codes designed in 1.
3. Show the big-O for each of the derived time functions $T(n)$ in 2.

3. Series and recurrence relations

Series used to compute time complexity

- arithmetic series:

$$\sum_{k=1}^n k = 1 + 2 + \cdots + n = \frac{n}{2}(n+1) \text{ where did you see it?}$$

- geometric series:

$$\sum_{k=0}^n c^k = 1 + c + c^2 + \cdots + c^n = \frac{c^{n+1} - 1}{c - 1} \text{ where did you see it?}$$

- harmonic series:

$$\sum_{k=1}^n \frac{1}{k} = 1 + \frac{1}{2} + \cdots + \frac{1}{n} = \ln(n+1)$$

3. Series and recurrence relations

If there is a known formula for a series, use it directly

If no known formula, how to solve them?

- via combinatorics/math methods
- use **recurrence relations**

e.g., $A_n = 1 + 2 + \cdots + (n-1) + n$, then

$$A_n = \begin{cases} 1 & n = 1 \\ A_{n-1} + n & n \geq 2 \end{cases}$$

We can prove $A_n = \sum_{k=1}^n k = 1 + 2 + \cdots + n = \frac{n}{2}(n+1)$ by proving with **math induction**

- (1) it works for A_1 ; and
- (2) if it works for A_{n-1} , it also works for A_n .

3. Series and recurrence relations

- It is easy to get recurrence from series

e.g., $G_n = \sum_{k=0}^n c^k = 1 + c + c^2 + \dots + c^k$

$$G_n = \begin{cases} 1 & n = 0 \\ G_{n-1} + c^n & n \geq 1 \end{cases}$$

Recurrence helps deriving formula for G_n without even using induction

3. Series and recurrence relations

Time complexities derived from recursive algorithms often come with recurrences.

```
Function Fib(n);  
1.  if ( n = 1) OR (n = 2)  
2.      return 1;  
3.  else  
4.      return Fib(n-1) + Fib(n-1)
```

3. Series and recurrence relations

Time complexities derived from recursive algorithms often come with recurrences.

```
Function Fib(n);  
1.  if ( n = 1) OR (n = 2)  
2.      return 1;  
3.  else  
4.      return Fib(n-1) + Fib(n-1)
```

- assume $T(n)$ to be worst case time for $\text{Fib}(n)$, then

$$T(n) = \begin{cases} c_1 & n = 1, 2 \\ T(n-1) + T(n-2) + c_2 & n \geq 3 \end{cases}$$

3. Series and recurrence relations

Time complexities derived from recursive algorithms often come with recurrences.

```
Function Fib(n);  
1.  if ( n = 1) OR (n = 2)  
2.      return 1;  
3.  else  
4.      return Fib(n-1) + Fib(n-1)
```

- assume $T(n)$ to be worst case time for $\text{Fib}(n)$, then

$$T(n) = \begin{cases} c_1 & n = 1, 2 \\ T(n-1) + T(n-2) + c_2 & n \geq 3 \end{cases}$$

But does '+' take just a constant time?

4. Time complexity of recursive algorithms

(1) How to creating recursive algorithms

- An algorithm deals with input data and produces output data
- **recursive definition of data** (input or output data) may lead to **recursive algorithms**

4. Time complexity of recursive algorithms

(1) How to creating recursive algorithms

- An algorithm deals with input data and produces output data
- **recursive definition of data** (input or output data) may lead to **recursive algorithms**

e.g., a list of n elements consists of a list of $n - 1$ elements concatenated with an additional element

- this leads to the following recursive **Insertion Sort** algorithm:

Step 0: if list has single element, return it as it is;

Step 1: sort the sublist of $(n - 1)$ elements;

Step 2: insert the last element into the sorted sublist;

4. Time complexity of recursive algorithms

(1) How to creating recursive algorithms

e.g., a sorted list of n elements consists of a sorted list of $n - 1$ elements concatenated with the largest element

4. Time complexity of recursive algorithms

(1) How to creating recursive algorithms

e.g., a sorted list of n elements consists of a sorted list of $n - 1$ elements concatenated with the largest element

this leads to the following recursive **Selection Sort** algorithm:

Step 0: if list has single element, return it as it is;

Step 1: swap the maximum element with the last element;

Step 2: sort the remaining sublist of $n - 1$ elements

4. Time complexity of recursive algorithms

(2) deriving time complexity for recursive algorithms

```
function Selection-Sort(L, n);  
1. if n=1 return;  
2. k = FindMaxInd(L, n); \\ find index of the max  
3. Swap(L, k, n);        \\ swap L[k] with L[n]  
4. Selection-Sort(L, n-1);
```

$$T(n) = \begin{cases} c_1 & n = 1 \\ O(n) + c_2 + T(n-1) & n \geq 2 \end{cases}$$

where $O(n)$ is the time for function $FindMaxInd(L, n)$, i.e.,

4. Time complexity of recursive algorithms

(2) deriving time complexity for recursive algorithms

```
function Selection-Sort(L, n);  
1. if n=1 return;  
2. k = FindMaxInd(L, n); \\ find index of the max  
3. Swap(L, k, n);        \\ swap L[k] with L[n]  
4. Selection-Sort(L, n-1);
```

$$T(n) = \begin{cases} c_1 & n = 1 \\ O(n) + c_2 + T(n-1) & n \geq 2 \end{cases}$$

where $O(n)$ is the time for function $FindMaxInd(L, n)$, i.e.,

$$T(n) = \begin{cases} c_1 & n = 1 \\ c_3 n + c_2 + T(n-1) & n \geq 2 \end{cases}$$

Take-home exercises I(B)

1. Design a recursive algorithm `FindMaxInd(L, n)` that returns the index of the maximum element in the input list L of n elements.

Hint: consider a recursive definition of the input list L .

2. Design a recursive algorithm `InsertList(L, k, x)` that inserts a given element of value x into sorted list $L[1..k]$.

Hint: consider a recursive definition of the input sorted list $L[1..k]$.

3. Design a recursive **Insertion Sort** algorithm that calls the subroutine `InsertList(L, k, x)` designed in 2.
4. Derive a time complexity recurrence for each algorithm in 1, 2, and 3, respectively.

4. Time complexity of recursive algorithms

(3) Solving recurrences to get analytic form

- deriving lower and upper bounds;
- precise solution via unfolding;
- precise solution via math induction