

Rohan Nyati

500075940

R177219148

Batch-5 ( Ai & MI )

## EXPERIMENT-8

```
#include<iostream>
#include<windows.h>
#include<math.h>
#include<GL/glut.h>
using namespace std;

typedef float Matrix4 [4][4];

Matrix4 theMatrix;
static GLfloat input[8][3]=
{
    {40,40,-50},{90,40,-50},{90,90,-50},{40,90,-50},
    {30,30,0},{80,30,0},{80,80,0},{30,80,0}
};

float output[8][3];
float tx,ty,tz;
float sx,sy,sz;
float angle;

int choice,choiceRot;

void setIdentityM(Matrix4 m)
{
    for(int i=0;i<4;i++)
        for(int j=0;j<4;j++)
            m[i][j]=(i==j);
}

void translate(int tx,int ty,int tz)
```

```

{

for(int i=0;i<8;i++)
{
output[i][0]=input[i][0]+tx;
output[i][1]=input[i][1]+ty;
output[i][2]=input[i][2]+tz;
}
}
void scale(int sx,int sy,int sz)
{
    theMatrix[0][0]=sx;
    theMatrix[1][1]=sy;
    theMatrix[2][2]=sz;
}
void RotateX(float angle) //Parallel to x
{

angle = angle*3.142/180;
    theMatrix[1][1] = cos(angle);
    theMatrix[1][2] = -sin(angle);
    theMatrix[2][1] = sin(angle);
    theMatrix[2][2] = cos(angle);

}
void RotateY(float angle) //parallel to y
{

angle = angle*3.14/180;
    theMatrix[0][0] = cos(angle);
    theMatrix[0][2] = -sin(angle);
    theMatrix[2][0] = sin(angle);
    theMatrix[2][2] = cos(angle);

}
void RotateZ(float angle) //parallel to z
{

angle = angle*3.14/180;
    theMatrix[0][0] = cos(angle);
    theMatrix[0][1] = sin(angle);
    theMatrix[1][0] = -sin(angle);
    theMatrix[1][1] = cos(angle);

```

```

}

void multiplyM()
{
//We Don't require 4th row and column in scaling and rotation
//[8][3]=[8][3]*[3][3] //4th not used
for(int i=0;i<8;i++)
{
    for(int j=0;j<3;j++)
    {
        output[i][j]=0;
        for(int k=0;k<3;k++)
        {
            output[i][j]=output[i][j]+input[i][k]*theMatrix[k][j];
        }
    }
}

}

void Axes(void)
{
glColor3f (0.0, 0.0, 0.0);           // Set the color to BLACK
glBegin(GL_LINES);                  // Plotting X-Axis
glVertex2s(-1000 ,0);
glVertex2s( 1000 ,0);
glEnd();
glBegin(GL_LINES);                  // Plotting Y-Axis
glVertex2s(0 ,-1000);
glVertex2s(0 , 1000);
glEnd();
}

void draw(float a[8][3])
{

    glBegin(GL_QUADS);
    glColor3f(0.7,0.4,0.5); //behind
    glVertex3fv(a[0]);
    glVertex3fv(a[1]);
    glVertex3fv(a[2]);
    glVertex3fv(a[3]);

    glColor3f(0.8,0.2,0.4); //bottom
    glVertex3fv(a[0]);

```

```

    glVertex3fv(a[1]);
    glVertex3fv(a[5]);
    glVertex3fv(a[4]);

    glColor3f(0.3,0.6,0.7); //left
    glVertex3fv(a[0]);
    glVertex3fv(a[4]);
    glVertex3fv(a[7]);
    glVertex3fv(a[3]);

    glColor3f(0.2,0.8,0.2); //right
    glVertex3fv(a[1]);
    glVertex3fv(a[2]);
    glVertex3fv(a[6]);
    glVertex3fv(a[5]);

    glColor3f(0.7,0.7,0.2); //up
    glVertex3fv(a[2]);
    glVertex3fv(a[3]);
    glVertex3fv(a[7]);
    glVertex3fv(a[6]);

    glColor3f(1.0,0.1,0.1);
    glVertex3fv(a[4]);
    glVertex3fv(a[5]);
    glVertex3fv(a[6]);
    glVertex3fv(a[7]);

    glEnd();
}

void init()
{
    glClearColor(1.0,1.0,1.0,1.0); //set background color to white
    glOrtho(-250.0,250.0,-250.0,250.0,-250.0,250.0);
    // Set the no. of Co-ordinates along X & Y axes and their gappings
    glEnable(GL_DEPTH_TEST);
    // To Render the surfaces Properly according to their depths
}

void display()
{
    glClear(GL_COLOR_BUFFER_BIT|GL_DEPTH_BUFFER_BIT);
    Axes();

```

```

glColor3f(1.0,0.0,0.0);
draw(input);
setIdentityM(theMatrix);
switch(choice)
{
case 1:
    translate(tx,ty,tz);
    break;
case 2:
    scale(sx,sy,sz);
multiplyM();
    break;
case 3:
    switch (choiceRot) {
    case 1:
        RotateX(angle);
        break;
    case 2: RotateY(angle);
        break;
    case 3:
        RotateZ(angle);
        break;
    default:
        break;
    }
multiplyM();
    break;
}

draw(output);
glFlush();
}

int main(int argc, char** argv)
{
    glutInit(&argc,argv);
    glutInitDisplayMode(GLUT_SINGLE|GLUT_RGB|GLUT_DEPTH);
    glutInitWindowSize(500,500);
    glutInitWindowPosition(0,0);
    glutCreateWindow("3D TRANSFORMATIONS");
    init();
    cout<<"Enter your choice number:\n1.Translation\n2.Scaling\n3.Rotation\nn=>";
    cin>>choice;
    switch (choice) {

```

```

case 1:
    cout<<"\nEnter Tx,Ty &Tz: \n";
    cin>>tx>>ty>>tz;
    break;
case 2:
    cout<<"\nEnter Sx,Sy & Sz: \n";
    cin>>sx>>sy>>sz;
    break;
case 3:
    cout<<"Enter your choice for Rotation about axis:\n1.parallel to X-axis."
        <<"(y& z)\n2.parallel to Y-axis.(x& z)\n3.parallel to Z-axis."
        <<"(x& y)\n ==>";
    cin>>choiceRot;
    switch (choiceRot) {
    case 1:
        cout<<"\nEnter Rotation angle: ";
        cin>>angle;
        break;
    case 2:
        cout<<"\nEnter Rotation angle: ";
        cin>>angle;
        break;
    case 3:
        cout<<"\nEnter Rotation angle: ";
        cin>>angle;
        break;
    default:
        break;
    }
    break;
default:
    break;
}
glutDisplayFunc(display);
glutMainLoop();
return 0;
}

```

