WEEK 6

Configure RIP routing Protocol in Routers.

OBSERVATION:



step 5 - IP address 10.0.0.10 255.0.0.0
step 6 - NO shut
step 7 - Exit
step 8 - Interface se 2/0
step 9 - IP address 20.0.0.10 255.0.0.0
step 10 - Encapsulation ppp
step 11 - clock rate 64000
step 12 - NO shut

- Here for Router with FastEthernet execute only till step 9 and type NO shut.
- Only for Router to Router connection execute all steps, also execute the step 11 only for the router connection which has a clock symbol at start.
  Repeat these steps for all routers.
- Again go to Router 0 → CLI mode and type these steps:
  step 1: config T
  step 2: router rip
  step 3: Network 10.0.0.0
  step 4: Network 20.0.0.0
  step 5: Exit.
- Repeat these steps for all routers.
- At last now go to each router and type show IP route. Here the IP addresses associated with that router will be labelled as C and other IP addresses are labbelled as R.
- Lastly go to PC0 and ping a message to PC1 using ping distination IP address command.

PING OUTPUT:

Packet tracer PC command line 1.0

PC> Ping 40.0.0.1

Pinging 40.0.0.1 with 32 bytes of data:

Request timed out.

Reply from 40.0.0.1 : bytes = 32 time = 8ms TTL = 125

Reply from 40.0.0.1 : bytes = 32 time = 5ms TTL = 125

Reply from 40.0.0.1 : bytes = 32 time = 10ms TTL = 125

Ping statistics for 40.0.0.1:

Packets: Sent = 4, Recived = 3, Lost = 1 (25% loss),

Approximate round trip times in milli seconds:

Minimum = 5ms, Maximum = 10ms, Average = 7ms.

OBSERVATION:

- Routing Information protocol (rip) is a dynamic routing protocol that uses hop count as a routing metric to find the best path between source and destination. It is a distance-vector routing protocol.
- Hop count is the no of routes coming in between source and destination. The path with least hop count is selected.
- updates of the NETWORK are exchanged periodically
- updates of routing information are always broadcast.
- Full routing tables are sent in updates.
- Routers always trust routing information recived from neighbor routers.

24/7/23

TOPOLOGY:



OUTPUT:




Cisco Packet Tracer Student - C:\Users\ysrmo\OneDrive - Base PU College\Desktop\4thsem\CN\CN_LAB\lab6.pkt
File Edit Options View Tools Extensions Help
Logical
[Root]
New Cluster
Move Object
Set Tiled Background
Viewport
20.0.0.20
Se2/0
30.0.0.10
Se3/0
Router-PT
Router1
10.0.0.10
Se2/0
Fa0/0
20.0.0.10
Router0
Se3/0
30.0.0.20
40.0.0.10
Fa0/1
Router2
Fa0
PC-PT
PC0
10.0.0.1
Fa0
PC-PT
PC1
40.0.0.1
Simulation Panel
Event List
Vis. Time(sec) Last De At De Type Info
0.006 Router2 Rout... ICMP
0.007 Router1 Rout... ICMP
0.008 Router0 PC0 ICMP
12.790 -- Rout... RIPv1
12.790 -- Rout... RIPv1
Reset Simulation
Constant Delay
Captured to:
12.790 s
Play Controls
Back
Auto Capture / Play
Capture / Forward
Event List Filters - Visible Events
ACL Filter, ARP, BGP, CDP, DHCP, DHCPv6, DNS, DTP, EIGRP, EIGRPv6, FTP, H.323, HSRP, HSRPv6, HTTP, HTTPS, ICMP, ICMPv6, IPSec, ISAKMP, LACP, NDP, NETFLOW, NTP, OSPF, OSPFv6, PAgP, POP3, RADIUS, RIP, RIPng, RTP, SCCP, SMTP, SNMP, SSH, STP, SYSLOG, TACACS, TCP, TFTP, Telnet, UDP, VTP
Edit Filters
Show All/None
Time: 00:01:22.953
Power Cycle Devices PLAY CONTROLS: Back
Auto Capture / Play
Capture / Forward
Event List
Simulation
Routers
Scenario 0
New
Delete
Fire Last Statu Sourc Destinatic Type Colo Time(s Period Num Edit Delete
Successful PC0 PC1 IC... 0.000 N 0 (ed... (delete)