




# **Dynamic Memory**

# Contents

- Objectives
  - Be able to allocate and manage heap memory using the new & delete operators.
  - Be able to describe the C language memory allocation & deallocation functions.
- Contents
  - The Stack & Heap
  - New & Delete

# The Stack & Heap



3

C++ has 4 distinct regions for memory distribution:

**Stack :** This region is used for function calls' return addresses , arguments and local variables. It typically has a fixed size (1Mb on Microsoft systems)

**Heap :** This region is for dynamic allocation of memory (dynamic variables created at run time use this memory)

**Global Variables :** This is used for global & static variables defined by the programmer

**Program Code :** This region is for the program code.

# New Operator

```
1#include <iostream>
2#include <string.h>
3using namespace std;
4
5int main(int argc, char** argv)
6{
7    int* iptr;
8    iptr = new int;
9    delete iptr;
10
11    char* msg;
12    msg = new char[255];
13    strcpy(msg, "Hello world!");
14    cout << msg << endl;
15    delete [] msg;
16
17    return 0;
18 }
```

The new operator is used to allocate memory from the free store or heap. When new is called a pointer to the new memory is returned. If there is insufficient free memory to satisfy the request a null pointer is returned. New [] is used to allocate a number of objects (an array??? See later!) Memory allocated with new [] MUST be deallocated with delete [] otherwise memory leakage & possibly heap corruption may take place.

# New Operator

```
1 #include <iostream>
2 #include <new>
3 #include <string.h>
4 using namespace std;
5
6 int main(int argc, char**argv)
7 {
8     int* iptr;
9     iptr = new int;
10    delete iptr;
11
12    char* msg;
13    try
14    {
15        msg = new char[255];
16    }
17    catch (std::bad_alloc ex)
18    {
19        // memory allocation error
20    }
21    strcpy(msg, "Hello world!");
22    cout << msg << endl;
23    delete [] msg;
24
25    return 0;
26 }
```

5

This simple example on the previous slide uses the standard global operator `new`. This has been superseded by a newer version of the operator which throws an exception if memory cannot be allocated.

The newer versions of the operators are used by including the `<new>` header file.

The Standard now states that operator `new` throws an exception of type `std::bad_alloc` when it fails, rather than returning a NULL pointer.

Although compiler vendors have been sluggish in adopting this change, most C++ compilers now conform to the standard in this respect, and throw an exception of type `std::bad_alloc` when `new` fails.

# New Operator

```
1 #include <iostream>
2 #include <new>
3 #include <string.h>
4 using namespace std;
5
6 int main(int argc, char**argv)
7 {
8     int* iptr;
9     iptr = new(nothrow) int;
10    delete iptr;
11
12    char* msg;
13    msg = new(nothrow) char[255];
14    strcpy(msg, "Hello world!");
15    cout << msg << endl;
16    delete [] msg;
17
18    return 0;
19 }
```

6

Under some circumstances, throwing an exception is undesirable. For example, exception handling might have been turned off to enhance performance; on some platforms, it might not be supported at all.

The Standardization committee was aware of this and added an exception-free version of new to the Standard. The exception-free version of new returns a NULL pointer in the event of a failure, rather than throwing a `std::bad_alloc` exception. This version of new takes an additional argument of type `const std::nothrow_t&` (defined in the header `<new>`). It comes in two flavours, one for plain new and another for new[].

## Delete Operator



The delete and delete [] operators immediately de-allocate memory. The memory is returned to the freestore for re-use in future memory allocation requests. It is NOT garbage collect a-la-Java & C#. No memory compression or defragmenting is performed.

## Exercise



EXERCISE

Write a program that stores the names & ages of the delegates on this course. This information should be stored in a structure that has a string and an int member. E.g.

```
struct delegate
{
    string name;
    int age;
};
```

The structures should be stored in an array of pointers e.g.

```
delegate * students[12];
```

Each delegate will require a new of the structure. When the array is populated print out a list of all the delegates. Ensure that memory management is correct. i.e. memory is allocated & deleted correctly.