




Introduction to Linux

Day 2/10




Prepared by:

Gaurav Pokhrel

Rohan Raj Poudel



Agenda



- Installation of Linux - Ubuntu
- Familiarization with GNOME
- Terminal and Shell
- Basic commands – Part 1
- ManPages in Linux

2.1 Installation

Disable Secure Boot

Enable Virtualization

Install Oracle VM VirtualBox

Install Ubuntu in your Virtual environment

SubTopic – Kernel Space vs User Space



Privileged vs Less-Privileged mode: Unrestricted Access vs Restricted Access

System Critical Operations vs User Applications

Direct Access To Hardware vs Interaction with Kernal using SystemCall

2.2 GNU and Open Source Licensing



- GNU (GNU's not UNIX): Project (1983) that aimed to create UNIX like OS
- Promotes the idea of Open source project / free software.
- GNU's license: General-Public-License(GPL), widely used open source license
- GNU lacked kernel (initially)
- Linux developed in 1991, combined with GNU to create complete OS – GNU/Linux system
- GNOME (defaults for most Linux distros) made for desktop environment on 1997

2.2 GUI

- Linux GUI refers to the graphical user interface provided by the desktop environment running on top of the Linux kernel.
- Various desktop environments are available for Linux including GNOME, KDE, Cinnamon, etc.
- GUI typically includes a graphical shell, window manager, file manager, system settings, and other graphical elements to provide a user-friendly interface.
- GUI allows users to interact with the operating system, launch applications, manage files, customize settings, and perform other tasks using a mouse or touchpad.

2.2 GNOME

Popular Desktop Environment



Clean, Simple and Easy to use

Extensions and theming options available



Provides a complete desktop experience

System-Menu, App-Launcher, Notification-Area

2.2 GNOME




2.3 Terminal and Shell




Basic Linux Commands

1. `ls`
2. `cd`
3. `pwd`
4. `mkdir`
5. `rmdir`
6. `cp`
7. `rm`
8. `touch`
9. `mv`



Basic Linux Commands



1. ls

Command: ls

Purpose: Lists files and directories in the current directory.

Eg: ls , ls -l, ls -a, ls - - almost-all, ls -l *.pdf


1. cd

Command: cd

Purpose: Changes the current working directory.

Eg: (cd ..), (cd./Pictures/), (cd../Pictures/)

Basic Linux Commands



3. pwd

Command: pwd

Purpose: Displays the current working directory.

Eg: pwd


4. mkdir

Command: mkdir

Purpose: Creates a new directory.

Eg: mkdir folder_name

Basic Linux Commands



5. `rmdir`

Command: `rmdir`

Purpose: Removes an empty directory.

Example: `rmdir Empty_folder_name`

6. `cp`

Command: `cp`

Purpose: Copies files or directories.

Example: `cp file.txt /home/destination`

Basic Linux Commands



7. rm

Command: rm

Purpose: Removes files or directories

Example: rm file_name , rm * , rm -r dir_name

8. touch

Command: touch

Purpose: Create file/ files.

Example: touch file or touch file1 file2....


Basic Linux Commands

9 mv

Command: mv

Purpose: move or rename files

Example: mv oldname newname , mv source destination



File Permissions



Permission Characters:

- Each set of three characters consists of r (read), w (write), and x (execute) permissions.
- If the permission is granted, the corresponding character is present; if not, a '-' is used.

File Type and Permissions:

- The first character indicates the file type. Common types include - for a regular file, d for a directory, and l for a symbolic link.
- The next nine characters represent the file permissions. They are divided into three sets of three:
 - The first set represents the owner's (user's) permissions.
 - The second set represents the group's permissions.
 - The third set represents others' (everyone else's) permissions.

File Permissions

Concept of Owner , group and world:



Owner:

- The owner of a file or directory is the user who created or owns it.
- The owner has the most control over the file, with the ability to read, write, and execute it.
- The owner can also change the file's permissions, change its owner, and modify its group.

File Permissions



Concept of Owner , group and world:

Group:

- A file or directory can be assigned a group, and members of that group are granted certain permissions based on the group settings.
- Every user in Linux belongs to one or more groups.

Create group : `sudo groupadd group_name`

Add user to group: `sudo usermod -aG group_name username`

Check which groups a user belongs to : `groups username`

File Permissions

Concept of Owner , group and world:



World(others):

- In Linux, the term "world" is often used in the context of file permissions to refer to everyone else who is not the owner of a file or a member of the group associated with that file.
- The "world" permissions are the permissions that apply to all users who are not the owner or part of the group.

2.5 ManPages in Linux (Manuals)



- Manual pages provide documentation and information about various commands, utilities, system calls, libraries, and other aspects of the operating system and software.
- `man [command_name]` eg. `man ls`
- Key navigation commands within the "man" pager include:
 - Arrow Keys or "j" and "k": Scroll up and down.
 - "q": Quit the manpager and return to the command prompt.
 - "/": Search for a specific term. Enter the term and press "Enter" to search forward. Press "n" to go to the next occurrence.
- Use the "apropos" command to search for manpages related to a specific keyword.
eg. `apropos copy`

Conclusion



- Mastering these commands is fundamental for Linux navigation and file manipulation.
- Understanding the file and directory structure is crucial for effective system administration.
- Practice using these commands to build confidence and efficiency.