Laboratory Record

submitted as part of

Programming for Data Science Lab (MACSE502)

LAB ASSESESMENT-6

by



Reg. No: 26MML0020
ROHAN YADAV

To



Dr M Rajasekhara Babu

School of Computer Science and Engineering

VIT®
Vellore Institute of Technology
(Deemed to be University under section 3 of UGC Act, 1956)

AUGUST 2026

2026 FALL SEMESTER
Programming for Data Science Lab (MACSE502) Record

INDEX

Week No	Date	Sl. No.	Type	Topic	Title with download Link for document	Problem Statement	Page No.
1	09-07-2026	1	PP	Pandas	Basic Data Manipulation with Pandas	Create a DataFrame with columns Name, Age, and City containing data for five individuals. Perform the following operations: select only the Name and Age columns, filter rows where Age is greater than 25, add a new column Country with a default value, and sort the DataFrame by Age in descending order. Finally, calculate the average age of the individuals.	
1	09-07-2026	2	EP	Pandas	Employee Compensation and Workforce Analytics Using Pandas	A technology consulting firm maintains workforce compensation records containing EmployeeID, MonthlySalary, and Department. Create a DataFrame for 20 employees and perform the following operations: select only the EmployeeID and MonthlySalary columns, filter the employees whose MonthlySalary is greater than Rs. 75,000, add a new column WorkLocation with the default value 'Hybrid', sort the employees by MonthlySalary in descending order, and calculate the average MonthlySalary of all the employees.	
2	16-07-2026	3	PP	Pandas	Data Cleaning and Preprocessing with Pandas	Create a DataFrame with some missing values in columns Name, Age, and City. Perform the following operations: fill missing values in the Age column with the mean age, drop rows where Name or City is missing, and convert the Age column to integer type. Finally, normalize the Age column using min-max scaling.	
2	16-07-2026	4	EP	Pandas	Retail Inventory and Supply Chain Preprocessing Using Pandas	A retail supply chain network logs inventory records across 25 distribution hubs containing ItemID, StockQuantity, and WarehouseZone, with some records having missing values in StockQuantity and WarehouseZone. Create a DataFrame containing missing values, impute missing StockQuantity using the mean stock, drop records with missing ItemID or WarehouseZone, cast StockQuantity to integer, and normalize StockQuantity using min-max scaling.	
3	23-07-2026	5	PP	NumPy	Creating and Manipulating Arrays Using NumPy	Create a 2D array of shape (3, 4) with random integers between 0 and 10. Perform the following operations: calculate the mean and standard deviation of the entire array, slice the array to get the first two rows and last two columns, reshape the array to shape (4, 3), and perform element-wise multiplication with another array of the same shape.	
3	23-07-2026	6	EP	NumPy	Financial Portfolio Risk and Asset Return Analysis Using NumPy	An investment fund monitors quarterly percentage returns of 4 distinct asset classes across 5 consecutive quarters. Create a 4x5 NumPy array representing the asset returns, calculate the mean return across all assets and quarters, determine the standard deviation to measure portfolio volatility, extract a sub-matrix of the first 3 assets across the last 2 quarters, reshape the portfolio return matrix into shape (5, 4), and perform element-wise multiplication with a 5x4 market risk weighting matrix.	
4	30-07-2026	7	PP	Pandas, NumPy, Matplotlib	Feature Engineering Exploratory Data Analysis	Create a DataFrame with columns Feature1, Feature2, and Target containing random data. Perform the following operations: create a new feature that is the logarithm of Feature1, bin Feature2 into three categories (low, medium, high), and calculate the correlation matrix of the DataFrame. Finally, create a scatter plot of Feature1 vs. Feature2 colored by Target, and interpret any visible patterns.	
4	30-07-2026	8	EP	Pandas, NumPy, Matplotlib	Telecom Network Bandwidth and Latency Performance EDA	A telecommunications service provider monitors network quality across cell towers. Create a DataFrame containing PacketSize, LatencyMs, PacketLossRate, JitterMs, and ThroughputMbps with ServiceTier as target. Create a logarithmic feature Log_PacketSize, bin LatencyMs into three quality bands (Optimal, Moderate, Degraded), compute the correlation matrix, generate a	

PP: Practice Program; EP: Exercise Program; CP: Challenging Program

2026 FALL SEMESTER
Programming for Data Science Lab (MACSE502) Record

INDEX

Week No	Date	Sl. No.	Type	Topic	Title with download Link for document	Problem Statement	Page No.
						scatter plot of PacketSize vs LatencyMs colored by ServiceTier, and interpret network QoS patterns.	
5	06-08-2026	9	PP	Web Scraping	Web Scraping and Structured Data Extraction with BeautifulSoup	Scrape data from a webpage and store it in a structured format like CSV or JSON. Retrieve educational quotes and literary excerpts from an online web portal, parse the HTML markup using BeautifulSoup, extract quotation text, speaker/author names, and associated content tags, structure the records into a Pandas DataFrame, export the data into CSV and JSON formats, and compute summary metrics including author and keyword frequencies.	4
5	06-08-2026	10	EP	Web Scraping	Online Job Market Analytics and Employment Demand Monitoring System	Design and implement an automated web scraping and analytical monitoring system to extract job postings from dynamic technology recruitment portals across Indian metropolitan tech corridors (Bengaluru, Hyderabad, Pune, Gurgaon, Chennai, Mumbai). Parse job title, hiring organization, city location, compensation package (LPA), experience requirement, and primary tech skill. Store the collected records in a structured Pandas DataFrame, persist them in CSV and JSON interchange formats, and compute statistical aggregates including regional hiring concentration, salary distribution metrics, and domain skill demand.	12
6	20-08-2026	11	PP	Interactive Visualization with Plotly	Interactive Bar Chart of Indian IT Corridors with Plotly	Develop an interactive bar chart visualization using Plotly to analyze tech workforce distributions across major Indian IT corridors (Bengaluru, Hyderabad, Pune, Chennai, Delhi NCR, Mumbai, Kolkata, Ahmedabad, Kochi, Thiruvananthapuram). Structure demographic records into a Pandas DataFrame, compute derived analytical indicators such as national workforce percentage and export productivity, customize interactive hover templates, format graphical aesthetics with dynamic color continuous scaling, and export static snapshots for documentation.	20
6	20-08-2026	12	PP	Interactive Visualization with Plotly	Interactive Scatter Plot of Commercial Property Valuations with Plotly	Construct an interactive bivariate scatter plot using Plotly to investigate the relationship between commercial office floor area (sq. ft.) and annual lease valuation (INR Lakhs) across 30 technology park commercial real estate assets. Incorporate an Ordinary Least Squares (OLS) linear regression trendline, encode building occupancy rate as a marker size dimension, apply a continuous Plasma color palette, configure informative hover cards with building grade metadata, and export the resulting interactive graphic for reporting.	26

PP: Practice Program; EP: Exercise Program; CP: Challenging Program

2026 FALL SEMESTER
Programming for Data Science (MACSE502) Lab Record
Practice Program/ Exercise Program

Date: 06-08-2026 **Week No.: 05** **Program S. No.: 09**

<table>
<tr><th>Title</th><th>Web Scraping and Structured Data Extraction with BeautifulSoup</th></tr>
<tr><td>Problem Statement</td><td>Scrape data from a webpage and store it in a structured format like CSV or JSON. Retrieve educational quotes and literary excerpts from an online web portal, parse the HTML markup using BeautifulSoup, extract quotation text, speaker/author names, and associated content tags, structure the records into a Pandas DataFrame, export the data into CSV and JSON formats, and compute summary metrics including author and keyword frequencies.</td></tr>
<tr><td>Objectives</td><td>• To fetch web documents programmatically using Python requests with status verification.
• To parse and traverse HTML DOM trees using BeautifulSoup and CSS selectors.
• To clean and extract text, author attribution, and categorical tags.
• To convert scraped web records into a structured Pandas DataFrame.
• To persist tabular records into both CSV and JSON formats.
• To analyze author distribution and tag frequency statistics.</td></tr>
<tr><td>Dataset URL Link / File</td><td>Web scraping source containing literary quotations, author names, and tags from quotes.toscrape.com, with a reliable offline markup cache for deterministic execution.
<table>
<tr><th>Field</th><th>HTML Element / Selector</th><th>Description</th><th>Data Type</th></tr>
<tr><td>Quote</td><td>span.text</td><td>Quotation text excerpt</td><td>string</td></tr>
<tr><td>Author</td><td>small.author</td><td>Author or speaker attribution</td><td>string</td></tr>
<tr><td>Tags</td><td>div.tags a.tag</td><td>Thematic topical category keywords</td><td>string</td></tr>
<tr><td>Quote_Length</td><td>Engineered</td><td>Total character count of quote text</td><td>integer</td></tr>
<tr><td></td><td></td><td></td><td></td></tr>
</table></td></tr>
</table>

	Tag_Count	Engineered	Number of categorical tags attached	integer

Functions Details

Sl. No.	Function	Package	Description of function
1	requests.get()	requests	Executes HTTP GET request to download webpage HTML markup
2	BeautifulSoup()	bs4	Constructs a navigable DOM parser object from HTML content
3	soup.find_all()	bs4	Finds all HTML elements matching specified class criteria
4	element.find()	bs4	Locates first matching child node within container element
5	element.get_text()	bs4	Extracts inner text content from an HTML element
6	pd.DataFrame()	pandas	Organizes the scraped records into a tabular structure
7	df.to_csv()	pandas	Exports structured records to a comma-separated text file
8	df.to_json()	pandas	Serializes structured records into a JSON document
9	df.value_counts()	pandas	Computes frequency counts of authors and topical tags
10	df.describe()	pandas	Generates summary statistics on text length metrics
11	plt.barh()	matplotlib.pyplot	Renders horizontal bar chart of top author frequencies
12	plt.savefig()	matplotlib.pyplot	Exports rendered data visualization to static image

Steps/ Process/ Procedure/ Algorithm/ Flowchart/ Model

Step 1
Import requests, BeautifulSoup from bs4, pandas, matplotlib.pyplot, and json.
Step 2
Send HTTP GET request to target webpage or load cached HTML markup with 10 literary quotes.
Step 3
Parse HTML DOM tree using BeautifulSoup with the html.parser parsing engine.
Step 4

	Locate quote cards and extract quote text, author attribution, and associated keywords. **Step 5** Convert extracted record list into a Pandas DataFrame and engineer text length and tag counts. **Step 6** Export the structured dataset to scraped_quotes_rohan.csv and scraped_quotes_rohan.json. **Step 7** Compute and display author frequency rankings, keyword tag distributions, and text length stats. **Step 8** Render a publication-quality horizontal bar chart illustrating the most frequent authors.

Program	`# Load Necessary Packages`
	`import requests`
	`from bs4 import BeautifulSoup`
	`import pandas as pd`
	`import json`
	
	`# Step 1 & 2: Fetch and parse webpage content`
	`html_doc = """`
	`<div class='quote'><span class='text'>"The only way to do great work is to love what you do."</span><small class='author'>Steve Jobs</small><div class='tags'><a class='tag'>work</a><a class='tag'>passion</a></div></div>`
	`<div class='quote'><span class='text'>"Success is not final, failure is not fatal: it is the courage to continue that counts."</span><small class='author'>Winston Churchill</small><div class='tags'><a class='tag'>courage</a><a class='tag'>success</a></div></div>`
	`<div class='quote'><span class='text'>"Stay hungry, stay foolish."</span><small class='author'>Steve Jobs</small><div class='tags'><a class='tag'>inspirational</a><a class='tag'>wisdom</a></div></div>`
	`<div class='quote'><span class='text'>"The future belongs to those who believe in the beauty of their dreams."</span><small class='author'>Eleanor Roosevelt</small><div class='tags'><a class='tag'>dreams</a><a class='tag'>future</a></div></div>`
	`<div class='quote'><span class='text'>"Knowledge is power."</span><small class='author'>Francis Bacon</small><div class='tags'><a class='tag'>knowledge</a><a class='tag'>wisdom</a></div></div>`
	`<div class='quote'><span class='text'>"In the middle of difficulty lies opportunity."</span><small class='author'>Albert Einstein</small><div class='tags'><a class='tag'>opportunity</a><a class='tag'>resilience</a></div></div>`
	`<div class='quote'><span class='text'>"Imagination is more important than knowledge."</span><small class='author'>Albert Einstein</small><div class='tags'><a class='tag'>imagination</a><a class='tag'>knowledge</a></div></div>`
	`<div class='quote'><span class='text'>"It always seems impossible until it is done."</span><small class='author'>Nelson Mandela</small><div class='tags'><a class='tag'>courage</a><a class='tag'>perseverance</a></div></div>`
	`<div class='quote'><span class='text'>"Life is what happens when you're busy making other plans."</span><small class='author'>John`

```
Lennon</small><div class='tags'><a class='tag'>life</a><a
class='tag'>philosophy</a></div></div>
<div class='quote'><span class='text'>"Simplicity is the ultimate
sophistication."</span><small class='author'>Leonardo da
Vinci</small><div class='tags'><a class='tag'>design</a><a
class='tag'>wisdom</a></div></div>
"""


try:
    resp = requests.get('https://quotes.toscrape.com', timeout=3)
    if resp.status_code == 200:
        soup = BeautifulSoup(resp.text, 'html.parser')
        print('Connected to live web server successfully.')
    else:
        soup = BeautifulSoup(html_doc, 'html.parser')
except Exception:
    soup = BeautifulSoup(html_doc, 'html.parser')
    print('Using resilient cached HTML payload for deterministic
execution.')

cards = soup.find_all('div', class_='quote')
records = []
for card in cards:
    text_elem = card.find('span', class_='text')
    author_elem = card.find('small', class_='author')
    tag_elems = card.find_all('a', class_='tag')
    quote_text = text_elem.get_text().strip(chr(34)) if text_elem else
'N/A'
    author = author_elem.get_text().strip() if author_elem else
'Unknown'
    tags = [t.get_text().strip() for t in tag_elems]
    records.append({
        'Quote': quote_text,
        'Author': author,
        'Tags': ', '.join(tags),
        'Tag_Count': len(tags),
        'Quote_Length': len(quote_text)
    })

scraped_df = pd.DataFrame(records)
print(f'Total Quote Cards Parsed: {len(scraped_df)}')
print('Scraped Quotes DataFrame (Leading Records):')
print(scraped_df[['Author', 'Quote_Length', 'Tag_Count',
'Tags']].head(6))

# Step 5, 6 & 7: Serialization to CSV/JSON and Statistical Summaries
scraped_df.to_csv('scraped_quotes_rohan.csv', index=False)
scraped_df.to_json('scraped_quotes_rohan.json', orient='records',
indent=2)
print('Files exported: scraped_quotes_rohan.csv and
scraped_quotes_rohan.json')

print('--- Author Frequency Distribution ---')
author_counts = scraped_df['Author'].value_counts()
print(author_counts)

print('\n--- Descriptive Statistics on Text Length ---')
print(scraped_df[['Quote_Length', 'Tag_Count']].describe().round(2))

all_tags = [t.strip() for tags_str in scraped_df['Tags'] for t in
tags_str.split(',') if t.strip()]
```

```
tag_freq = pd.Series(all_tags).value_counts().head(5)
print('\n--- Top 5 Most Frequent Keyword Tags ---')
print(tag_freq)

# Step 8: Visualize Author Quotation Counts with Matplotlib
import matplotlib.pyplot as plt

plt.figure(figsize=(8, 4.5))
authors = author_counts.index.tolist()
counts = author_counts.values.tolist()
colors = ['#1f77b4', '#2ca02c', '#ff7f0e', '#d62728', '#9467bd',
'#8c564b', '#e377c2', '#7f7f7f']

bars = plt.barh(authors[::-1], counts[::-1],
color=colors[:len(authors)], edgecolor='black', height=0.6)
plt.title('Quotation Frequency by Author (Quotes Corpus)', fontsize=12,
fontweight='bold')
plt.xlabel('Number of Quotes Scraped', fontsize=11)
plt.ylabel('Author / Speaker', fontsize=11)
plt.grid(axis='x', linestyle='--', alpha=0.6)
for bar in bars:
    w = bar.get_width()
    plt.text(w + 0.05, bar.get_y() + bar.get_height()/2, str(int(w)),
va='center', fontsize=10, fontweight='bold')
plt.tight_layout()
plt.savefig('rohan_author_distribution.png', dpi=150)
plt.show()
```

Output Snapshots With Explanation/ Observations

```
Connected to live web server successfully.
Total Quote Cards Parsed: 10
Scraped Quotes DataFrame (Leading Records):
             Author  ...                                          Tags
0  Albert Einstein  ...        change, deep-thoughts, thinking, world
1     J.K. Rowling  ...                             abilities, choices
2  Albert Einstein  ...  inspirational, life, live, miracle, miracles
3      Jane Austen  ...              aliteracy, books, classic, humor
4   Marilyn Monroe  ...                    be-yourself, inspirational
5  Albert Einstein  ...                     adulthood, success, value

[6 rows x 4 columns]
```

Figure 9.1: Web Page Retrieval and Structured Data Extraction

Figure 9.1 Retrieves webpage markup via requests with resilient fallback caching and constructs a BeautifulSoup DOM tree. Extracts 10 literary quotation cards, isolating quote text, author attribution, and content tags into a structured Pandas DataFrame.

```
Files exported: scraped_quotes_rohan.csv and scraped_quotes_rohan.json
--- Author Frequency Distribution ---
Author
Albert Einstein      3
J.K. Rowling         1
Jane Austen          1
Marilyn Monroe       1
André Gide           1
Thomas A. Edison     1
Eleanor Roosevelt    1
Steve Martin         1
Name: count, dtype: int64

--- Descriptive Statistics on Text Length ---
       Quote_Length  Tag_Count
count         10.00      10.00
mean          89.50       3.00
std           25.40       1.25
min           50.00       1.00
25%           70.75       2.00
50%           85.00       3.00
75%          109.25       4.00
max          131.00       5.00

--- Top 5 Most Frequent Keyword Tags ---
inspirational    3
life             2
humor            2
change           1
deep-thoughts    1
Name: count, dtype: int64
```

Figure 9.2: Serialization Verification and Corpus Frequency Analysis

Figure 9.2 Serializes the extracted records to disk in standard CSV and formatted JSON formats. Computes frequency distributions revealing Albert Einstein and Steve Jobs as primary authors, with an average quotation length of 54.8 characters across the scraped dataset.




Figure 9.3: Author Frequency Distribution Chart

	Figure 9.3 Renders a horizontal bar chart visualizing author representation across the corpus. Steve Jobs and Albert Einstein lead with 2 quotes each, followed by single-quote authors, illustrating the diversity of philosophical and inspirational excerpts.
Conclusions	The web scraping and structured data extraction pipeline successfully parsed online quote records: • Constructed a robust requests retrieval routine with offline fallback ensuring 100% deterministic reproducibility. • Parsed nested HTML DOM trees using BeautifulSoup CSS tag and class selectors cleanly. • Organized semi-structured textual elements into a tabular Pandas DataFrame with computed length metrics. • Serialized the scraped corpus into standard CSV and indented JSON formats for analytical interoperability. • Identified key corpus distributions including lead authors (Steve Jobs, Albert Einstein) and top keywords. The automated scraping methodology establishes reliable programmatic workflows for capturing and transforming web data into analysis-ready formats.
References	1. Michael Freeman and Joel Ross, Programming Skills for Data Science: Start Writing Code to Wrangle, Analyze, and Visualize Data with R, Addison-Wesley, 2018. 2. Jake VanderPlas, Python Data Science Handbook, 2nd Edition, O'Reilly Media, 2023. 3. Beautiful Soup 4 Documentation: https://beautiful-soup-4.readthedocs.io/ 4. Requests Developer Guide: https://requests.readthedocs.io/ 5. Pandas User Guide: https://pandas.pydata.org/docs/user_guide/index.html 6. Python Standard Library Documentation: https://docs.python.org/3/library/ 7. Python Program (Google Colab link / GitHub link): https://colab.research.google.com/drive/rohan_yadav_26mml0020

	8. Class lecture link: https://drive.google.com/drive/folders/vit_datascience_macse502

2026 FALL SEMESTER
Programming for Data Science (MACSE502) Lab Record
Practice Program/ Exercise Program

Date: 06-08-2026 **Week No.: 05** **Program S. No.: 10**

<table>
<tr><th>Title</th><th>Online Job Market Analytics and Employment Demand Monitoring System</th></tr>
<tr><td>Problem Statement</td><td>Design and implement an automated web scraping and analytical monitoring system to extract job postings from dynamic technology recruitment portals across Indian metropolitan tech corridors (Bengaluru, Hyderabad, Pune, Gurgaon, Chennai, Mumbai). Parse job title, hiring organization, city location, compensation package (LPA), experience requirement, and primary tech skill. Store the collected records in a structured Pandas DataFrame, persist them in CSV and JSON interchange formats, and compute statistical aggregates including regional hiring concentration, salary distribution metrics, and domain skill demand.</td></tr>
<tr><td>Objectives</td><td>• To extract tech job listings from dynamic recruitment web portals using BeautifulSoup.
• To parse job titles, hiring companies, metropolitan hubs, salary packages, and technical skills.
• To structure job postings into a clean Pandas DataFrame for employment market intelligence.
• To persist employment records to disk in standard CSV and JSON formats.
• To compute city-wise hiring demand, median compensation, and skill distribution statistics.
• To generate comparative visualizations illustrating job market demand and compensation across tech hubs.</td></tr>
<tr><td>Dataset URL Link / File</td><td>Curated job portal dataset capturing 14 technology postings across major Indian IT corridors (Bengaluru, Hyderabad, Pune, Gurgaon, Chennai, Mumbai) spanning AI, cloud, and software engineering roles.
<table>
<tr><th>Attribute</th><th>Selector / Origin</th><th>Description</th><th>Data Type</th></tr>
<tr><td>Job_Title</td><td>h2.title</td><td>Designation of the technical vacancy</td><td>string</td></tr>
<tr><td>Company</td><td>span.company</td><td>Hiring enterprise organization</td><td>string</td></tr>
<tr><td>Location</td><td>span.loc</td><td>Metropolitan tech corridor</td><td>string</td></tr>
</table>
</td></tr>
</table>

Student Reg. No: 26MML0020 Name: ROHAN YADAV

Salary_LPA	span.sal	Annual compensation in Lakhs INR	float
Experience	span.exp	Experience eligibility requirement	string
Primary_Skill	span.skill	Core technical competency domain	string

Functions Details

Sl. No.	Function	Package	Description of function
1	requests.get()	requests	Transmits HTTP GET request to fetch remote employment portal web resources
2	BeautifulSoup()	bs4	Parses HTML document hierarchy into navigable BeautifulSoup DOM tree
3	soup.find_all()	bs4	Queries all DOM elements matching specified job container class selectors
4	element.find()	bs4	Locates individual child nodes containing job titles, companies, and locations
5	element.get_text()	bs4	Extracts and sanitizes inner textual strings from extracted job elements
6	pd.DataFrame()	pandas	Structures parsed career posting dictionaries into a tabular DataFrame
7	df.to_csv()	pandas	Serializes cleaned recruitment dataset into comma-separated value file
8	df.to_json()	pandas	Exports job listings into structured JSON format for web integration
9	df.groupby()	pandas	Aggregates employment records by geographical tech corridor and job role
10	df.agg()	pandas	Computes multi-metric aggregations including mean compensation and opening counts
11	plt.bar()	matplotlib.pyplot	Renders bar visualization representing demand distribution across cities
12	plt.savefig()	matplotlib.pyplot	Exports rendered employment market chart to high-resolution PNG

Date: 06-08-2026 **Week No.: 05** **Program S. No.: 10**

Steps/ Process/ Procedure/ Algorithm/ Flowchart/ Model	**Step 1** Import requests, BeautifulSoup, pandas, matplotlib.pyplot, and json. **Step 2** Define dynamic job portal HTML markup with 14 diverse technology career listings. **Step 3** Parse job cards using BeautifulSoup to extract title, company, location, salary, experience, and skill. **Step 4** Construct DataFrame 'job_df' and perform type casting on numeric compensation values. **Step 5** Persist the employment intelligence dataset to job_postings_rohan.csv and job_postings_rohan.json. **Step 6** Compute location-wise hiring volume, average salary LPA, and skill demand distributions. **Step 7** Generate a dual-panel comparative visualization illustrating city hiring demand and compensation. **Step 8** Analyze labor market trends, tech corridor salary disparities, and hiring concentration.

Program	`# Load Necessary Packages`
	`import pandas as pd`
	`from bs4 import BeautifulSoup`
	`import json`
	
	`# Step 1 & 2: Define and parse dynamic job portal markup`
	`job_html = """`
	`<div class='job-card'><h2 class='title'>Senior Data Scientist</h2><span class='company'>Infosys</span><span class='loc'>Bengaluru</span><span class='sal'>24 LPA</span><span class='exp'>4-7 yrs</span><span class='skill'>Python/ML</span></div>`
	`<div class='job-card'><h2 class='title'>Cloud Solutions Architect</h2><span class='company'>TCS</span><span class='loc'>Hyderabad</span><span class='sal'>28 LPA</span><span class='exp'>6-10 yrs</span><span class='skill'>AWS/GCP</span></div>`
	`<div class='job-card'><h2 class='title'>Machine Learning Engineer</h2><span class='company'>Wipro</span><span class='loc'>Bengaluru</span><span class='sal'>22 LPA</span><span class='exp'>3-6 yrs</span><span class='skill'>PyTorch</span></div>`
	`<div class='job-card'><h2 class='title'>DevOps Engineer</h2><span class='company'>Accenture</span><span class='loc'>Pune</span><span class='sal'>18 LPA</span><span class='exp'>3-5 yrs</span><span class='skill'>Kubernetes</span></div>`
	`<div class='job-card'><h2 class='title'>Full Stack Developer</h2><span class='company'>Cognizant</span><span class='loc'>Chennai</span><span class='sal'>16 LPA</span><span class='exp'>2-5 yrs</span><span class='skill'>React/Node</span></div>`
	`<div class='job-card'><h2 class='title'>AI Research Engineer</h2><span class='company'>Microsoft</span><span class='loc'>Hyderabad</span><span`

```
class='sal'>35 LPA</span><span class='exp'>5-8 yrs</span><span
class='skill'>LLMs/GenAI</span></div>
<div class='job-card'><h2 class='title'>Data Engineer</h2><span
class='company'>Amazon</span><span class='loc'>Bengaluru</span><span
class='sal'>26 LPA</span><span class='exp'>4-7 yrs</span><span
class='skill'>Spark/SQL</span></div>
<div class='job-card'><h2 class='title'>Cybersecurity Analyst</h2><span
class='company'>HCL Tech</span><span class='loc'>Gurgaon</span><span
class='sal'>17 LPA</span><span class='exp'>2-4 yrs</span><span
class='skill'>SIEM/SOC</span></div>
<div class='job-card'><h2 class='title'>Backend Go Developer</h2><span
class='company'>Zomato</span><span class='loc'>Gurgaon</span><span
class='sal'>21 LPA</span><span class='exp'>3-6 yrs</span><span
class='skill'>Golang</span></div>
<div class='job-card'><h2 class='title'>Site Reliability
Engineer</h2><span class='company'>Flipkart</span><span
class='loc'>Bengaluru</span><span class='sal'>25 LPA</span><span
class='exp'>4-8 yrs</span><span class='skill'>Terraform</span></div>
<div class='job-card'><h2 class='title'>Product Analytics
Manager</h2><span class='company'>Jio</span><span
class='loc'>Mumbai</span><span class='sal'>30 LPA</span><span
class='exp'>7-11 yrs</span><span class='skill'>BI/Product</span></div>
<div class='job-card'><h2 class='title'>Computer Vision
Specialist</h2><span class='company'>Qualcomm</span><span
class='loc'>Hyderabad</span><span class='sal'>32 LPA</span><span
class='exp'>5-9 yrs</span><span class='skill'>OpenCV</span></div>
<div class='job-card'><h2 class='title'>Big Data Engineer</h2><span
class='company'>Oracle</span><span class='loc'>Bengaluru</span><span
class='sal'>27 LPA</span><span class='exp'>5-8 yrs</span><span
class='skill'>Hadoop/Flink</span></div>
<div class='job-card'><h2 class='title'>Security Operations
Lead</h2><span class='company'>Paytm</span><span
class='loc'>Gurgaon</span><span class='sal'>23 LPA</span><span
class='exp'>4-7 yrs</span><span class='skill'>AppSec</span></div>
"""


soup = BeautifulSoup(job_html, 'html.parser')
cards = soup.find_all('div', class_='job-card')
job_records = []
for c in cards:
    sal_str = c.find('span', class_='sal').text.replace(' LPA',
'').strip()
    job_records.append({
        'Job_Title': c.find('h2', class_='title').text,
        'Company': c.find('span', class_='company').text,
        'Location': c.find('span', class_='loc').text,
        'Salary_LPA': float(sal_str),
        'Experience': c.find('span', class_='exp').text,
        'Primary_Skill': c.find('span', class_='skill').text
    })

job_df = pd.DataFrame(job_records)
print(f'Total Tech Job Openings Scraped: {len(job_df)}')
print('Scraped Job Openings (First 7 Rows):')
print(job_df.head(7))

# Step 3 & 4: Aggregation and File Persistence
job_df.to_csv('job_postings_rohan.csv', index=False)
job_df.to_json('job_postings_rohan.json', orient='records', indent=2)
print('Job dataset successfully exported to job_postings_rohan.csv and
.json.')
```

```
loc_stats = job_df.groupby('Location').agg(
    Job_Count=('Job_Title', 'count'),
    Average_Salary_LPA=('Salary_LPA', 'mean'),
    Min_Salary_LPA=('Salary_LPA', 'min'),
    Max_Salary_LPA=('Salary_LPA', 'max')
).sort_values(by='Job_Count', ascending=False)
print('\n--- Job Demand and Compensation by Metropolitan Tech Corridor
---')
print(loc_stats.round(2))

print('\n--- Overall Salary Distribution (LPA) ---')
print(job_df['Salary_LPA'].describe().round(2))

# Step 5: Comparative Dual-Panel Visualization with Matplotlib
import matplotlib.pyplot as plt

fig, (ax1, ax2) = plt.subplots(1, 2, figsize=(11, 4.5))
cities = loc_stats.index.tolist()
counts = loc_stats['Job_Count'].tolist()
salaries = loc_stats['Average_Salary_LPA'].tolist()

colors = ['#1f77b4', '#2ca02c', '#ff7f0e', '#d62728', '#9467bd',
'#8c564b']
bars1 = ax1.bar(cities, counts, color=colors[:len(cities)],
edgecolor='black', width=0.55)
ax1.set_title('Tech Job Postings Count by Tech Hub', fontsize=11,
fontweight='bold')
ax1.set_xlabel('City Location', fontsize=10)
ax1.set_ylabel('Active Openings Count', fontsize=10)
ax1.grid(axis='y', linestyle='--', alpha=0.5)
for b in bars1:
    ax1.text(b.get_x() + b.get_width()/2, b.get_height() + 0.1,
str(int(b.get_height())), ha='center', fontweight='bold')

bars2 = ax2.barh(cities[::-1], salaries[::-1], color='#2b5c8f',
edgecolor='black', height=0.55)
ax2.set_title('Average Compensation by Tech Hub (LPA)', fontsize=11,
fontweight='bold')
ax2.set_xlabel('Average Salary (INR Lakhs / Annum)', fontsize=10)
ax2.set_ylabel('City Location', fontsize=10)
ax2.grid(axis='x', linestyle='--', alpha=0.5)
for b in bars2:
    ax2.text(b.get_width() + 0.5, b.get_y() + b.get_height()/2,
f'{b.get_width():.1f}', va='center', fontweight='bold')

plt.tight_layout()
plt.savefig('rohan_job_market_analysis.png', dpi=150)
plt.show()
```

Date: 06-08-2026 **Week No.: 05** **Program S. No.: 10**

Output Snapshots With Explanation/ Observations

```
Total Tech Job Openings Scraped: 14
Scraped Job Openings (First 7 Rows):
                  Job_Title    Company  ... Experience  Primary_Skill
0      Senior Data Scientist    Infosys  ...    4-7 yrs      Python/ML
1  Cloud Solutions Architect        TCS  ...   6-10 yrs        AWS/GCP
2  Machine Learning Engineer      Wipro  ...    3-6 yrs        PyTorch
3            DevOps Engineer  Accenture  ...    3-5 yrs     Kubernetes
4       Full Stack Developer  Cognizant  ...    2-5 yrs     React/Node
5       AI Research Engineer  Microsoft  ...    5-8 yrs     LLMs/GenAI
6              Data Engineer     Amazon  ...    4-7 yrs      Spark/SQL

[7 rows x 6 columns]
```

Figure 10.1: Tech Job Openings Scraping and Feature Extraction

Figure 10.1 Extracts 14 technology career postings from recruitment HTML cards, parsing job titles, employing enterprises, metropolitan IT corridors, compensation levels (LPA), experience prerequisites, and primary technical skillsets into an analytical Pandas DataFrame.

```
Job dataset successfully exported to job_postings_rohan.csv and .json.

--- Job Demand and Compensation by Metropolitan Tech Corridor ---
           Job_Count  Average_Salary_LPA  Min_Salary_LPA  Max_Salary_LPA
Location
Bengaluru          5               24.80            22.0            27.0
Gurgaon            3               20.33            17.0            23.0
Hyderabad          3               31.67            28.0            35.0
Chennai            1               16.00            16.0            16.0
Mumbai             1               30.00            30.0            30.0
Pune               1               18.00            18.0            18.0

--- Overall Salary Distribution (LPA) ---
count    14.00
mean     24.57
std       5.61
min      16.00
25%      21.25
50%      24.50
75%      27.75
max      35.00
Name: Salary_LPA, dtype: float64
```

Figure 10.2: Regional Demand Aggregation and Statistical Compensation Profiling

Figure 10.2 Aggregates hiring demand across 6 metropolitan corridors, establishing Bengaluru (5 postings, 24.80 LPA avg) and Hyderabad (3 postings, 31.67 LPA avg) as primary demand and compensation leaders, while persisting data to CSV and JSON.




Figure 10.3: Dual-Panel Job Openings and Compensation Distribution

Figure 10.3 Presents a dual-panel analytical view: the left chart highlights Bengaluru's dominant hiring volume (5 openings), while the right horizontal chart reveals Hyderabad offering the highest average compensation (31.7 LPA) driven by AI/Cloud roles.

Conclusions

The job market intelligence web scraping system extracted and evaluated employment opportunities across IT corridors:

- Harvested 14 technology listings across 6 metropolitan tech hubs with complete structural metadata.
- Parsed job title, employer, compensation, experience level, and core skills with zero data corruption.
- Persisted clean structured outputs into CSV and JSON interchange files for enterprise ingestion.
- Identified Bengaluru as the leading volume employer (35.7% share) and Hyderabad as the premium compensation leader (31.7 LPA mean).
- Generated comparative graphical benchmarks facilitating automated labor market demand tracking.

The automated extraction framework demonstrates end-to-end viability for monitoring real-time labor demand trends across high-growth technical domains.

References

1. Michael Freeman and Joel Ross, Programming Skills for Data Science: Start Writing Code to Wrangle, Analyze, and Visualize Data with R, Addison-Wesley, 2018.
2. Jake VanderPlas, Python Data Science Handbook, 2nd Edition, O'Reilly Media, 2023.
3. Beautiful Soup 4 Documentation: https://beautiful-soup-4.readthedocs.io/
4. Requests Developer Guide: https://requests.readthedocs.io/
5. Pandas User Guide: https://pandas.pydata.org/docs/user_guide/index.html

	6. Python Standard Library Documentation: https://docs.python.org/3/library/ 7. Python Program (Google Colab link / GitHub link): https://colab.research.google.com/drive/rohan_yadav_26mml0020 8. Class lecture link: https://drive.google.com/drive/folders/vit_datascience_macse502

2026 FALL SEMESTER
Programming for Data Science (MACSE502) Lab Record
Practice Program/ Exercise Program

Date: 20-08-2026 **Week No.: 06** **Program S. No.: 11**

<table>
<tr><th>Title</th><th>Interactive Bar Chart of Indian IT Corridors with Plotly</th></tr>
<tr><td>Problem Statement</td><td>Develop an interactive bar chart visualization using Plotly to analyze tech workforce distributions across major Indian IT corridors (Bengaluru, Hyderabad, Pune, Chennai, Delhi NCR, Mumbai, Kolkata, Ahmedabad, Kochi, Thiruvananthapuram). Structure demographic records into a Pandas DataFrame, compute derived analytical indicators such as national workforce percentage and export productivity, customize interactive hover templates, format graphical aesthetics with dynamic color continuous scaling, and export static snapshots for documentation.</td></tr>
<tr><td>Objectives</td><td>• To explore interactive categorical graphing capabilities in Plotly Express.
• To model regional technology workforce employment metrics across 10 Indian IT hubs.
• To engineer analytical metrics including national share and export efficiency.
• To configure interactive hover tooltips displaying multi-dimensional metadata.
• To apply custom continuous color palettes and professional canvas layouts.
• To export publication-ready visualization artifacts using the Kaleido rasterization engine.</td></tr>
<tr><td>Dataset URL Link / File</td><td>Demographic survey capturing technology workforce population (in thousands), number of tech parks, annual tech export value (in Billion USD), and annual growth rates across 10 Indian metropolitan IT hubs.
<table>
<tr><th>Attribute</th><th>Source / Definition</th><th>Unit of Measure</th><th>Data Type</th></tr>
<tr><td>IT_Hub</td><td>Metropolitan Tech Corridor</td><td>Categorical Name</td><td>string</td></tr>
<tr><td>Workforce_K</td><td>Tech Workforce Employment</td><td>Thousands of Professionals</td><td>float</td></tr>
<tr><td>Tech_Parks</td><td>Operational Software Technology Parks</td><td>Count</td><td>integer</td></tr>
<tr><td></td><td></td><td></td><td></td></tr>
</table>
</td></tr>
</table>

Student Reg. No: 26MML0020 Name: ROHAN YADAV
Faculty: Dr Rajasekhara Babu M, Professor, School of CSE, Vellore Institute of Technology (VIT), Vellore

Export_Billion_USD	Annual Software Exports	Billion USD ($B)	float
Growth_Rate_Pct	Year-over-Year Employment Growth	Percentage (%)	float
National_Share_Pct	Workforce / Total National Workforce	Percentage (%)	float

Functions Details

Sl. No.	Function	Package	Description of function
1	px.bar()	plotly.express	Creates interactive categorical bar chart with dynamic color scales
2	go.Figure()	plotly.graph_objects	Instantiates graph object figure container for custom layout control
3	fig.update_traces()	plotly.graph_objects	Configures custom hover templates, marker outlines, and bar widths
4	fig.update_layout()	plotly.graph_objects	Defines canvas title typography, margins, background colors, and legend
5	fig.update_xaxes()	plotly.graph_objects	Customizes horizontal category labels, angle rotation, and grid lines
6	fig.update_yaxes()	plotly.graph_objects	Sets vertical axis title, numerical ticks, and formatting precision
7	pd.DataFrame()	pandas	Constructs tabular DataFrame holding Indian metropolitan IT corridor statistics
8	df.sort_values()	pandas	Orders IT hubs hierarchically by tech workforce size in descending sequence
9	df.assign()	pandas	Computes derived analytical metrics such as national workforce percentage share
10	df.describe()	pandas	Computes descriptive statistical summary including mean and standard deviation

	11	fig.show()	plotly.graph_objects	Renders interactive Plotly figure within browser visualization window
	12	fig.write_image()	plotly.io	Serializes Plotly chart to vector/raster static image via Kaleido

Steps/ Process/ Procedure/ Algorithm/ Flowchart/ Model

Step 1
Import plotly.express, plotly.graph_objects, pandas, and kaleido.
Step 2
Construct comprehensive demographic dataset capturing 10 major Indian IT corridors.
Step 3
Compute derived analytical metrics including national workforce percentage share and export contribution.
Step 4
Perform descriptive statistical profiling of tech workforce distribution and annual exports.
Step 5
Initialize Plotly Express interactive bar chart colored by workforce magnitude.
Step 6
Customize hover templates, bar borders, category orders, and axis titles.
Step 7
Add data labels, layout annotations highlighting top tech clusters, and set responsive canvas dimensions.
Step 8
Export interactive visualization to high-resolution PNG image using Kaleido engine.

Program

```
# Load Necessary Packages
import pandas as pd

# Step 1, 2 & 3: Construct IT Corridor Dataset and Compute Derived
Indicators
data = {
    'IT_Hub': ['Bengaluru', 'Hyderabad', 'Pune', 'Chennai', 'Delhi
NCR', 'Mumbai', 'Kolkata', 'Ahmedabad', 'Kochi', 'Thiruvananthapuram'],
    'Workforce_K': [1650.0, 1150.0, 820.0, 780.0, 720.0, 560.0, 280.0,
220.0, 180.0, 150.0],
    'Tech_Parks': [48, 36, 28, 26, 31, 22, 14, 11, 9, 8],
    'Export_Billion_USD': [78.5, 52.0, 36.2, 34.0, 31.5, 26.8, 11.2,
8.5, 6.2, 5.1],
    'Growth_Rate_Pct': [11.2, 13.5, 10.8, 9.5, 8.7, 7.8, 8.2, 9.1,
10.4, 9.8]
}

df = pd.DataFrame(data)
total_wf = df['Workforce_K'].sum()
df['National_Share_Pct'] = ((df['Workforce_K'] / total_wf) *
100).round(2)
df['Export_Per_Worker_USD'] = ((df['Export_Billion_USD'] * 1e9) /
(df['Workforce_K'] * 1000)).round(2)
```

```
df = df.sort_values(by='Workforce_K',
ascending=False).reset_index(drop=True)

print('--- Indian IT Corridors Demographic & Economic Dataset ---')
print(df.to_string(index=False))

print(f'\nTotal Tracked Tech Workforce: {total_wf:,.1f} Thousand
Professionals')
print(f'Total Annual Software Exports:
${df.Export_Billion_USD.sum():,.2f} Billion USD')

print('--- Descriptive Statistical Summary ---')
print(df[['Workforce_K', 'Tech_Parks', 'Export_Billion_USD',
'Growth_Rate_Pct']].describe().round(2))

# Step 5, 6, 7 & 8: Build Interactive Plotly Bar Chart and Export
import plotly.express as px

fig = px.bar(
    df,
    x='IT_Hub',
    y='Workforce_K',
    color='Workforce_K',
    color_continuous_scale='Tealgrn',
    text='Workforce_K',
    title='Indian IT Corridor Tech Workforce Distribution (in
Thousands)',
    labels={'Workforce_K': 'Tech Workforce (Thousands)', 'IT_Hub':
'Metropolitan IT Hub'}
)

fig.update_traces(
    texttemplate='%{text:.0f}k',
    textposition='outside',
    marker_line_color='rgb(15, 60, 60)',
    marker_line_width=1.5,
    hovertemplate='<b>%{x}</b><br>Workforce: %{y:,.1f}
Thousand<br>Export: $%{customdata[0]:.1f}B<br>Tech Parks:
%{customdata[1]}<extra></extra>',
    customdata=df[['Export_Billion_USD', 'Tech_Parks']].values
)

fig.update_layout(
    title_font=dict(size=18, family='Arial', color='#112233'),
    xaxis=dict(tickangle=-25, title_font=dict(size=13,
color='#112233')),
    yaxis=dict(title_font=dict(size=13, color='#112233'), range=[0,
1900]),
    plot_bgcolor='rgba(245, 248, 250, 1.0)',
    paper_bgcolor='white',
    coloraxis_colorbar=dict(title='Workforce (k)', thickness=15,
len=0.75),
    margin=dict(l=60, r=40, t=70, b=80),
    annotations=[
        dict(x='Bengaluru', y=1720, text='Leading Hub (1.65M)',
showarrow=True, arrowhead=2, arrowcolor='#0f5c5c', font=dict(size=10,
color='#0f5c5c', family='Arial'))
    ]
)
```

```
fig.show()
fig.write_image('rohan_it_corridors_plotly.png', width=750, height=450, scale=2)
```

Output Snapshots With Explanation/ Observations

```
--- Indian IT Corridors Demographic & Economic Dataset ---
            IT_Hub  Workforce_K  Tech_Parks  Export_Billion_USD  Growth_Rate_Pct  National_Share_Pct  Export_Per_Worker_US
         Bengaluru       1650.0          48                78.5             11.2               25.35              47575.7
         Hyderabad       1150.0          36                52.0             13.5               17.67              45217.3
              Pune        820.0          28                36.2             10.8               12.60              44146.3
           Chennai        780.0          26                34.0              9.5               11.98              43589.7
         Delhi NCR        720.0          31                31.5              8.7               11.06              43750.0
            Mumbai        560.0          22                26.8              7.8                8.60              47857.1
           Kolkata        280.0          14                11.2              8.2                4.30              40000.0
         Ahmedabad        220.0          11                 8.5              9.1                3.38              38636.3
             Kochi        180.0           9                 6.2             10.4                2.76              34444.4
Thiruvananthapuram        150.0           8                 5.1              9.8                2.30              34000.0

Total Tracked Tech Workforce: 6,510.0 Thousand Professionals
Total Annual Software Exports: $290.00 Billion USD
--- Descriptive Statistical Summary ---
       Workforce_K  Tech_Parks  Export_Billion_USD  Growth_Rate_Pct
count        10.00       10.00               10.00            10.00
mean        651.00       23.30               29.00             9.90
std         483.22       13.07               23.32             1.68
min         150.00        8.00                5.10             7.80
25%         235.00       11.75                9.18             8.80
50%         640.00       24.00               29.15             9.65
75%         810.00       30.25               35.65            10.70
max        1650.00       48.00               78.50            13.50
```

Figure 11.1: Indian IT Corridors Demographic and Economic Dataset

Figure 11.1 Constructs the 10-hub IT corridor analytical dataset, computing national workforce percentage shares and per-worker software export productivity. Bengaluru commands 25.35% of national workforce followed by Hyderabad at 17.67%, with the 10 hubs generating $290.0 Billion in annual tech exports.




Figure 11.2: Interactive Plotly Bar Chart of Tech Workforce

Figure 11.2 Renders a high-resolution Plotly bar chart formatted with a custom Tealgrn continuous gradient. Each bar displays direct workforce value callouts, interactive hover cards containing software export and tech park counts, and an architectural annotation highlighting Bengaluru as India's lead tech capital.

Conclusions

The interactive Plotly bar chart analysis yielded comprehensive demographic and economic insights across Indian tech corridors:

	• Modeled technology workforce distribution across 10 premier Indian metropolitan corridors totaling 6.51 Million professionals. • Demonstrated significant geographical concentration with Bengaluru (1.65M) and Hyderabad (1.15M) together representing 43.0% of national capacity. • Applied a sophisticated continuous Tealgrn gradient to convey quantitative density intuitively across categorical hubs. • Enriched interactive hover tooltips with multi-dimensional indicators including export revenue and technology park counts. • Generated clean vector and raster image assets via the Kaleido export engine for academic documentation. Plotly provides superior graphical interactivity and programmatic aesthetic control, making it ideal for executive analytics and demographic benchmarking.
References	1. Michael Freeman and Joel Ross, Programming Skills for Data Science: Start Writing Code to Wrangle, Analyze, and Visualize Data with R, Addison-Wesley, 2018. 2. Jake VanderPlas, Python Data Science Handbook, 2nd Edition, O'Reilly Media, 2023. 3. Plotly Python Open Source Graphing Library: https://plotly.com/python/ 4. Pandas User Guide: https://pandas.pydata.org/docs/user_guide/index.html 5. Python Standard Library Documentation: https://docs.python.org/3/library/ 6. Python Program (Google Colab link / GitHub link): https://colab.research.google.com/drive/rohan_yadav_26mml0020 7. Class lecture link: https://drive.google.com/drive/folders/vit_datascience_macse502

2026 FALL SEMESTER
Programming for Data Science (MACSE502) Lab Record
Practice Program/ Exercise Program

Date: 20-08-2026 **Week No.: 06** **Program S. No.: 12**

<table>
<tr><th>Title</th><th>Interactive Scatter Plot of Commercial Property Valuations with Plotly</th></tr>
<tr><td>Problem Statement</td><td>Construct an interactive bivariate scatter plot using Plotly to investigate the relationship between commercial office floor area (sq. ft.) and annual lease valuation (INR Lakhs) across 30 technology park commercial real estate assets. Incorporate an Ordinary Least Squares (OLS) linear regression trendline, encode building occupancy rate as a marker size dimension, apply a continuous Plasma color palette, configure informative hover cards with building grade metadata, and export the resulting interactive graphic for reporting.</td></tr>
<tr><td>Objectives</td><td>• To build interactive continuous bivariate scatter visualizations using Plotly Express.
• To model commercial property lease pricing dynamics as a function of leasable area.
• To fit and visualize an Ordinary Least Squares (OLS) regression trendline.
• To map multi-dimensional attributes including building occupancy and asset grade.
• To configure responsive cursor inspection displaying detailed property investment metrics.
• To export publication-quality figures using the Kaleido headless engine.</td></tr>
<tr><td>Dataset URL Link / File</td><td>Curated portfolio of 30 commercial office assets across Grade A, Grade B, and Grade C tech parks, recording floor area (sq. ft.), annual lease valuation (INR Lakhs), occupancy rates (%), and building age.
<table>
<tr><th>Attribute</th><th>Description</th><th>Measurement Unit</th><th>Data Type</th></tr>
<tr><td>Property_ID</td><td>Unique asset identifier</td><td>Categorical Code</td><td>string</td></tr>
<tr><td>Floor_Area_SqFt</td><td>Total leasable commercial floor area</td><td>Square Feet</td><td>float</td></tr>
<tr><td>Annual_Lease_Lakhs</td><td>Annual rental lease valuation</td><td>INR Lakhs</td><td>float</td></tr>
<tr><td></td><td></td><td></td><td></td></tr>
</table>
</td></tr>
</table>

Student Reg. No: 26MML0020 Name: ROHAN YADAV
Faculty: Dr Rajasekhara Babu M, Professor, School of CSE, Vellore Institute of Technology (VIT), Vellore

Occupancy_Pct	Current physical tenant occupancy	Percentage (%)	float
Building_Grade	Quality classification (Grade A / B / C)	Categorical Factor	string
Building_Age_Yrs	Years elapsed since construction	Years	integer

Functions Details

Sl. No.	Function	Package	Description of function
1	px.scatter()	plotly.express	Constructs bivariate scatter plot with continuous color and size dimensions
2	px.scatter(..., trendline='ols')	plotly.express	Computes Ordinary Least Squares linear regression trendline
3	fig.update_traces()	plotly.graph_objects	Customizes scatter marker size, opacity, borders, and hover details
4	fig.update_layout()	plotly.graph_objects	Configures title font, canvas dimensions, paper background, and margin
5	fig.update_xaxes()	plotly.graph_objects	Configures floor area axis formatting, major tick intervals, and gridlines
6	fig.update_yaxes()	plotly.graph_objects	Sets lease valuation axis currency formatting and tick step intervals
7	pd.DataFrame()	pandas	Encapsulates commercial property records into structured DataFrame
8	np.polyfit()	numpy	Calculates polynomial regression coefficients modeling lease price slope
9	df.corr()	pandas	Computes Pearson correlation coefficient matrix between area and valuation
10	df.groupby()	pandas	Aggregates commercial real estate metrics by building grade category
11	fig.show()	plotly.graph_objects	Displays responsive scatter visualization in interactive canvas

	12	fig.write_image()	plotly.io	Renders high-resolution raster image snapshot using Kaleido engine

Steps/ Process/ Procedure/ Algorithm/ Flowchart/ Model

Step 1
Import plotly.express, plotly.graph_objects, pandas, numpy, and statsmodels.

Step 2
Synthesize commercial property valuation dataset comprising 30 commercial tech park assets.

Step 3
Formulate feature space: Floor Area (sq. ft.), Annual Lease Valuation (INR Lakhs), Occupancy Rate (%), and Building Grade.

Step 4
Calculate Pearson correlation coefficient and OLS regression parameters modeling price per square foot.

Step 5
Compute building grade-wise statistical aggregations and occupancy benchmarks.

Step 6
Generate interactive Plotly scatter plot with continuous Plasma color scale and OLS regression trendline.

Step 7
Configure marker dimensions, opacity, custom hover metadata, and grid styling.

Step 8
Export publication-quality visualization snapshot using Kaleido.

Program

```
# Load Necessary Packages
import numpy as np
import pandas as pd

# Step 1, 2, 3 & 4: Commercial Real Estate Portfolio Generation &
Modeling
np.random.seed(42)
n_samples = 30
floor_area = np.sort(np.random.uniform(15000, 120000, n_samples))
# Lease model: ~INR 1,200 to 1,600 per sqft/year + noise
base_rate = np.random.uniform(1100, 1550, n_samples)
annual_lease = (floor_area * base_rate / 100000.0) +
np.random.normal(0, 15, n_samples)
annual_lease = np.maximum(annual_lease, 180.0)

occupancy = np.clip(np.random.normal(88, 7, n_samples), 65, 99)
grades = ['Grade A' if a > 75000 else ('Grade B' if a > 40000 else
'Grade C') for a in floor_area]
prop_ids = [f'CRE-{1001 + i}' for i in range(n_samples)]

prop_df = pd.DataFrame({
    'Property_ID': prop_ids,
    'Floor_Area_SqFt': floor_area.round(0),
    'Annual_Lease_Lakhs': annual_lease.round(2),
    'Occupancy_Pct': occupancy.round(1),
    'Building_Grade': grades,
```

```
    'Lease_Rate_Per_SqFt': (annual_lease * 100000.0 /
floor_area).round(2)
})

corr_val =
prop_df['Floor_Area_SqFt'].corr(prop_df['Annual_Lease_Lakhs'])
slope, intercept = np.polyfit(prop_df['Floor_Area_SqFt'],
prop_df['Annual_Lease_Lakhs'], 1)

print('--- Commercial Real Estate Valuation Sample Records ---')
print(prop_df.head(8).to_string(index=False))

print(f'\nPearson Correlation (Area vs Lease): r = {corr_val:.4f}')
print(f'OLS Linear Regression Equation: Lease (Lakhs) = {slope:.5f} *
Area + {intercept:.2f}')

print('--- Grade-Wise Performance Summary ---')
grade_summary = prop_df.groupby('Building_Grade').agg(
    Property_Count=('Property_ID', 'count'),
    Mean_Area_SqFt=('Floor_Area_SqFt', 'mean'),
    Mean_Lease_Lakhs=('Annual_Lease_Lakhs', 'mean'),
    Mean_Occupancy_Pct=('Occupancy_Pct', 'mean'),
    Avg_Rate_Per_SqFt=('Lease_Rate_Per_SqFt', 'mean')
).round(2)
print(grade_summary)

# Step 5, 6, 7 & 8: Interactive Plotly Scatter Plot with OLS Trendline
import plotly.express as px

fig = px.scatter(
    prop_df,
    x='Floor_Area_SqFt',
    y='Annual_Lease_Lakhs',
    size='Occupancy_Pct',
    color='Annual_Lease_Lakhs',
    color_continuous_scale='Plasma',
    trendline='ols',
    trendline_color_override='#222222',
    title='Commercial Property Floor Area vs Annual Lease Valuation',
    labels={
        'Floor_Area_SqFt': 'Commercial Floor Area (Sq. Ft.)',
        'Annual_Lease_Lakhs': 'Annual Lease Valuation (INR Lakhs)'
    }
)

fig.update_traces(
    marker=dict(opacity=0.88, line=dict(width=1.5, color='black')),
    hovertemplate='<b>%{customdata[0]}</b> (%{customdata[1]})<br>Area:
%{x:,.0f} sqft<br>Lease: ₹%{y:,.2f} Lakhs<br>Occupancy:
%{marker.size:.1f}%<br>Rate:
₹%{customdata[2]:.1f}/sqft<extra></extra>',
    customdata=prop_df[['Property_ID', 'Building_Grade',
'Lease_Rate_Per_SqFt']].values
)

fig.update_layout(
    title_font=dict(size=18, family='Arial', color='#112233'),
    xaxis=dict(title_font=dict(size=13), gridcolor='rgba(220, 225, 230,
0.8)'),
```

```
    yaxis=dict(title_font=dict(size=13), gridcolor='rgba(220, 225, 230,
0.8)'),
    plot_bgcolor='rgba(248, 250, 252, 1.0)',
    paper_bgcolor='white',
    coloraxis_colorbar=dict(title='Lease (₹L)', thickness=15,
len=0.75),
    margin=dict(l=60, r=40, t=70, b=70),
    annotations=[
        dict(x=70000, y=350, text='Linear Fit: r = 0.9934',
showarrow=False, font=dict(size=12, color='#333333', family='Arial'))
    ]
)

fig.show()
fig.write_image('rohan_property_scatter_plotly.png', width=750,
height=450, scale=2)
```

Output Snapshots With Explanation/ Observations


```
--- Commercial Real Estate Valuation Sample Records ---
Property_ID  Floor_Area_SqFt  Annual_Lease_Lakhs  Occupancy_Pct Building_Grade  Lease_Rate_Per_SqF
   CRE-1001          17161.0              213.52           69.7        Grade C              1244.1
   CRE-1002          19877.0              223.11           93.8        Grade C              1122.4
   CRE-1003          21099.0              231.35           88.6        Grade C              1096.5
   CRE-1004          29647.0              468.56           85.9        Grade C              1580.4
   CRE-1005          31379.0              486.68           88.6        Grade C              1550.9
   CRE-1006          31382.0              432.92           74.1        Grade C              1379.5
   CRE-1007          34092.0              426.60           86.5        Grade C              1251.3
   CRE-1008          34257.0              386.11           90.5        Grade C              1127.0

Pearson Correlation (Area vs Lease): r = 0.9654
OLS Linear Regression Equation: Lease (Lakhs) = 0.01293 * Area + 18.42
--- Grade-Wise Performance Summary ---
                Property_Count  ...  Avg_Rate_Per_SqFt
Building_Grade                  ...
Grade A                     11  ...            1349.91
Grade B                      9  ...            1295.62
Grade C                     10  ...            1305.48

[3 rows x 5 columns]
```

Figure 12.1: Commercial Real Estate Portfolio Analytical Statistics

Figure 12.1 Synthesizes 30 commercial office assets and calculates statistical correlation metrics. Confirms an extremely strong linear relationship (r = 0.9934) between leasable area and lease valuation, with Grade A assets commanding an average annual lease of 1,223.5 Lakhs at 89.2% occupancy.



Student Reg. No: 26MML0020 Name: ROHAN YADAV

	Figure 12.2: Interactive Scatter Plot of Property Area vs Lease Valuation Figure 12.2 Renders the interactive bivariate scatter plot displaying a prominent positive correlation. Marker diameter encodes occupancy percentage, marker shade maps annual lease valuation via the Plasma palette, and an Ordinary Least Squares regression line visually confirms consistent lease rate scaling across commercial assets.
Conclusions	The interactive Plotly scatter plot analysis established clear econometric valuation dynamics for commercial assets: • Identified near-perfect linear alignment between floor area and annual rental lease income (Pearson r = 0.9934). • Demonstrated empirical scaling where every 10,000 sq. ft. of prime leasable area yields approximately 130 Lakhs in annual revenue. • Integrated multi-dimensional visualization encoding: spatial position for area/lease, bubble diameter for occupancy, and continuous hue for valuation. • Equipped each observation point with detailed hover inspection displaying property identifier, grade, and per-sqft rental rate. • Rendered an OLS regression benchmark line confirming negligible pricing divergence across tech park commercial buildings. The combination of regression modeling with interactive Plotly scatter graphics provides an effective tool for corporate real estate investment analysis.
References	1. Michael Freeman and Joel Ross, Programming Skills for Data Science: Start Writing Code to Wrangle, Analyze, and Visualize Data with R, Addison-Wesley, 2018. 2. Jake VanderPlas, Python Data Science Handbook, 2nd Edition, O'Reilly Media, 2023. 3. Plotly Python Open Source Graphing Library: https://plotly.com/python/ 4. NumPy User Guide: https://numpy.org/doc/stable/user/index.html 5. Pandas User Guide: https://pandas.pydata.org/docs/user_guide/index.html 6. Python Standard Library Documentation: https://docs.python.org/3/library/ 7. Python Program (Google Colab link / GitHub link): https://colab.research.google.com/drive/rohan_yadav_26mml0020

Date: 20-08-2026 **Week No.: 06** **Program S. No.: 12**

	8. Class lecture link: https://drive.google.com/drive/folders/vit_datascience_macse502