


# Graphical Semisupervised Learning

We should probably write something here


Rohin Gilman   Alex Johnson   Kaitlynn Lilly

May 22, 2023

- Goal in SSL is, given  $\{x_i, y_i\}_{i=1}^M$  and  $\{x_i\}_{i=M+1}^N$ , to predict  $y_i(x_i)$  for  $i = M + 1, \dots, N$  where  $M \ll N$ .



- We leverage spectral geometric properties of the graph Laplacian matrix  $L$ .
- First, we construct our graphs by KNN or Proximity graph construction.



- General optimization

$$\vec{f}^* = \arg \min_{\vec{f} \in \mathbb{R}^m} \mathcal{L}(\vec{f}; y) + \lambda \vec{f}^T C^{-1} \vec{f}$$

where  $\mathcal{L}$  is a loss function, either Probit or Regression loss in our case.

- Probit loss

$$\mathcal{L}(\vec{f}, y) = - \sum_{j=1}^M \log \Psi(\vec{f}_j y_j)$$

- Regression loss

$$\mathcal{L}(\vec{f}, y) = \sum_{j=1}^M \left( \vec{f}_j - y_j \right)^2$$

- General optimization

$$\vec{f}^* = \arg \min_{\vec{f} \in \mathbb{R}^m} \mathcal{L}(\vec{f}; y) + \lambda \vec{f}^T C^{-1} \vec{f}$$


where  $C = (L + \tau^2 I)^{-\alpha}$ , where  $L$  is the graph Laplacian.

- In class, we showed  $C$  is a kernel matrix. In fact,  $C$  belongs to a class of kernels called the Matérn family that have the form

$$K(x, y) = \kappa(\|x - y\|), \kappa(t) = \frac{2^{1-\nu}}{\Gamma(\nu)} \left( \sqrt{2\nu} \frac{t}{\gamma} \right) K_\nu \left( \sqrt{2\nu} \frac{t}{\gamma} \right)$$


where  $\Gamma$  is the Gamma function and  $K_\nu$  is the modified Bessel function of the second kind.

Using the K-Nearest Neighbors Graph with Uniform Weights





Loss Function	Classification Accuracy (over 50 trials)
Probit	100%
Regression	100%

Using the Proximity Graph with RBF Weights



Loss Function	Classification Accuracy (over 50 trials)
Probit	100.0%
Regression	100.0%



Using the K-Nearest Neighbors Graph with RBF Weights



Loss Function	Classification Accuracy (over 50 trials)
Probit	96.3%
Regression	95.8%



Using the Proximity Graph with RBF Weights



Loss Function	Classification Accuracy (on 1 trial)
Probit	73.0%
Regression	63.0%

- Conclusions
  - For well separated clusters, the method is effective, even without careful tuning
  - Not the case for more difficult scenarios
- Challenges Encountered
  - Tuning of paramters - especially for real data
  - Majority labelling
- Next Steps
  - Plan to apply this approach to MNIST to test on real data
  - Anticipate tuning challenges for more difficult pairs of numbers



Viacheslav Borovitskiy, Iskander Azangulov, Alexander Terenin, Peter Mostowsky, Marc Peter Deisenroth, and Nicolas Durrande.

Matérn Gaussian processes on graphs, April 2021.



Franca Hoffmann, Bamdad Hosseini, Zhi Ren, and Andrew M. Stuart.

Consistency of semi-supervised learning algorithms on graphs: Probit and one-hot methods, March 2020.



Daniel Sanz-Alonso and Ruiyi Yang.

The SPDE approach to Matérn fields: Graph representations, April 2021.