

Spiral

May 16, 2023

```
[ ]: import numpy as np
      from numpy.random import multivariate_normal as mvn

      import matplotlib.pyplot as plt

      from scipy.stats import norm
      from scipy.optimize import minimize

      from math import log
      from math import dist
      from math import floor
      from math import pi

      from random import shuffle

      from tqdm import tqdm

      from weights import KNN
      from weights import proximity

      from accuracy import KNN_acc
      from accuracy import Prox_acc

      from points import spiralPoints
```

1 Complete Spiral Example

1.1 Generating the Points

We first write a function to generate three well-separated clusters, depending on the number of points desired and the centers and covariance matrix of the distributions

```
[ ]: def clusters(m, tranges, var):
      # m is the number of points

      knownvals = [int(j*int(m/8)) for j in range(8)] # Points for which we
      → know the value of the label
```

```

        X = spiralPoints(int(m/2), tranges[0,0], tranges[0,1], var)
        X = np.append(X, spiralPoints(int(m/4), tranges[1,0], tranges[1,1],
↪var), axis=0)
        X = np.append(X, spiralPoints(int(m/4), tranges[2,0], tranges[2,1],
↪var), axis=0)

        y = [1 for i in range(int(m/2))]
        y = y + [-1 for i in range(int(m/2))]

        return X, y, knownvals

```

We use this to generate the points

```

[ ]: M = 400 # Multiple of 4

tranges = np.array([[pi,5*pi/2], [3*pi,7*pi/2], [4*pi,9*pi/2]])
var = 1

X, y, knownvals = clusters(M, tranges, var)

```

```

[ ]: xs = X[:,0]
     ys = X[:,1]

     xs_k = [xs[j] for j in knownvals]
     ys_k = [ys[j] for j in knownvals]

     ts = np.linspace(0, 6*pi,1000)
     plt.plot(ts*np.cos(ts), ts*np.sin(ts), zorder = -1)


     plt.scatter(xs, ys, c=y, cmap = "viridis")
     plt.scatter(xs_k, ys_k, color="red")

```

```

[ ]: <matplotlib.collections.PathCollection at 0x21fd6b49510>

```



1.2 Build a Graph on the Points and Run Regression

To build a graph on the points, we have some choices to make: the choice of weight function and its parameters and whether we use a KNN approach or a full proximity graph approach

Here is an example of some of these graphs


1.2.1 KNN with uniform kernel

```
[ ]: unif = lambda x1, x2: 1
k = 5

L, W = KNN(X, M, k, unif)

plt.scatter(xs, ys)
plt.scatter(xs_k, ys_k, color="red")

for i in range(M):
    for j in range(i,M):
        if W[i,j] > 0:
            plt.plot([X[i,0],X[j,0]],[X[i,1],X[j,1]], color = "
↪"gray", zorder = 0)
```



Performing the classification, we see that the model performs well with both probit and regression loss. Note that it was not necessary to tune parameters to get good results.

```
[ ]: def probit(kvals, y, f): # Probits Loss
      return -sum([log(norm.cdf(y[j]*f[j])) for j in kvals])

def regression(kvals, y, f): # Regression Loss
      return sum([(y[j]-f[j])**2 for j in kvals])

def regular(lamb,C_inv,f): # Regularization
      f_T = np.array(f).T
      return lamb*f_T.dot(C_inv).dot(f)

def to_minimize(f,kvals,y,lamb,C_inv, loss): # Funtional to minimize
      return loss(kvals,y,f) + regular(lamb,C_inv,f)
```

```
[ ]: tau = 1
      alpha = 2
      lamb = (tau**(2*alpha))/2
      C = np.linalg.matrix_power(((L + (tau**2)*np.eye(M))),-alpha)
      C_inv = np.linalg.inv(C)
```

Probit Loss

```
[ ]: loss = probit

f0 = np.zeros(M)
result = minimize(to_minimize, f0, args=(knownvals,y,lamb,C_inv,loss),
                 method='BFGS') # Perform minimization


f_star = result.x
y_pred = np.sign(f_star) # Predicted labels
```

```
[ ]: xs = X[:,0]
ys = X[:,1]

xs_k = [xs[j] for j in knownvals]
ys_k = [ys[j] for j in knownvals]

plt.scatter(xs, ys, c=y_pred, cmap = "viridis")
plt.scatter(xs_k, ys_k, color="red")
```

```
[ ]: <matplotlib.collections.PathCollection at 0x21fd4725f50>
```



```
[ ]: accuracy = sum([x[0] == x[1] for x in zip(y_pred,y)])/M
print(accuracy)
```

0.91

Regression Loss

```
[ ]: loss = regression

f0 = np.zeros(M)
result = minimize(to_minimize, f0, args=(knownvals,y,lamb,C_inv,loss),
    ↪method='BFGS') # Perform minimization


f_star = result.x
y_pred = np.sign(f_star) # Predicted labels
```

```
[ ]: xs = X[:,0]
ys = X[:,1]

xs_k = [xs[j] for j in knownvals]
ys_k = [ys[j] for j in knownvals]

plt.scatter(xs, ys, c=y_pred, cmap = "viridis")
plt.scatter(xs_k, ys_k, color="red")
```

```
[ ]: <matplotlib.collections.PathCollection at 0x21fd47ece50>
```



```
[ ]: accuracy = sum([x[0] == x[1] for x in zip(y_pred,y)])/M
      print(accuracy)
```

0.91

1.2.2 KNN with RBF Kernel

We can see that KNN with the uniform kernel is not particularly effective for this scenario. Let's see if we can fix this problem with the RBF kernel

We first need to make a guess at the gamma parameter in the RBF kernel. We use the first quartile of the distances between vertices. Then we adjust using our multiplier

```
[ ]: dists = []
      for x1 in X:
          for x2 in X:
              dists += [dist(x1,x2)]
      dists.sort()

      mult = 0.15
      gamma = dists[floor(len(dists)/4)]*mult


      rbf = lambda x1, x2: np.exp(gamma**2*-0.5*dist(x1,x2)**2)
```

```
[ ]: L, W = KNN(X, M, k, rbf)

plt.scatter(xs, ys)
plt.scatter(xs_k, ys_k, color="red")

l1 = [*range(M)] # Shuffle vertices to make plot more even
shuffle(l1)
l2 = [*range(M)]
shuffle(l2)

for i in l1:
    for j in l2:
        if W[i,j] > 0:
            plt.plot([X[i,0],X[j,0]],[X[i,1],X[j,1]], color = str(1_
↵ 0.5*W[i,j]), zorder = 0)
```



```
[ ]: tau = 1
alpha = 2
lamb = (tau**(2*alpha))/2
C = np.linalg.matrix_power(((L + (tau**2)*np.eye(M))),-alpha)
C_inv = np.linalg.inv(C)
```


Probit Loss

```
[ ]: loss = probit

f0 = np.zeros(M)
result = minimize(to_minimize, f0, args=(knownvals,y,lamb,C_inv,loss),
                 method='BFGS') # Perform minimization


f_star = result.x
y_pred = np.sign(f_star) # Predicted labels
```

```
[ ]: xs = X[:,0]
ys = X[:,1]

xs_k = [xs[j] for j in knownvals]
ys_k = [ys[j] for j in knownvals]

plt.scatter(xs, ys, c=y_pred, cmap = "viridis")
plt.scatter(xs_k, ys_k, color="red")
```

```
[ ]: <matplotlib.collections.PathCollection at 0x21fdcbcc710>
```



```
[ ]: accuracy = sum([x[0] == x[1] for x in zip(y_pred,y)])/M
print(accuracy)
```

0.9225

Regression Loss

```
[ ]: loss = regression

f0 = np.zeros(M)
result = minimize(to_minimize, f0, args=(knownvals,y,lamb,C_inv,loss),
    ↪method='BFGS') # Perform minimization


f_star = result.x
y_pred = np.sign(f_star) # Predicted labels
```

```
[ ]: xs = X[:,0]
ys = X[:,1]

xs_k = [xs[j] for j in knownvals]
ys_k = [ys[j] for j in knownvals]

plt.scatter(xs, ys, c=y_pred, cmap = "viridis")
plt.scatter(xs_k, ys_k, color="red")
```

```
[ ]: <matplotlib.collections.PathCollection at 0x21fd9b97850>
```



```
[ ]: accuracy = sum([x[0] == x[1] for x in zip(y_pred,y)])/M
      print(accuracy)
```

0.925

This approach does a slightly better job

1.2.3 Proximity with RBF Kernel

We first need to make a guess at the gamma parameter in the RBF kernel. We use the first quartile of the distances between vertices. Then we adjust using our multiplier

```
[ ]: dists = []
      for x1 in X:
          for x2 in X:
              dists += [dist(x1,x2)]
      dists.sort()

      mult = 0.05
      gamma = dists[floor(len(dists)/4)]*mult


      rbf = lambda x1, x2: np.exp(gamma**2*-0.5*dist(x1,x2)**2)
```

```
[ ]: L, W = proximity(X, M, 20, rbf)

plt.scatter(xs, ys)
plt.scatter(xs_k, ys_k, color="red")

l1 = [*range(M)] # Shuffle vertices to make plot more even
shuffle(l1)
l2 = [*range(M)]
shuffle(l2)

for i in l1:
    for j in l2:
        if W[i,j] > 0:
            plt.plot([X[i,0],X[j,0]],[X[i,1],X[j,1]], color = str(1_
↪ 0.5*W[i,j]), zorder = 0)
```



Now we do the classification

We need to tune the tau parameter here, we want τ^2 to be on the order of epsilon

```
[ ]: W2 = np.copy(W)
W2 = W2.flatten()
W2.sort()
```

```
tau = W2[floor(3*len(W2)/4)]**(1/2) # 75th percentile of W2 terms
```


```
[ ]: alpha = 2  
lamb = (tau**(2*alpha))/2  
C = np.linalg.matrix_power(((L + (tau**2)*np.eye(M))),-alpha)  
C_inv = np.linalg.inv(C)
```

Probit Loss

```
[ ]: loss = probit  
  
f0 = np.zeros(M)  
result = minimize(to_minimize, f0, args=(knownvals,y,lamb,C_inv,loss),  
↳method='BFGS') # Perform minimization  
  
f_star = result.x  
y_pred = np.sign(f_star) # Predicted labels
```

```
[ ]: xs = X[:,0]  
ys = X[:,1]  
  
xs_k = [xs[j] for j in knownvals]  
ys_k = [ys[j] for j in knownvals]  
  
plt.scatter(xs, ys, c=y_pred, cmap = "viridis")  
plt.scatter(xs_k, ys_k, color="red")
```

```
[ ]: <matplotlib.collections.PathCollection at 0x21fd9b976d0>
```



```
[ ]: accuracy = sum([x[0] == x[1] for x in zip(y_pred,y)])/M
      print(accuracy)
```

0.73

1.2.4 Regression Loss

```
[ ]: loss = regression

f0 = np.zeros(M)
result = minimize(to_minimize, f0, args=(knownvals,y,lamb,C_inv,loss),
                  method='BFGS') # Perform minimization


f_star = result.x
y_pred = np.sign(f_star) # Predicted labels
```

```
[ ]: xs = X[:,0]
      ys = X[:,1]

      xs_k = [xs[j] for j in knownvals]
      ys_k = [ys[j] for j in knownvals]
```

```
plt.scatter(xs, ys, c=y_pred, cmap = "viridis")
plt.scatter(xs_k, ys_k, color="red")
```

```
[ ]: <matplotlib.collections.PathCollection at 0x21f72655bd0>
```



```
[ ]: accuracy = sum([x[0] == x[1] for x in zip(y_pred,y)])/M
      print(accuracy)
```

0.63

We can see that the full RBF graph was both slower to run, and worse in performance than the KNN graph

1.3 Validation of accuracy with multiple trials

We run this process 50 times for each case to confirm this result

1.3.1 KNN Graph - Uniform Kernel

```
[ ]: M = 400 # Multiple of 4

      tranges = np.array([[pi,5*pi/2], [3*pi,7*pi/2], [4*pi,9*pi/2]])
      var = 1
```

```

k = 5
tau = 1
alpha = 2
lamb = (tau**(2*alpha))/2

sum_acc = 0
for j in tqdm(range(50)):
    X, y, knownvals = clusters(M, tranges, var)

    sum_acc += KNN_acc(X, y, knownvals, alpha = alpha, tau = tau, lossf = ↵
↵"probit", k = k, kernel = unif)

probit_accuracy = sum_acc/50

sum_acc = 0
for j in tqdm(range(50)):
    X, y, knownvals = clusters(M, tranges, var)

    sum_acc += KNN_acc(X, y, knownvals, alpha = alpha, tau = tau, lossf = ↵
↵"regression", k = k, kernel = unif)

regression_accuracy = sum_acc/50

```

```

100%|      | 50/50 [37:19<00:00, 44.79s/it]
100%|      | 50/50 [08:51<00:00, 10.62s/it]

```

```

[ ]: print(probit_accuracy)
     print(regression_accuracy)

```

```

0.9479999999999998
0.93505

```

1.3.2 KNN Graph - RBF Kernel

```

[ ]: M = 400 # Multiple of 4

tranges = np.array([[pi,5*pi/2], [3*pi,7*pi/2], [4*pi,9*pi/2]])
var = 1

k = 5
tau = 1
alpha = 2
lamb = (tau**(2*alpha))/2

sum_acc = 0
for j in tqdm(range(50)):

```



```

X, y, knownvals = clusters(M, tranges, var)

dists = []
for x1 in X:
    for x2 in X:
        dists += [dist(x1,x2)]
dists.sort()

mult = 0.15
gamma = dists[floor(len(dists)/4)]*mult

rbf = lambda x1, x2: np.exp(gamma**2*-0.5*dist(x1,x2)**2)

sum_acc += KNN_acc(X, y, knownvals, alpha = alpha, tau = tau, lossf =
↳ "probit", k = k, kernel = rbf)

probit_accuracy = sum_acc/50

sum_acc = 0
for j in tqdm(range(50)):
    X, y, knownvals = clusters(M, tranges, var)

    dists = []
    for x1 in X:
        for x2 in X:
            dists += [dist(x1,x2)]
    dists.sort()

    mult = 0.15
    gamma = dists[floor(len(dists)/4)]*mult

    rbf = lambda x1, x2: np.exp(gamma**2*-0.5*dist(x1,x2)**2)

    sum_acc += KNN_acc(X, y, knownvals, alpha = alpha, tau = tau, lossf =
↳ "regression", k = k, kernel = rbf)

regression_accuracy = sum_acc/50

```

```

100%|      | 50/50 [32:49<00:00, 39.38s/it]
100%|      | 50/50 [08:48<00:00, 10.58s/it]

```

```

[ ]: print(probit_accuracy)
     print(regression_accuracy)

```

```

0.9629999999999999
0.95765

```

We can see that with the choices made above, both the disconnected and $O(Eps)$ graphs classify

the data with 100% accuracy