

**Bayesian Learning and Inference  
in Recurrent Switching Linear Dynamical Systems**

Charbel Abi Younes, Marvyn Bailly,  
Bart Boom, Rohin Gilman, Daran Xu

April 29, 2023



# Table of Contents

---

## 1. Introduction and Motivation

## 2. Model

## 3. Conclusion

## 4. Next Step

### 4.1 A Subsection

### 4.2 Another Subsection

## 5. Second Section

## 6. Bibliography



# Frame Title



## Frame Subtitle

---

Rohin

## SLDS and rSLDS

- Observation  $y_t = Cx_t + d + w_t$ ,  $w_t \stackrel{\text{iid}}{\sim} \mathcal{N}(0, S)$
- Continuous latent state  $x_{t+1} = A_{z_{t+1}}x_t + b_{z_{t+1}} + \nu_t$ ,  $\nu_t \stackrel{\text{iid}}{\sim} \mathcal{N}(0, Q_{z_{t+1}})$
- Discrete latent state  $z_t \in \{1, \dots, K\}$ 
  - SLDS [1]  $z_{t+1} | z_t \sim \pi_{z_t}$
  - rSLDS [2]  $z_{t+1} | z_t, x_t \sim \pi_{SB}(\nu_{t+1})$ ,  $\nu_{t+1} = R_{z_t}x_t + r_{z_t}$



## Stick Breaking Logistic Regression [3]

- $p(z|x) \sim \pi_{SB}(\nu)$ ,  $\nu = Rx + r$
  - Link function:  $\pi_{SB}(\nu) = \left( \pi_{SB}^{(1)}(\nu), \dots, \pi_{SB}^{(K)}(\nu) \right)$  (with  $\sigma(x) = \frac{e^x}{1+e^x}$ )
 
$$\pi_{SB}^{(k)}(\nu) = \begin{cases} \sigma(\nu_k) \prod_{j < k} \sigma(-\nu_j), & \text{if } k = 1, \dots, K-1 \\ \prod_{j=1}^K \sigma(-\nu_j), & \text{if } k = K \end{cases}$$
  - $p(z|x) \sim \prod_{k=1}^K \sigma(\nu_k)^{\mathbb{1}[z=k]} \sigma(-\nu_k)^{\mathbb{1}[z > k]}$  (Likelihood)
- With a Gaussian Prior  $p(x)$ , the posterior  $p(x|z) \propto p(x) * p(z|x)$  is non-Gaussian
  - Bayesian updating is not efficient
    - Gibbs Sampler: sampling  $x^{(i+1)} \sim p(x|z = z^{(i)})$ , sampling  $z^{(i+1)} \sim p(z|x = x^{(i+1)})$
    - Message Passing  $m_{t \rightarrow (t+1)}(x_{t+1}) = \int \psi(x_t, y_t) \psi(x_t, z_{t+1}) \psi(x_t, x_{t+1}, z_{t+1}) m_{(t-1) \rightarrow t}(x_t) dx_t$

## Polya-gamma augmentation [3]

$$\frac{(e^\nu)^a}{(1 + e^\nu)^b} = 2^{-b} \int_0^\infty e^{\kappa\nu} e^{-\omega\nu^2/2} p_{\text{PG}}(\omega \mid b, 0) d\omega \quad (\kappa = a - \frac{b}{2}) \quad (2.1)$$

$$p(x_t | z_{t+1}) \propto \prod_{k=1}^{K-1} \frac{(e^{\nu_{t+1,k}})^{\mathbb{I}[z_{t+1}=k]}}{(1 + e^{\nu_{t+1,k}})^{\mathbb{I}[z_{t+1} \geq k]}} \quad (2.2)$$

$$p(x_t | z_{t+1}) = \int p(x_t, \omega_t | z_{t+1}) d\omega_t = \int \mathbf{p}(x_t | z_{t+1}, \omega_t) p(\omega_t) d\omega_t \quad (2.3)$$

$$\omega_{t,k} \mid x_t, z_{t+1} \sim \text{PG}(\mathbb{I}[z_{t+1} \geq k], \nu_{t+1,k}) \quad (2.4)$$

- $p(x_t | z_{t+1}, \omega_t)$  is Gaussian
- Message Passing  $\psi(x_t, z_{t+1}, \omega_t) \propto \mathcal{N}(\nu_{t+1} | \Omega_t^{-1} \kappa_{t+1}, \Omega_t^{-1})$
- Thus instantiating these auxiliary variables in a Gibbs sampler enables efficient block updates



# Frame Title

## Frame Subtitle

---

Rohin



# Frame Title

## Frame Subtitle

---

Rohin





# Frame Title

## Frame Subtitle

---

This is a frame with a title and a subtitle.



---

This is a frame with no title.

This is a frame with no header.



This is underlined text.

*This is italic text.*

**This is bold text.**

`This is mono-spaced text.`

This is a bulleted list:

- An item
- Another item
  - A subitem
  - Another subitem

This is a numbered list:

1. An item
2. Another item
  - 2.1 A subitem
  - 2.2 Another subitem



# Colored Blocks

---

Block Title

This is a block.

Alert Block Title

This is an alertblock.

Example

This is an example block.



This is a frame the second section.



This is a frame with a...





This is a frame with a...

\pause.



Guy A. Ackerson and King-Sun Fu.

On state estimation in switching environments.

*IEEE Transactions on Automatic Control*, 15(1):10–17, 1970.



David Barber.

Expectation correction for smoothed inference in switching linear dynamical systems.

*Journal of Machine Learning Research*, page 7(Nov):2515–2540, 2006.



Scott W Linderman, Matthew J Johnson, and Ryan P Adams.

Dependent multinomial models made easy: Stick-breaking with the poly-gamma augmentation.