

LABORATORY OBSERVATION

Course: Full Stack Web Development

Course Code: 23CM4121

Experiment No.: 4

Student Name: A.Rohit

Roll No.: 324126510006

Date: 30-08-2026

1. TITLE

State Management and DOM Traversal using JavaScript Event Listeners

2. AIM

To build an interactive To-Do List application that demonstrates state management, class inheritance, dynamic element creation, DOM traversal, and event-driven architectural patterns.

3. OBJECTIVE

The objectives of this experiment are:

- To implement ES6 Class inheritance using `extends` and `super()`.
- To manage a global state counter for unique DOM element identification.
- To dynamically append HTML segments to a parent container.
- To pass specific identifying parameters into inline onclick event handlers.
- To remove and style specific DOM nodes upon user interaction.

4. THEORY

Interactive web applications rely heavily on event listeners and DOM manipulation. When a user interacts with the page (e.g., clicking a button), JavaScript captures the event and executes logic to modify the UI.

Class inheritance in JavaScript allows a child class to inherit properties and methods from a parent class, promoting code reusability. A child class calls `super()` to invoke the parent's constructor.

Dynamically generated elements must often carry unique identifiers so that subsequent interactions (like deleting or completing a specific item) know exactly which DOM node to target.

Application Flow:

User Input -> Create WebTask Instance -> Generate Unique HTML -> Append to DOM -> Handle Inline Events (Complete/Delete) -> Update State

5. ALGORITHM / PROCEDURE

1. Define a parent Task class with basic properties (id, text).
2. Define a child WebTask class that extends Task and adds a getHTML() method returning a formatted UI string.
3. Initialize a global taskCounter to track unique IDs.
4. Create an addTask() function that reads input, validates it, and instantiates a WebTask.
5. Append the generated HTML to the list container and increment the counter.
6. Create a completeTask(id) function that finds the specific text span by ID and applies inline CSS (line-through).
7. Create a deleteTask(id) function that finds the specific task box by ID and executes .remove().
8. Implement a helper function to toggle the visibility of an "Empty List" message based on container content.
9. Test adding, completing, and deleting multiple tasks.

6. PROGRAM / SOURCE CODE

Source File: index.html

File not found

Source File: script.js

File not found

7. CODE EXPLANATION

Code / Syntax	Explanation
<code>class WebTask extends Task</code>	Creates a child class inheriting from the Task parent class.
<code>super(id, text);</code>	Invokes the parent class constructor to initialize inherited properties.
<code>document.getElementById('id').innerHTML += ...</code>	Appends a new HTML string to the end of an element's existing content.

<code>onclick='deleteTask(\${this.id})'</code>	Binds a dynamic integer parameter to an inline event handler.
<code>specificText.style.textDecoration = 'line-through';</code>	Applies an inline CSS style to visually strike out completed text.
<code>specificBox.remove();</code>	Completely detaches and deletes a node from the DOM.

8. TEST CASES AND EXECUTION DATA

The experiment was tested with both positive and negative validation test cases:

Test Case	Input / Action	Expected Result	Actual Result	Status
TC-01	Add New Task	Input text and click Add Task	New task UI block appended to DOM successfully	Pass
TC-02	Complete Task Action	Click Complete button on a specific task	Target task text becomes gray and struck-through	Pass
TC-03	Empty State Validation	Check state rendering	No tasks available message dynamically handled	Pass

9. OUTPUT

10. TEST CASES SCREENSHOTS

11. RESULT

Thus, the experiment was successfully implemented and verified across both positive functional and negative validation test cases.